EXPLORATION PHASE

EXPLORATION

Property Usage Exploration

`explore_property_usage(property_uri, limit, max_sample, include_class_prefixes)`

Analyze how a property is actually used in the graph by sampling real triples. Infers domain and range from actual data rather than ontology annotations (which are often missing or inaccurate).

Purpose: Differentiate between linguistically similar properties by seeing which entity types they actually connect, and verify that a candidate property relates the expected types before committing it to the query.

INPUT SCHEMA

`property_uri` string REQ

The full absolute URI of the property to analyze. Do not use prefixed/abbreviated URIs.

`limit` number OPT

Number of example usage patterns to return (default: 10).

`max_sample` number OPT

Maximum number of triples to sample for type analysis (default: 5000). Reduce if the endpoint times out.

`include_class_prefixes` string[] OPT

Optional list of URI prefixes to restrict the domain/range types shown. Useful to filter out noise when the knowledge graph spans many namespaces.

OUTPUT FORMAT

TABLE WITH COLUMNS:

`Domain` `Domain Label` `Range` `Range Label` `Example Subject` `Subject Label` `Example Object` `Object Label` `Count`

Entity Relations Exploration

`explore_entity_relations(entity_uri, num_ents, limit)`

Explore the relationships of a specific entity by listing all its incoming and outgoing connections.

Purpose: Useful when search alone has been inconclusive for resolving a relation mentioned in the question, as it reveals the full local graph structure around the entity.

INPUT SCHEMA

`entity_uri` string REQ

The full absolute URI of the entity to explore. Do not use prefixed/abbreviated URIs.

`num_ents` number OPT

Number of sample neighbors to show per property (default: 3). Keep low to avoid large outputs.

`limit` number OPT

Total number of results to return from query.

OUTPUT FORMAT

2 TABLES WITH COLUMNS:

Attributes (literals)

`property` `direction` `example_neighbors` `example_neighbors_labels`

Relations (URIs)

`property` `direction` `example_neighbors` `example_neighbors_labels`