


Introduction to Machine Learning

Neural Networks

Single hidden layer neural networks



Learning goals

- Architecture of single hidden layer neural networks
- Representation learning/ understanding the advantage of hidden layers
- Typical (non-linear) activation functions



MOTIVATION

- The graphical way of representing simple functions/models, like logistic regression. Why is that useful?
- Because individual neurons can be used as building blocks of more complicated functions.
- Networks of neurons can represent extremely complex hypothesis spaces.
- Most importantly, it allows us to define the “right” kinds of hypothesis spaces to learn functions that are common in our universe in a data-efficient way (see Lin, Tegmark et al. 2016).




MOTIVATION

Can a single neuron perform binary classification of these points?




MOTIVATION

- As a single neuron is restricted to learning only linear decision boundaries, its performance on the following task is quite poor:




- However, the neuron can easily separate the classes if the original features are transformed (e.g., from Cartesian to polar coordinates):




MOTIVATION

- Instead of classifying the data in the original representation,




- we classify it in a new feature space.



REPRESENTATION LEARNING

- It is *very* critical to feed a classifier the “right” features in order for it to perform well.
- Before deep learning took off, features for tasks like machine vision and speech recognition were “hand-designed” by domain experts. This step of the machine learning pipeline is called **feature engineering**.
- DL automates feature engineering. This is called **representation learning**.




SINGLE HIDDEN LAYER NETWORKS I

Single neurons perform a 2-step computation:

- ➊ **Affine Transformation:** a weighted sum of inputs plus bias.
- ➋ **Activation:** a non-linear transformation on the weighted sum.


Single hidden layer networks consist of two layers (without input layer):

- ➊ **Hidden Layer:** having a set of neurons.
 - ➋ **Output Layer:** having one or more output neurons.
- Multiple inputs are simultaneously fed to the network.
 - Each neuron in the hidden layer performs a 2-step computation.
 - The final output of the network is then calculated by another 2-step computation performed by the neuron in the output layer.




SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

Each neuron in the hidden layer performs an **affine transformation** on the inputs:





$$z_{1,\text{in}} = w_{11}x_1 + w_{21}x_2 + w_{31}x_3 + b_1$$


$$z_{1,\text{in}} = 3 * (-3) + (-9) * 1 + 2 * 5 + 5 = -3$$



Each neuron in the hidden layer performs an **affine transformation** on the inputs:




SINGLE HIDDEN LAYER NETWORKS: EXAMPLE



$$z_{3,\text{in}} = w_{13}x_1 + w_{23}x_2 + w_{33}x_3 + b_3$$

SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

Each neuron in the hidden layer performs an **affine transformation** on the inputs:





$$Z_{4,in} = w_{14}X_1 + w_{24}X_2 + w_{34}X_3 + b_4$$

$$Z_{4,in} = 6 * (-3) + (-1) * 1 + 5 * 5 + 1 = 7$$




SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

Each neuron in the hidden layer performs an **affine transformation** on the inputs:




SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

Each hidden neuron performs a non-linear **activation** transformation on the weight sum:




$$z_{i,out} = \sigma(z_{i,in}) = \frac{1}{1 + e^{-z_{i,in}}}$$




SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

The output neuron performs an **affine transformation** on its inputs:





$$f_{in} = u_1 z_{1,out} + u_2 z_{2,out} + u_3 z_{3,out} + u_4 z_{4,out} + c$$



SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

The output neuron performs an **affine transformation** on its inputs:




$$f_{in} = u_1 z_{1,out} + u_2 z_{2,out} + u_3 z_{3,out} + u_4 z_{4,out} + c$$


$$f_{in} = 3 * 0.05 + (-12) * 0.88 + 8 * 0.50 + 1 * 0.99 + 6 = 0.57$$

SINGLE HIDDEN LAYER NETWORKS: EXAMPLE

The output neuron performs a non-linear **activation** transformation on the weight sum:



$$f_{\text{out}} = \sigma(f_{\text{in}}) = \frac{1}{1 + e^{-f_{\text{in}}}}$$
$$f_{\text{out}} = \frac{1}{1 + e^{-0.57}} = 0.64$$



HIDDEN LAYER: ACTIVATION FUNCTION

- If the hidden layer does not have a non-linear activation, the network can only learn linear decision boundaries.
- A lot of different activation functions exist.





HIDDEN LAYER: ACTIVATION FUNCTION I

ReLU Activation:

- Currently the most popular choice is the ReLU (rectified linear unit):

$$\sigma(v) = \max(0, v)$$



HIDDEN LAYER: ACTIVATION FUNCTION II

Sigmoid Activation Function:

- The sigmoid function can be used even in the hidden layer:

$$\sigma(v) = \frac{1}{1 + \exp(-v)}$$

