

Assignment 1

Exercise 2

Note: Throughout this exercise we have assumed that a list l_1 can be split only if $|l_1| \geq 2$, i.e. cases like $g(\text{src}(l_1), \text{src}([]))$ shall never occur and only calls to g like $g(\text{src}(l_1), \text{src}(l_2))$ with non-empty lists l_1 and l_2 are valid calls.

(i)

From the definition of $\text{src}[e, f, g]$, we see that for a non empty list $l_1 = \{x_1, \dots, x_n\}$,

f takes input x with type T . And f is applied to all elements in the list l_1 , and returns a type Q variable.

g takes input (λ_1, λ_2) with type $Q \times Q$ and returns

(ii)

- *Determining the length (if not stored)*

$$\begin{cases} e := 0 \\ f(x) := 1 \\ g(\lambda_1, \lambda_2) := \lambda_1 + \lambda_2 \end{cases}$$

- *Applying a function to all elements of a list*

Let h be the specified operation on elements of the given list.

$$\begin{cases} e := [] \\ f(x) := h(x) \\ g(l_1, l_2) := \text{concat}(l_1, l_2) \end{cases}$$

- *Creating a sublist of list elements satisfying a condition φ*

Let φ be the condition that a element needs to satisfy.

$$\begin{cases} e := [] \\ f(x) := I\{x\}. \varphi(x) \\ g(l_1, l_2) := l_1 \cup l_2 \end{cases}$$

Note: $f(x)$ returns an empty list if x does not satisfy φ , and returns a list containing x if x satisfies φ

(iii)

Let the length of the given list be n . In the process, f is applied n times and g is applied $n - 1$ times.

For the complexity of f , assume the operation of f take t_f steps, then the complexity of f amounts to $O(t_f n)$.

As for g , there are two cases:

- If we consider data types where when splitting a list into sublist, no allocation and copying is necessary, then assume the cost of splitting to be some constant c , then the complexity of g amounts to $O(c(n - 1)) = O(n)$.

And the total complexity of src amounts to $O(mn + n) = O(mn)$.

- If we consider data types where when splitting a list, extra actions are needed (see my implementation of src on $AList$), then the complexity of g becomes different: In case of $AList$, each time a list is split, src have to copy all elements of the original list into its sublist. Let the cost of copying be some constant c , then the complexity of g amounts to $O(c * n * \lfloor \log_2(n) \rfloor) = O(n * \log_2(n))$

And the total complexity of src amounts to $O(mn + n \log_2(n))$

(iv)

C++ code implementation are in the folder. After compilation, the executable you get provides 2 test cases:

1. Generate the length of an auto-generated $AList$. $SIZE$ of the list is defined using macro definition and the list is filled to natural numbers. The default setting has

```
#define SIZE 20
```

2. Using the same testing list, the test cases defines e, f, g such that the src function returns a sublist with all elements ≥ 14