E - Problem E

Source file name: `stones.cpp`
Time limit: 1 second

Squirrel Liss lived in a forest peacefully, but unexpected trouble happens. Stones fall from a mountain. Initially Squirrel Liss occupies an interval [0..1]. Next, n stones will fall and Liss will escape from the stones. The stones are numbered from 1 to n in order.

The stones always fall to the center of Liss's interval. When Liss occupies the interval $[k - d, k + d]$ and a stone falls to k, she will escape to the left or to the right. If she escapes to the left, her new interval will be $[k - d, k]$. If she escapes to the right, her new interval will be $[k, k + d]$.

You are given a string s of length n. If the i-th character of s is `'l'` or `'r'`, when the i-th stone falls Liss will escape to the left or to the right, respectively. Find the sequence of stones' numbers from left to right after all the n stones falls.

Input

The input consists of multiple cases. For each case there is an only line that contains the string s ($1 \leq |s| \leq 10^6$). Each character in s will be either `'l'` or `'r'`.

The input must be read from standard input.

Output

For each test case, output n lines — on the i-th line you should print the i-th stone's number from the left. There is an empty line between consecutive cases.

Explanation first case: In the first example, the positions of stones 1, 2, 3, 4, 5 will be $\frac{1}{2}, \frac{1}{4}$, respectively. So you should print the sequence: 3, 5, 4, 2, 1.

The output must be written to standard output.

Sample Input	**Sample Output**

`llrlr`
`rrlll`
`lrlrr`
	`3`
	`5`
	`4`
	`2`
	`1`
	
	`1`
	`2`
	`5`
	`4`
	`3`
	
	`2`
	`4`
	`5`
	`3`
	`1`