

DP-USACO 1.1 Broken Necklace(破碎的项链)-环状板子

C++

```
#include<bits/stdc++.h>
using namespace std;
using ll = long long;
#define all(a) (a).begin(), (a).end()

void work(){
    int n;
    cin >> n;
    string s;
    cin >> s;
    s += s;
    char c = 'w';
    int cnt1=0, cnt2=0, cntw=0, ans = 0;
    for(int i=0; i<n*2; i++){
        if(s[i] == 'w') ++cnt1, ++cntw;
        // 如果之前全是白色, 或者当前颜色匹配
        else if(c == 'w' || s[i] == c) ++cnt1, cntw = 0, c = s[i];
        else{
            ans = max(ans, cnt1+cnt2);
            cnt2 = cnt1 - cntw; //因为部分w可以继承, 干脆就全部去掉了, 继承本轮字母个数
            cnt1 = cntw + 1; //包含了这一轮的s[i]
            cntw = 0;
            c = s[i];
        }
    }
    if(ans == 0) ans = n;
    ans = min(ans, n);
    cout << ans << '\n';
} signed main(){
    ios::sync_with_stdio(0);
    cin.tie(0);
    cout.tie(0);
    int T=1;
    //    cin >> T;
    while(T--) work();
}

/*
29
wwwbbrwrbrbrrrbrrwrwwrbwrwrrb

11

8
rrwwwbbb

8
*/
```