AI ANALYTICS
Complete Implementation Guide

Foundation + Primary Actions for Five Micro-Verticals Ecosystem

Executive Summary

AI Analytics is the intelligence layer that powers the **Five Micro-Verticals** ecosystem, delivering actionable insights across Finance, Sales, Operations, Marketing, and Customer Success.

- Real-time Performance Monitoring
- Predictive Analytics & Forecasting
- Automated Reporting & Alerts
- Cross-vertical Data Integration
- Custom Dashboard Creation
- Explore Features Before Purchasing

Core Technologies

- **Supabase** — Database & Backend
- **Vercel** — Edge Functions

Architecture Overview

Data Layer

Supabase PostgreSQL with real-time subscriptions, row security & scheduling

Processing Layer

Edge functions, workflows, and automated analytics for calculations, data transformation, and scoring

Visualization Layer

Real-time dashboards, predictive models, and AI-powered insights & reporting

Supabase Database Setup

1. Database Schema

```sql
-- ============================================
-- AI ANALYTICS DATABASE SCHEMA
-- Foundation + Primary Actions
-- ============================================

-- Enable required extensions
CREATE EXTENSION IF NOT EXISTS "uuid-ossp";
CREATE EXTENSION IF NOT EXISTS "pg_cron";

-- ============================================
-- CORE TABLES
-- ============================================

-- Organizations (multi-tenant support)
CREATE TABLE organizations (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    name TEXT NOT NULL,
    slug TEXT UNIQUE NOT NULL,
    plan TEXT DEFAULT 'free' CHECK (plan IN ('free', 'pro', 'enterprise')),
    settings JSONB DEFAULT '{}',
    created_at TIMESTAMPTZ DEFAULT NOW(),
    updated_at TIMESTAMPTZ DEFAULT NOW()
);

-- Users
CREATE TABLE users (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    organization_id UUID REFERENCES organizations(id) ON DELETE CASCADE,
    email TEXT UNIQUE NOT NULL,
    name TEXT,
    role TEXT DEFAULT 'member' CHECK (role IN ('admin', 'member', 'viewer')),
    avatar_url TEXT,
    last_login_at TIMESTAMPTZ,
    created_at TIMESTAMPTZ DEFAULT NOW()
);

-- Data Sources
CREATE TABLE data_sources (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    organization_id UUID REFERENCES organizations(id) ON DELETE CASCADE,
    name TEXT NOT NULL,
    type TEXT NOT NULL CHECK (type IN ('postgres', 'api', 'csv', 'webhook', 'stripe', 'hubspot', 'salesforce')),
    connection_config JSONB DEFAULT '{}',
    sync_frequency INTERVAL DEFAULT '1 hour',
    last_sync_at TIMESTAMPTZ,
    status TEXT DEFAULT 'active' CHECK (status IN ('active', 'paused', 'error')),
    created_at TIMESTAMPTZ DEFAULT NOW()
);

-- Metrics Definitions
CREATE TABLE metrics (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    organization_id UUID REFERENCES organizations(id) ON DELETE CASCADE,
    name TEXT NOT NULL,
    slug TEXT NOT NULL,
    description TEXT,
    formula TEXT,
    unit TEXT DEFAULT 'number',
    category TEXT,
    is_active BOOLEAN DEFAULT true,
    created_at TIMESTAMPTZ DEFAULT NOW(),
    UNIQUE(organization_id, slug)
);

-- Metric Values (time-series)
CREATE TABLE metric_values (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    metric_id UUID REFERENCES metrics(id) ON DELETE CASCADE,
    value NUMERIC NOT NULL,
    dimensions JSONB DEFAULT '{}',
    recorded_at TIMESTAMPTZ DEFAULT NOW()
);

-- Create index for time-series queries
CREATE INDEX idx_metric_values_lookup ON metric_values(metric_id, recorded_at DESC);

-- Dashboards
CREATE TABLE dashboards (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    organization_id UUID REFERENCES organizations(id) ON DELETE CASCADE,
    name TEXT NOT NULL,
    description TEXT,
    layout JSONB DEFAULT '[]',
    is_default BOOLEAN DEFAULT false,
    created_by UUID REFERENCES users(id),
    created_at TIMESTAMPTZ DEFAULT NOW()
);

-- Dashboard Widgets
CREATE TABLE widgets (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    dashboard_id UUID REFERENCES dashboards(id) ON DELETE CASCADE,
    type TEXT NOT NULL CHECK (type IN ('line_chart', 'bar_chart', 'pie_chart', 'number', 'table', 'funnel', 'heatmap')),
    title TEXT,
    config JSONB DEFAULT '{}',
    position JSONB DEFAULT '{"x": 0, "y": 0, "w": 4, "h": 3}',
    created_at TIMESTAMPTZ DEFAULT NOW()
);

-- Alerts
CREATE TABLE alerts (
    id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
    organization_id UUID REFERENCES organizations(id) ON DELETE CASCADE,
    metric_id UUID REFERENCES metrics(id) ON DELETE CASCADE,
    name TEXT NOT NULL,
    condition JSONB NOT NULL,
    -- e.g., {"operator": ">", "threshold": 100, "duration": "5m"}
    notification_channels JSONB DEFAULT '[]',
    -- e.g., ["email", "slack", "webhook"]
    is_active BOOLEAN DEFAULT true,
    last_triggered_at TIMESTAMPTZ,
    created_at TIMESTAMPTZ DEFAULT NOW()
);
```

2. Real-time Subscriptions

```sql
-- Enable real-time for live dashboards
ALTER PUBLICATION supabase_realtime ADD TABLE metric_values;
ALTER PUBLICATION supabase_realtime ADD TABLE alerts;

-- Row Level Security
ALTER TABLE organizations ENABLE ROW LEVEL SECURITY;
ALTER TABLE users ENABLE ROW LEVEL SECURITY;
ALTER TABLE data_sources ENABLE ROW LEVEL SECURITY;
ALTER TABLE metrics ENABLE ROW LEVEL SECURITY;
ALTER TABLE metric_values ENABLE ROW LEVEL SECURITY;
ALTER TABLE dashboards ENABLE ROW LEVEL SECURITY;
ALTER TABLE widgets ENABLE ROW LEVEL SECURITY;
ALTER TABLE alerts ENABLE ROW LEVEL SECURITY;

-- Policies (example - adjust based on auth setup)
CREATE POLICY "Users can view their organization's data"
    ON organizations FOR SELECT
    USING (id IN (SELECT organization_id FROM users WHERE id = auth.uid()));

CREATE POLICY "Users can view their organization's metrics"
    ON metrics FOR SELECT
    USING (organization_id IN (SELECT organization_id FROM users WHERE id = auth.uid()));

CREATE POLICY "Users can view their organization's metric values"
    ON metric_values FOR SELECT
    USING (metric_id IN (SELECT id FROM metrics WHERE organization_id IN (SELECT organization_id FROM users WHERE id = auth.uid())));
```

3. Analytics Functions

```sql
-- Function to calculate metric aggregations
CREATE OR REPLACE FUNCTION get_metric_aggregation(
    p_metric_id UUID,
    p_start_date TIMESTAMPTZ,
    p_end_date TIMESTAMPTZ,
    p_granularity TEXT DEFAULT 'day'
)
RETURNS TABLE (
    period TIMESTAMPTZ,
    value NUMERIC,
    change_percent NUMERIC
) AS $$
BEGIN
    RETURN QUERY
    WITH aggregated AS (
        SELECT
            DATE_TRUNC(p_granularity, recorded_at) AS period,
            SUM(value) AS value
        FROM metric_values
        WHERE metric_id = p_metric_id
            AND recorded_at BETWEEN p_start_date AND p_end_date
        GROUP BY DATE_TRUNC(p_granularity, recorded_at)
        ORDER BY period
    )
    SELECT
        a.period,
        a.value,
        CASE
            WHEN LAG(a.value) OVER (ORDER BY a.period) = 0 THEN NULL
            ELSE ROUND(((a.value - LAG(a.value) OVER (ORDER BY a.period)) / LAG(a.value) OVER (ORDER BY a.period)) * 100, 2)
        END AS change_percent
    FROM aggregated a;
END;
$$ LANGUAGE plpgsql;
```

GitHub Actions Automation

1. Analytics Workflow

```yaml
# .github/workflows/analytics.yml
name: Analytics Automation

on:
  schedule:
    # Run every hour
    - cron: '0 * * * *'
  workflow_dispatch:
    inputs:
      task:
        description: 'Task to run'
        required: true
        default: 'sync'
        type: choice
        options:
          - sync
          - aggregate
          - alerts
          - reports

jobs:
  sync-data:
    if: github.event.inputs.task == 'sync' || github.event_name == 'schedule'
    runs-on: ubuntu-latest
    steps:
      - name: Sync Stripe Data
        run: |
          curl -X POST "${{ secrets.SUPABASE_URL }}/functions/v1/sync-stripe" \
            -H "Authorization: Bearer ${{ secrets.SUPABASE_SERVICE_KEY }}"

      - name: Sync HubSpot Data
        run: |
          curl -X POST "${{ secrets.SUPABASE_URL }}/functions/v1/sync-hubspot" \
            -H "Authorization: Bearer ${{ secrets.SUPABASE_SERVICE_KEY }}"

  aggregate-metrics:
    if: github.event.inputs.task == 'aggregate' || github.event_name == 'schedule'
    runs-on: ubuntu-latest
    steps:
      - name: Run Aggregations
        run: |
          curl -X POST "${{ secrets.SUPABASE_URL }}/functions/v1/aggregate-metrics" \
            -H "Authorization: Bearer ${{ secrets.SUPABASE_SERVICE_KEY }}"

  check-alerts:
    if: github.event.inputs.task == 'alerts' || github.event_name == 'schedule'
    runs-on: ubuntu-latest
    steps:
      - name: Check Alert Conditions
        run: |
          curl -X POST "${{ secrets.SUPABASE_URL }}/functions/v1/check-alerts" \
            -H "Authorization: Bearer ${{ secrets.SUPABASE_SERVICE_KEY }}"

  generate-reports:
    if: github.event.inputs.task == 'reports'
    runs-on: ubuntu-latest
    steps:
      - name: Generate Daily Report
        run: |
          curl -X POST "${{ secrets.SUPABASE_URL }}/functions/v1/generate-report" \
            -H "Authorization: Bearer ${{ secrets.SUPABASE_SERVICE_KEY }}" \
            -d '{"type": "daily"}'
```

2. Python Analytics Script

```python
# scripts/analytics_processor.py
import os
import pandas as pd
from supabase import create_client
from datetime import datetime, timedelta

supabase = create_client(
    os.environ['SUPABASE_URL'],
    os.environ['SUPABASE_SERVICE_KEY']
)

def calculate_growth_rate(metric_id: str, days: int = 30):
    """Calculate growth rate for a metric over specified days"""
    end_date = datetime.now()
    start_date = end_date - timedelta(days=days)

    response = supabase.table('metric_values') \
        .select('value, recorded_at') \
        .eq('metric_id', metric_id) \
        .gte('recorded_at', start_date.isoformat()) \
        .lte('recorded_at', end_date.isoformat()) \
        .order('recorded_at') \
        .execute()

    df = pd.DataFrame(response.data)
    if len(df) < 2:
        return None

    first_value = df['value'].iloc[0]
    last_value = df['value'].iloc[-1]

    if first_value == 0:
        return None

    growth_rate = ((last_value - first_value) / first_value) * 100
    return round(growth_rate, 2)

def detect_anomalies(metric_id: str, threshold: float = 2.0):
    """Detect anomalies using standard deviation"""
    response = supabase.table('metric_values') \
        .select('value, recorded_at') \
        .eq('metric_id', metric_id) \
        .order('recorded_at', desc=True) \
        .limit(100) \
        .execute()

    df = pd.DataFrame(response.data)
    if len(df) < 10:
        return []

    mean = df['value'].mean()
    std = df['value'].std()

    anomalies = df[abs(df['value'] - mean) > threshold * std]
    return anomalies.to_dict('records')

def forecast_metric(metric_id: str, periods: int = 7):
    """Simple linear forecast for next N periods"""
    response = supabase.table('metric_values') \
        .select('value, recorded_at') \
        .eq('metric_id', metric_id) \
        .order('recorded_at') \
        .execute()

    df = pd.DataFrame(response.data)
    if len(df) < 10:
        return []

    df['recorded_at'] = pd.to_datetime(df['recorded_at'])
    df['days'] = (df['recorded_at'] - df['recorded_at'].min()).dt.days

    # Simple linear regression
    from numpy.polynomial.polynomial import polyfit
    b, m = polyfit(df['days'], df['value'], 1)

    last_day = df['days'].max()
    forecasts = []
    for i in range(1, periods + 1):
        forecasts.append({
            'day': last_day + i,
            'value': b + m * (last_day + i)
        })

    return forecasts

if __name__ == '__main__':
    print("Analytics processor ready")
```

ML Predictions Script

```python
# scripts/ml_predictions.py
import os
import pandas as pd
import numpy as np
from supabase import create_client
from sklearn.linear_model import LinearRegression
from sklearn.preprocessing import StandardScaler
from datetime import datetime, timedelta

supabase = create_client(
    os.environ['SUPABASE_URL'],
    os.environ['SUPABASE_SERVICE_KEY']
)

def train_and_predict(metric_id: str, forecast_days: int = 30):
    """Train model and generate predictions"""

    # Fetch historical data
    response = supabase.table('metric_values') \
        .select('value, recorded_at') \
        .eq('metric_id', metric_id) \
        .order('recorded_at') \
        .execute()

    df = pd.DataFrame(response.data)
    if len(df) < 30:
        print(f"Insufficient data for metric {metric_id}")
        return None

    df['recorded_at'] = pd.to_datetime(df['recorded_at'])
    df['day_num'] = (df['recorded_at'] - df['recorded_at'].min()).dt.days

    # Prepare features
    X = df[['day_num']].values
    y = df['value'].values

    # Scale features
    scaler = StandardScaler()
    X_scaled = scaler.fit_transform(X)

    # Train model
    model = LinearRegression()
    model.fit(X_scaled, y)

    # Generate predictions
    last_day = df['day_num'].max()
    future_days = np.array([[last_day + i] for i in range(1, forecast_days + 1)])
    future_scaled = scaler.transform(future_days)
    predictions = model.predict(future_scaled)

    # Calculate confidence intervals (simple approach)
    residuals = y - model.predict(X_scaled)
    std_error = np.std(residuals)

    forecasts = []
    for i, pred in enumerate(predictions):
        forecasts.append({
            'metric_id': metric_id,
            'value': pred,
            'dimensions': {
                'type': 'forecast',
                'confidence_lower': pred - 1.96 * std_error,
                'confidence_upper': pred + 1.96 * std_error
            },
            'recorded_at': (datetime.now() + timedelta(days=i+1)).isoformat()
        })

    # Store predictions
    supabase.table('metric_values').insert(forecasts).execute()

    return {
        'model_score': model.score(X_scaled, y),
        'predictions': len(forecasts)
    }

if __name__ == '__main__':
    print("ML predictions ready")
```

Real-time Analytics Dashboard

System Performance

Agent Efficiency

Sales Velocity

$50,000

Revenue per day

Active Agents

12

Currently online

Success Rate

92.5%

Tasks completed

Dashboard Implementation

```jsx
// components/AnalyticsDashboard.jsx
import { useEffect, useState } from 'react';
import { createClient } from '@supabase/supabase-js';
import { LineChart, Line, BarChart, Bar, PieChart, Pie, XAxis, YAxis, CartesianGrid, Tooltip, Legend, ResponsiveContainer } from 'recharts';

const supabase = createClient(
  process.env.NEXT_PUBLIC_SUPABASE_URL,
  process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY
);

export default function AnalyticsDashboard({ organizationId }) {
  const [metrics, setMetrics] = useState([]);
  const [selectedMetric, setSelectedMetric] = useState(null);
  const [timeSeries, setTimeSeries] = useState([]);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    fetchMetrics();
  }, [organizationId]);

  async function fetchMetrics() {
    const { data } = await supabase
      .from('metrics')
      .select('*')
      .eq('organization_id', organizationId)
      .eq('is_active', true);

    setMetrics(data || []);
    if (data?.length > 0) {
      setSelectedMetric(data[0]);
      fetchTimeSeries(data[0].id);
    }
    setLoading(false);
  }

  async function fetchTimeSeries(metricId) {
    const { data } = await supabase
      .from('metric_values')
      .select('value, recorded_at')
      .eq('metric_id', metricId)
      .order('recorded_at')
      .limit(100);

    setTimeSeries(data?.map(d => ({
      ...d,
      recorded_at: new Date(d.recorded_at).toLocaleDateString()
    })) || []);
  }

  if (loading) return <div>Loading...</div>;

  return (
    <div>
      <h1>Analytics Dashboard</h1>

      <select
        value={selectedMetric?.id}
        onChange={(e) => {
          const metric = metrics.find(m => m.id === e.target.value);
          setSelectedMetric(metric);
          fetchTimeSeries(metric.id);
        }}
      >
        {metrics.map(m => (
          <option key={m.id} value={m.id}>{m.name}</option>
        ))}
      </select>

      <ResponsiveContainer width="100%" height={400}>
        <LineChart data={timeSeries}>
          <CartesianGrid strokeDasharray="3 3" />
          <XAxis dataKey="recorded_at" />
          <YAxis />
          <Tooltip />
          <Legend />
          <Line type="monotone" dataKey="value" stroke="#8884d8" />
        </LineChart>
      </ResponsiveContainer>
    </div>
  );
}
```

Integration with Ecosystem Components

Real-time Data Integration

- Connect to Supabase PostgreSQL with real-time WebSocket updates
- Process customer interactions from Micro-Verticals
- Build synchronized business data warehouse
- Enable cross-vertical analytics and insights
- Set up unified data synchronization

AI Generation Integration

- Use AI to generate insights from collected analytics
- Create personalized recommendations
- Optimize operations using AI-powered insights
- Generate predictive models for business outcomes

API Integration Example

```bash
# Fetch analytics data
curl -X GET "https://your-project.supabase.co/rest/v1/metrics?organization_id=eq.YOUR_ORG_ID" \
  -H "apikey: YOUR_ANON_KEY" \
  -H "Authorization: Bearer YOUR_JWT_TOKEN"

# Get metric values with aggregation
curl -X POST "https://your-project.supabase.co/rest/v1/rpc/get_metric_aggregation" \
  -H "apikey: YOUR_ANON_KEY" \
  -H "Authorization: Bearer YOUR_JWT_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "p_metric_id": "METRIC_UUID",
    "p_start_date": "2024-01-01",
    "p_end_date": "2024-12-31",
    "p_granularity": "month"
  }'

# Create a new dashboard
curl -X POST "https://your-project.supabase.co/rest/v1/dashboards" \
  -H "apikey: YOUR_ANON_KEY" \
  -H "Authorization: Bearer YOUR_JWT_TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "organization_id": "YOUR_ORG_ID",
    "name": "Executive Dashboard",
    "layout": [],
    "is_default": true
  }'
```

Revenue Analytics & Optimization

Revenue Trends

Revenue Sources

Monthly Revenue

$45,230

Growth

+12.5%

Subscriptions

$32,000

Services

$13,230

Pipeline

$67,500

Revenue Optimization Strategy

```sql
-- Revenue analytics queries
-- Monthly recurring revenue (MRR)
SELECT
    DATE_TRUNC('month', recorded_at) AS month,
    SUM(value) AS mrr
FROM metric_values
WHERE metric_id = 'mrr_metric_id'
GROUP BY DATE_TRUNC('month', recorded_at)
ORDER BY month;

-- Customer lifetime value (CLV)
WITH customer_revenue AS (
    SELECT
        dimensions->>'customer_id' AS customer_id,
        SUM(value) AS total_revenue,
        COUNT(DISTINCT DATE_TRUNC('month', recorded_at)) AS months_active
    FROM metric_values
    WHERE metric_id = 'revenue_metric_id'
    GROUP BY dimensions->>'customer_id'
)
SELECT
    AVG(total_revenue / NULLIF(months_active, 0)) * 24 AS estimated_clv
FROM customer_revenue;

-- Churn rate calculation
WITH monthly_customers AS (
    SELECT
        DATE_TRUNC('month', recorded_at) AS month,
        COUNT(DISTINCT dimensions->>'customer_id') AS customers
    FROM metric_values
    WHERE metric_id = 'customer_metric_id'
    GROUP BY DATE_TRUNC('month', recorded_at)
)
SELECT
    month,
    customers,
    LAG(customers) OVER (ORDER BY month) - customers AS churned,
    ROUND((LAG(customers) OVER (ORDER BY month) - customers)::NUMERIC /
          NULLIF(LAG(customers) OVER (ORDER BY month), 0) * 100, 2) AS churn_rate
FROM monthly_customers;
```

Implementation Roadmap

Phase 1: Foundation Setup (Week 1-2)

- Supabase database schema deployment
- Authentication & RLS policies
- Basic data source connections
- Core metrics definitions

Phase 2: Real-time Analytics (Week 3-4)

- Live dashboard implementation
- Real-time subscriptions setup
- Alert system configuration
- Basic reporting features

Phase 3: Predictive Analytics (Week 5-6)

- Machine learning models
- Forecasting algorithms
- Anomaly detection system
- Advanced visualizations

Phase 4: Advanced Features (Week 7-8)

- Custom report builder
- Cross-vertical analytics
- Performance optimization
- Documentation & training

Security & Best Practices

Security Measures

- Row Level Security (RLS) policies on all tables
- Encrypted connections for sensitive data
- API key rotation every 90 days
- Audit logging for all data access

Performance Optimization

- Database indexes on frequently queried columns
- Materialized views for complex aggregations
- Caching strategy for dashboard data
- Efficient pagination for large datasets

Ready for The New Civilization

AI Analytics provides the intelligence layer that powers the entire ecosystem. Our integrated Supabase + GitHub Actions + Vercel architecture delivers:

- **Real-time Insights** — Live dashboards and instant alerts
- **Predictive Intelligence** — AI-powered forecasting and anomaly detection
- **Unified Data** — Cross-vertical analytics and reporting

Built with ❤️ for the future of business intelligence