AI GENERATIVE

Advanced Content Generation & Creative AI

Hugging Face • Autodoc • LLM Integration

Architecture Overview

Hugging Face Integration
Model hub access, fine-tuning, and deployment pipelines

Autodoc Framework
Automated documentation generation and maintenance

LLM Integration
Large language model orchestration and optimization

Core Components Implementation

1. Hugging Face Integration

```
# huggingface_integration.yaml
name: Hugging Face Model Integration
on:
  workflow_dispatch:
    inputs:
      model_name:
        description: 'Hugging Face model name'
        required: true
        default: 'microsoft/DialoGPT-medium'
      task:
        description: 'Task type'
        required: true
        default: 'text-generation'
        type: choice
        options:
          - text-generation
          - text-classification
          - question-answering
          - summarization
          - translation
      fine_tune:
        description: 'Fine-tune model'
        required: false
        default: false
        type: boolean
      dataset_name:
        description: 'Dataset for fine-tuning'
        required: false
        default: ''
      training_epochs:
        description: 'Training epochs'
        required: false
        default: '3'
      batch_size:
        description: 'Batch size'
        required: false
        default: '8'
      learning_rate:
        description: 'Learning rate'
        required: false
        default: '5e-5'
      push_to_hub:
        description: 'Push to Hugging Face Hub'
        required: false
        default: false
        type: boolean
      hub_model_id:
        description: 'Hub model ID'
        required: false
        default: ''
      private_repo:
        description: 'Private repository'
        required: false
        default: false
        type: boolean
      quantization:
        description: 'Quantization method'
        required: false
        default: 'none'
        type: choice
        options:
          - none
          - int8
          - int4
          - gptq
          - awq
      optimization:
        description: 'Optimization level'
        required: false
        default: 'O1'
        type: choice
        options:
          - O0
          - O1
          - O2
          - O3
      deployment_target:
        description: 'Deployment target'
        required: false
        default: 'inference_api'
        type: choice
        options:
          - inference_api
          - spaces
          - endpoints
          - local
      gpu_type:
        description: 'GPU type for training'
        required: false
        default: 'T4'
        type: choice
        options:
          - T4
          - V100
          - A100
          - A10G
      max_length:
        description: 'Maximum sequence length'
        required: false
        default: '512'
      warmup_steps:
        description: 'Warmup steps'
        required: false
        default: '500'
      weight_decay:
        description: 'Weight decay'
        required: false
        default: '0.01'
      gradient_accumulation:
        description: 'Gradient accumulation steps'
        required: false
        default: '1'
      fp16:
        description: 'Use FP16 precision'
        required: false
        default: true
        type: boolean
      deepspeed:
        description: 'Use DeepSpeed'
        required: false
        default: false
        type: boolean
      lora_config:
        description: 'LoRA configuration'
        required: false
        default: ''
      evaluation_strategy:
        description: 'Evaluation strategy'
        required: false
        default: 'steps'
        type: choice
        options:
          - steps
          - epoch
          - no
      save_strategy:
        description: 'Save strategy'
        required: false
        default: 'steps'
        type: choice
        options:
          - steps
          - epoch
          - no
      logging_steps:
        description: 'Logging steps'
        required: false
        default: '100'
      eval_steps:
        description: 'Evaluation steps'
        required: false
        default: '500'
      save_steps:
        description: 'Save steps'
        required: false
        default: '1000'
      early_stopping:
        description: 'Early stopping patience'
        required: false
        default: '3'
      metric_for_best_model:
        description: 'Metric for best model'
        required: false
        default: 'eval_loss'
      greater_is_better:
        description: 'Greater is better'
        required: false
        default: false
        type: boolean
      load_best_model:
        description: 'Load best model at end'
        required: false
        default: true
        type: boolean
      report_to:
        description: 'Report to (wandb, tensorboard, etc.)'
        required: false
        default: 'wandb'
      run_name:
        description: 'Run name'
        required: false
        default: ''
      output_dir:
        description: 'Output directory'
        required: false
        default: './results'
      cache_dir:
        description: 'Cache directory'
        required: false
        default: './cache'
      seed:
        description: 'Random seed'
        required: false
        default: '42'
      dataloader_num_workers:
        description: 'DataLoader workers'
        required: false
        default: '4'
      remove_unused_columns:
        description: 'Remove unused columns'
        required: false
        default: true
        type: boolean
      label_smoothing:
        description: 'Label smoothing factor'
        required: false
        default: '0.0'
      group_by_length:
        description: 'Group by length'
        required: false
        default: false
        type: boolean
      length_column_name:
        description: 'Length column name'
        required: false
        default: 'length'
      ignore_data_skip:
        description: 'Ignore data skip'
        required: false
        default: false
        type: boolean
      sharded_ddp:
        description: 'Sharded DDP'
        required: false
        default: ''
      deepspeed_config:
        description: 'DeepSpeed config file'
        required: false
        default: ''
      resume_from_checkpoint:
        description: 'Resume from checkpoint'
        required: false
        default: ''
      auto_find_batch_size:
        description: 'Auto find batch size'
        required: false
        default: false
        type: boolean
      full_determinism:
        description: 'Full determinism'
        required: false
        default: false
        type: boolean
      torch_compile:
        description: 'Torch compile'
        required: false
        default: false
        type: boolean
      torch_compile_backend:
        description: 'Torch compile backend'
        required: false
        default: 'inductor'
      torch_compile_mode:
        description: 'Torch compile mode'
        required: false
        default: 'default'
      include_inputs_for_metrics:
        description: 'Include inputs for metrics'
        required: false
        default: false
        type: boolean
      include_tokens_per_second:
        description: 'Include tokens per second'
        required: false
        default: false
        type: boolean
      include_num_input_tokens_seen:
        description: 'Include num input tokens seen'
        required: false
        default: false
        type: boolean
      neftune_noise_alpha:
        description: 'NEFTune noise alpha'
        required: false
        default: ''
      optim_target_modules:
        description: 'Optim target modules'
        required: false
        default: ''
      batch_eval_metrics:
        description: 'Batch eval metrics'
        required: false
        default: false
        type: boolean
      eval_on_start:
        description: 'Eval on start'
        required: false
        default: false
        type: boolean
      eval_use_gather_object:
        description: 'Eval use gather object'
        required: false
        default: false
        type: boolean
      prediction_loss_only:
        description: 'Prediction loss only'
        required: false
        default: false
        type: boolean
      push_to_hub_model_id:
        description: 'Push to hub model ID'
        required: false
        default: ''
      push_to_hub_organization:
        description: 'Push to hub organization'
        required: false
        default: ''
      push_to_hub_token:
        description: 'Push to hub token'
        required: false
        default: ''
      hub_strategy:
        description: 'Hub strategy'
        required: false
        default: 'every_save'
      hub_private_repo:
        description: 'Hub private repo'
        required: false
        default: false
        type: boolean
      hub_always_push:
        description: 'Hub always push'
        required: false
        default: false
        type: boolean
      gradient_checkpointing:
        description: 'Gradient checkpointing'
        required: false
        default: false
        type: boolean
      gradient_checkpointing_kwargs:
        description: 'Gradient checkpointing kwargs'
        required: false
        default: ''
      include_tokens_per_second:
        description: 'Include tokens per second'
        required: false
        default: false
        type: boolean
      include_num_input_tokens_seen:
        description: 'Include num input tokens seen'
        required: false
        default: false
        type: boolean
      neftune_noise_alpha:
        description: 'NEFTune noise alpha'
        required: false
        default: ''
      optim_target_modules:
        description: 'Optim target modules'
        required: false
        default: ''
      batch_eval_metrics:
        description: 'Batch eval metrics'
        required: false
        default: false
        type: boolean
      eval_on_start:
        description: 'Eval on start'
        required: false
        default: false
        type: boolean
      eval_use_gather_object:
        description: 'Eval use gather object'
        required: false
        default: false
        type: boolean
      prediction_loss_only:
        description: 'Prediction loss only'
        required: false
        default: false
        type: boolean
      push_to_hub_model_id:
        description: 'Push to hub model ID'
        required: false
        default: ''
      push_to_hub_organization:
        description: 'Push to hub organization'
        required: false
        default: ''
      push_to_hub_token:
        description: 'Push to hub token'
        required: false
        default: ''
      hub_strategy:
        description: 'Hub strategy'
        required: false
        default: 'every_save'
      hub_private_repo:
        description: 'Hub private repo'
        required: false
        default: false
        type: boolean
      hub_always_push:
        description: 'Hub always push'
        required: false
        default: false
        type: boolean
      gradient_checkpointing:
        description: 'Gradient checkpointing'
        required: false
        default: false
        type: boolean
      gradient_checkpointing_kwargs:
        description: 'Gradient checkpointing kwargs'
        required: false
        default: ''

jobs:
  huggingface-integration:
    runs-on: ubuntu-latest
    steps:
      - name: Checkout repository
        uses: actions/checkout@v4

      - name: Set up Python
        uses: actions/setup-python@v4
        with:
          python-version: '3.10'

      - name: Install dependencies
        run: |
          pip install transformers datasets torch accelerate
          pip install huggingface_hub wandb tensorboard
          pip install peft bitsandbytes scipy
          pip install deepspeed
          pip install optimum
          pip install auto-gptq
          pip install autoawq

      - name: Login to Hugging Face
        run: |
          huggingface-cli login --token ${{ secrets.HUGGINGFACE_TOKEN }}

      - name: Create training script
        run: |
          cat > train_model.py << 'EOF'
          import os
          import torch
          from transformers import (
              AutoTokenizer, AutoModelForCausalLM, AutoModelForSequenceClassification,
              AutoModelForQuestionAnswering, AutoModelForSeq2SeqLM,
              TrainingArguments, Trainer, DataCollatorForLanguageModeling,
              DataCollatorForSeq2Seq, pipeline
          )
          from datasets import load_dataset, Dataset
          from peft import LoraConfig, get_peft_model, TaskType
          import wandb
          import json

          # Configuration
          model_name = os.environ.get('MODEL_NAME', 'microsoft/DialoGPT-medium')
          task = os.environ.get('TASK', 'text-generation')
          fine_tune = os.environ.get('FINE_TUNE', 'false').lower() == 'true'
          dataset_name = os.environ.get('DATASET_NAME', '')
          training_epochs = int(os.environ.get('TRAINING_EPOCHS', '3'))
          batch_size = int(os.environ.get('BATCH_SIZE', '8'))
          learning_rate = float(os.environ.get('LEARNING_RATE', '5e-5'))
          push_to_hub = os.environ.get('PUSH_TO_HUB', 'false').lower() == 'true'
          hub_model_id = os.environ.get('HUB_MODEL_ID', '')
          private_repo = os.environ.get('PRIVATE_REPO', 'false').lower() == 'true'
          quantization = os.environ.get('QUANTIZATION', 'none')
          optimization = os.environ.get('OPTIMIZATION', 'O1')
          deployment_target = os.environ.get('DEPLOYMENT_TARGET', 'inference_api')
          gpu_type = os.environ.get('GPU_TYPE', 'T4')
          max_length = int(os.environ.get('MAX_LENGTH', '512'))
          warmup_steps = int(os.environ.get('WARMUP_STEPS', '500'))
          weight_decay = float(os.environ.get('WEIGHT_DECAY', '0.01'))
          gradient_accumulation = int(os.environ.get('GRADIENT_ACCUMULATION', '1'))
          fp16 = os.environ.get('FP16', 'true').lower() == 'true'
          deepspeed = os.environ.get('DEEPSPEED', 'false').lower() == 'true'
          lora_config = os.environ.get('LORA_CONFIG', '')
          evaluation_strategy = os.environ.get('EVALUATION_STRATEGY', 'steps')
          save_strategy = os.environ.get('SAVE_STRATEGY', 'steps')
          logging_steps = int(os.environ.get('LOGGING_STEPS', '100'))
          eval_steps = int(os.environ.get('EVAL_STEPS', '500'))
          save_steps = int(os.environ.get('SAVE_STEPS', '1000'))
          early_stopping = int(os.environ.get('EARLY_STOPPING', '3'))
          metric_for_best_model = os.environ.get('METRIC_FOR_BEST_MODEL', 'eval_loss')
          greater_is_better = os.environ.get('GREATER_IS_BETTER', 'false').lower() == 'true'
          load_best_model = os.environ.get('LOAD_BEST_MODEL', 'true').lower() == 'true'
          report_to = os.environ.get('REPORT_TO', 'wandb')
          run_name = os.environ.get('RUN_NAME', '')
          output_dir = os.environ.get('OUTPUT_DIR', './results')
          cache_dir = os.environ.get('CACHE_DIR', './cache')
          seed = int(os.environ.get('SEED', '42'))
          dataloader_num_workers = int(os.environ.get('DATALOADER_NUM_WORKERS', '4'))
          remove_unused_columns = os.environ.get('REMOVE_UNUSED_COLUMNS', 'true').lower() == 'true'
          label_smoothing = float(os.environ.get('LABEL_SMOOTHING', '0.0'))
          group_by_length = os.environ.get('GROUP_BY_LENGTH', 'false').lower() == 'true'
          length_column_name = os.environ.get('LENGTH_COLUMN_NAME', 'length')
          ignore_data_skip = os.environ.get('IGNORE_DATA_SKIP', 'false').lower() == 'true'
          sharded_ddp = os.environ.get('SHARDED_DDP', '')
          deepspeed_config = os.environ.get('DEEPSPEED_CONFIG', '')
          resume_from_checkpoint = os.environ.get('RESUME_FROM_CHECKPOINT', '')
          auto_find_batch_size = os.environ.get('AUTO_FIND_BATCH_SIZE', 'false').lower() == 'true'
          full_determinism = os.environ.get('FULL_DETERMINISM', 'false').lower() == 'true'
          torch_compile = os.environ.get('TORCH_COMPILE', 'false').lower() == 'true'
          torch_compile_backend = os.environ.get('TORCH_COMPILE_BACKEND', 'inductor')
          torch_compile_mode = os.environ.get('TORCH_COMPILE_MODE', 'default')
          include_inputs_for_metrics = os.environ.get('INCLUDE_INPUTS_FOR_METRICS', 'false').lower() == 'true'
          include_tokens_per_second = os.environ.get('INCLUDE_TOKENS_PER_SECOND', 'false').lower() == 'true'
          include_num_input_tokens_seen = os.environ.get('INCLUDE_NUM_INPUT_TOKENS_SEEN', 'false').lower() == 'true'
          neftune_noise_alpha = os.environ.get('NEFTUNE_NOISE_ALPHA', '')
          optim_target_modules = os.environ.get('OPTIM_TARGET_MODULES', '')
          batch_eval_metrics = os.environ.get('BATCH_EVAL_METRICS', 'false').lower() == 'true'
          eval_on_start = os.environ.get('EVAL_ON_START', 'false').lower() == 'true'
          eval_use_gather_object = os.environ.get('EVAL_USE_GATHER_OBJECT', 'false').lower() == 'true'
          prediction_loss_only = os.environ.get('PREDICTION_LOSS_ONLY', 'false').lower() == 'true'
          push_to_hub_model_id = os.environ.get('PUSH_TO_HUB_MODEL_ID', '')
          push_to_hub_organization = os.environ.get('PUSH_TO_HUB_ORGANIZATION', '')
          push_to_hub_token = os.environ.get('PUSH_TO_HUB_TOKEN', '')
          hub_strategy = os.environ.get('HUB_STRATEGY', 'every_save')
          hub_private_repo = os.environ.get('HUB_PRIVATE_REPO', 'false').lower() == 'true'
          hub_always_push = os.environ.get('HUB_ALWAYS_PUSH', 'false').lower() == 'true'
          gradient_checkpointing = os.environ.get('GRADIENT_CHECKPOINTING', 'false').lower() == 'true'
          gradient_checkpointing_kwargs = os.environ.get('GRADIENT_CHECKPOINTING_KWARGS', '')
          include_tokens_per_second = os.environ.get('INCLUDE_TOKENS_PER_SECOND', 'false').lower() == 'true'
          include_num_input_tokens_seen = os.environ.get('INCLUDE_NUM_INPUT_TOKENS_SEEN', 'false').lower() == 'true'
          neftune_noise_alpha = os.environ.get('NEFTUNE_NOISE_ALPHA', '')
          optim_target_modules = os.environ.get('OPTIM_TARGET_MODULES', '')
          batch_eval_metrics = os.environ.get('BATCH_EVAL_METRICS', 'false').lower() == 'true'
          eval_on_start = os.environ.get('EVAL_ON_START', 'false').lower() == 'true'
          eval_use_gather_object = os.environ.get('EVAL_USE_GATHER_OBJECT', 'false').lower() == 'true'
          prediction_loss_only = os.environ.get('PREDICTION_LOSS_ONLY', 'false').lower() == 'true'
          push_to_hub_model_id = os.environ.get('PUSH_TO_HUB_MODEL_ID', '')
          push_to_hub_organization = os.environ.get('PUSH_TO_HUB_ORGANIZATION', '')
          push_to_hub_token = os.environ.get('PUSH_TO_HUB_TOKEN', '')
          hub_strategy = os.environ.get('HUB_STRATEGY', 'every_save')
          hub_private_repo = os.environ.get('HUB_PRIVATE_REPO', 'false').lower() == 'true'
          hub_always_push = os.environ.get('HUB_ALWAYS_PUSH', 'false').lower() == 'true'
          gradient_checkpointing = os.environ.get('GRADIENT_CHECKPOINTING', 'false').lower() == 'true'
          gradient_checkpointing_kwargs = os.environ.get('GRADIENT_CHECKPOINTING_KWARGS', '')

          print(f"Loading model: {model_name}")
          print(f"Task: {task}")
          print(f"Fine-tuning: {fine_tune}")

          # Load tokenizer
          tokenizer = AutoTokenizer.from_pretrained(model_name, cache_dir=cache_dir)
          if tokenizer.pad_token is None:
              tokenizer.pad_token = tokenizer.eos_token

          # Load model based on task
          if task == 'text-generation':
              model = AutoModelForCausalLM.from_pretrained(model_name, cache_dir=cache_dir)
          elif task == 'text-classification':
              model = AutoModelForSequenceClassification.from_pretrained(model_name, cache_dir=cache_dir)
          elif task == 'question-answering':
              model = AutoModelForQuestionAnswering.from_pretrained(model_name, cache_dir=cache_dir)
          elif task == 'summarization' or task == 'translation':
              model = AutoModelForSeq2SeqLM.from_pretrained(model_name, cache_dir=cache_dir)
          else:
              model = AutoModelForCausalLM.from_pretrained(model_name, cache_dir=cache_dir)

          # Apply quantization
          if quantization != 'none':
              if quantization == 'int8':
                  model = model.to(torch.int8)
              elif quantization == 'int4':
                  model = model.to(torch.int4)
              elif quantization == 'gptq':
                  from auto_gptq import AutoGPTQForCausalLM
                  model = AutoGPTQForCausalLM.from_pretrained(model_name, cache_dir=cache_dir)
              elif quantization == 'awq':
                  from awq import AutoAWQForCausalLM
                  model = AutoAWQForCausalLM.from_pretrained(model_name, cache_dir=cache_dir)

          # Apply LoRA if specified
          if lora_config:
              lora_config = json.loads(lora_config)
              peft_config = LoraConfig(
                  task_type=TaskType.CAUSAL_LM,
                  r=lora_config.get('r', 16),
                  lora_alpha=lora_config.get('lora_alpha', 32),
                  lora_dropout=lora_config.get('lora_dropout', 0.1),
                  target_modules=lora_config.get('target_modules', ['q_proj', 'v_proj'])
              )
              model = get_peft_model(model, peft_config)
              model.print_trainable_parameters()

          # Load dataset
          if dataset_name:
              dataset = load_dataset(dataset_name, cache_dir=cache_dir)
          else:
              # Create dummy dataset for demonstration
              dataset = Dataset.from_dict({
                  'text': ['Hello world', 'How are you?', 'I am fine'] * 100
              })

          # Tokenize dataset
          def tokenize_function(examples):
              return tokenizer(examples['text'], truncation=True, max_length=max_length)

          tokenized_dataset = dataset.map(tokenize_function, batched=True)

          # Training arguments
          training_args = TrainingArguments(
              output_dir=output_dir,
              num_train_epochs=training_epochs,
              per_device_train_batch_size=batch_size,
              per_device_eval_batch_size=batch_size,
              warmup_steps=warmup_steps,
              weight_decay=weight_decay,
              gradient_accumulation_steps=gradient_accumulation,
              fp16=fp16,
              deepspeed=deepspeed_config if deepspeed else None,
              evaluation_strategy=evaluation_strategy,
              save_strategy=save_strategy,
              logging_steps=logging_steps,
              eval_steps=eval_steps,
              save_steps=save_steps,
              early_stopping_patience=early_stopping,
              metric_for_best_model=metric_for_best_model,
              greater_is_better=greater_is_better,
              load_best_model_at_end=load_best_model,
              report_to=report_to,
              run_name=run_name,
              seed=seed,
              dataloader_num_workers=dataloader_num_workers,
              remove_unused_columns=remove_unused_columns,
              label_smoothing_factor=label_smoothing,
              group_by_length=group_by_length,
              length_column_name=length_column_name,
              ignore_data_skip=ignore_data_skip,
              sharded_ddp=sharded_ddp,
              resume_from_checkpoint=resume_from_checkpoint,
              auto_find_batch_size=auto_find_batch_size,
              full_determinism=full_determinism,
              torch_compile=torch_compile,
              torch_compile_backend=torch_compile_backend,
              torch_compile_mode=torch_compile_mode,
              include_inputs_for_metrics=include_inputs_for_metrics,
              include_tokens_per_second=include_tokens_per_second,
              include_num_input_tokens_seen=include_num_input_tokens_seen,
              neftune_noise_alpha=neftune_noise_alpha,
              optim_target_modules=optim_target_modules,
              batch_eval_metrics=batch_eval_metrics,
              eval_on_start=eval_on_start,
              eval_use_gather_object=eval_use_gather_object,
              prediction_loss_only=prediction_loss_only,
              push_to_hub_model_id=push_to_hub_model_id,
              push_to_hub_organization=push_to_hub_organization,
              push_to_hub_token=push_to_hub_token,
              hub_strategy=hub_strategy,
              hub_private_repo=hub_private_repo,
              hub_always_push=hub_always_push,
              gradient_checkpointing=gradient_checkpointing,
              gradient_checkpointing_kwargs=gradient_checkpointing_kwargs,
              include_tokens_per_second=include_tokens_per_second,
              include_num_input_tokens_seen=include_num_input_tokens_seen,
              neftune_noise_alpha=neftune_noise_alpha,
              optim_target_modules=optim_target_modules,
              batch_eval_metrics=batch_eval_metrics,
              eval_on_start=eval_on_start,
              eval_use_gather_object=eval_use_gather_object,
              prediction_loss_only=prediction_loss_only,
              push_to_hub_model_id=push_to_hub_model_id,
              push_to_hub_organization=push_to_hub_organization,
              push_to_hub_token=push_to_hub_token,
              hub_strategy=hub_strategy,
              hub_private_repo=hub_private_repo,
              hub_always_push=hub_always_push,
              gradient_checkpointing=gradient_checkpointing,
              gradient_checkpointing_kwargs=gradient_checkpointing_kwargs
          )

          # Data collator
          if task == 'text-generation':
              data_collator = DataCollatorForLanguageModeling(tokenizer=tokenizer, mlm=False)
          elif task == 'summarization' or task == 'translation':
              data_collator = DataCollatorForSeq2Seq(tokenizer=tokenizer, model=model)
          else:
              data_collator = DataCollatorForLanguageModeling(tokenizer=tokenizer, mlm=False)

          # Trainer
          trainer = Trainer(
              model=model,
              args=training_args,
              train_dataset=tokenized_dataset['train'] if 'train' in tokenized_dataset else tokenized_dataset,
              eval_dataset=tokenized_dataset['validation'] if 'validation' in tokenized_dataset else None,
              data_collator=data_collator,
              tokenizer=tokenizer
          )

          # Train model
          if fine_tune:
              print("Starting fine-tuning...")
              trainer.train()

          # Save model
          trainer.save_model()
          tokenizer.save_pretrained(output_dir)

          # Push to hub
          if push_to_hub:
              print("Pushing to Hugging Face Hub...")
              trainer.push_to_hub()

          # Create pipeline for inference
          pipe = pipeline(task, model=model, tokenizer=tokenizer)

          # Test inference
          test_input = "Hello, how are you?"
          result = pipe(test_input)
          print(f"Test input: {test_input}")
          print(f"Test output: {result}")

          # Save configuration
          config = {
              'model_name': model_name,
              'task': task,
              'fine_tune': fine_tune,
              'dataset_name': dataset_name,
              'training_epochs': training_epochs,
              'batch_size': batch_size,
              'learning_rate': learning_rate,
              'push_to_hub': push_to_hub,
              'hub_model_id': hub_model_id,
              'private_repo': private_repo,
              'quantization': quantization,
              'optimization': optimization,
              'deployment_target': deployment_target,
              'gpu_type': gpu_type,
              'max_length': max_length,
              'warmup_steps': warmup_steps,
              'weight_decay': weight_decay,
              'gradient_accumulation': gradient_accumulation,
              'fp16': fp16,
              'deepspeed': deepspeed,
              'lora_config': lora_config,
              'evaluation_strategy': evaluation_strategy,
              'save_strategy': save_strategy,
              'logging_steps': logging_steps,
              'eval_steps': eval_steps,
              'save_steps': save_steps,
              'early_stopping': early_stopping,
              'metric_for_best_model': metric_for_best_model,
              'greater_is_better': greater_is_better,
              'load_best_model': load_best_model,
              'report_to': report_to,
              'run_name': run_name,
              'output_dir': output_dir,
              'cache_dir': cache_dir,
              'seed': seed,
              'dataloader_num_workers': dataloader_num_workers,
              'remove_unused_columns': remove_unused_columns,
              'label_smoothing': label_smoothing,
              'group_by_length': group_by_length,
              'length_column_name': length_column_name,
              'ignore_data_skip': ignore_data_skip,
              'sharded_ddp': sharded_ddp,
              'deepspeed_config': deepspeed_config,
              'resume_from_checkpoint': resume_from_checkpoint,
              'auto_find_batch_size': auto_find_batch_size,
              'full_determinism': full_determinism,
              'torch_compile': torch_compile,
              'torch_compile_backend': torch_compile_backend,
              'torch_compile_mode': torch_compile_mode,
              'include_inputs_for_metrics': include_inputs_for_metrics,
              'include_tokens_per_second': include_tokens_per_second,
              'include_num_input_tokens_seen': include_num_input_tokens_seen,
              'neftune_noise_alpha': neftune_noise_alpha,
              'optim_target_modules': optim_target_modules,
              'batch_eval_metrics': batch_eval_metrics,
              'eval_on_start': eval_on_start,
              'eval_use_gather_object': eval_use_gather_object,
              'prediction_loss_only': prediction_loss_only,
              'push_to_hub_model_id': push_to_hub_model_id,
              'push_to_hub_organization': push_to_hub_organization,
              'push_to_hub_token': push_to_hub_token,
              'hub_strategy': hub_strategy,
              'hub_private_repo': hub_private_repo,
              'hub_always_push': hub_always_push,
              'gradient_checkpointing': gradient_checkpointing,
              'gradient_checkpointing_kwargs': gradient_checkpointing_kwargs
          }

          with open('model_config.json', 'w') as f:
              json.dump(config, f, indent=2)

          print("Training completed successfully!")
          EOF

      - name: Run training
        env:
          MODEL_NAME: ${{ github.event.inputs.model_name }}
          TASK: ${{ github.event.inputs.task }}
          FINE_TUNE: ${{ github.event.inputs.fine_tune }}
          DATASET_NAME: ${{ github.event.inputs.dataset_name }}
          TRAINING_EPOCHS: ${{ github.event.inputs.training_epochs }}
          BATCH_SIZE: ${{ github.event.inputs.batch_size }}
          LEARNING_RATE: ${{ github.event.inputs.learning_rate }}
          PUSH_TO_HUB: ${{ github.event.inputs.push_to_hub }}
          HUB_MODEL_ID: ${{ github.event.inputs.hub_model_id }}
          PRIVATE_REPO: ${{ github.event.inputs.private_repo }}
          QUANTIZATION: ${{ github.event.inputs.quantization }}
          OPTIMIZATION: ${{ github.event.inputs.optimization }}
          DEPLOYMENT_TARGET: ${{ github.event.inputs.deployment_target }}
          GPU_TYPE: ${{ github.event.inputs.gpu_type }}
          MAX_LENGTH: ${{ github.event.inputs.max_length }}
          WARMUP_STEPS: ${{ github.event.inputs.warmup_steps }}
          WEIGHT_DECAY: ${{ github.event.inputs.weight_decay }}
          GRADIENT_ACCUMULATION: ${{ github.event.inputs.gradient_accumulation }}
          FP16: ${{ github.event.inputs.fp16 }}
          DEEPSPEED: ${{ github.event.inputs.deepspeed }}
          LORA_CONFIG: ${{ github.event.inputs.lora_config }}
          EVALUATION_STRATEGY: ${{ github.event.inputs.evaluation_strategy }}
          SAVE_STRATEGY: ${{ github.event.inputs.save_strategy }}
          LOGGING_STEPS: ${{ github.event.inputs.logging_steps }}
          EVAL_STEPS: ${{ github.event.inputs.eval_steps }}
          SAVE_STEPS: ${{ github.event.inputs.save_steps }}
          EARLY_STOPPING: ${{ github.event.inputs.early_stopping }}
          METRIC_FOR_BEST_MODEL: ${{ github.event.inputs.metric_for_best_model }}
          GREATER_IS_BETTER: ${{ github.event.inputs.greater_is_better }}
          LOAD_BEST_MODEL: ${{ github.event.inputs.load_best_model }}
          REPORT_TO: ${{ github.event.inputs.report_to }}
          RUN_NAME: ${{ github.event.inputs.run_name }}
          OUTPUT_DIR: ${{ github.event.inputs.output_dir }}
          CACHE_DIR: ${{ github.event.inputs.cache_dir }}
          SEED: ${{ github.event.inputs.seed }}
          DATALOADER_NUM_WORKERS: ${{ github.event.inputs.dataloader_num_workers }}
          REMOVE_UNUSED_COLUMNS: ${{ github.event.inputs.remove_unused_columns }}
          LABEL_SMOOTHING: ${{ github.event.inputs.label_smoothing }}
          GROUP_BY_LENGTH: ${{ github.event.inputs.group_by_length }}
          LENGTH_COLUMN_NAME: ${{ github.event.inputs.length_column_name }}
          IGNORE_DATA_SKIP: ${{ github.event.inputs.ignore_data_skip }}
          SHARDED_DDP: ${{ github.event.inputs.sharded_ddp }}
          DEEPSPEED_CONFIG: ${{ github.event.inputs.deepspeed_config }}
          RESUME_FROM_CHECKPOINT: ${{ github.event.inputs.resume_from_checkpoint }}
          AUTO_FIND_BATCH_SIZE: ${{ github.event.inputs.auto_find_batch_size }}
          FULL_DETERMINISM: ${{ github.event.inputs.full_determinism }}
          TORCH_COMPILE: ${{ github.event.inputs.torch_compile }}
          TORCH_COMPILE_BACKEND: ${{ github.event.inputs.torch_compile_backend }}
          TORCH_COMPILE_MODE: ${{ github.event.inputs.torch_compile_mode }}
          INCLUDE_INPUTS_FOR_METRICS: ${{ github.event.inputs.include_inputs_for_metrics }}
          INCLUDE_TOKENS_PER_SECOND: ${{ github.event.inputs.include_tokens_per_second }}
          INCLUDE_NUM_INPUT_TOKENS_SEEN: ${{ github.event.inputs.include_num_input_tokens_seen }}
          NEFTUNE_NOISE_ALPHA: ${{ github.event.inputs.neftune_noise_alpha }}
          OPTIM_TARGET_MODULES: ${{ github.event.inputs.optim_target_modules }}
          BATCH_EVAL_METRICS: ${{ github.event.inputs.batch_eval_metrics }}
          EVAL_ON_START: ${{ github.event.inputs.eval_on_start }}
          EVAL_USE_GATHER_OBJECT: ${{ github.event.inputs.eval_use_gather_object }}
          PREDICTION_LOSS_ONLY: ${{ github.event.inputs.prediction_loss_only }}
          PUSH_TO_HUB_MODEL_ID: ${{ github.event.inputs.push_to_hub_model_id }}
          PUSH_TO_HUB_ORGANIZATION: ${{ github.event.inputs.push_to_hub_organization }}
          PUSH_TO_HUB_TOKEN: ${{ github.event.inputs.push_to_hub_token }}
          HUB_STRATEGY: ${{ github.event.inputs.hub_strategy }}
          HUB_PRIVATE_REPO: ${{ github.event.inputs.hub_private_repo }}
          HUB_ALWAYS_PUSH: ${{ github.event.inputs.hub_always_push }}
          GRADIENT_CHECKPOINTING: ${{ github.event.inputs.gradient_checkpointing }}
          GRADIENT_CHECKPOINTING_KWARGS: ${{ github.event.inputs.gradient_checkpointing_kwargs }}
        run: |
          python train_model.py

      - name: Upload model artifacts
        uses: actions/upload-artifact@v3
        with:
          name: model-artifacts
          path: |
            ./results
            ./model_config.json
            ./cache

      - name: Create model card
        run: |
          cat > README.md << 'EOF'
          # Model Card

          This model was trained using the Hugging Face integration workflow.

          ## Model Details

          - **Model Name**: ${{ github.event.inputs.model_name }}
          - **Task**: ${{ github.event.inputs.task }}
          - **Fine-tuned**: ${{ github.event.inputs.fine_tune }}
          - **Dataset**: ${{ github.event.inputs.dataset_name }}
          - **Training Epochs**: ${{ github.event.inputs.training_epochs }}
          - **Batch Size**: ${{ github.event.inputs.batch_size }}
          - **Learning Rate**: ${{ github.event.inputs.learning_rate }}
          - **Quantization**: ${{ github.event.inputs.quantization }}
          - **Optimization**: ${{ github.event.inputs.optimization }}
          - **Deployment Target**: ${{ github.event.inputs.deployment_target }}
          - **GPU Type**: ${{ github.event.inputs.gpu_type }}

          ## Usage

          ```python
          from transformers import pipeline

          pipe = pipeline("${{ github.event.inputs.task }}", model="${{ github.event.inputs.hub_model_id }}")
          result = pipe("Your input text here")
          print(result)
          ```

          ## Training Configuration

          ```
          $(cat model_config.json)
          ```
          EOF

      - name: Push to Hugging Face Hub
        if: github.event.inputs.push_to_hub == 'true'
        run: |
          huggingface-cli upload ${{ github.event.inputs.hub_model_id }} ./results --repo-type model --private ${{ github.event.inputs.private_repo }}
          huggingface-cli upload ${{ github.event.inputs.hub_model_id }} ./README.md --repo-type model
```

2. Autodoc Multi-Agent Framework

```
# autodoc_framework.yaml
name: Autodoc Multi-Agent Framework
on:
  workflow_dispatch:
    inputs:
      project_path:
        description: 'Project path to document'
        required: true
        default: '.'
      agent_count:
        description: 'Number of agents'
        required: true
        default: '5'
      documentation_type:
        description: 'Documentation type'
        required: true
        default: 'comprehensive'
        type: choice
        options:
          - comprehensive
          - api-only
          - user-guide
          - technical-spec
      output_format:
        description: 'Output format'
        required: true
        default: 'markdown'
        type: choice
        options:
          - markdown
          - html
          - pdf
          - docx
      include_examples:
        description: 'Include code examples'
        required: false
        default: true
        type: boolean
      include_diagrams:
        description: 'Include diagrams'
        required: false
        default: true
        type: boolean
      language:
        description: 'Primary language'
        required: false
        default: 'auto-detect'
        type: choice
        options:
          - auto-detect
          - python
          - javascript
          - typescript
          - java
          - go
          - rust
          - cpp
      agent_specialization:
        description: 'Agent specialization'
        required: false
        default: 'balanced'
        type: choice
        options:
          - balanced
          - backend-focused
          - frontend-focused
          - devops-focused
          - security-focused
      quality_threshold:
        description: 'Quality threshold (0-100)'
        required: false
        default: '80'
      max_iterations:
        description: 'Maximum iterations'
        required: false
        default: '3'
      timeout_minutes:
        description: 'Timeout in minutes'
        required: false
        default: '30'
      parallel_processing:
        description: 'Parallel processing'
        required: false
        default: true
        type: boolean
      cache_enabled:
        description: 'Enable caching'
        required: false
        default: true
        type: boolean
      custom_templates:
        description: 'Custom templates path'
        required: false
        default: ''
      exclude_patterns:
        description: 'Exclude patterns (comma-separated)'
        required: false
        default: 'node_modules,*.test.*,*.spec.*,dist,build'
      include_patterns:
        description: 'Include patterns (comma-separated)'
        required: false
        default: '*.py,*.js,*.ts,*.java,*.go,*.rs,*.cpp,*.h'
      max_file_size:
        description: 'Max file size (KB)'
        required: false
        default: '1000'
      depth_limit:
        description: 'Directory depth limit'
        required: false
        default: '10'
      git_integration:
        description: 'Git integration'
        required: false
        default: true
        type: boolean
      commit_changes:
        description: 'Commit changes'
        required: false
        default: false
        type: boolean
      branch_name:
        description: 'Branch name for changes'
        required: false
        default: 'autodoc-updates'
      pr_creation:
        description: 'Create pull request'
        required: false
        default: false
        type: boolean
      pr_title:
        description: 'Pull request title'
        required: false
        default: 'Automated documentation updates'
      pr_body:
        description: 'Pull request body'
        required: false
        default: 'Generated by autodoc multi-agent framework'
      reviewers:
        description: 'Reviewers (comma-separated)'
        required: false
        default: ''
      labels:
        description: 'Labels (comma-separated)'
        required: false
        default: 'documentation,automated'
      assignees:
        description: 'Assignees (comma-separated)'
        required: false
        default: ''
      milestone:
        description: 'Milestone'
        required: false
        default: ''
      project_board:
        description: 'Project board'
        required: false
        default: ''
      notification_webhook:
        description: 'Notification webhook URL'
        required: false
        default: ''
      slack_channel:
        description: 'Slack channel'
        required: false
        default: ''
      email_notifications:
        description: 'Email notifications'
        required: false
        default: false
        type: boolean
      debug_mode:
        description: 'Debug mode'
        required: false
        default: false
        type: boolean
      verbose_logging:
        description: 'Verbose logging'
        required: false
        default: false
        type: boolean
      dry_run:
        description: 'Dry run (no changes)'
        required: false
        default: false
```