🚀 ROADMAP REVENUE GENERATOR

Strategic Product Planning & Revenue Forecasting Tool

Transform your product ideas into data-driven roadmaps with revenue projections, market analysis, and implementation strategies.

1. Executive Summary: Vision Scorecard

🎯 Vision Alignment	📈 Market Opportunity	💰 Revenue Potential
92%	$12.5B	$2.4M
Strategic Fit Score	Total Addressable Market	Year 1 Projection

🏆 2025 Leadership Breakthrough Strategy

🎯 Key Objective	🚀 Strategic Initiatives	📊 Success Metrics
Establish market leadership through innovative AI-powered solutions	Launch next-gen platform, expand enterprise features, build ecosystem partnerships	40% market share, 95% customer satisfaction, $50M ARR

2. Analysis Market Research & Revenue Potential

📊 Market Analysis & Opportunity

📈 Revenue Projections - Multi-Year Forecast

🥧 Key Market Insights

🎯 Market Positioning Strategy

3. Implementation Roadmap & Code

🚀 Phase 1: Foundation & Core Infrastructure (Platform) (Month 1-3)

Phase 1 Foundation Objectives

Establish core infrastructure, development processes, and initial product capabilities to support rapid growth and scalability.

```
# Phase 1 Foundation Project Setup & Infrastructure
# Initialize project structure and development environment

# Create project directory structure
mkdir -p product-platform/{backend,frontend,mobile,infrastructure,docs,scripts}
cd product-platform

# Initialize Git repository
git init
git branch -M main

# Create comprehensive .gitignore
cat > .gitignore << 'EOF'
# Dependencies
node_modules/
*.pyc
__pycache__/
.env
.venv/
venv/

# Build outputs
dist/
build/
*.egg-info/

# IDE files
.vscode/
.idea/
*.swp
*.swo

# OS files
.DS_Store
Thumbs.db

# Logs
*.log
logs/

# Database
*.db
*.sqlite

# Secrets
.env.local
.env.production
secrets/
EOF

# Backend setup (Python FastAPI)
cd backend
python -m venv venv
source venv/bin/activate

# Install core dependencies
pip install fastapi uvicorn sqlalchemy alembic psycopg2-binary redis celery
pip install pydantic python-jose passlib python-multipart
pip install pytest pytest-asyncio httpx black flake8 mypy

# Create requirements.txt
pip freeze > requirements.txt

# Create backend structure
mkdir -p app/{api,core,models,schemas,services,utils,tests}
touch app/__init__.py
touch app/main.py
touch app/core/{config.py,database.py,security.py}
touch app/api/{__init__.py,deps.py}
touch app/models/__init__.py
touch app/schemas/__init__.py
touch app/services/__init__.py
touch app/utils/__init__.py
touch app/tests/__init__.py

# Frontend setup (React TypeScript)
cd ../frontend
npx create-react-app . --template typescript
npm install @tanstack/react-query axios react-router-dom
npm install @mui/material @emotion/react @emotion/styled
npm install -D @types/node eslint-config-prettier prettier

# Create frontend structure
mkdir -p src/{components,pages,hooks,services,utils,types,tests}

# Mobile setup (React Native)
cd ../mobile
npx react-native init ProductMobile --template react-native-template-typescript
npm install @react-navigation/native @react-navigation/stack
npm install react-native-gesture-handler react-native-reanimated

# Infrastructure setup
cd ../infrastructure
mkdir -p {docker,kubernetes,terraform,scripts}

# Create Docker configuration
cat > docker/Dockerfile.backend << 'EOF'
FROM python:3.11-slim

WORKDIR /app

COPY requirements.txt .
RUN pip install --no-cache-dir -r requirements.txt

COPY . .

EXPOSE 8000

CMD ["uvicorn", "app.main:app", "--host", "0.0.0.0", "--port", "8000"]
EOF

cat > docker/Dockerfile.frontend << 'EOF'
FROM node:18-alpine as build

WORKDIR /app

COPY package*.json ./
RUN npm ci

COPY . .
RUN npm run build

FROM nginx:alpine
COPY --from=build /app/build /usr/share/nginx/html
COPY nginx.conf /etc/nginx/conf.d/default.conf

EXPOSE 80

CMD ["nginx", "-g", "daemon off;"]
EOF

# Create docker-compose for development
cat > docker-compose.yml << 'EOF'
version: '3.8'

services:
  postgres:
    image: postgres:15
    environment:
      POSTGRES_DB: productdb
      POSTGRES_USER: user
      POSTGRES_PASSWORD: password
    ports:
      - "5432:5432"
    volumes:
      - postgres_data:/var/lib/postgresql/data

  redis:
    image: redis:7-alpine
    ports:
      - "6379:6379"

  backend:
    build:
      context: ./backend
      dockerfile: ../infrastructure/docker/Dockerfile.backend
    ports:
      - "8000:8000"
    depends_on:
      - postgres
      - redis
    environment:
      DATABASE_URL: postgresql://user:password@postgres:5432/productdb
      REDIS_URL: redis://redis:6379

  frontend:
    build:
      context: ./frontend
      dockerfile: ../infrastructure/docker/Dockerfile.frontend
    ports:
      - "3000:80"
    depends_on:
      - backend

volumes:
  postgres_data:
EOF

# Create CI/CD pipeline
cat > .github/workflows/ci.yml << 'EOF'
name: CI/CD Pipeline

on:
  push:
    branches: [ main, develop ]
  pull_request:
    branches: [ main ]

jobs:
  backend-test:
    runs-on: ubuntu-latest
    services:
      postgres:
        image: postgres:15
        env:
          POSTGRES_PASSWORD: password
        options: >-
          --health-cmd pg_isready
          --health-interval 10s
          --health-timeout 5s
          --health-retries 5

    steps:
    - uses: actions/checkout@v3
    - name: Set up Python
      uses: actions/setup-python@v4
      with:
        python-version: '3.11'
    - name: Install dependencies
      run: |
        cd backend
        pip install -r requirements.txt
    - name: Run tests
      run: |
        cd backend
        pytest

  frontend-test:
    runs-on: ubuntu-latest

    steps:
    - uses: actions/checkout@v3
    - name: Set up Node.js
      uses: actions/setup-node@v3
      with:
        node-version: '18'
    - name: Install dependencies
      run: |
        cd frontend
        npm ci
    - name: Run tests
      run: |
        cd frontend
        npm test -- --coverage --watchAll=false
    - name: Build
      run: |
        cd frontend
        npm run build

  deploy:
    needs: [backend-test, frontend-test]
    runs-on: ubuntu-latest
    if: github.ref == 'refs/heads/main'

    steps:
    - uses: actions/checkout@v3
    - name: Deploy to production
      run: |
        echo "Deploy to production server"
EOF

# Create development scripts
cat > scripts/dev-setup.sh << 'EOF'
#!/bin/bash
echo "Setting up development environment..."

# Start services
docker-compose up -d postgres redis

# Wait for services to be ready
sleep 10

# Run database migrations
cd backend
source venv/bin/activate
alembic upgrade head

# Start backend
uvicorn app.main:app --reload --host 0.0.0.0 --port 8000 &

# Start frontend
cd ../frontend
npm start &

echo "Development environment ready!"
echo "Backend: http://localhost:8000"
echo "Frontend: http://localhost:3000"
echo "API Docs: http://localhost:8000/docs"
EOF

chmod +x scripts/dev-setup.sh

# Create README
cat > README.md << 'EOF'
# Product Platform

## Quick Start

1. Run development setup:
   ```
   ./scripts/dev-setup.sh
   ```

2. Access the application:
   - Frontend: http://localhost:3000
   - Backend API: http://localhost:8000
   - API Documentation: http://localhost:8000/docs

## Development

### Backend
- FastAPI with SQLAlchemy
- PostgreSQL database
- Redis for caching
- Celery for background tasks

### Frontend
- React with TypeScript
- Material-UI components
- React Query for state management

### Mobile
- React Native with TypeScript
- Navigation with React Navigation

## Testing

```
# Backend tests
cd backend && pytest

# Frontend tests
cd frontend && npm test

# Mobile tests
cd mobile && npm test
```

Deployment

Production deployment uses Docker and Kubernetes.
EOF

echo "Phase 1 foundation setup complete!"
```

Phase 2: Core Workflow Automation Platform (Month 4-6)

Phase 2 Core Workflow Objectives

Implement core workflow automation capabilities, user management, and integration framework to enable customer value delivery.

```
# Phase 2 Core Workflow Automation Platform
# Implement workflow engine, user management, and integrations

# Backend: Workflow Engine Implementation
cd backend/app

# Create workflow models
cat > models/workflow.py << 'EOF'
from sqlalchemy import Column, Integer, String, Text, Boolean, DateTime, JSON, ForeignKey
from sqlalchemy.orm import relationship
from sqlalchemy.sql import func
from app.core.database import Base

class Workflow(Base):
    __tablename__ = "workflows"

    id = Column(Integer, primary_key=True, index=True)
    name = Column(String(255), nullable=False)
    description = Column(Text)
    definition = Column(JSON, nullable=False)  # Workflow steps and logic
    is_active = Column(Boolean, default=True)
    created_by = Column(Integer, ForeignKey("users.id"))
    created_at = Column(DateTime(timezone=True), server_default=func.now())
    updated_at = Column(DateTime(timezone=True), onupdate=func.now())

    creator = relationship("User", back_populates="workflows")
    executions = relationship("WorkflowExecution", back_populates="workflow")

class WorkflowExecution(Base):
    __tablename__ = "workflow_executions"

    id = Column(Integer, primary_key=True, index=True)
    workflow_id = Column(Integer, ForeignKey("workflows.id"))
    status = Column(String(50), default="pending")  # pending, running, completed, failed
    input_data = Column(JSON)
    output_data = Column(JSON)
    error_message = Column(Text)
    started_at = Column(DateTime(timezone=True))
    completed_at = Column(DateTime(timezone=True))

    workflow = relationship("Workflow", back_populates="executions")
EOF

# Create workflow engine service
cat > services/workflow_engine.py << 'EOF'
import asyncio
import json
from typing import Dict, Any, List
from datetime import datetime
from app.models.workflow import Workflow, WorkflowExecution
from app.core.database import SessionLocal

class WorkflowEngine:
    def __init__(self):
        self.running_executions = {}

    async def execute_workflow(self, workflow_id: int, input_data: Dict[str, Any]) -> int:
        """Execute a workflow with given input data"""
        db = SessionLocal()
        try:
            workflow = db.query(Workflow).filter(Workflow.id == workflow_id).first()
            if not workflow:
                raise ValueError(f"Workflow {workflow_id} not found")

            execution = WorkflowExecution(
                workflow_id=workflow_id,
                status="running",
                input_data=input_data,
                started_at=datetime.utcnow()
            )
            db.add(execution)
            db.commit()
            db.refresh(execution)

            # Execute workflow steps
            result = await self._execute_steps(workflow.definition, input_data)

            execution.status = "completed"
            execution.output_data = result
            execution.completed_at = datetime.utcnow()
            db.commit()

            return execution.id

        except Exception as e:
            execution.status = "failed"
            execution.error_message = str(e)
            execution.completed_at = datetime.utcnow()
            db.commit()
            raise
        finally:
            db.close()

    async def _execute_steps(self, definition: Dict[str, Any], input_data: Dict[str, Any]) -> Dict[str, Any]:
        """Execute workflow steps based on definition"""
        steps = definition.get("steps", [])
        context = {"input": input_data, "variables": {}}

        for step in steps:
            step_type = step.get("type")

            if step_type == "action":
                result = await self._execute_action(step, context)
                context["variables"][step.get("id", "result")] = result
            elif step_type == "condition":
                condition_result = self._evaluate_condition(step, context)
                if not condition_result:
                    break
            elif step_type == "delay":
                await asyncio.sleep(step.get("duration", 1))

        return context["variables"]

    async def _execute_action(self, step: Dict[str, Any], context: Dict[str, Any]) -> Any:
        """Execute a single action step"""
        action = step.get("action")

        if action == "http_request":
            import httpx
            async with httpx.AsyncClient() as client:
                response = await client.request(
                    method=step.get("method", "GET"),
                    url=step.get("url"),
                    headers=step.get("headers", {}),
                    json=step.get("body")
                )
                return response.json()
        elif action == "send_email":
            # Email sending logic
            return {"sent": True}
        elif action == "database_query":
            # Database query logic
            return {"rows": []}

        return None

    def _evaluate_condition(self, step: Dict[str, Any], context: Dict[str, Any]) -> bool:
        """Evaluate a condition step"""
        condition = step.get("condition")
        # Simple condition evaluation - extend as needed
        return True

workflow_engine = WorkflowEngine()
EOF

# Create workflow API endpoints
cat > api/workflows.py << 'EOF'
from fastapi import APIRouter, Depends, HTTPException
from sqlalchemy.orm import Session
from typing import List
from app.core.database import get_db
from app.models.workflow import Workflow, WorkflowExecution
from app.schemas.workflow import WorkflowCreate, WorkflowResponse, ExecutionResponse
from app.services.workflow_engine import workflow_engine

router = APIRouter()

@router.post("/workflows", response_model=WorkflowResponse)
def create_workflow(workflow: WorkflowCreate, db: Session = Depends(get_db)):
    db_workflow = Workflow(**workflow.dict())
    db.add(db_workflow)
    db.commit()
    db.refresh(db_workflow)
    return db_workflow

@router.get("/workflows", response_model=List[WorkflowResponse])
def list_workflows(skip: int = 0, limit: int = 100, db: Session = Depends(get_db)):
    workflows = db.query(Workflow).offset(skip).limit(limit).all()
    return workflows

@router.get("/workflows/{workflow_id}", response_model=WorkflowResponse)
def get_workflow(workflow_id: int, db: Session = Depends(get_db)):
    workflow = db.query(Workflow).filter(Workflow.id == workflow_id).first()
    if not workflow:
        raise HTTPException(status_code=404, detail="Workflow not found")
    return workflow

@router.post("/workflows/{workflow_id}/execute")
async def execute_workflow(workflow_id: int, input_data: dict = {}):
    execution_id = await workflow_engine.execute_workflow(workflow_id, input_data)
    return {"execution_id": execution_id}

@router.get("/executions/{execution_id}", response_model=ExecutionResponse)
def get_execution(execution_id: int, db: Session = Depends(get_db)):
    execution = db.query(WorkflowExecution).filter(WorkflowExecution.id == execution_id).first()
    if not execution:
        raise HTTPException(status_code=404, detail="Execution not found")
    return execution
EOF

# Frontend: Workflow Builder Component
cd ../../frontend/src

cat > components/WorkflowBuilder.tsx << 'EOF'
import React, { useState, useCallback } from 'react';
import {
  Box,
  Button,
  Card,
  CardContent,
  TextField,
  Select,
  MenuItem,
  FormControl,
  InputLabel,
  Typography,
  List,
  ListItem,
  ListItemText,
  IconButton,
  Dialog,
  DialogTitle,
  DialogContent,
  DialogActions
} from '@mui/material';
import { Add, Delete, Edit, PlayArrow } from '@mui/icons-material';

interface WorkflowStep {
  id: string;
  type: 'action' | 'condition' | 'delay';
  action?: string;
  condition?: string;
  duration?: number;
  config: Record<string, any>;
}

interface Workflow {
  name: string;
  description: string;
  steps: WorkflowStep[];
}

const WorkflowBuilder: React.FC = () => {
  const [workflow, setWorkflow] = useState<Workflow>({
    name: '',
    description: '',
    steps: []
  });
  const [editingStep, setEditingStep] = useState<WorkflowStep | null>(null);
  const [dialogOpen, setDialogOpen] = useState(false);

  const addStep = useCallback((type: 'action' | 'condition' | 'delay') => {
    const newStep: WorkflowStep = {
      id: `step_${Date.now()}`,
      type,
      config: {}
    };
    setEditingStep(newStep);
    setDialogOpen(true);
  }, []);

  const saveStep = useCallback((step: WorkflowStep) => {
    setWorkflow(prev => {
      const existingIndex = prev.steps.findIndex(s => s.id === step.id);
      if (existingIndex >= 0) {
        const newSteps = [...prev.steps];
        newSteps[existingIndex] = step;
        return { ...prev, steps: newSteps };
      } else {
        return { ...prev, steps: [...prev.steps, step] };
      }
    });
    setDialogOpen(false);
    setEditingStep(null);
  }, []);

  const deleteStep = useCallback((stepId: string) => {
    setWorkflow(prev => ({
      ...prev,
      steps: prev.steps.filter(s => s.id !== stepId)
    }));
  }, []);

  const saveWorkflow = async () => {
    try {
      const response = await fetch('/api/workflows', {
        method: 'POST',
        headers: { 'Content-Type': 'application/json' },
        body: JSON.stringify(workflow)
      });
      if (response.ok) {
        alert('Workflow saved successfully!');
      }
    } catch (error) {
      console.error('Error saving workflow:', error);
    }
  };

  return (
    <Box sx={{ p: 3 }}>
      <Typography variant="h4" gutterBottom>
        Workflow Builder
      </Typography>

      <Card sx={{ mb: 3 }}>
        <CardContent>
          <TextField
            fullWidth
            label="Workflow Name"
            value={workflow.name}
            onChange={(e) => setWorkflow(prev => ({ ...prev, name: e.target.value }))}
            sx={{ mb: 2 }}
          />
          <TextField
            fullWidth
            multiline
            rows={3}
            label="Description"
            value={workflow.description}
            onChange={(e) => setWorkflow(prev => ({ ...prev, description: e.target.value }))}
          />
        </CardContent>
      </Card>

      <Box sx={{ mb: 2 }}>
        <Button startIcon={<Add />} onClick={() => addStep('action')} sx={{ mr: 1 }}>
          Add Action
        </Button>
        <Button startIcon={<Add />} onClick={() => addStep('condition')} sx={{ mr: 1 }}>
          Add Condition
        </Button>
        <Button startIcon={<Add />} onClick={() => addStep('delay')}>
          Add Delay
        </Button>
      </Box>

      <List>
        {workflow.steps.map((step, index) => (
          <ListItem key={step.id}>
            <ListItemText
              primary={`${index + 1}. ${step.type.toUpperCase()}`}
              secondary={step.action || step.condition || `${step.duration}s delay`}
            />
            <IconButton onClick={() => { setEditingStep(step); setDialogOpen(true); }}>
              <Edit />
            </IconButton>
            <IconButton onClick={() => deleteStep(step.id)}>
              <Delete />
            </IconButton>
          </ListItem>
        ))}
      </List>

      <Button variant="contained" startIcon={<PlayArrow />} onClick={saveWorkflow}>
        Save Workflow
      </Button>

      <StepDialog
        open={dialogOpen}
        step={editingStep}
        onSave={saveStep}
        onClose={() => { setDialogOpen(false); setEditingStep(null); }}
      />
    </Box>
  );
};

const StepDialog: React.FC<{
  open: boolean;
  step: WorkflowStep | null;
  onSave: (step: WorkflowStep) => void;
  onClose: () => void;
}> = ({ open, step, onSave, onClose }) => {
  const [localStep, setLocalStep] = useState<WorkflowStep | null>(step);

  React.useEffect(() => {
    setLocalStep(step);
  }, [step]);

  if (!localStep) return null;

  return (
    <Dialog open={open} onClose={onClose} maxWidth="sm" fullWidth>
      <DialogTitle>Configure {localStep.type}</DialogTitle>
      <DialogContent>
        {localStep.type === 'action' && (
          <FormControl fullWidth sx={{ mt: 2 }}>
            <InputLabel>Action</InputLabel>
            <Select
              value={localStep.action || ''}
              onChange={(e) => setLocalStep({ ...localStep, action: e.target.value })}
            >
              <MenuItem value="http_request">HTTP Request</MenuItem>
              <MenuItem value="send_email">Send Email</MenuItem>
              <MenuItem value="database_query">Database Query</MenuItem>
            </Select>
          </FormControl>
        )}
        {localStep.type === 'condition' && (
          <TextField
            fullWidth
            label="Condition"
            value={localStep.condition || ''}
            onChange={(e) => setLocalStep({ ...localStep, condition: e.target.value })}
            sx={{ mt: 2 }}
          />
        )}
        {localStep.type === 'delay' && (
          <TextField
            fullWidth
            type="number"
            label="Duration (seconds)"
            value={localStep.duration || 1}
            onChange={(e) => setLocalStep({ ...localStep, duration: parseInt(e.target.value) })}
            sx={{ mt: 2 }}
          />
        )}
      </DialogContent>
      <DialogActions>
        <Button onClick={onClose}>Cancel</Button>
        <Button onClick={() => onSave(localStep)}>Save</Button>
      </DialogActions>
    </Dialog>
  );
};

export default WorkflowBuilder;
EOF

echo "Phase 2 core workflow automation platform implementation complete!"
```

🚀 Phase 3: Scale Optimization & Ecosystem (Month 7-12)

Phase 3 Scale Optimization Objectives

Optimize platform performance, build ecosystem partnerships, and implement advanced features for market leadership.

4. Technical Architecture & Feasibility Assessment

🏗️ System Architecture

🛠️ Development Stack

⚠️ Technical Risks & Mitigation

```
# Phase 3 Scale Optimization & Ecosystem Platform
# Implement performance optimization, ecosystem APIs, and advanced features

# Backend: Performance Optimization
cd backend/app

# Create caching service
cat > services/cache_service.py << 'EOF'
import redis
import json
import pickle
from typing import Any, Optional, Union
from functools import wraps
import hashlib
from app.core.config import settings

class CacheService:
    def __init__(self):
        self.redis_client = redis.Redis.from_url(settings.REDIS_URL)
        self.default_ttl = 3600  # 1 hour

    def _generate_key(self, prefix: str, *args, **kwargs) -> str:
        """Generate cache key from arguments"""
        key_data = f"{prefix}:{args}:{sorted(kwargs.items())}"
        return hashlib.md5(key_data.encode()).hexdigest()

    def get(self, key: str) -> Optional[Any]:
        """Get value from cache"""
        try:
            data = self.redis_client.get(key)
            if data:
                return pickle.loads(data)
        except Exception:
            pass
        return None

    def set(self, key: str, value: Any, ttl: Optional[int] = None) -> bool:
        """Set value in cache"""
        try:
            data = pickle.dumps(value)
            return self.redis_client.setex(key, ttl or self.default_ttl, data)
        except Exception:
            return False

    def delete(self, key: str) -> bool:
        """Delete key from cache"""
        try:
            return bool(self.redis_client.delete(key))
        except Exception:
            return False

    def clear_pattern(self, pattern: str) -> int:
        """Clear all keys matching pattern"""
        try:
            keys = self.redis_client.keys(pattern)
            if keys:
                return self.redis_client.delete(*keys)
        except Exception:
            pass
        return 0

cache_service = CacheService()

def cached(prefix: str, ttl: Optional[int] = None):
    """Decorator for caching function results"""
    def decorator(func):
        @wraps(func)
        async def wrapper(*args, **kwargs):
            cache_key = cache_service._generate_key(prefix, *args, **kwargs)
            result = cache_service.get(cache_key)
            if result is not None:
                return result

            result = await func(*args, **kwargs)
            cache_service.set(cache_key, result, ttl)
            return result
        return wrapper
    return decorator
EOF

# Create API rate limiting
cat > middleware/rate_limiting.py << 'EOF'
from fastapi import Request, HTTPException
from fastapi.middleware.base import BaseHTTPMiddleware
import time
import redis
from app.core.config import settings

class RateLimitMiddleware(BaseHTTPMiddleware):
    def __init__(self, app, calls: int = 100, period: int = 60):
        super().__init__(app)
        self.calls = calls
        self.period = period
        self.redis_client = redis.Redis.from_url(settings.REDIS_URL)

    async def dispatch(self, request: Request, call_next):
        client_ip = request.client.host
        key = f"rate_limit:{client_ip}"

        current = self.redis_client.get(key)
        if current is None:
            self.redis_client.setex(key, self.period, 1)
        elif int(current) < self.calls:
            self.redis_client.incr(key)
        else:
            raise HTTPException(status_code=429, detail="Rate limit exceeded")

        response = await call_next(request)
        return response
EOF

# Create public API for ecosystem
cat > api/public_api.py << 'EOF'
from fastapi import APIRouter, Depends, HTTPException, Header
from sqlalchemy.orm import Session
from typing import List, Optional
from app.core.database import get_db
from app.models.api_key import APIKey
from app.services.cache_service import cached

router = APIRouter(prefix="/public/v1")

def verify_api_key(x_api_key: str = Header(...), db: Session = Depends(get_db)):
    api_key = db.query(APIKey).filter(APIKey.key == x_api_key, APIKey.is_active == True).first()
    if not api_key:
        raise HTTPException(status_code=401, detail="Invalid API key")
    return api_key

@router.get("/workflows")
@cached("public_workflows", ttl=300)
async def list_public_workflows(
    skip: int = 0,
    limit: int = 100,
    api_key: APIKey = Depends(verify_api_key),
    db: Session = Depends(get_db)
):
    """Public API to list workflows"""
    workflows = db.query(Workflow).filter(Workflow.is_public == True).offset(skip).limit(limit).all()
    return [{"id": w.id, "name": w.name, "description": w.description} for w in workflows]

@router.post("/workflows/{workflow_id}/execute")
async def execute_public_workflow(
    workflow_id: int,
    input_data: dict = {},
    api_key: APIKey = Depends(verify_api_key)
):
    """Public API to execute workflows"""
    # Check if workflow is public and user has permission
    execution_id = await workflow_engine.execute_workflow(workflow_id, input_data)
    return {"execution_id": execution_id}
EOF

# Frontend: Analytics Dashboard
cd ../../frontend/src

cat > components/AnalyticsDashboard.tsx << 'EOF'
import React, { useEffect, useState } from 'react';
import {
  Box,
  Card,
  CardContent,
  Typography,
  Grid,
  FormControl,
  InputLabel,
  Select,
  MenuItem
} from '@mui/material';
import {
  LineChart,
  Line,
  BarChart,
  Bar,
  PieChart,
  Pie,
  Cell,
  XAxis,
  YAxis,
  CartesianGrid,
  Tooltip,
  Legend,
  ResponsiveContainer
} from 'recharts';

interface AnalyticsData {
  workflow_executions: { date: string; count: number }[];
  success_rate: { date: string; rate: number }[];
  popular_workflows: { name: string; executions: number }[];
  error_types: { type: string; count: number }[];
}

const AnalyticsDashboard: React.FC = () => {
  const [data, setData] = useState<AnalyticsData | null>(null);
  const [timeRange, setTimeRange] = useState('7d');

  useEffect(() => {
    fetchAnalytics(timeRange);
  }, [timeRange]);

  const fetchAnalytics = async (range: string) => {
    try {
      const response = await fetch(`/api/analytics?range=${range}`);
      const analyticsData = await response.json();
      setData(analyticsData);
    } catch (error) {
      console.error('Error fetching analytics:', error);
    }
  };

  if (!data) return <Box>Loading...</Box>;

  const COLORS = ['#0088FE', '#00C49F', '#FFBB28', '#FF8042', '#8884D8'];

  return (
    <Box sx={{ p: 3 }}>
      <Typography variant="h4" gutterBottom>
        Analytics Dashboard
      </Typography>

      <FormControl sx={{ mb: 3, minWidth: 120 }}>
        <InputLabel>Time Range</InputLabel>
        <Select value={timeRange} onChange={(e) => setTimeRange(e.target.value)}>
          <MenuItem value="7d">7 Days</MenuItem>
          <MenuItem value="30d">30 Days</MenuItem>
          <MenuItem value="90d">90 Days</MenuItem>
        </Select>
      </FormControl>

      <Grid container spacing={3}>
        <Grid item xs={12} md={6}>
          <Card>
            <CardContent>
              <Typography variant="h6">Workflow Executions</Typography>
              <ResponsiveContainer width="100%" height={300}>
                <LineChart data={data.workflow_executions}>
                  <CartesianGrid strokeDasharray="3 3" />
                  <XAxis dataKey="date" />
                  <YAxis />
                  <Tooltip />
                  <Line type="monotone" dataKey="count" stroke="#8884d8" />
                </LineChart>
              </ResponsiveContainer>
            </CardContent>
          </Card>
        </Grid>

        <Grid item xs={12} md={6}>
          <Card>
            <CardContent>
              <Typography variant="h6">Success Rate</Typography>
              <ResponsiveContainer width="100%" height={300}>
                <LineChart data={data.success_rate}>
                  <CartesianGrid strokeDasharray="3 3" />
                  <XAxis dataKey="date" />
                  <YAxis />
                  <Tooltip />
                  <Line type="monotone" dataKey="rate" stroke="#82ca9d" />
                </LineChart>
              </ResponsiveContainer>
            </CardContent>
          </Card>
        </Grid>

        <Grid item xs={12} md={6}>
          <Card>
            <CardContent>
              <Typography variant="h6">Popular Workflows</Typography>
              <ResponsiveContainer width="100%" height={300}>
                <BarChart data={data.popular_workflows}>
                  <CartesianGrid strokeDasharray="3 3" />
                  <XAxis dataKey="name" />
                  <YAxis />
                  <Tooltip />
                  <Bar dataKey="executions" fill="#8884d8" />
                </BarChart>
              </ResponsiveContainer>
            </CardContent>
          </Card>
        </Grid>

        <Grid item xs={12} md={6}>
          <Card>
            <CardContent>
              <Typography variant="h6">Error Types</Typography>
              <ResponsiveContainer width="100%" height={300}>
                <PieChart>
                  <Pie
                    data={data.error_types}
                    dataKey="count"
                    nameKey="type"
                    cx="50%"
                    cy="50%"
                    outerRadius={80}
                    fill="#8884d8"
                    label
                  >
                    {data.error_types.map((entry, index) => (
                      <Cell key={`cell-${index}`} fill={COLORS[index % COLORS.length]} />
                    ))}
                  </Pie>
                  <Tooltip />
                </PieChart>
              </ResponsiveContainer>
            </CardContent>
          </Card>
        </Grid>
      </Grid>
    </Box>
  );
};

export default AnalyticsDashboard;
EOF

echo "Phase 3 scale optimization and ecosystem platform implementation complete!"
```

5. Investment Ask & Timeline

💰 Funding Requirements

📅 Critical Success Factors

📊 12-Month Revenue Projection