🧠 MACHINE BRAIN

BDI Agent Implementation Guide

Complete BDI Architecture for Quantum Devices + VNC + Jupyter Ecosystem

🏗️ Architecture Overview

Technical Core

- Quantum device integration
- BDI agent reasoning engine
- Multi-agent coordination
- Android native integration

VNC Interface

- Remote desktop access
- Real-time visualization
- Multi-client connectivity
- Secure authentication

Jupyter Hub

- Interactive development
- Real-time code execution
- Data analysis workflows
- Collaborative notebooks

🚀 Installation Guide

Step 1: Termux Setup

```
# Update Termux packages
pkg update && pkg upgrade -y

# Install essential packages
pkg install -y \
    python \
    python-pip \
    git \
    wget \
    curl \
    openssh \
    tmux \
    vim \
    nano \
    htop \
    neofetch

# Install build tools
pkg install -y \
    clang \
    make \
    cmake \
    pkg-config \
    libffi \
    openssl

# Setup storage access
termux-setup-storage

# Create project directory
mkdir -p ~/machine_brain
cd ~/machine_brain
```

Step 2: VNC Configuration

```
# Install VNC server
pkg install -y tigervnc

# Install desktop environment
pkg install -y \
    xfce4 \
    xfce4-terminal \
    dbus-x11 \
    fonts-dejavu

# Configure VNC password
vncpasswd

# Create VNC startup script
mkdir -p ~/.vnc
cat > ~/.vnc/xstartup << 'EOF'
#!/data/data/com.termux/files/usr/bin/bash
unset SESSION_MANAGER
unset DBUS_SESSION_BUS_ADDRESS
exec startxfce4
EOF

chmod +x ~/.vnc/xstartup

# Start VNC server
vncserver :1 -geometry 1920x1080 -depth 24

# To stop VNC server
# vncserver -kill :1
```

Step 3: BDI Agent Core Setup

```
# Create virtual environment
python -m venv ~/machine_brain/venv
source ~/machine_brain/venv/bin/activate

# Install BDI framework dependencies
pip install --upgrade pip
pip install \
    numpy \
    scipy \
    networkx \
    asyncio \
    aiohttp \
    websockets \
    pydantic \
    loguru

# Install quantum computing libraries
pip install \
    qiskit \
    qiskit-aer \
    cirq \
    pennylane

# Install Android integration
pip install \
    pyjnius \
    plyer

# Clone BDI agent framework
cd ~/machine_brain
git clone https://github.com/machine-brain/bdi-agent.git
cd bdi-agent
pip install -e .
```

🧠 BDI Core Implementation

Belief System

```
# ~/machine_brain/bdi-agent/src/beliefs/belief_system.py
from typing import Dict, Any, List, Optional, Set
from dataclasses import dataclass, field
from datetime import datetime
import asyncio
import json
from loguru import logger

@dataclass
class Belief:
    """Represents a single belief in the BDI system"""
    key: str
    value: Any
    confidence: float = 1.0
    timestamp: datetime = field(default_factory=datetime.now)
    source: str = "unknown"
    metadata: Dict[str, Any] = field(default_factory=dict)

    def update(self, value: Any, confidence: float = None, source: str = None):
        """Update belief with new information"""
        self.value = value
        if confidence is not None:
            self.confidence = confidence
        if source is not None:
            self.source = source
        self.timestamp = datetime.now()

    def is_stale(self, max_age_seconds: float = 300) -> bool:
        """Check if belief is stale"""
        age = (datetime.now() - self.timestamp).total_seconds()
        return age > max_age_seconds

class BeliefSystem:
    """Manages the agent's beliefs about the world"""

    def __init__(self):
        self.beliefs: Dict[str, Belief] = {}
        self.belief_history: List[Belief] = []
        self.max_history = 1000
        self._lock = asyncio.Lock()

    async def add_belief(self, key: str, value: Any,
                         confidence: float = 1.0,
                         source: str = "unknown",
                         metadata: Dict = None):
        """Add or update a belief"""
        async with self._lock:
            if key in self.beliefs:
                old_belief = self.beliefs[key]
                self.belief_history.append(old_belief)
                old_belief.update(value, confidence, source)
                logger.debug(f"Updated belief: {key} = {value}")
            else:
                self.beliefs[key] = Belief(
                    key=key,
                    value=value,
                    confidence=confidence,
                    source=source,
                    metadata=metadata or {}
                )
                logger.debug(f"Added belief: {key} = {value}")

            # Trim history if needed
            if len(self.belief_history) > self.max_history:
                self.belief_history = self.belief_history[-self.max_history:]

    async def get_belief(self, key: str) -> Optional[Belief]:
        """Retrieve a belief by key"""
        async with self._lock:
            return self.beliefs.get(key)

    async def get_value(self, key: str, default: Any = None) -> Any:
        """Get belief value directly"""
        belief = await self.get_belief(key)
        return belief.value if belief else default

    async def remove_belief(self, key: str):
        """Remove a belief"""
        async with self._lock:
            if key in self.beliefs:
                del self.beliefs[key]
                logger.debug(f"Removed belief: {key}")

    async def query_beliefs(self, pattern: str) -> Dict[str, Belief]:
        """Query beliefs matching a pattern"""
        async with self._lock:
            return {k: v for k, v in self.beliefs.items() if pattern in k}

    async def get_all_beliefs(self) -> Dict[str, Belief]:
        """Get all current beliefs"""
        async with self._lock:
            return self.beliefs.copy()

    async def clear_stale_beliefs(self, max_age_seconds: float = 300):
        """Remove stale beliefs"""
        async with self._lock:
            stale_keys = [k for k, v in self.beliefs.items()
                          if v.is_stale(max_age_seconds)]
            for key in stale_keys:
                del self.beliefs[key]
            logger.debug(f"Cleared {len(stale_keys)} stale beliefs")

    async def to_dict(self) -> Dict[str, Any]:
        """Serialize beliefs to dictionary"""
        async with self._lock:
            return {
                k: {
                    "value": v.value,
                    "confidence": v.confidence,
                    "timestamp": v.timestamp.isoformat(),
                    "source": v.source,
                    "metadata": v.metadata
                }
                for k, v in self.beliefs.items()
            }
```

Desire Engine

```
# ~/machine_brain/bdi-agent/src/desires/desire_engine.py
from typing import Dict, List, Optional, Callable, Any
from dataclasses import dataclass, field
from enum import Enum
import asyncio
from loguru import logger

class DesirePriority(Enum):
    CRITICAL = 5
    HIGH = 4
    MEDIUM = 3
    LOW = 2
    BACKGROUND = 1

@dataclass
class Desire:
    """Represents a goal or desire"""
    name: str
    priority: DesirePriority
    condition: Callable[[], bool]
    utility: float = 1.0
    deadline: Optional[float] = None
    dependencies: List[str] = field(default_factory=list)
    metadata: Dict[str, Any] = field(default_factory=dict)

    def is_satisfied(self) -> bool:
        """Check if desire is satisfied"""
        return self.condition()

class DesireEngine:
    """Manages the agent's desires and goals"""

    def __init__(self):
        self.desires: Dict[str, Desire] = {}
        self.active_desires: List[str] = []
        self._lock = asyncio.Lock()

    async def add_desire(self, desire: Desire):
        """Add a new desire"""
        async with self._lock:
            self.desires[desire.name] = desire
            logger.debug(f"Added desire: {desire.name} (priority: {desire.priority.name})")

    async def remove_desire(self, name: str):
        """Remove a desire"""
        async with self._lock:
            if name in self.desires:
                del self.desires[name]
                if name in self.active_desires:
                    self.active_desires.remove(name)
                logger.debug(f"Removed desire: {name}")

    async def evaluate_desires(self) -> List[Desire]:
        """Evaluate and prioritize desires"""
        async with self._lock:
            # Filter unsatisfied desires
            unsatisfied = [d for d in self.desires.values()
                           if not d.is_satisfied()]

            # Sort by priority and utility
            sorted_desires = sorted(
                unsatisfied,
                key=lambda d: (d.priority.value, d.utility),
                reverse=True
            )

            # Update active desires
            self.active_desires = [d.name for d in sorted_desires]

            return sorted_desires

    async def get_active_desires(self) -> List[Desire]:
        """Get currently active desires"""
        async with self._lock:
            return [self.desires[name] for name in self.active_desires
                    if name in self.desires]

    async def get_highest_priority_desire(self) -> Optional[Desire]:
        """Get the highest priority unsatisfied desire"""
        desires = await self.evaluate_desires()
        return desires[0] if desires else None
```

Intention System

```
# ~/machine_brain/bdi-agent/src/intentions/intention_system.py
from typing import Dict, List, Optional, Callable, Any
from dataclasses import dataclass, field
from enum import Enum
import asyncio
from loguru import logger

class IntentionStatus(Enum):
    PENDING = "pending"
    EXECUTING = "executing"
    SUSPENDED = "suspended"
    COMPLETED = "completed"
    FAILED = "failed"

@dataclass
class Plan:
    """Represents a plan to achieve an intention"""
    name: str
    steps: List[Callable]
    context_condition: Callable[[], bool]
    success_condition: Callable[[], bool]
    failure_condition: Callable[[], bool]

@dataclass
class Intention:
    """Represents a committed plan of action"""
    desire_name: str
    plan: Plan
    status: IntentionStatus = IntentionStatus.PENDING
    current_step: int = 0
    result: Any = None
    error: Optional[str] = None

class IntentionSystem:
    """Manages the agent's intentions and plan execution"""

    def __init__(self):
        self.intentions: Dict[str, Intention] = {}
        self.plan_library: Dict[str, List[Plan]] = {}
        self._lock = asyncio.Lock()

    def register_plan(self, desire_name: str, plan: Plan):
        """Register a plan for a desire"""
        if desire_name not in self.plan_library:
            self.plan_library[desire_name] = []
        self.plan_library[desire_name].append(plan)
        logger.debug(f"Registered plan '{plan.name}' for desire '{desire_name}'")

    async def select_plan(self, desire_name: str) -> Optional[Plan]:
        """Select an applicable plan for a desire"""
        plans = self.plan_library.get(desire_name, [])
        for plan in plans:
            if plan.context_condition():
                return plan
        return None

    async def commit_intention(self, desire_name: str) -> Optional[Intention]:
        """Commit to an intention for a desire"""
        async with self._lock:
            plan = await self.select_plan(desire_name)
            if plan:
                intention = Intention(desire_name=desire_name, plan=plan)
                self.intentions[desire_name] = intention
                logger.debug(f"Committed intention: {desire_name} with plan '{plan.name}'")
                return intention
            logger.warning(f"No applicable plan for desire: {desire_name}")
            return None

    async def execute_intention(self, desire_name: str) -> bool:
        """Execute the current step of an intention"""
        async with self._lock:
            intention = self.intentions.get(desire_name)
            if not intention:
                return False

            intention.status = IntentionStatus.EXECUTING

            try:
                if intention.current_step < len(intention.plan.steps):
                    step = intention.plan.steps[intention.current_step]
                    intention.result = await step() if asyncio.iscoroutinefunction(step) else step()
                    intention.current_step += 1

                # Check success
                if intention.plan.success_condition():
                    intention.status = IntentionStatus.COMPLETED
                    logger.debug(f"Intention completed: {desire_name}")
                    return True

                # Check failure
                if intention.plan.failure_condition():
                    intention.status = IntentionStatus.FAILED
                    logger.warning(f"Intention failed: {desire_name}")
                    return False

                return True

            except Exception as e:
                intention.status = IntentionStatus.FAILED
                intention.error = str(e)
                logger.error(f"Intention error: {desire_name} - {e}")
                return False

    async def suspend_intention(self, desire_name: str):
        """Suspend an intention"""
        async with self._lock:
            intention = self.intentions.get(desire_name)
            if intention:
                intention.status = IntentionStatus.SUSPENDED

    async def drop_intention(self, desire_name: str):
        """Drop an intention"""
        async with self._lock:
            if desire_name in self.intentions:
                del self.intentions[desire_name]
                logger.debug(f"Dropped intention: {desire_name}")
```

🌌 Quantum Cognitive Processing

Quantum Decision Engine

```
# ~/machine_brain/bdi-agent/src/quantum/decision_engine.py
import numpy as np
from typing import Dict, List, Tuple, Any
from qiskit import QuantumCircuit, Aer, execute
from qiskit.circuit.library import RealAmplitudes
from qiskit.algorithms.optimizers import SPSA
import asyncio
from loguru import logger

class QuantumDecisionEngine:
    """Quantum-enhanced decision making for BDI agents"""

    def __init__(self, num_qubits: int = 4):
        self.num_qubits = num_qubits
        self.backend = Aer.get_backend('qasm_simulator')
        self.shots = 1024
        self.circuit_cache = {}

    def create_decision_circuit(self, num_options: int) -> QuantumCircuit:
        """Create a quantum circuit for decision making"""
        qc = QuantumCircuit(self.num_qubits, self.num_qubits)

        # Initialize superposition
        for i in range(self.num_qubits):
            qc.h(i)

        # Add entanglement layer
        for i in range(self.num_qubits - 1):
            qc.cx(i, i + 1)

        # Add parameterized rotation layer
        ansatz = RealAmplitudes(self.num_qubits, reps=2)
        qc = qc.compose(ansatz)

        # Measure
        qc.measure(range(self.num_qubits), range(self.num_qubits))

        return qc

    async def quantum_choice(self, options: List[Any],
                             weights: List[float] = None) -> Any:
        """Make a quantum-enhanced choice between options"""
        if not options:
            return None

        num_options = len(options)
        if weights is None:
            weights = [1.0 / num_options] * num_options

        # Normalize weights
        total = sum(weights)
        weights = [w / total for w in weights]

        # Create or retrieve circuit
        if num_options not in self.circuit_cache:
            self.circuit_cache[num_options] = self.create_decision_circuit(num_options)

        qc = self.circuit_cache[num_options]

        # Execute circuit
        job = execute(qc, self.backend, shots=self.shots)
        result = job.result()
        counts = result.get_counts()

        # Map quantum results to options based on weights
        cumulative = 0
        quantum_value = np.random.random()
        for state, count in counts.items():
            cumulative += count / self.shots
            if cumulative >= quantum_value:
                index = int(state, 2) % num_options
                return options[index]

        return options[-1]

    async def quantum_utility_optimization(self,
                                           utility_function: callable,
                                           parameter_bounds: List[Tuple[float, float]]) -> Dict[str, float]:
        """Optimize utility function using quantum-inspired algorithm"""
        num_params = len(parameter_bounds)

        def cost_function(params):
            return -utility_function(params)

        optimizer = SPSA(maxiter=100)
        initial_point = np.random.random(num_params)

        result = optimizer.minimize(cost_function, initial_point)

        optimized_params = {}
        for i, (low, high) in enumerate(parameter_bounds):
            optimized_params[f"param_{i}"] = low + result.x[i] * (high - low)

        return optimized_params
```

Quantum Entanglement Network

```
# ~/machine_brain/bdi-agent/src/quantum/entanglement_network.py
import numpy as np
from typing import Dict, List, Set, Tuple
from qiskit import QuantumCircuit, Aer, execute
import asyncio
from loguru import logger

class EntanglementNetwork:
    """Manages quantum entanglement between agent components"""

    def __init__(self, max_qubits: int = 16):
        self.max_qubits = max_qubits
        self.backend = Aer.get_backend('statevector_simulator')
        self.entangled_pairs: Dict[str, Tuple[int, int]] = {}
        self.qubit_allocation: Set[int] = set()

    def allocate_qubit(self) -> int:
        """Allocate a qubit for entanglement"""
        for i in range(self.max_qubits):
            if i not in self.qubit_allocation:
                self.qubit_allocation.add(i)
                return i
        raise RuntimeError("No available qubits for entanglement")

    def release_qubit(self, qubit: int):
        """Release a qubit back to the pool"""
        self.qubit_allocation.discard(qubit)

    async def create_entangled_pair(self, pair_id: str) -> Tuple[int, int]:
        """Create an entangled pair of qubits"""
        q1 = self.allocate_qubit()
        q2 = self.allocate_qubit()

        qc = QuantumCircuit(2)
        qc.h(0)
        qc.cx(0, 1)

        job = execute(qc, self.backend)
        result = job.result()

        self.entangled_pairs[pair_id] = (q1, q2)
        logger.debug(f"Created entangled pair: {pair_id} ({q1}, {q2})")

        return (q1, q2)

    async def measure_entangled_pair(self, pair_id: str) -> Tuple[int, int]:
        """Measure an entangled pair"""
        if pair_id not in self.entangled_pairs:
            raise KeyError(f"Unknown entangled pair: {pair_id}")

        q1, q2 = self.entangled_pairs[pair_id]

        qc = QuantumCircuit(2, 2)
        qc.h(0)
        qc.cx(0, 1)
        qc.measure([0, 1], [0, 1])

        job = execute(qc, Aer.get_backend('qasm_simulator'), shots=1)
        result = job.result()
        counts = result.get_counts()

        measurement = list(counts.keys())[0]
        return (int(measurement[0]), int(measurement[1]))

    async def destroy_entangled_pair(self, pair_id: str):
        """Destroy an entangled pair and release qubits"""
        if pair_id in self.entangled_pairs:
            q1, q2 = self.entangled_pairs[pair_id]
            self.release_qubit(q1)
            self.release_qubit(q2)
            del self.entangled_pairs[pair_id]
            logger.debug(f"Destroyed entangled pair: {pair_id}")
```

🤖 Master Agent Implementation

Master BDI Agent

```
# ~/machine_brain/bdi-agent/src/agents/master_agent.py
import asyncio
from typing import Dict, Any, Optional
from loguru import logger

from beliefs.belief_system import BeliefSystem
from desires.desire_engine import DesireEngine, Desire, DesirePriority
from intentions.intention_system import IntentionSystem, Plan
from quantum.decision_engine import QuantumDecisionEngine
from quantum.entanglement_network import EntanglementNetwork

class MasterBDIAgent:
    """Master BDI agent with quantum-enhanced reasoning"""

    def __init__(self, name: str = "MasterBrain"):
        self.name = name
        self.beliefs = BeliefSystem()
        self.desires = DesireEngine()
        self.intentions = IntentionSystem()
        self.quantum_decision = QuantumDecisionEngine()
        self.entanglement = EntanglementNetwork()
        self.running = False
        self.cycle_count = 0

    async def initialize(self):
        """Initialize the agent"""
        logger.info(f"Initializing {self.name}...")

        # Set initial beliefs
        await self.beliefs.add_belief("agent_name", self.name)
        await self.beliefs.add_belief("status", "initializing")

        # Register default plans
        self._register_default_plans()

        logger.info(f"{self.name} initialized")

    def _register_default_plans(self):
        """Register default plans for common desires"""
        # Example: Maintain connection plan
        maintain_connection = Plan(
            name="maintain_connection",
            steps=[self._check_connection, self._reconnect_if_needed],
            context_condition=lambda: True,
            success_condition=lambda: self.beliefs.beliefs.get("connected", False),
            failure_condition=lambda: False
        )
        self.intentions.register_plan("maintain_connection", maintain_connection)

    async def _check_connection(self):
        """Check connection status"""
        connected = await self.beliefs.get_value("connected", False)
        logger.debug(f"Connection check: {connected}")

    async def _reconnect_if_needed(self):
        """Reconnect if needed"""
        connected = await self.beliefs.get_value("connected", False)
        if not connected:
            logger.info("Attempting reconnection...")
            await self.beliefs.add_belief("connected", True)

    async def perceive(self, percepts: Dict[str, Any]):
        """Process perceptions and update beliefs"""
        for key, value in percepts.items():
            await self.beliefs.add_belief(key, value, source="perception")

    async def deliberate(self):
        """Deliberate about desires and commit to intentions"""
        # Evaluate desires
        prioritized = await self.desires.evaluate_desires()

        if prioritized:
            # Use quantum decision for ambiguous choices
            if len(prioritized) > 1:
                top_desires = prioritized[:3]
                chosen = await self.quantum_decision.quantum_choice(
                    top_desires,
                    [d.utility for d in top_desires]
                )
            else:
                chosen = prioritized[0]

            # Commit to intention
            await self.intentions.commit_intention(chosen.name)

    async def act(self):
        """Execute current intentions"""
        active = await self.desires.get_active_desires()
        for desire in active:
            await self.intentions.execute_intention(desire.name)

    async def run_cycle(self):
        """Run one BDI cycle"""
        self.cycle_count += 1
        logger.debug(f"Cycle {self.cycle_count}")

        # Perceive
        percepts = {"cycle": self.cycle_count}
        await self.perceive(percepts)

        # Deliberate
        await self.deliberate()

        # Act
        await self.act()

    async def run(self, max_cycles: int = None):
        """Run the agent"""
        self.running = True
        await self.initialize()

        while self.running:
            if max_cycles and self.cycle_count >= max_cycles:
                break
            await self.run_cycle()
            await asyncio.sleep(0.1)

    async def shutdown(self):
        """Shutdown the agent"""
        logger.info(f"Shutting down {self.name}...")
        self.running = False
        await self.beliefs.add_belief("status", "shutdown")

if __name__ == "__main__":
    agent = MasterBDIAgent()
    asyncio.run(agent.run(max_cycles=100))
```

📓 Jupyter Integration

Real-time Monitoring Notebook

```
{
 "cells": [
  {
   "cell_type": "markdown",
   "metadata": {},
   "source": [
    "# 🧠 Machine Brain - Real-time Monitoring\n",
    "\n",
    "Live monitoring of BDI agent state and quantum operations"
   ]
  },
  {
   "cell_type": "code",
   "execution_count": null,
   "metadata": {},
   "outputs": [],
   "source": [
    "import asyncio\n",
    "import json\n",
    "import websockets\n",
    "from datetime import datetime\n",
    "import matplotlib.pyplot as plt\n",
    "import numpy as np\n",
    "from IPython.display import clear_output\n",
    "\n",
    "# Connect to agent WebSocket\n",
    "WS_URL = 'ws://localhost:8765'"
   ]
  },
  {
   "cell_type": "code",
   "execution_count": null,
   "metadata": {},
   "outputs": [],
   "source": [
    "async def monitor_agent():\n",
    "    async with websockets.connect(WS_URL) as ws:\n",
    "        while True:\n",
    "            data = await ws.recv()\n",
    "            state = json.loads(data)\n",
    "            clear_output(wait=True)\n",
    "            print(f\"[{datetime.now()}] Cycle: {state.get('cycle', 0)}\")\n",
    "            print(f\"Beliefs: {len(state.get('beliefs', {}))}\")\n",
    "            print(f\"Active Desires: {state.get('active_desires', [])}\")\n",
    "            print(f\"Intentions: {state.get('intentions', {})}\")\n",
    "\n",
    "# Run monitoring\n",
    "# asyncio.run(monitor_agent())"
   ]
  }
 ],
 "metadata": {
  "kernelspec": {
   "display_name": "Python 3",
   "language": "python",
   "name": "python3"
  }
 },
 "nbformat": 4,
 "nbformat_minor": 4
}
```

Quantum Experiments Notebook

```
{
 "cells": [
  {
   "cell_type": "markdown",
   "metadata": {},
   "source": [
    "# ⚛️ Quantum Experiments\n",
    "\n",
    "Testing quantum decision algorithms"
   ]
  },
  {
   "cell_type": "code",
   "execution_count": null,
   "metadata": {},
   "outputs": [],
   "source": [
    "from qiskit import QuantumCircuit, Aer, execute\n",
    "from qiskit.visualization import plot_histogram\n",
    "import matplotlib.pyplot as plt\n",
    "\n",
    "# Create Bell state\n",
    "qc = QuantumCircuit(2, 2)\n",
    "qc.h(0)\n",
    "qc.cx(0, 1)\n",
    "qc.measure([0, 1], [0, 1])\n",
    "\n",
    "# Execute\n",
    "backend = Aer.get_backend('qasm_simulator')\n",
    "job = execute(qc, backend, shots=1024)\n",
    "result = job.result()\n",
    "counts = result.get_counts()\n",
    "\n",
    "plot_histogram(counts)"
   ]
  }
 ],
 "metadata": {
  "kernelspec": {
   "display_name": "Python 3",
   "language": "python",
   "name": "python3"
  }
 },
 "nbformat": 4,
 "nbformat_minor": 4
}
```

⚡ Performance Optimization

Android Configuration

Memory Optimization

```
# ~/machine_brain/config/memory.conf
# Memory optimization settings

# Limit Python memory usage
export PYTHONMALLOC=malloc
export MALLOC_ARENA_MAX=2

# Configure swap
# Add to /etc/sysctl.conf
vm.swappiness=10
vm.vfs_cache_pressure=50

# Limit concurrent processes
ulimit -n 4096
ulimit -u 256

# Memory-efficient Python settings
export PYTHONOPTIMIZE=2
export PYTHONDONTWRITEBYTECODE=1
```

CPU Optimization

```
# ~/machine_brain/config/cpu.conf
# CPU optimization settings

# Set CPU governor to performance
# Requires root
# echo performance > /sys/devices/system/cpu/cpu*/cpufreq/scaling_governor

# Limit CPU usage for background processes
nice -n 10 python agent.py

# Use specific CPU cores
taskset -c 0-3 python agent.py

# Thread configuration
export OMP_NUM_THREADS=4
export MKL_NUM_THREADS=4
export NUMEXPR_NUM_THREADS=4
```

Resource Monitoring Dashboard

🚀 Deployment Guide

Quick Start Deployment

```
#!/data/data/com.termux/files/usr/bin/bash
# ~/machine_brain/deploy.sh
# Machine Brain Deployment Script

set -e

echo "🧠 Machine Brain Deployment"
echo "=========================="

# Configuration
PROJECT_DIR="$HOME/machine_brain"
VENV_DIR="$PROJECT_DIR/venv"
LOG_DIR="$PROJECT_DIR/logs"

# Create directories
mkdir -p "$LOG_DIR"

# Activate virtual environment
source "$VENV_DIR/bin/activate"

# Start VNC server
echo "Starting VNC server..."
vncserver :1 -geometry 1920x1080 -depth 24

# Start Jupyter
echo "Starting Jupyter..."
jupyter lab --no-browser --port=8888 --ip=0.0.0.0 \
    --NotebookApp.token='' \
    --NotebookApp.password='' \
    > "$LOG_DIR/jupyter.log" 2>&1 &

# Start BDI agent
echo "Starting BDI agent..."
cd "$PROJECT_DIR/bdi-agent"
python src/agents/master_agent.py > "$LOG_DIR/agent.log" 2>&1 &

# Start WebSocket server for monitoring
echo "Starting WebSocket server..."
python src/server/websocket_server.py > "$LOG_DIR/websocket.log" 2>&1 &

echo ""
echo "✅ Deployment complete!"
echo ""
echo "Access points:"
echo "  VNC: localhost:5901"
echo "  Jupyter: http://localhost:8888"
echo "  WebSocket: ws://localhost:8765"
echo ""
echo "Logs: $LOG_DIR"
```

Systemd Service (for rooted devices)

```
# /etc/systemd/system/machine-brain.service
[Unit]
Description=Machine Brain BDI Agent
After=network.target

[Service]
Type=simple
User=root
WorkingDirectory=/data/data/com.termux/files/home/machine_brain
ExecStart=/data/data/com.termux/files/home/machine_brain/venv/bin/python src/agents/master_agent.py
Restart=always
RestartSec=10
StandardOutput=append:/data/data/com.termux/files/home/machine_brain/logs/agent.log
StandardError=append:/data/data/com.termux/files/home/machine_brain/logs/agent.log

[Install]
WantedBy=multi-user.target
```

🎉 Machine Brain Ready!

Complete BDI agent architecture with quantum computing, VNC, Jupyter, and Android integration.