```
CREATE DATABASE maquin_f1;

USE maquin_f1;
CREATE TABLE tb_paises (
   codigoP INT PRIMARY KEY,
   nomeP VARCHAR(100) NOT NULL
);

CREATE TABLE tb_equipes (
   sigla VARCHAR(10) PRIMARY KEY,
   nomeE VARCHAR(100) NOT NULL,
   cod_pais INT,
   FOREIGN KEY (cod_pais) REFERENCES tb_paises(codigoP)
);

CREATE TABLE tb_pilotos (
   numero INT PRIMARY KEY,
   nomePI VARCHAR(100) NOT NULL,
   cod_pais INT,
   sigla_equipe VARCHAR(10),
   FOREIGN KEY (cod_pais) REFERENCES tb_paises(codigoP),
   FOREIGN KEY (sigla_equipe) REFERENCES tb_equipes(sigla)
);

CREATE TABLE tb_corridas (
   sigla_gp VARCHAR(10) PRIMARY KEY,
   nome_gp VARCHAR(100) NOT NULL,
   cod_pais INT,
```

```
  qtd_voltas INT,
  FOREIGN KEY (cod_pais) REFERENCES tb_paises(codigoP)
);

CREATE TABLE tb_participantes (
  sigla_gp VARCHAR(10),
  num_piloto INT,
  posicao_largada INT,
  PRIMARY KEY (sigla_gp, num_piloto),
  FOREIGN KEY (sigla_gp) REFERENCES tb_corridas(sigla_gp),
  FOREIGN KEY (num_piloto) REFERENCES tb_pilotos(numero)
);

-- PAISES
INSERT INTO tb_paises (codigoP, nomeP) VALUES
(55, 'Brasil'),
(64, 'Italia'),
(67, 'Franca'),
(45, 'Inglaterra'),
(22, 'Jamaica'),
(13, 'Holanda'),
(35, 'Australia'),
(1, 'Estados Unidos'),
(49, 'Alemanha'),
(81, 'Japao');

-- EQUIPES
INSERT INTO tb_equipes (sigla, nomeE, cod_pais) VALUES
```

('RDR', 'Red Bull Racing', 13),

('GDR', 'Guarana Driver Racing', 55),

('MCL', 'Mclaren', 45),

('HAS', 'Hass', 45),

('MER', 'Mercedes', 49),

('WIL', 'Wilians', 67),

('FER', 'Ferrari', 64);

-- PILOTOS

INSERT INTO tb_pilotos (numero, nomePI, cod_pais, sigla_equipe) VALUES

(1, 'Gabriel Bortoleto', 55, 'GDR'),

(16, 'Jair Bolsonaro', 55, 'GDR'),

(12, 'Roberto Carlos', 55, 'MCL'),

('22', 'Fravio Bolsonabo', '55', 'FER'),

('23', 'Juiz Infarto Lole', '55', 'HAS'),

(44, 'Adalberto Ferreira junior', 13, 'RDR'),

(81, 'Jailson Mendes', 67, 'WIL'),

(13, 'Gomersindo Oliveira Pinto', 64, 'FER'),

(55, 'Carlo Ancelot', 64, 'FER'),

(21, 'Lomaine Ylamao', 45, 'HAS'),

(4, 'Fred Merculis', 49, 'MER'),

(15, 'Mbape Frinkeing', 64, 'MER'),

(67, 'Kiravatchkela Oliver', 67, 'MCL');

-- CORRIDAS

INSERT INTO tb_corridas (sigla_gp, nome_gp, cod_pais, qtd_voltas) VALUES

('BRA', 'GP do Brasil', 55, 63),

('ITA', 'GP da Italia', 64, 61),

```
('JAP', 'GP do Japao', 81, 67),
('EUA', 'GP dos Estados Unidos', 1, 55),
('ALM', 'GP da Alemanha', 49, 47),
('FRA', 'GP da Franca', 67, 49);

-- PARTICIPANTES CORRIGIDO - AGORA SÓ COM PILOTOS QUE EXISTEM
INSERT INTO tb_participantes (sigla_gp, num_piloto, posicao_largada) VALUES
('BRA', 1, 1),
('BRA', 16, 2),
('BRA', 13, 3),
('BRA', 44, 4),
('BRA', 55, 5),
('BRA', 4, 6),
('BRA', 81, 7),
('BRA', 21, 8),
('BRA', 15, 9),
('BRA', 67, 10);

INSERT INTO tb_participantes (sigla_gp, num_piloto, posicao_largada) VALUES
('ITA', 16, 1),
('ITA', 1, 2),
('ITA', 55, 3),
('ITA', 13, 4),
('ITA', 4, 5),
('ITA', 44, 6),
('ITA', 81, 7),
('ITA', 21, 8);
```

```
ALTER TABLE tb_pilotos ADD salario DECIMAL(10,2);

UPDATE tb_pilotos SET salario = 95000.00 WHERE numero = 1;
UPDATE tb_pilotos SET salario = 70000.00 WHERE numero = 16;
UPDATE tb_pilotos SET salario = 120000.00 WHERE numero = 44;
UPDATE tb_pilotos SET salario = 65000.00 WHERE numero = 81;
UPDATE tb_pilotos SET salario = 80000.00 WHERE numero = 13;
UPDATE tb_pilotos SET salario = 80000.00 WHERE numero = 55;
UPDATE tb_pilotos SET salario = 70000.00 WHERE numero = 21;
UPDATE tb_pilotos SET salario = 100000.00 WHERE numero = 4;
UPDATE tb_pilotos SET salario = 90000.00 WHERE numero = 15;
UPDATE tb_pilotos SET salario = 72000.00 WHERE numero = 67;

-- Queries
select nomeP as 'Paises'
from tb_paises
where nomeP like "b%l";

SELECT tb_pilotos.nomePI as 'Pilotos', tb_paises.nomeP as 'Paises'
FROM tb_pilotos, tb_paises
WHERE tb_pilotos.cod_pais = tb_paises.codigoP
AND tb_paises.nomeP IN ('Brasil', 'Italia', 'Franca');

select nomePI as 'Piloto'
from tb_pilotos;

 -- Gp
SELECT nome_gp AS Grande_Premio, qtd_voltas AS Voltas
```

```
FROM tb_corridas;


SELECT nomePI as 'Piloto', salario
FROM tb_pilotos
WHERE salario >= 70000 and salario <= 100000;


-- media salarial
SELECT cod_pais as 'Pais', round(AVG(salario),2) AS "Media Salarial"
FROM tb_pilotos
GROUP BY cod_pais;


-- Valor salarial
SELECT DISTINCT tb_pilotos.salario AS "Salarios"
FROM tb_pilotos
ORDER BY tb_pilotos.salario ASC;
```