

08

Cyber Security
Codec Technologies India
Internship 2026

Network Traffic Analysis

Offline PCAP analyzer with 5 detectors

AT A GLANCE

378

Packets

1 (60 ports)

SYN scan

CV ~0.006

Beacon

50 in 3 s

DNS burst

1

Plaintext creds

8 / 8

Recorded tests

no (scapy)

Re-run here

VERDICT

TESTS 8/8

RECORDED RUN

DEPENDENCY UNAVAILABLE

DECLARED SYNTHETIC

DEFENSIVE ONLY


Objective & brief mapping

The brief asked for network traffic analysis. I built an offline analyzer on scapy that reads a PCAP and produces a protocol breakdown, top talkers, conversations, DNS/HTTP extraction, and five security detections. So it always runs and is testable, the project generates its own declared-synthetic PCAP embedding one of each threat; real captures are also supported.

Architecture

generate_pcap.py writes the synthetic capture (normal web + DNS plus injected scan/beacon/DNS-burst/creds/large-transfer). analyzer.py builds a PcapAnalyzer with the five detectors. report.py emits the markdown report, findings JSON and three PNG charts.

```
generate_pcap -> data/sample_traffic.pcap (SYNTHETIC)
analyzer: protocols, talkers, 5 detectors
report -> traffic_report.md + findings.json + PNGs
```



Packets over time with scan + beacon marked (results/packets_over_time.png).

Reproduction & artefacts

Everything below was produced by the project's own code in this container (or is the project's recorded run where a dependency is unavailable). The commands that regenerate it:

```
python3 main.py # generate synthetic pcap + analyze (~2.5 s)
python3 main.py path/to/real.pcap
python3 -m pytest tests/ -q # recorded: 8 passed (scapy unavailable here)
```

The artefacts each figure and table above are drawn from:

- **findings.json** — 5 detections
- **traffic_report.md** — analyst report
- **protocol_pie.png / top_talkers.png / packets_over_time.png** — charts

Method & implementation

SYN scan = one source sending bare SYNs to many ports with zero completed handshakes. Beacon = flows whose inter-arrival coefficient of variation is ≤ 0.15 over ≥ 6 events. DNS burst = ≥ 25 queries in 3 s. Plaintext creds = cleartext payloads with password= / Basic. Large transfer = flows over 80 KB. Detectors are heuristic and need tuning on real traffic.

Results

From results/findings.json over a 378-packet synthetic capture. Every planted threat was detected.

Detection	Result
Protocols	TCP 313, UDP 65, DNS 65, HTTP 41
SYN scan	192.168.10.66 -> .50 across 60 ports, 0 handshakes
Beacon	-> 198.51.100.77:443 every ~30 s, CV ~0.006
DNS burst	50 queries in a 3 s window
Plaintext creds	username/password over HTTP :80
Large transfer	~115 KB flow (80 x 1400 B)

Detector reasoning

Detector	Signal	Threshold
SYN scan	many ports, 0 handshakes	--
beacon	low inter-arrival CV	CV ≤ 0.15 , ≥ 6
DNS burst	queries/window	25 in 3 s
large transfer	bytes/flow	> 80 KB

Verification

Eswar Mahalingam
Cyber Security Intern
Ghaziabad, UP, India
+91-9360548243
eswarmba05313@gmail.com
linkedin.com/in/eswar-mahalingam

08

Cyber Security
Codec Technologies India
Internship 2026

Network Traffic Analysis

Offline PCAP analyzer with 5 detectors

AT A GLANCE

378

Packets

1 (60 ports)

SYN scan

CV ~0.006

Beacon

50 in 3 s

DNS burst

1

Plaintext creds

8 / 8

Recorded tests

no (scapy)

Re-run here

VERDICT

TESTS 8/8

RECORDED RUN

DEPENDENCY UNAVAILABLE

DECLARED SYNTHETIC

DEFENSIVE ONLY

Eswar Mahalingam

Cyber Security Intern
Ghaziabad, UP, India
+91-9360548243
eswarmba05313@gmail.com
linkedin.com/in/eswar-mahalingam

Tests not re-run here — scapy is unavailable in this container and both the analyzer and the tests import it at load. The recorded run is **8 passed**. I verified the findings JSON and the three PNG charts are present and match the reported counts.

Test group	Checks	Result (recorded)
Parsing	378 packets, protocol counts	PASS
Detectors	scan / beacon / DNS burst fire	PASS
Content	creds + large transfer found	PASS
Recorded total	8 tests	8/8

How I re-ran & verified in this container

pytest is not installed here, so I re-ran each suite with a small unittest-style runner that discovers tests/test_*.py, resolves fixtures (conftest, module-level @pytest.fixture, tmp_path, monkeypatch, request) and records pass / fail / skip. I executed nothing against a network target — every project uses localhost lab targets or synthetic data, and I kept it that way. Where a project imports a dependency that is unavailable in this container, I did not fabricate a pass: I state that the tests were not re-run here and cite the project's own recorded run instead.

Constraint here	How I handled it
pytest not installed	unittest-style runner over tests/
network targets	never contacted; localhost / synthetic only
scapy / bcrypt / argon2 unavailable	recorded run cited, not fabricated

Real-tool mapping, limitations & next steps

The analyzer is scapy-based; the same detectors are expressed as Snort rules for a real sensor.

Ran here (recorded)	Real tool	Note
scapy PCAP analyzer	Wireshark / tshark	interactive equivalent
5 heuristic detectors	Snort/Suricata rules	example rules in README
synthetic capture	tcpdump on your net	sudo tcpdump -i eth0 -w cap.pcap

Ethics, data integrity & declared substitutions

Defensive. **Data integrity:** the bundled capture is synthetic and declared as such — all addresses are RFC 5737 documentation / RFC 1918 private ranges; no real host or user is represented. **Declared substitution:** scapy is unavailable here, so the analyzer/tests were not re-run in this container; the recorded pass stands. Live capture (tcpdump/Wireshark) and the documented Snort rules must only be used on networks you own or are authorised to monitor.

Learnings

Writing the reasoning for each detector — especially the coefficient-of-variation beacon test — taught me that the hard part of detection is not the pattern but the false-positive story (NTP and keepalives also look beacon-like). Encoding the threat model explicitly per detector is what makes the output defensible.

Honest limitations & data-integrity notes

Honest limitations of this build, and how it maps to production tooling:

- Detectors are heuristic and threshold-based; real traffic needs tuning.
- No TCP reassembly — HTTP/credential spotting works on single packets only.
- Plaintext-credential detection is limited to obvious form/Basic-auth markers.
- Scapy loads the whole pcap into memory, so very large captures won't scale.
- Beacon detector uses inter-arrival coefficient of variation (CV <= 0.15).
- All addresses are RFC 5737 documentation / RFC 1918 private ranges.
- SYN scan = many ports, zero completed handshakes from one source.
- DNS burst threshold: >= 25 queries within a 3 s sliding window.
- Synthetic capture holds 378 packets with one of each threat.
- Protocols: TCP 313, UDP 65, DNS 65, HTTP 41.
- SYN scan: 192.168.10.66 -> .50 across 60 ports, 0 handshakes.
- Beacon: ~30 s interval over 12 events, CV ~0.006.
- DNS burst: 50 queries in a 3 s window.
- Plaintext creds captured over HTTP :80.
- Large transfer ~115 KB (80 x 1400-byte packets).
- Snort rule concepts documented for a real sensor.
- Reference: scapy docs; Snort rule writing; Wireshark User's Guide.
- Reference: tcpdump manual; RFC 5737 documentation IP ranges.
- Reference: MITRE ATT&CK; Application Layer Protocol / C2 (TA0011).
- Recorded run: 8/8 tests pass (scapy unavailable here).
- The bundled capture is synthetic and declared as such.