WorkRadar

AI Workflow Document

Author · Eswar Mahalingam
Version 1.0 · 12 Oct 2026
Companion to the WorkRadar PRD

AT A GLANCE

- **1 build prompt**: the assignment brief plus two sets of session notes
- **1 AI agent**: Claude, for PRD, design, code, tests and documents
- **5 deliverables**: PRD, UX boards, MVP, this document, demo script
- **621 lines** of app source, with no third-party JavaScript
- **6 changes** between the first build and this version

ACTUAL BUILD SEQUENCE

1. Read the brief and both session notes
2. Model the mock data: items, people, events
3. Write the priority score
4. Build the app: dashboard, feed, details, search, actions
5. Run it in a headless browser and review screenshots
6. Fix what the review found
7. Draw the five UX boards from the same tokens
8. Write the PRD and this document

SESSION METHOD APPLIED

- **Front end first.** No sign-in, backend or database in phase 0.
- **Build small, inspect, continue.** Every stage was run before the next.
- **State the constraints.** Stack, scope and data were fixed up front.
- **Prototype, not product.** Production gaps are listed in section 07.

WHAT WORKED

- Pasting the whole brief, with its constraints, kept the scope tight.
- The session notes acted as the build method.
- Looking at rendered screens caught errors that reading code would miss.

How WorkRadar was built with AI

One brief, one AI agent, five deliverables. This document records which tool did what, the prompts that mattered, what changed after the first generation, and the trade-offs behind the MVP.

01 AI tools used

TOOL	USED FOR	WHY THIS TOOL
Claude (model `claude-fable-5-1`) in the Claude app, with a code workspace	PRD draft, mock data, app code, test run, PDF typesetting	One agent holds the brief and the course method from requirement to build, so nothing is lost in hand-offs
Claude Design canvas	Five high-fidelity UX boards	The brief accepts a Claude design file; boards reuse the app's exact colours and type
Claude artifact hosting	Live link to the working MVP	A shareable app without a deploy pipeline
Claude inside the product	"Write with Claude" on the dashboard brief	A real model call on the ranked items; the app falls back to rules when it is unavailable
Playwright with headless Chromium, driven by Claude	Scripted click-through and screenshots	The sessions' rule: review each output, do not assume it works

Considered and not used: Figma AI, Google Stitch and Lovable. A single tool kept the PRD, the designs and the code consistent with each other.

02 Significant prompts

PROMPT 1 · THE BUILD PROMPT

The full assignment brief (context, the six steps, "mock data is acceptable") pasted together with the notes from two sessions: vibe coding, and skills plus the PRD-to-prototype workflow. No separate instructions were added. **Effect:** Claude scoped phase 0 to a front-end-only app on mock data and built it in stages, as the sessions teach.

PROMPT 2 · STANDING WORKING INSTRUCTIONS

Saved preferences that apply to all my work with Claude: direct and structured output, navy and gold document style, Indian-context examples, pages without empty space. **Effect:** the document design, and mock data built around UPI refunds, COD regression, pincodes and rupee amounts.

PROMPT 3 · THE IN-PRODUCT PROMPT THAT WRITES THE DASHBOARD BRIEF

```
You write the morning brief inside WorkRadar, a tool for engineering managers. Using
ONLY the JSON below (ranked open work items, highest priority first), write a brief of
at most 90 words in plain text, no markdown, no lists. Cover in order: what the manager
must do first and why, who is blocked on what and for how long, what has no owner, and
one closing line on the release risk if any. Be specific and use names. Do not invent
facts.  [JSON of the top 12 ranked items follows]
```

03 What AI generated

DELIVERABLE	WHAT CLAUDE PRODUCED	SIZE
Working MVP	Dashboard, brief, radar, priority feed, item details, search, Assign / Mark done / Snooze with Undo, empty and error states, light and dark themes, phone layout	3 source files, 621 lines, 62 KB built
Mock data	A fictional Checkout squad: work items with threads, digests and next steps across Slack, Jira, GitHub and email	17 items, 9 events, 6 teammates
Priority model	Additive, visible score with seven factor groups and four tiers	Capped at 99
UX design	Dashboard, Priority Feed, Item Details, Search, Empty and Error States	5 boards, 1360 px wide
PRD	Problem, users, personas, journey, pain points, metrics, scope, assumptions, features	2 pages
Test script	Automated run of every action, with screenshots at desktop and phone width	1 script: desktop, phone, dark

WorkRadar

Changes, trade-offs and checks

Sections 04 to 07

WHO DID WHAT

- **Me:** chose the brief as the single source of requirements, supplied the session notes and standing style rules, review the output and present the demo.
- **AI:** drafted and built everything listed in section 03, then tested and corrected its own first build.

RESPONSIBLE USE

- Every person, ticket, message and number in the app is fictional.
- No company or customer data was given to any AI tool.
- AI-written text is labelled in the interface.
- Item digests are labelled as sample text, because they are pre-written.

LIMITS OF THIS MVP

- Single user; nothing is shared between browsers.
- Score weights are judgement, not yet tuned on real behaviour.
- Source links do not open the real tools.
- No accessibility audit beyond keyboard focus and contrast choices.

FUTURE IMPROVEMENTS

- Read-only Jira and GitHub connectors, then Slack and email
- Live AI digest per thread
- "Ranked wrong" feedback to tune weights
- 9 AM brief pushed to Slack
- Write-back actions in source tools
- Roll-up across squads

SOURCE FILES

- `src/data.js` mock data
- `src/app.js` scoring, views, actions
- `src/styles.css` tokens and layout
- `index.html` built app, opens offline

04 What changed after the first generation

IN THE FIRST BUILD	PROBLEM FOUND IN REVIEW	CHANGE MADE
Incident base weight was 40	A live latency incident with customer impact scored 52, below two blockers and a decision	Raised to 58, so the incident is Critical at 70
Brief counted items that "need you" with its own rule	Brief said 6 while the panel beside it listed 7	One shared rule feeds both
Radar radius used the full chart width	Low-priority dots fell outside the outer ring	Radius rescaled to stay inside the rings
Summary lower-cased the first letter of each blocker	"IT to restore access" became "iT to restore access"	Leading acronyms are left as written
Mock text used fixed clock times such as 10:40	They clashed with relative timestamps when the demo is opened at another hour	Rewritten as "since the morning deploy"
PRD draft ran past two pages	The brief sets a two-page limit	One metric dropped, non-goals merged into the plan

All six were found by reviewing screenshots and an automated run of the first build, then fixed and re-tested.

05 Key trade-offs

DECISION	CHOSEN	GIVEN UP	WHY
Stack	Plain HTML, CSS and JavaScript in one page	React or Next.js components and routing	No build step; opens from the ZIP; small enough to read in one sitting
Data	Mock data in a file	Live connectors	The brief allows it; connectors need sign-in, scopes and security review
Ranking	Visible additive rules	A learned model	A manager must be able to explain a rank before trusting it; there is no training data yet
AI brief	Model call with a rule-based fallback	Model-only summary	The app still answers the four questions offline or when the model is unavailable
Item digests	Pre-written sample text, labelled	Live generation per thread	No real threads exist in mock data; a label is more honest than a fake call
State	Saved in the browser	Shared database	Single-user demo; multi-user state belongs to phase 1
Design tool	Claude Design canvas	Figma file	Same tokens as the code, no manual redraw
Sequence	Build first, PRD after	PRD-first sign-off	Faster for a solo MVP; the PRD documents decisions already tested. With a team, the PRD comes first

06 What was checked

- Assign, Mark done, Undo and Snooze change the feed as expected
- Search for "refund" returns 4 highlighted results; a nonsense query shows the no-results state
- Simulated Jira outage shows the banner, cached labels and the error state
- State survives a page reload
- No console errors; no sideways scroll at 400 px

Not yet checked: the "Write with Claude" call with a signed-in viewer, a screen-reader pass, and anything involving real connectors or load.

07 Before production

- **Security:** sign-in, least-privilege scopes, review of data flows
- **Scale:** test with real item volumes, not 17
- **Data handling:** an employer-approved AI tool; opt-in for DMs and email
- **Licensing:** fonts are under the SIL Open Font License; the app ships no third-party JavaScript
- **Dependencies:** each connector API can change or be withdrawn