
# GRU WITH SPATIAL PRIOR FOR HYPERSPECTRAL IMAGE CLASSIFICATION

**Erting Pan**<sup>1</sup>, Yong Ma<sup>1,2</sup>, Xiaobing Dai<sup>1,2</sup>, Fan Fan<sup>1,2</sup>, Jun Huang<sup>1,2</sup>, Xiaoguang Mei<sup>1,2</sup>, and Jiayi Ma<sup>1,2</sup>

<sup>1</sup>Electronic Information School, Wuhan University, Wuhan 430072,China <sup>2</sup> Institute of Aerospace Science and Technology, Wuhan university, Wuhan, 430072, China




#### **Motivations**






## WUHAN UNIVERSITY


#### **Motivations**















## **Proposed Method**

#### Overall Architecture






## **Fusion Spatial information**





## Proposed Method





## Experimental settings

 Compared Methods: SVM, CNN, RNN(band by band), RNN(all), SPGRU

Training & Testing Set: Pavia University & Pavia Center

Evaluate Criteria: OA, AA, kappa



### Performance

**Table 1**: Classification performance of different methods for the Pavia University dataset. Bold indicates the best result.


Label	SVM	CNN	RNN	RNN	SPGRU
		(2D)	(band by band)	(all)	
OA	84.43	89.20	91.68	97.24	98.38
AA	88.59	92.20	86.68	88.51	93.82
Kappa	79.94	85.91	88.84	92.34	95.49

**Table 2**: Classification performance of different methods for the Pavia Center dataset. Bold indicates the best result.

Label	SVM	CNN	RNN	RNN	SPGRU
		(2D)	(band by band)	(all)	
OA	84.48	86.20	96.83	97.24	99.73
AA	84.88	91.20	91.12	91.73	95.89
Kappa	83.0	68.91	95.81	96.09	99.18


#### Performance















- Propose a tiny effective model based on a single GRU
- Introduce a new way to fusion spatial information
- Competitive results and less computational cost.

Conclusion

## THANKS FOR YOUR ATTENTION

Erting Pan
Electronic Information School
Wuhan University
panerting@whu.edu.cn