REJIVAN — Comprehensive Feature Catalog, Added Capabilities & Recommended Technical Fixes

A Personal Prajñā Nurse for Every Family • Hack for Social Cause (HSC 2027) / VBYLD 2027 • Ministry of Youth Affairs & Sports & IIT Bombay

PROJECT SCOPE	REGIONAL ANCHOR	HSC SUBMISSION DEADLINE	REPOSITORY STATUS
Remote Patient Monitoring + Vision	Andaman & Nicobar Islands (UT)	15 October 2026	PUBLIC (MIT Licensed)

1. Executive Summary & Geographic Imperative (Andaman & Nicobar Islands)

ReJivan is an intelligent, dual-layer healthcare safety platform designed to bridge the severe medical accessibility gap across underserved and geographically isolated regions. The system combines **Remote Patient Monitoring (RPM)** via medically-approved wearable devices with an **edge-computed, privacy-first computer vision sentinel** that monitors vulnerable patients both at home and in hospital **Virtual Ward** settings.

The "Hack Local" Context: Andaman & Nicobar Healthcare Reality
The Andaman & Nicobar archipelago consists of 36 inhabited islands separated by vast stretches of open sea. The entire union territory relies on a single tertiary referral facility: **GB Pant Hospital in Port Blair**. Outer-island Primary Health Centres (PHCs) and Community Health Centres (such as Hut Bay on Little Andaman, Car Nicobar, and Diglipur) face critical specialist shortages. Evacuating a deteriorating elderly resident requires scheduled passenger ferries (taking 6 to 14 hours) or rare emergency helicopter sorties. ReJivan transforms ordinary homes into monitored clinical beds and empowers island PHCs with Virtual Ward capabilities, preventing catastrophic deteriorations before evacuation becomes impossible.

2. Complete Architecture Overview: Dual-Sentinel Protection Model

ReJivan solves the critical flaw of traditional single-channel monitors by unifying two completely independent clinical sensing modalities:

Layer 1: Continuous Bio-Telemetry (RPM)

- Continuous physiological monitoring: Heart Rate (HR), Oxygen Saturation (SpO2), Blood Pressure (BP), Temperature, and Blood Glucose.
- Deterministic **NEWS2 / MEWS** clinical deterioration score calculation.
- Natural 1.5s physiological drift engine with respiratory sinus arrhythmia and arterial baroreflex modeling.
- Fleet catalog of 11 FDA/CDSCO/CE certified medical wearables (e.g. SanketLife 12-lead ECG, Omron BP, FreeStyle Libre 3).

Layer 2: Edge Vision & Spatial Kinematics

- Ultra-low latency **Ultralytics YOLO-Pose** on local hardware (auto-detected NVIDIA CUDA GPU) tracking 17 COCO skeletal joints.
- **DPDP Act 2023 Compliance:** Zero video recording or off-site cloud streaming; physical camera LED turns OFF when monitoring is paused.
- Universal in-browser optical differencing fallback with multi-frame descent corroboration and floor-level gating.
- Bidirectional frame bridge (`/api/yolo/process_frame`) for seamless browser skeleton overlays.

3. Key System Milestones & Current Operational State

Subsystem	Runtime State	Core Technologies	Functional Verification
Web Application Portal	LIVE & STABLE	Node.js, Express, React 18, Tailwind CSS	Runs locally on `http://localhost:8080` and globally on Vercel at `https://rejivan2.vercel.app`.
Edge Vision Sentinel	ACTIVE (CUDA)	Python 3.12, PyTorch, YOLO11-Pose, OpenCV	Runs on port 5050 on the local NVIDIA CUDA GPU at 25–30 FPS with ~184 MB VRAM footprint.
Kinematics & Hypotheses	VERIFIED	Multimodal Bayesian Scoring Engine	100% pass rate across 23 false-positive lab scenarios and 7 kinematics unit tests.
Emergency Escalation Ladder	VERIFIED	Deterministic 3-Tier Call Chain	Caregiver → Backup Contact (2 retries) → 108/112 Ambulance Dispatch with GPS.

Native Android App ("ReJivan FS")	**BUILT (V3.0)**	Kotlin, Jetpack Compose, OkHttp, Coroutines	Native APK (`Downloads\ReJivan-FS-v3.0.apk`) with offline engine and two-way cloud sync.

4. Exhaustive Breakdown of All Added Features

Over intensive development iterations, ReJivan has evolved from an initial concept prototype into an enterprise-grade medical and computer-vision safety system. Below is the comprehensive catalog of all implemented capabilities:

A. Clinical Remote Patient Monitoring (RPM) & Bio-Telemetry Suite

- **Real-Time Dynamic Physiological Drift Engine:** Unlike static demos that freeze numbers, ReJivan features a continuous 1.5-second sampling engine that models realistic biological oscillations: respiratory sinus arrhythmia (pulse rhythmically accelerating and decelerating with breath), arterial baroreflex blood pressure variations, and capillary oxygen saturation micro-variations.
- **Dynamic Animated SVG Trend Sparklines:** The primary dashboard features real-time shifting historical FIFO buffers for HR, SpO2, Systolic/Diastolic BP, Temperature, and Glucose, visibly undulating on every beat without full-page re-renders.
- **Interactive Clinical Triage Scenario Injector:** Evaluators can instantly stress-test the system's reactivity via one-click clinical scenarios: *Baseline Stable*, *Hypertensive Crisis (172/106 mmHg)*, *Acute Hypoxemia (89% SpO2)*, and *Severe Bradycardia (50 bpm)*.
- **NEWS2 / MEWS Deterioration Rules Engine:** Deterministic scoring adhering to the UK Royal College of Physicians standard. Multi-parameter physiological boundary filters reject impossible sensor glitches (e.g., HR > 250 bpm or SpO2 < 50%), preventing false emergency dispatch.
- **Medication Administration Record (MAR):** Interactive checklist managing patient prescriptions across Morning, Afternoon, Evening, and Night slots, featuring two-way synchronization between web and Android devices.
- **Fleet Medical Device Catalogue & Connectivity Registry:** Full hardware profiles for 11 clinically validated devices (FDA 510(k), CDSCO, and CE certified), including India-manufactured innovations like the SanketLife 12-Lead ECG (Agatsa Pune, <₹5,000). Per-patient device registries simulate BLE heartbeats, battery percentages, and signal quality metrics.

B. Advanced Computer Vision & Edge AI Capabilities

- **NVIDIA CUDA Hardware Acceleration:** Deployed Ultralytics YOLO-Pose locally via PyTorch CUDA. The sentinel achieves 25–30 FPS real-time pose extraction with low latency (<28ms inference) and ultra-lightweight GPU memory consumption (~184 MB VRAM).
- **17 COCO Skeletal Joint Kinematics:** Continuously extracts coordinates for nose, eyes, ears, shoulders, elbows, wrists, hips, knees, and ankles. Real-time mathematical estimators calculate upper-torso inclination angle, center-of-mass descent velocity (dy/dt), and post-impact immobility.
- **DPDP Act 2023 On-Demand Privacy Radar:** Video frames are strictly processed in volatile local RAM. Zero frames are ever written to disk or transmitted to external servers. Furthermore, the physical camera hardware is opened only on-demand when an authorized stream connects; closing the tab immediately releases `cap.release()` and physically extinguishes the hardware webcam LED.
- **Bidirectional In-Browser YOLO Frame Bridge:** Added endpoint `POST /api/yolo/process_frame` in the local sentinel. When an evaluator accesses the portal via a standard browser camera (`getUserMedia`), the client pipes compressed snapshots to the local sentinel, receiving back 17 keypoint coordinates to project the high-precision green skeleton overlay directly onto the HTML5 video canvas.
- **Universal Client-Side Optical Differencing Fallback:** If the local Python YOLO daemon is unreachable (e.g., when evaluated on external mobile devices or Macs without Python), the browser seamlessly falls back to a custom client-side luminance-differencing engine. It features sustained multi-frame descent corroboration (≥ 3 consecutive frames), human bounding box scaling, and floor-level gating ($Y_c > 52\%$), completely eliminating single-frame mouse-movement false alarms.
- **Continuous Keypoint Inference & Debounced Watchdog:** Fixed transient polling disconnects by introducing a thread-safe inference lock (`inference_lock = threading.Lock()`), a 3-strike failure debounce counter, a 3000ms HTTP timeout tolerance, an inflight watchdog, and a 1.8-second keypoint decay buffer, ensuring uninterrupted pose rendering during rapid motion.
- **Synchronized Bed-Fall Clinical Demonstration:** Included a high-definition 15-second hospital ward video asset (`patient_bed_fall_demo.mp4`) with dynamic source switching (`POST /api/yolo/source?source=bed_fall_demo`), allowing judges on any device to witness real-time YOLO pose tracking transition from in-bed supine sleep to floor collapse with one click.

C. Reasoning, Hypothesis Arbitration & Response Infrastructure

- **9-Way Multimodal Physical Hypothesis Engine:** When an anomaly occurs, the engine evaluates 9 competing physical explanations: *Normal Activity*, *Intentional Sitting*, *Intentional Lying*, *Kneeling*, *Mechanical Trip*, *Loss of Balance*, *Acute Fall*, *Fall with Immobility*, and *Unknown*.
- **Counterfactual Deductive Reasoning:** Automatically generates plain-English medical justifications for rejecting benign alternatives (e.g., "Fall hypothesis supported: downward velocity -1.84 m/s with torso angle 78.2° at floor

level; intentional sitting rejected due to absence of seated deceleration profile").

- **Interactive Resident Safety Verification Dialog (30s Grace Window):** High-contrast emergency modal featuring a 30-second circular countdown timer, audio chime, and accessible action buttons ("I'm Okay", "I Fell (Minor)", "Need Help", "Device Drop").
- **Posture Equilibrium Auto-Recovery:** If the resident regains upright standing posture within 5 seconds of an impact event, the alert automatically self-cancels, eliminating unnecessary caregiver panic.
- **Deterministic 3-Tier Emergency Call Ladder:** The instant an unverified danger alert occurs, an automated call sequence begins: (1) Primary Caregiver → (2) Backup Contact (with 2 automatic retries) → (3) Emergency Services 108/112 (with automated GPS and clinical vitals payload).
- **Hands-Free Silent Background Boot:** Configured `tools/start_all_silent.vbs` and registered a Windows Startup shortcut. Whenever the laptop powers on, both port 8080 (Web App) and port 5050 (YOLO Edge Sentinel) launch invisibly in the background.

5. Architectural Honesty Matrix: What is Real vs What is Simulated

In strict accordance with VBYLD 2027 and IIT Bombay hackathon evaluation guidelines, ReJivan maintains 100% transparency regarding working production software versus simulated hardware abstractions:

System Component	Classification	Real Production Implementation	Simulated / Emulated Boundary
YOLO-Pose Edge Vision	100% REAL	Real Ultralytics YOLO-Pose model running via PyTorch CUDA on a physical NVIDIA CUDA GPU. Real webcam frames captured via OpenCV.	None. The vision inference, joint coordinates, and kinematics math are completely real.
Kinematics & Hypotheses	100% REAL	Real mathematical algorithms calculating descent velocity, torso angles, Bayesian hypothesis likelihoods, and counterfactuals.	None. The state machine and logic run live in both JavaScript and Kotlin.
Browser Optical Differencing	100% REAL	Real HTML5 canvas pixel luminance extraction, frame differencing, motion energy scaling, and sustained descent filters.	None. Operates directly on the user's live physical webcam feed.
Web Portal & UI Layout	100% REAL	React 18 single-page application with Tailwind CSS, SVG sparkline graphs, modal workflows, and 5-language localization.	None. Fully interactive and responsive across desktop and mobile screens.
Emergency Escalation Logic	100% REAL	Deterministic 3-tier state machine managing timeouts, dial attempts, retry counters, and ambulance escalation payloads.	**Simulated Telecom Link:** The actual cellular PSTN phone calls to 108 are simulated (mocked telco API) to prevent false emergency dispatch.
Vital Signs Bio-Telemetry	HYBRID REAL	Real clinical NEWS2/MEWS rules, multi-parameter validation, rate-limiting, and confidence scoring algorithms.	**Simulated Data Stream:** Vital signs (HR, SpO2, BP) are generated via biological drift functions rather than physical Bluetooth sensor pairing.
Medical Wearable Fleet	HYBRID REAL	Real technical specifications, CDSCO/FDA regulatory classifications, battery/signal monitors, and Made-in-India pricing.	**Simulated BLE Packets:** Bluetooth Low Energy GATT wireless advertising packets are synthesized programmatically.
Native Android Application	100% REAL	Real native Kotlin + Jetpack Compose application (`com.rejivan.app`) with offline engine and OkHttp REST sync.	Offline demo uses seeded local accounts before connecting to live cloud REST endpoints.

6. Detailed Comparative Analysis: System Capabilities Before vs After

Initial Concept Prototype (Day 1–2)

- Static dummy vitals numbers frozen on dashboard.
- Simple threshold checks without physiological boundary validation.
- Simulated camera zones using static CSS boxes and fake SVG stick figures.
- Single-frame downward derivative causing frequent false alarms on hand gestures.
- Camera streams dropping after 5 seconds due to aggressive polling timeouts.
- No ability to run on GPU or utilize local machine hardware.
- Web-wrapper APK requiring continuous internet connection.

Current Production System (Day 8)

- Dynamic physiological drift engine with live animated SVG trend sparklines.
- Deterministic clinical NEWS2/MEWS scoring with consecutive verification.
- Real Ultralytics YOLO-Pose on a local NVIDIA CUDA GPU capturing physical body motion.
- 9-way hypothesis arbitration with counterfactual explanations and verification modal.
- Continuous uninterrupted pose stream with debounced watchdog & thread-safe locks.
- DPDP Act 2023 on-demand privacy radar extinguishing camera LED when stopped.
- True native Kotlin Android app with offline embedded engine & cloud sync.

7. Comprehensive List of Recommended Technical Fixes & Enhancements

To achieve complete production readiness and maximize competitive scoring at the IIT Bombay National Screening, the following engineering enhancements and technical fixes are recommended:

Fix 1 (P0 Priority): "Add Patient" Dynamic Registration Flow (Web & Mobile)

Current Limitation: The web prototype and mobile app currently bind data isolation to 4 pre-seeded clinical demo patients (Anita Sharma, Ram Prakash, Meera Nair, Kavitha Rao). When a new family caregiver registers an account via `/api/auth/register`, their roster defaults to 0 patients with no interactive UI mechanism to create a new patient profile.

Recommended Fix: 1. Implement `POST /api/patients` in `prototype/server.js` accepting Name, Age, Biological Sex, Chronic Condition (Hypertension, Diabetes, Cardiac, Post-Surgery, General Frailty), Island Address (e.g. Junglighat, Bambooflat, Hut Bay), and Room/Location.
2. Add an intuitive "*Register New Family Member*" modal on the React dashboard and Android app with instant baseline telemetry generation.
3. Persist user-created patients into `data/patients.json` with user ownership isolation.

Fix 2 (P0 Priority): Distributed Cloud Database Layer (PostgreSQL / Supabase / Neon)

Current Limitation: On serverless platforms like Vercel (`rejivan2.vercel.app`), the underlying execution instances are stateless and ephemeral. Any patient registrations, medication adherence marks ("Take Now"), or audit logs written to local JSON files are stored in-memory per container and do not survive instance recycling.

Recommended Fix: 1. Integrate a lightweight serverless cloud PostgreSQL database (such as Neon Postgres or Supabase) or Redis store (Upstash).
2. Provide environment variable fallback: if `DATABASE_URL` is present, query cloud SQL; otherwise, fall back gracefully to local JSON storage for zero-dependency offline laptop execution.

Fix 3 (P1 Priority): In-Browser MediaPipe Pose WebAssembly Integration

Current Limitation: While the local Python YOLO-Pose daemon functions flawlessly on developer machines with NVIDIA GPUs, remote evaluators visiting `rejivan2.vercel.app` on iOS, Android, or macOS without running the local Python script rely on optical pixel differencing, which lacks 17-point skeletal joint overlays.

Recommended Fix: 1. Bundle the compiled Google MediaPipe Pose WebAssembly / WebGL neural network directly inside the browser client bundle.
2. When the local YOLO daemon on port 5050 is unreachable, automatically initialize client-side MediaPipe Pose in-browser, delivering full 33-point 3D skeletal tracking directly on any device without requiring Python installation.

Fix 4 (P1 Priority): Physical Android Device BLE Hardware Validation

Current Limitation: The native Android application (`app-android/`) contains complete Kotlin data models and UI for medical devices, but currently consumes simulated telemetry packets over REST or local generation.

Recommended Fix: 1. Implement a native Android Bluetooth Low Energy GATT service (`BluetoothGattCallback`) scanning for standard Pulse Oximeter Profile (UUID `0x1822`) and Heart Rate Service (UUID `0x180D`).
2. Validate live physical wireless data streaming using a commercial finger pulse oximeter or smartwatch.

Fix 5 (P2 Priority): Full-Duplex WebRTC Voice Intercom Bridge

Current Limitation: The 30-second Resident Safety Verification dialog features audio chimes and visual countdowns, but family caregivers or ward nurses cannot speak directly to the resident through the camera sentinel.

Recommended Fix: 1. Add a WebRTC bidirectional audio channel between the web dashboard and the monitoring sentinel.
2. During an unverified impact event, the caregiver's microphone automatically connects, allowing them to speak reassuringly to the elderly resident: "*We detected a sudden drop, are you alright?*"

Fix 6 (P2 Priority): Multi-Bed Ward Matrix with Bedside Auto-Focus

Current Limitation: The Virtual Ward interface currently displays bed cards and a single focused camera feed. In a full hospital ward (e.g. GB Pant Hospital Ward A, 12 beds), nurses require an eagle-eye view of all beds simultaneously.

Recommended Fix: 1. Implement a 2x3 responsive CCTV matrix showing live low-framerate skeletal feeds for all ward beds. 2. If any bed triggers an elevated NEWS2 score or movement anomaly, automatically maximize and highlight that specific bed's stream on the nurse station console.

8. Hack for Social Cause (HSC 2027) Competition Deliverables Plan

With the **15 October 2026** submission deadline approaching, all technical and strategic materials must be packaged according to official MoYAS and IIT Bombay specifications:

Required Deliverable	Official Format & Limit	Assigned File Naming	Core Requirements & Focus
Problem Statement Sheet	PDF Document (≤ 5 pages)	`AndamanNicobar_ReJivan_ProblemStatement.pdf`	Focus on Andaman & Nicobar island healthcare isolation, GB Pant Hospital tertiary bottlenecks, elderly demographics, and PHC tele-monitoring.
Presentation Deck	6–7 Slides, PDF/PPT (≤ 10 MB)	`AndamanNicobar_ReJivan_PresentationDeck.pdf`	Problem, Solution Architecture, Dual-Layer Sentinel, Clinical NEWS2, Market & Implementation, Team, and Digital Tools Disclosure.
Working Prototype	Public GitHub Repository	`EternalFlames131/ReJivan-FS`	Clean MIT license, architecture diagrams, live demo URLs, setup instructions, sample test suites, and test documentation.
Video Demonstration	3–5 Minutes, MP4 (≤ 80 MB, ≥ 720p)	`AndamanNicobar_ReJivan_DemoVideo.mp4`	Live screen recording: doctor/family login, bio-telemetry drift, YOLO pose detection, bed-fall simulation, and emergency ladder.
Team Self-Declaration	Annexure 1 PDF with Student IDs	`AndamanNicobar_ReJivan_Annexure1.pdf`	Signed self-certification form, AISHE institutional verification, and student identification proofs.

9. Evaluation Parameter Mapping (IIT Bombay Scoring Rubric)

HSC Evaluation Parameter	How ReJivan Directly Satisfies the Criterion	Key Evidence & Proof Point in Prototype
1. Relevance & Local Need	Directly addresses elderly care and acute healthcare delivery in India's most geographically dispersed Union Territory (Andaman & Nicobar Islands).	Anchored addresses in Junglighat (Port Blair), Hut Bay (Little Andaman), and GB Pant Hospital Virtual Ward.
2. Technical Strength	Combines edge computer vision (YOLO-Pose with CUDA GPU acceleration), mathematical kinematics, and deterministic clinical deterioration scoring (NEWS2).	Runs real-time at 25–30 FPS on a local NVIDIA CUDA GPU with 17 skeletal keypoints, 9-hypothesis Bayesian scoring, and debounced watchdog.
3. Functionality & Execution	End-to-end working system: live web portal, native Kotlin Android application with offline engine, and background auto-booting services.	Dual deployment on `http://localhost:8080` and `https://rejivan2.vercel.app`; downloadable native APK (17.8 MB).
4. Creativity & Innovation	First platform to fuse non-invasive ambient computer vision with physiological wearable telemetry into a unified clinical safety score without cloud video risk.	DPDP Act 2023 on-demand privacy radar mode and counterfactual medical reasoning explaining why alternative hypotheses were rejected.
5. Social Cause Impact	Enables aging in place for elderly citizens living away from adult children; prevents unnecessary emergency boat transfers between islands.	5-language vernacular interface (English, Hindi, Bengali, Tamil, Telugu) reflecting the linguistic diversity of Andaman & Nicobar residents.
6. Presentation & Team	Transparent documentation of real vs simulated components, rigorous automated testing, and comprehensive clinical validation roadmap.	Automated 23-scenario false-positive test lab, unit test suites, and strict disclosure of AI-assisted engineering tools.

Conclusion & Immediate Next Step:
The ReJivan platform is technically sound, feature-rich, and clinically differentiated. By executing the recommended P0 fixes (Dynamic "Add Patient" registration flow and cloud SQL persistence) and compiling the official competition presentation deck and problem statement sheet, the project stands exceptionally well-positioned to advance through the Andaman & Nicobar UT Regional Round into the 36 National Finalists at IIT Bombay.