Joint Scheduling of Intersection Access and Shared Charging Resources for Delivery Robots in a Dual-Loop Network

EE6228 course project (topics M02 + M04)

Pure-software 2-D online simulation

Abstract

Four delivery robots serve two one-way loops that share a single mutually exclusive intersection and one charging area reachable only through that intersection. We build a deterministic discrete-event simulator with an independent schedule validator and a browser replay, define a normalised objective, and compare four heuristics, an offline CP-SAT model that decides order assignment, order sequence, intersection time slots, charger choice and charging amount jointly, and an online rolling-horizon variant of it. Over 700 validated runs (10 settings $\times$ 10 seeds $\times$ 7 strategies), CP-SAT reduces the objective by about 50 % against first-come-first-served (62 % less tardiness, 28 % shorter makespan) and the online rolling variant by about 37 %, while the single-rule baselines stay within a few percent of each other. We also show that a fair comparison requires the same end-of-horizon battery reserve for every method, and we discuss the limits of the normalised objective.

1 Case introduction

Two delivery zones, A and B, are each served by a closed one-way loop. The loops meet at a single mutually exclusive intersection X, and both zones share one charging area (entrance H, bays C1 and C2) that can only be reached through X. Four virtual robots work in the network: R1 and R2 serve zone A, R3 and R4 serve zone B. Pick-up-and-delivery orders arrive over time, each with a release time, pick-up station, drop-off station, handling times, a due time and a priority.

The two shared resources are coupled. A robot that needs to charge must cross X twice (out and back), so intersection congestion delays charging; a charging queue in turn shifts every later intersection request of that robot and of the robots behind it. Batteries make the problem harder still: a robot may only accept an order if, after completing it, it can still reach a charger without falling below the safety threshold. The project studies how to coordinate **task assignment, task order, intersection time slots, charger choice and charging duration** so that the fleet stays safe and on time under high load.

Scope. Self-designed map and data; robots move along fixed directed routes (no continuous kinematics or obstacle avoidance); battery, handling and charging are software states. The emphasis is on scheduling and resource conflicts.

2 System description

2.1 Network

Each loop is the directed cycle $X \to Z_1 \to Z_2 \to Z_3 \to Z_4 \to W_Z \to X$ for $Z \in \{A, B\}$ (Figure 1). W_A and W_B are the only places where a robot may wait for the intersection. Every edge that enters X ($W_A \to X$, $W_B \to X$, $H \to X$) is a *crossing*; X can hold at most one robot, and two consecutive crossings must be separated by a safety buffer β on each side. The charging branch is

$X \to H \to C_p \to H \to X$; robots queue at H, never inside X or an occupied bay, and leave the bay as soon as charging ends.

Because a robot travels around its loop, every lap passes through X: the intersection is not only on the way to the chargers but on every delivery whose drop-off lies "behind" its pick-up, and on every empty repositioning that wraps around the loop.




Figure 1: Implemented network. Red arrows are crossings into the exclusive intersection X; dashed nodes are the waiting points in front of X. R1/R2 start at A1, R3/R4 at B1.

2.2 Default parameters

Parameter	Base setting	Tested range
Robots	4 (2 per loop)	–
Orders	40	20, 40, 60
Initial SOC	uniform 50–100 % per robot (seeded)	–
Safety threshold $S_{\min}$	10 %	10, 20, 30 %
Ordinary edge	20 m, 20 s, 2 %	editable lengths
Crossing into X	6 s	5–8 s
Safety buffer β	2 s each side (4 s between crossings)	1–4 s
Waiting drain ρ_w	0.2 %/min	0–0.5 %/min
Load / unload	10–20 s each, 0.5 % each	–
Charging rate ρ_c	linear, 5 %/min	3–8 %/min
Charging bays	2	1, 2
Due time	release + 8–15 min (tight: 4–8 min)	–
Priority	1 (50 %), 2, 3	urgent orders 4–5
Zone A share	50 %	1:1, 2:1, 3:1
Urgent orders	0	+10 %, +20 % (due in 3–6 min)

Table 1: Default parameters (SOC: battery state of charge in percentage points).

Orders are released uniformly over $[0, 12n)$ seconds for n orders. The generator is seeded, and urgent orders and initial SOC come from separate random streams, so adding urgent orders never changes the base workload of the same seed. All strategies are evaluated on the identical instance.

2.3 Objective

The proposal's objective adds terms with different units: seconds of makespan, seconds of priority-weighted lateness, seconds of queueing and percentage points of energy. Under load the lateness term reaches tens of thousands of seconds and would swamp everything else. Each term is therefore

normalised by its value in the FCFS schedule of the same instance, and the four normalised terms are weighted equally:

$$J = \frac{1}{4}\left(\frac{C_{\max}}{\hat{R}_C} + \frac{\sum_i p_i T_i}{\hat{R}_T} + \frac{W_{\text{cross}} + W_{\text{charge}}}{\hat{R}_W} + \frac{E}{\hat{R}_E}\right), \tag{1}$$

$$T_i = \max(0,\, C_i - d_i), \qquad \hat{R}_k = \max\Big(R_k^{\text{FCFS}},\, f_k\Big), \qquad f = (1\,\text{s},\ 60\,\text{s},\ 60\,\text{s},\ 1\,\%), \tag{2}$$

where $C_{\max}$ is the completion time of the last order, p_i the priority, C_i and d_i the completion and due time of order i, T_i its tardiness, W the total intersection and charger queueing time and E the total energy consumed. The floors f_k only matter when FCFS has (almost) no lateness or queueing. FCFS therefore scores $J = 1$ (slightly less when one of its terms is below its floor), and $J = 0.6$ reads as "40 % better than FCFS on this weighted balance". Battery safety is *not* traded off: falling below the safety threshold is a hard constraint checked by an independent validator, so $N_{\text{unsafe}} = 0$ in every reported schedule.

3 Simulator

The simulator is a dependency-free Python web application (standard-library HTTP server, SVG front end). Its core is a deterministic discrete-event engine with reservation calendars:

- **World and energy model** (`simulator.py`, `customization.py`): directed edges with length, travel time and energy; per-action SOC updates for moving, crossing, waiting, handling and charging.
- **Reservation calendars**: one for X (with the 2β gap) and one per bay. A robot requesting a resource receives the earliest feasible slot, and the waiting time is recorded as an explicit `cross_wait` or `charge_wait` action at an allowed waiting point.
- **Independent validator** (`validate_result`): recomputes from the returned action log alone the energy of every action, edge legality, route continuity, pickup-before-delivery, release times, robot capacity, action overlap per robot, exclusive and buffered resource use (derived from the physical trace, not from reservation labels), waiting locations, immediate charger departure and SOC bounds. A schedule that fails validation is never returned as a result.
- **Replay and analytics** (`static/`): the 2-D animation reads only the event log (it never recomputes timing), plus a Gantt chart, battery curves, reservation timelines for X/C1/C2, a delivery table and a strategy comparison. Tasks, schedule, events, robots and summary export to CSV.
- **Command mode**: an external plan (robot, start time, action) can be executed strictly; timing, resource and battery conflicts are reported instead of being repaired.

4 Scheduling strategies

4.1 Baselines

1. **FCFS** — orders in release order; each goes to the compatible robot with the earliest predicted completion; a robot below 20 % SOC charges before its next order; intersection slots are granted in booking order.
2. **Staged** — the proposal's "assign, then reserve the intersection, then charge" decomposition. Stage 1 assigns orders by list scheduling on nominal travel times, ignoring X, chargers and battery. Stage 2 executes each robot's fixed sequence with intersection reservations. Stage 3 inserts a charge only when the next order would otherwise be unsafe.

3. **Deadline + reservations** — earliest due date first (priority breaks ties), with the resource reservations and energy checks of the full engine.
4. **Joint greedy** — evaluates up to eight upcoming orders on both compatible robots, including the resulting intersection and charger reservations and charging insertions, and picks the candidate with the lowest score

$$\text{score} = C_i + 3\,p_i T_i + 0.5\,W^{\text{new}} + 2\,E^{\text{new}},$$

where W^{new} and E^{new} are the queueing and energy added by the candidate.

All automatic strategies keep a battery reserve before accepting an order: the robot must be able to finish it, reach H and survive the currently booked charger queue plus a conservative allowance for the other three robots. All heuristics charge to a fixed target of 95 %.

4.2 CP-SAT joint optimisation

The full formulation is in `docs/optimizer_model.md`; this section summarises it. The key observation is that routes are fixed, so for every pair of consecutive jobs of a robot the travel time, the energy and the *set of crossings of X* are known in advance. Each robot k gets a graph $V_k = \{0\} \cup I_k \cup Q_k$ whose vertices are a depot 0 (its current state), every order I_k of its loop, and optional charging visits Q_k.

Decision variables. $x_{ik} \in \{0,1\}$ assigns order i to robot k; arc literals $a_{kab} \in \{0,1\}$ choose the successor of each vertex; s_i, c_i are order start and completion; for each crossing r the entry time e_{kr} and the wait $w_{kr} \geq 0$ in front of X, with exit $l_{kr} = e_{kr} + \tau_r$; for each charging visit q a presence literal y_{kq}, bay literals b_{kqp}, the queue w^C_{kq} at H, charging start u_{kq} and duration D_{kq}; the SOC after incoming travel and after service at every vertex; tardiness T_i and makespan $C_{\max}$.

Constraints.

$$\textstyle\sum_k x_{ik} = 1 \quad \forall i, \qquad \textsc{Circuit}\big(\{a_{kab}\}\big) \quad \forall k \qquad \text{(assignment)} \qquad (3)$$

$$a_{kab} = 1 \;\Rightarrow\; s_b \geq c_a, \qquad s_i \geq r_i \qquad \text{(precedence)} \qquad (4)$$

$$e_{kr} = \text{arrival}_{kr} + w_{kr}, \qquad l_{kr} = e_{kr} + \tau_r \qquad \text{(crossing)} \qquad (5)$$

$$\textsc{NoOverlap}\big(\{[e_{kr},\, l_{kr} + 2\beta)\}_{k,r}\big) \qquad \text{(exclusive X)} \qquad (6)$$

$$u_{kq} = h_{kq} + w^C_{kq} + \tau_{Hp}, \qquad S^-_{kq} = S_{H,kq} - \rho_w w^C_{kq} - g_{Hp} \geq S_{\min} \qquad \text{(queue at H)} \qquad (7)$$

$$S^+_{kq} = S^-_{kq} + \rho_c D_{kq} \leq 100, \qquad \textstyle\sum_p b_{kqp} = y_{kq} \qquad \text{(charging)} \qquad (8)$$

$$\textsc{NoOverlap}\big(\{[u_{kq},\, u_{kq} + D_{kq}) : b_{kqp} = 1\}\big) \quad \forall p \qquad \text{(exclusive bays)} \qquad (9)$$

$$soc_{\text{out}} = soc_{\text{in}} - \textstyle\sum g_{ab} - \sum g_h - \rho_w \sum w \;\geq\; S_{\min} \qquad \text{(energy)} \qquad (10)$$

$$soc_{\text{last}(k)} \geq S_{\min} + G_{k \to H \to p} + \rho_w\, \bar{W}_{\text{queue}} + \delta \qquad \text{(reserve)} \qquad (11)$$

Here τ and g are edge durations and energies, g_h the handling energy, h_{kq} and $S_{H,kq}$ the arrival time and SOC at H, $G_{k \to H \to p}$ the energy from the robot's last station to the cheapest bay, $\bar{W}_{\text{queue}} = 3\,(95 - S_{\min})/\rho_c$ the heuristics' allowance of waiting behind three other full recharges, and $\delta = 0.5\,\%$ a small margin. Every crossing on every arc and inside every order is an optional interval that exists only if its arc is chosen; the waits happen at the incoming waiting point (W_A, W_B or H), never inside X. The robot leaves a bay as soon as charging ends, and the charged amount $\rho_c D_{kq}$ is a decision, unlike the heuristics' fixed 95 % target. The terminal reserve is the same condition the heuristics enforce before accepting any order. Without the margin δ the optimum ended exactly on the boundary and was then rejected by the simulator's check, which also drains while queueing for X. Tardiness and makespan are linearised with $T_i = \max(0, c_i - d_i)$ and $C_{\max} = \max_i c_i$ (`AddMaxEquality`).

The objective is exactly the normalised J of Eq. (1); its references $\hat{R}_k$ are constants computed before the solve, so J stays linear. Time is scaled to milliseconds and SOC to integer units, with every duration and consumption rounded *up* so that integer-feasible schedules remain feasible in the exact simulator. The model is warm-started with the joint greedy schedule (`AddHint`).

Decoding. The solver's choices (sequence, crossing entry times, bay, charging start and target SOC) are replayed through the simulator's own planner, so times and energy in the returned schedule come from the simulator, and the result must pass the independent validator. If the decoded schedule is worse than the warm start or fails validation, the warm start is returned and the fallback is recorded, so CP-SAT never reports a schedule worse than joint greedy.

Search. CP-SAT runs with 8 parallel workers. With a single worker the solver did not improve the warm start on 40-order instances even after about two minutes, while the parallel portfolio, whose large-neighbourhood-search workers do most of the work, improved it substantially within the same time. On small instances (4–6 orders) the model reaches proven optimality and matches the analytical lower bound (unit tests). On realistic sizes the lower bound stays weak, so the results are good incumbents, not proven optima.

4.3 Rolling-horizon re-optimisation

Offline optimisation assumes all orders are known at time 0. The rolling strategy removes that assumption: an order becomes visible only at its release time (Algorithm 1).

Algorithm 1 Rolling-horizon CP-SAT

$t \leftarrow 0$
while orders remain **do**
  $\mathcal{K} \leftarrow$ orders released by t and not yet started
  $\mathcal{W} \leftarrow$ orders of $\mathcal{K}$, most urgent first, until $\approx 600\,\mathrm{s}$ of work per loop
  $\hat{R} \leftarrow$ FCFS references of $\mathcal{K}$ continued from the current state ▷ online normalisation
  plan $\leftarrow$ CP-SAT on $\mathcal{W}$ from the robots' current states, committed X and bay reservations fixed (1 worker, deterministic budget $\approx 0.5\,\mathrm{s}$, warm start = joint greedy)
  commit every job of plan that starts before $t + 60\,\mathrm{s}$; freeze its reservations
  $t \leftarrow t + 60\,\mathrm{s}$
end while

Committed actions are never revised. Each window solve requires the last planned job of every robot to leave the terminal reserve, so that the next window is never left in an energy dead end. Even the normalisation is online: the references come from an FCFS schedule of only the orders known so far. An earlier version used full-instance references; the code review showed that this changed decisions, i.e. it leaked future information. The final schedule is scored with the full-instance J like every other strategy.

5 Experiments

5.1 Setup

The experiment plan of the proposal is run by `experiments.py`. Every configuration uses seeds 1–10; for a given seed all seven strategies (six plus the ablation of Section 6.2) receive the identical order list, configuration and seeded initial SOC. The base setting is 40 orders, 2 bays, a 10 % safety threshold, a 1:1 zone split and no urgent orders; one factor is varied per experiment (Table 2).

Experiment	Settings
Algorithm comparison	base
Load	20, 40, 60 orders
Charging resources	1 or 2 bays
Zone imbalance	A:B = 1:1, 2:1, 3:1
Safety threshold	10, 20, 30 %
Dynamic orders	+0, +10, +20 % urgent orders (due 3–6 min after release, priority 4–5)

Table 2: Experiment plan.

Identical instances that occur in several experiments (the base setting) are solved once, giving 10 distinct settings × 10 seeds × 7 strategies = 700 runs. Each run reports J, its four raw terms, the late-order rate, queueing at X and at the chargers, energy, charging sessions and runtime. Because the seeds differ strongly in difficulty, the tables also give the *paired* change of J against FCFS on the same instance.

Compute. The four heuristics and the rolling strategy are deterministic (rolling solves are bounded by CP-SAT deterministic time, not wall time), so their schedules do not depend on the machine; this was checked by reproducing a rolling run bit for bit on two different machines. CP-SAT is wall-time bounded (120 s, 8 workers) and therefore hardware dependent; all CP-SAT runs used the same machine type (Google Colab high-RAM CPU VMs, 8 vCPU Intel Xeon @ 2.20 GHz, OR-Tools 9.15), one solve per VM at a time.

Fairness caveats. The heuristics and offline CP-SAT know the whole order list in advance (but never start an order before its release); rolling is the only truly online method. All strategies end the horizon with the same battery reserve (every robot that executes orders must still be able to reach a charger behind a full queue; robots without orders never move in any strategy). A first run of offline CP-SAT without that reserve, kept as the ablation `cpsat-nores`, often ended near the safety floor and frequently skipped charging altogether, which inflated its advantage; Section 6.2 quantifies this. The heuristics always charge to 95 %, whereas CP-SAT chooses the amount.

5.2 Algorithm comparison (base setting)

Strategy	J	vs FCFS mean / median	Late orders	Tardiness (s)	Makespan (s)	Charges	Energy (%)	Runtime[a]
FCFS	1.000	–	52 %	26 028	3 233	5.0	443	< 0.1 s
Staged	1.067	+7 / +2 %	51 %	27 264	3 441	5.4	449	< 0.1 s
Deadline + reservations	1.003	0 / −4 %	51 %	25 994	3 210	4.9	438	< 0.1 s
Joint greedy	0.793	−21 / −23 %	37 %	17 826	3 021	3.9	386	0.3 s
Rolling CP-SAT (online)	0.636	−36 / −37 %	37 %	15 651	2 741	4.3	389	49 s
CP-SAT	**0.468**	**−53 / −54 %**	33 %	9 934	2 317	4.2	359	121 s
CP-SAT w/o reserve (ablation)	0.349	−65 / −64 %	23 %	5 032	1 732	2.0	316	121 s

Table 3: Base setting (40 orders, 2 bays, 10 % threshold, 1:1 zones); means over 10 seeds, paired change of J against FCFS as mean / median. [a]Measured wall time per instance (the CP-SAT budget is 120 s; rolling on a 2-vCPU VM). Full tables: `results/results.md`.




Figure 2: Base setting, 10 seeds: objective J, total tardiness and charger queueing per strategy.

All 700 runs produced validated, energy-safe schedules; no strategy failed on any instance. Mean and median give the same performance tiers, and these hold on most individual seeds (Figure 2): the three single-rule baselines stay within ±7 % of each other (their internal order differs: by mean FCFS is marginally ahead of deadline-first, by median deadline-first is 4 % ahead), joint greedy is about a fifth better, rolling about a third and offline CP-SAT about a half. Offline CP-SAT never had to fall back to its warm start, but its optimality gap stays large (base setting: median 58 %, range 51–70 %; all 100 instances: median 63 %, range 18–76 %): the lower bound of the circuit model is weak, so these are good incumbents, not proven optima.

5.3 Sensitivity experiments

Table 4 gives the median paired change of J against FCFS. Means are in `results/results.md`; they differ strongly where near-zero FCFS terms inflate individual runs (Section 6.3), e.g. at 20 orders staged +81 % and deadline +134 % by mean against +7 % and +10 % by median.

Experiment	Setting	Staged	Deadline	Joint	Rolling	CP-SAT
Load	20 orders	+7	+10	−30	−43	−62
	40 orders	+2	−4	−23	−37	−54
	60 orders	+8	+10	−16	−18	−47
Chargers	1 bay	+45	−1	−20	−28	−60
	2 bays	+2	−4	−23	−37	−54
Imbalance A:B	2:1	+4	+2	−15[b]	−25	−48
	3:1	0	−6	−29	−30	−47
Safety threshold	20 %	+2	+11	−18	−16	−51
	30 %	+17	−1	−13	−16	−52
Urgent orders	+10 %	+1	−3	−12	−24	−52
	+20 %	+4	−5	−8	−20	−50

Table 4: Median paired change of J against FCFS (%), 10 seeds per cell. [b]Mean +19 %: one seed scores $J = 3.7$ although joint beats FCFS on makespan, lateness and energy there (Section 6.3).




Figure 3: Load experiment: median J and late-order rate with interquartile range.

- **Load.** Every method degrades as orders are added, but the gap to FCFS shrinks for the heuristics and for rolling (−43 % → −18 %) while CP-SAT keeps −47 % to −62 % (Figure 3). At 60 orders every method is late on more than half the orders (late rate 54–69 %); the fleet is over capacity, and charging (7–10 sessions of up to 17 min) is the binding resource.
- **One charging bay.** FCFS's charger queue grows from 1 437 s to 4 001 s, and the staged baseline collapses (+45 %): it decides charging last, so robots arrive at the single bay together. Joint greedy and CP-SAT, which decide charging together with the orders, hold their advantage; CP-SAT improves most (−60 %).
- **Zone imbalance.** With more work on loop A, makespan grows for all methods because R1/R2 become the bottleneck. The tiers are unchanged (CP-SAT, then rolling and joint greedy, then the single-rule baselines), although within the baseline tier deadline-first falls slightly behind FCFS by median at 2:1 (+2 %).
- **Safety threshold.** A higher threshold forces more charging for everyone. CP-SAT is insensitive (−51 % / −52 %), while rolling falls back to the level of joint greedy (−16 %): each of its windows must end with a full reserve, which with a 20–30 % threshold forces early charging that an offline view would avoid.
- **Urgent orders.** Short-deadline, high-priority orders hurt every method; offline CP-SAT keeps about −50 %, rolling −20 % to −24 %. Deadline-first ordering, the obvious rule for urgent work, gains only 3–5 %.




Figure 4: Charger and zone-imbalance experiments (median, IQR).




Figure 5: Safety-threshold and urgent-order experiments (median, IQR).

6 Discussion

6.1 Where does the improvement come from?

Decomposing J into its four normalised terms (base setting, mean contribution; FCFS contributes 0.25 per term) shows that the methods improve in different ways (Table 5).

Strategy	$C_{\max}$	Tardiness	Queueing	Energy	J	J'^{c}
FCFS	0.250	0.250	0.250	0.250	1.00	1.00
Joint greedy	0.233	0.182	0.160	0.218	0.79	0.84
Rolling	0.211	0.157	0.048	0.219	0.64	0.78
CP-SAT	0.178	0.088	0.000	0.202	0.47	0.62
CP-SAT w/o reserve	0.132	0.039	0.000	0.178	0.35	0.47

Table 5: Mean contribution of each normalised term to J (base setting). [c] $J' = (C_{\max} + \text{tardiness} + \text{energy})/0.75$, i.e. J re-weighted over the three terms other than queueing.

Both CP-SAT methods *almost eliminate queueing* (CP-SAT: 5.6 s on average, all of it on one seed; the heuristics: 23–37 s at X plus 0.9–1.5 thousand seconds at the chargers). The robots still wait, but as powered-down standby at their last station before departing, not in front of X or at H. In the model, standby is free while queueing drains the battery and counts in J, so the optimiser delays departures until the resource is free; the heuristics instead book a slot and drive to the waiting point. This is legitimate within the model, but about half of CP-SAT's gain in J is the queueing term. Without that term the tiers are unchanged (J' in Table 5) and CP-SAT is still the clear winner: it cuts total tardiness by 62 % and the makespan by 28 % against FCFS (44 % and 23 % against joint greedy).

A plausible main source of the tardiness reduction is charging: CP-SAT charges about as often as joint greedy (4.2 vs 3.9 sessions) but chooses *how much* to charge and when, whereas the heuristics always charge to 95 %, at 5 %/min up to 17 minutes per session, often in the middle of a busy period. CP-SAT also changes assignment, order and departure times at the same time, so the experiments do not isolate this effect; a CP-SAT run with a fixed 95 % target would be the controlled test.

6.2 The end-of-horizon reserve

The first CP-SAT experiments did not require any battery left after the last order. The optimiser then often ended near the safety threshold and skipped charging whenever the initial charge sufficed: on every 20-order instance it never charged, and on 40 orders it charged half as often as the heuristics (2.0 vs 3.9–5.4 sessions). The heuristics always keep enough charge to reach a bay behind a full queue. Imposing the same reserve on CP-SAT raised its J from 0.349 to 0.468 at 40 orders but hardly mattered at 60 orders (-51 % vs -47 % median), where robots must charge anyway. About a fifth of offline CP-SAT's apparent advantage at moderate load (12 of 65 percentage points) was therefore an end-of-horizon effect. Any offline comparison against continuous-operation policies needs an explicit terminal condition.

A second, smaller lesson: the optimiser placed the terminal SOC exactly on the reserve boundary, and the simulator's reserve check, which also drains while queueing for X, rejected many of those plans, which then fell back to the warm start (during development, 32 of 115 result rows of a partial run, some instances counted in several experiments; those rows were discarded). After the margin $\delta = 0.5$ % was added, none of the 100 final instances fell back. Exact model/simulator agreement matters most precisely where an optimiser pushes against a constraint.

6.3 The normalised objective

Normalising by FCFS achieved its purpose: without it, priority-weighted tardiness (tens of thousands of seconds) would dominate the other terms by two orders of magnitude, and the four terms contribute comparably. The price is instability on instances where an FCFS term is close to zero. On one 2:1 instance FCFS queued for only 18 s, so the queueing term was divided by its 60 s floor, and joint greedy's 735 s of queueing alone added $0.25 \times 735/60 \approx 3.06$ to its J (total 3.7), although joint beat FCFS on makespan, lateness and energy. The same effect produces means above 1 for staged and deadline at 20 orders (medians 0.96–0.97). Medians and paired comparisons are therefore reported throughout. A more robust choice would normalise by fixed, instance-independent scales (e.g. the mean over the whole experiment) or by the instance's median over all strategies.

6.4 Online versus offline

Rolling is the only method that does not know future orders, yet in the base setting it beats every heuristic that does (median −37 % vs −23 % for joint greedy), and it stays 8–14 percentage points ahead of joint greedy with 20 orders, one bay, 2:1 imbalance and urgent orders. Its weaknesses are the ones expected of a receding horizon: with a 20–30 % safety threshold its per-window reserve forces early charging, and at 60 orders or 3:1 imbalance its short look-ahead cannot plan around the bottleneck, so it is only level with joint greedy (and slightly behind it at a 20 % threshold). Its re-plans are bounded by deterministic solver work (about 1 s each on a 2-vCPU machine, 49 s for a full 40-order day), so it would run in real time. With the same OR-Tools version, one worker and a wall-clock cap that does not bind, its schedules are bit-identical across machines (checked on two machines); runtimes of course differ.

6.5 Limitations

- CP-SAT results depend on hardware (wall-time budget); all were produced on one machine type.
- Optimality gaps are large; better lower bounds (e.g. a relaxation per loop) would be needed to claim near-optimality.
- The heuristics see all future orders, which favours them against rolling, but not against offline CP-SAT.
- The charging model is linear, the network has a single intersection, and robots move on fixed routes without kinematics.

7 Conclusion

A simulator for two delivery loops that share one intersection and one charging area was built, with an independent validator, a browser replay and an experiment pipeline that compares six strategies (plus one ablation) on identical, seeded instances. Over 700 validated runs:

1. **Deciding orders, intersection slots and charging jointly pays off.** In the base setting the single-rule baselines (FCFS, deadline-first, staged) stay within a few percent of each other, the joint greedy heuristic gains about 20 % and CP-SAT, which optimises all decisions in one model, about 50 % in J (62 % less tardiness, 28 % shorter makespan than FCFS). Across all sensitivity settings CP-SAT stays at −47 % to −62 % (median), joint greedy varies between −8 % and −30 %, and the staged baseline can be much worse than FCFS (+45 % with one bay).
2. **Charging is the bottleneck.** Under load the chargers, not the intersection, limit the fleet: for every heuristic the mean queueing at X stays under a minute per run, while charger queues reach thousands of seconds. Choosing how much and when to charge is the most

plausible source of CP-SAT's lower lateness (not isolated experimentally), and separating the charging decision from assignment (the staged baseline) is worst with a single bay.

3. **Online re-optimisation is practical.** Rolling CP-SAT, without knowledge of future orders, beats all heuristics at moderate load with about a second per re-plan; under heavy load or a high safety threshold it is only level with the joint greedy heuristic.

4. **Fair comparison needs care.** Requiring the same end-of-horizon battery reserve changed the CP-SAT result substantially (J: $0.35 \rightarrow 0.47$), and the normalised objective must be read with medians because near-zero reference terms can dominate it.