

New ROD Fw tests



New ROD Fw from Nico under test: Fifth Iteration

“--pixTestFw” in SR1 → rodSlave_top_boot_TriggerInhibition.ace


- Loading new Fw only in C1 _S7 only (git hash 7a1b51....despite should be 5f6bd1..)
 - C1_S17 stays with HLT count Fw (git hash 33bce3...)
- Detector in STANDBY → 1 BC read out only → no hits....only empty frames.
- Reading back at 80 Mb/s.
- L1Trigger Rate (Prescale) varied using Dave Card:
 - **40(2) kHz** / 15(4) kHz / 4(6) kHz
- **Complex Dead time** settings is important here:
 - → set to a more reasonable value **9/350** like in ATLAS
- Simple Dead time settings is also important:
 - → set to **20 BC**.




Rx active 10/11/12/13 → Fmt-Link in the header word 0x62/0x73/0x44/0x55.

Checking Chipscope:

- despite the dead time settings and the empty frames(STANDBY), I could catch pending triggers different for different trigger rates;
- counter is in the module trailers and match the same for all the modules
→ 0x4000x**F8**x in this case
→ no pending triggers in previous fragments 0x4000x**00**x



- NO special sequence of L1A signals that seem to generate the counter overflow (underflow?)
- Observed sequences from **x00** to maximum value (**xF8**) and vice versa...hard to justify in both cases.
- Other sequences look reasonable with +/-1 pending trigger or values that remain constant between consecutive events !! ➔ **try with different Simple Dead time...**
- 4000AD02 4000AD02 4000AD02 4000AD02 4000AC82
- 4000AB82 4000AC02 4000AB82 4000AB82 4000AC02
- 4000AB02 4000AA82 4000AA82 4000AA82 4000AA82



- Stop seeing pending triggers with
 - Simple Dead time = 140 BC;
 - Even after increasing the trigger rate up to 40 kHz.
- Still sporadic cases of pending triggers with Simple Dead time = 120 BC
- Try with LTP constant pattern?

