

PORTABLE

OIL LESS

ASME tanks and safety valves
Oversized components
Powder coated tanks
1 Year Warranty



Direct drive
Low noise
Low vibration
Low maintenance
1 year warranty



Recommended for:
Oil less applications
Dental offices



PARTS IN STOCK




AIR FILTERS

MAGNETIC STARTERS
VIBRATION PADS
AUTO TANK DRAINS
LOW OIL MONITORS
DUAL CONTROLS

REFRIGERATED DRYERS
AFTERCOOLERS



3420 Novis Pointe
Acworth - GA - Zip 30101 - U.S.A.
sales@schulzamerica.com
www.schulzamerica.com

 Schulz of America, Inc.
Phone (770) 529-4731
Fax (770) 529-4733



PORTABLE

Single Stage - 125 psi								
MODEL	MOTOR			FREE AIR CFM	ASME TANK		Schulz Pump	APPROX WEIGHT lbs
	hp	phase	volt		gallon	type		
17HL52-1	1,0	single	110/220	3,1	7	horiz	MSI5,2ML	70
SIDESTACK	1,5	single	110	2,5	2x2	stack	CSA7,8	60
PANCAKE	1,5	single	110	2,5	4,5	panc	CSA7,8	50
28TTL10X-1	2,0	single	110/220	6,1	2x4	twin	MSL10MAX	195
220HL10X-1	2,0	single	110/220	6,1	20	horiz	MSL10MAX	150
230VL10X-1	2,0	single	110/220	6,1	30	vert	MSL10MAX	195
55TTL15X-G	5,5	Honda GX Series		9,2	2x4	twin	MSL15MAX	195
5520HL15X-G	5,5	Honda GX Series		9,2	20	horiz	MSL15MAX	165
Two Stage - 140 psi								
88TTL20X-G	8,0	Honda GX Series		16,4	2x4	twin	MSL20MAX	230

OIL LESS

Single Stage - 125 psi								
MODEL	MOTOR			FREE AIR	ASME TANK		Schulz Pump	APPROX WEIGHT lbs
	hp	phase	volt		gallon	type		
18PMSV6-1	1,0	single	110/220	2,5	8	panc	MSV6	100
226HMSV6-1	2,0	single	220	5,0	26	horiz	2 x MSV6	150
330HMSV6-1	3,0	single	220	7,5	30	horiz	3 x MSV6	200



The Benefits of a Better Design

- Swedish steel valves
- Two year pump warranty
- Slotted crankcase bolt holes
- All components CNC machined
- Easy access to adjust belt tension
- Deeper cylinder fins for heat dissipation
- T.E.F.C. motors standard 10/15 HP
- Oversized in line check valves
- Counter balanced crankshaft
- Oversized main bearings
- Notched belts standard
- Cast iron pumps
- Powder coated
- Low RPM



SCHULZ
OF AMERICA, INC.

“A New Evolution is in the Air”

STANDARD EQUIPMENT

- Low RPM
- Balanced drive pulleys
- Pressure gauge indicator
- Manual condensate tank drain
- T.E.F.C. motors standard 10-20 HP
- NEMA designed motors
- Heavy duty cast iron construction
- ASME air receivers
- Large intake filter/silencers
- ASME approved tank shut off valve
- ASME safety relief valves
- Easy access to belts
- Enclosed belt guard
- Vertical and horizontal designs
- UL approved pressure switch
- 2 Year Pump Warranty



Two Stage - 175 psi								
MODEL	MOTOR			FREE AIR	ASME TANK		Schulz Pump	APPROX WEIGHT lbs
	hp	phase	volt		gallon	type		
580VV20X-1	5,0	single	230	17,20	80	vert	MSV20MAX	535
580VV20X-3	5,0	three	230/460	17,20	80	vert	MSV20MAX	535
7580VV30X-1	7,5	single	230	25,1	80	vert	MSV30MAX	605
7580VV30X-3	7,5	three	230/460	25,1	80	vert	MSV30MAX	605
10120HW40X-3	10,0	three	230/460	32,5	120	horiz	MSW40MAX	800
15120HW60X-3	15,0	three	230/460	51,2	120	horiz	MSW60MAX	930
20120HW80X-3	20,0	three	230/460	64,1	120	horiz	MSW80MAX	1100

STANDARD EQUIPMENT

- Cast iron construction
- Single and two stage
- ASME air receiver
- Low RPM
- Manual condensate drain
- UL approved pressure switch
- Loadless start
- Large intake filter/silencers
- Auto start/stop
- Pressure gauge
- Easy access to belts
- Enclosed belt guards
- Vertical and horizontal designs
- ASME relief valve
- ASME approved tank shut off valve
- 2 Year Pump Warranty



Single Stage - 125 psi								
MODEL	MOTOR			FREE AIR	ASME TANK		Schulz Pump	APPROX WEIGHT lbs
	hp	phase	volt		gallon	type		
360VL15X-1	3,0	single	230	9,2	60	vert	MSL15MAX	235
Two Stage - 175 psi								
580VL20X-1	5,0	single	230	17,1	80	vert	MSL20MAX	515
7580VL30X-1	7,5	single	230	24,6	80	vert	MSL30MAX	565
830HL20X-G	8,0	Honda Engine GX Series		17,1	30	horiz	MSL20MAX	365
10120HL40X-3	10,0	three	230/460	32,3	120	horiz	MSL40MAX	855
1330HL30X-G	13,0	Honda Engine GX Series		25,5	30	horiz	MSL30MAX	395