

EthicalPay API Documentation

Introduction

EthicalPay is a **dummy payment gateway** designed for **test mode payments** in **college-level projects**. It provides a **free, open-source platform** for developers to integrate a basic payment system without real transactions.

Developer: Ganesh Telore

EthicalPay is developed by **Ganesh Telore** to help students and developers test payment functionality in their projects.

How EthicalPay Works

EthicalPay does **not** process real transactions. Instead, it simulates a payment workflow:

1. **Users must first create an account** to obtain API credentials.
2. **Users send a payment request** via GET or POST to EthicalPay.
3. **EthicalPay verifies the request credentials.**
4. **User is redirected to a specified URL**, regardless of success or failure.
5. **No JSON response is sent** to the user's program; all responses appear on the EthicalPay page.

💡 **EthicalPay is a test-mode payment gateway for college-level projects.**

🚀 **Future Upgrades Coming Soon!** EthicalPay will be improved with new features in future versions.

API Endpoint

<https://localhost:2005/verifycred>

This is the endpoint where users send payment requests.

Request Parameters

The following parameters must be sent using **GET or POST**:

Parameter	Description
tb1	API ID (Required)
tb2	API Key (Required)
tb3	Amount in Rupees (Required)
tb4	Redirect URL (Required)

 **Important:** The input field names **must not be changed**.

API Integration in Different Languages

Below are examples of how to integrate EthicalPay into different programming languages.

Rust (using reqwest)

```
use reqwest::blocking::Client;

fn main() {
    let url = "https://localhost:2005/verifycred";
    let params = [
        ("tb1", "EPy42fLAJ4"),
        ("tb2", "bniPOyWZjTEaS2WThsJxGAJX7Km3M6JJ"),
        ("tb3", "100"),
        ("tb4", "https://example.com/payment-status")
    ];
    let client = Client::new();
    let res = client.get(url).query(&params).send().unwrap();
}
```

```
println!("Response: {:?}", res.text().unwrap());  
}
```

Go (using http package)

```
package main
```

```
import (  
    "fmt"  
    "net/http"  
    "net/url"  
)
```

```
func main() {  
    endpoint := "https://localhost:2005/verifycred"  
    params := url.Values{}  
    params.Add("tb1", "EPy42fLAJ4")  
    params.Add("tb2", "bniPOyWZjTEaS2WThsJxGAJX7Km3M6JJ")  
    params.Add("tb3", "100")  
    params.Add("tb4", "https://example.com/payment-status")  
  
    res, _ := http.Get(endpoint + "?" + params.Encode())  
    fmt.Println(res.Status)  
}
```

PHP

```
<?php  
$url = "https://localhost:2005/verifycred";  
$params = http_build_query([  
    "tb1" => "EPy42fLAJ4",  
    "tb2" => "bniPOyWZjTEaS2WThsJxGAJX7Km3M6JJ",  
    "tb3" => "100",  
    "tb4" => "https://example.com/payment-status"  
]);  
$response = file_get_contents("$url?$params");
```

```
echo $response;  
?>
```

Python (using requests)

```
import requests  
  
url = "https://localhost:2005/verifycred"  
params = {  
    "tb1": "EPy42fLAJ4",  
    "tb2": "bniPOyWZjTEaS2WThsJxGAJX7Km3M6JJ",  
    "tb3": "100",  
    "tb4": "https://example.com/payment-status"  
}  
response = requests.get(url, params=params)  
print(response.text)
```

Java (using HttpURLConnection)

```
import java.net.*;  
import java.io.*;  
  
public class EthicalPay {  
    public static void main(String[] args) throws Exception {  
        String url =  
"https://localhost:2005/verifycred?tb1=EPy42fLAJ4&tb2=bniPOyWZjTEaS2WThsJxGAJX7K  
m3M6JJ&tb3=100&tb4=https://example.com/payment-status";  
        HttpURLConnection con = (HttpURLConnection) new URL(url).openConnection();  
        con.setRequestMethod("GET");  
        BufferedReader in = new BufferedReader(new  
InputStreamReader(con.getInputStream()));  
        String inputLine;  
        StringBuilder content = new StringBuilder();  
        while ((inputLine = in.readLine()) != null) {  
            content.append(inputLine);  
        }  
    }  
}
```

```

        in.close();
        System.out.println(content.toString());
    }
}

```

JavaScript (Using Fetch API)

```

fetch('https://localhost:2005/verifycred?tb1=EPy42fLAJ4&tb2=bniPOyWZjTEaS2WThsJxGAJX7Km3M6JJ&tb3=100&tb4=https://example.com/payment-status')
    .then(response => response.text())
    .then(data => console.log(data));

```

C# (using HttpClient)

```

using System;
using System.Net.Http;
using System.Threading.Tasks;

class Program
{
    static async Task Main()
    {
        using HttpClient client = new HttpClient();
        string url =
"https://localhost:2005/verifycred?tb1=EPy42fLAJ4&tb2=bniPOyWZjTEaS2WThsJxGAJX7Km3M6JJ&tb3=100&tb4=https://example.com/payment-status";
        HttpResponseMessage response = await client.GetAsync(url);
        string responseBody = await response.Content.ReadAsStringAsync();
        Console.WriteLine(responseBody);
    }
}

```

Conclusion

EthicalPay is a **free, open-source** dummy payment gateway designed for testing purposes in **college-level projects**. It helps developers integrate a **test-mode payment system** without real transactions.

- **Users must first create an account** to obtain API credentials.
- **No actual payments occur** – only redirections.
- **No API response** is sent to the user's code; the response is shown on the EthicalPay page.
- **Mandatory parameters (tb1****, tb2, tb3, tb4) must not be changed.**
- **EthicalPay will be upgraded with new features soon (as this is just the first prototype).**

Developed by: Ganesh Telore [GT]

Enjoy seamless test payments with **EthicalPay!** 

Let's Do It with Maximum Efforts!