



UNIVERSIDAD COMPLUTENSE MADRID

Sprint 1

Anexo A: Uso de la IA

Ética de Datos e IA

Yao Chen

Jiahao Cheng

Jorge Hernández Palop

Alicia Pereda Bordejé

Jiayi Wang

27/09/2026

Para la organización del repositorio se uso la IA para la creación del script build.sh el objetivo de este script era tener una manera cómoda, rápida y uniforme de compilar los archivos de Typst del repositorio.

Para ello se hizo uso del agente de código Pi con el modelo DeepSeek V4.1 Flash.

Prompt:

I need a simple script that goes to every folder sprint<N> and compiles a pdf from main with the name Sprint <N> - <Title>.pdf

Salida:

Works. build.sh at the repo root:

```
#!/usr/bin/env bash
set -euo pipefail
cd "$(dirname "$0")"

if [ "$#" -gt 0 ]; then dirs=("$@"); else shopt -s nullglob; dirs=(sprint*/); fi

for dir in "${dirs[@]}; do
    [ -d "$dir" ] || continue
    dir="${dir%}/"
    main="${dir}main.typ"
    [ -f "$main" ] || continue

    n="${dir#sprint}"; n="${n%}/"
    title="$(sed -nE 's/
^[[[:space:]]*#let [[[:space:]]+nombre[[[:space:]]*=[[[:space:]]*"([^\"]*)"*/\1/p' "$main"
|
head -n1)"
    [ -n "$title" ] || title="$(sed -nE 's/.*#portada\("[^\"]*"*/\1/p' "$main" |
head -n1)"
    [ -n "$title" ] || title="Sprint ${n}"

    out="${dir}Sprint ${n} - ${title}.pdf"
    echo "==> ${main} -> ${out}"
    typst compile --root . "$main" "$out"
done
```

How it works:

- Iterates every sprint/ (or just the folders you pass: ./build.sh sprint1).
- Sprint number comes from the folder name (sprint2 → 2).
- Title comes from the #let nombre = "... " variable in main.typ, falling back to the portada(«...») first arg, then the folder name.
- Runs from any cwd (cd "\$(dirname "\$0")"), uses --root . so the shared template/ image resolves.
- Output: sprint/Sprint N - .pdf.

Verified: built sprint1/Sprint 1 - Especificación.pdf, and a throwaway sprint2 produced sprint2/Sprint 2 - Diseño.pdf before cleanup.

Want me to add *.pdf to .gitignore so build artifacts aren't committed?