

# Unsupervised Machine Learning with Python


# Section 6.1: K Means Clustering Algorithm

# K Means Clustering: What is it?


- K Means Clustering is a centroid based approach
- User specifies the number of clusters  $K$  and an initial guess for the mean (centre) of each cluster
- K Means Clustering iteratively calculates improved guesses for the means and points associated with each cluster
- K means performs a “hard” clustering - each data point is assigned to exactly one cluster
- See [UnsupervisedML\\_Resources.pdf](#) for links to additional resources

# K Means Clustering: Basic Step

- (A) Start with dataset and current estimate for cluster means
  - (B) For each point in dataset, determine closest cluster mean and assign point to that cluster
  - (C) Recompute cluster means based on assignments in (B)
- Go back to (A) and repeat process until means converge (until change in cluster means is less than a tolerance)



# K Means Algorithm: Voronoi Diagram in 2D



- K Means splits plane into Voronoi cells
- Black dot is “mean”
- Shaded region around black dot is closer to its mean than any other mean
- Results for L2 distance measure (cells different for other distance measures)
- For K Means: Voronoi cell indicates extent of region where data point will assigned to region’s mean

See [https://en.wikipedia.org/wiki/Voronoi\\_diagram](https://en.wikipedia.org/wiki/Voronoi_diagram)

By Balu Ertl - Own work, CC BY-SA 4.0, <https://commons.wikimedia.org/w/index.php?curid=38534275>

# K Means Algorithm

- Assume  $M$  data points  $\{X_i\}$
- Specify number of clusters  $K$  and tolerance  $\varepsilon$
- (1) Randomly choose  $K$  data points to be the initial cluster means  $\{C_k\}$
- (2) While change in cluster means is greater than  $\varepsilon$ 
  - Assign each data point  $X_i$  to cluster with closest mean  $C_k$
  - Re-compute means  $\{C_k\}$  based on latest assignment of points
  - Compute change in cluster means
- Typically, also specify a maximum number of iterations in while loop



# K Means Algorithm: Minimizing Objective Function

- Let  $\{X\}$  denote the data points (drop subscript for simplicity)
- Let  $S_k$  denote the set of points in cluster  $k=0,\dots,K-1$  and let  $C_k$  denote the cluster mean
- K Means tries to partition the points into K cluster so as to minimize the objective function = within cluster sum of squares of distance:

$$Objective = \sum_{k=0}^{K-1} \sum_{X \in S_k} dist(X, C_k)^2$$

# K Means Clustering: Example

- Dataset: sklearn varied\_blobs1 data set with 200 points
- Specify 3 clusters and pick initial means at random from data points
- Set stopping tolerance  $\epsilon=10^{-5}$





# K Means Algorithm: Complexity


- Assume:  $M$  data points in  $d$  dimensions,  $K$  clusters,  $I$  iterations
- At each iteration, need to compute distance between each data point and each cluster centre
- If we assume fixed number of iterations, then algorithm requires  $O(M)$  operations as  $M \rightarrow \infty$
- Amount of memory required is  $O(M)$  as  $M \rightarrow \infty$

# K Means ++ for Picking Initial Cluster Means


- (1) Pick point from dataset at random as Cluster Mean 1
- (2) Loop for Cluster Means = 2, ..., K
  - (a) For each data point  $X$  compute distance  $D(X)$  to nearest existing cluster mean
  - (b) Pick point with largest  $D(X)$  as next cluster mean

Notes:


- After 1<sup>st</sup> mean, approach picks cluster means at the edges of the data set
- Typically, pick point in (b) at random with probability proportional to  $[D(x)]^2$




Dataset



1st Mean





2nd Mean



3rd Mean

# K Means Clustering: using K Means ++

- Dataset: sklearn varied\_blobs1 data set with 200 points
- Specify 3 clusters and pick initial means using kmeans++
- Set stopping tolerance  $\epsilon=10^{-5}$




# K Means++ Initialization: Notes

- Significantly fewer iterations required for convergence using kmeans++ versus random initialization
- Additional work to pick initial guesses using kmeans++ is compensated by reduction in work in main K Means algorithm

# Determining Number of Clusters: Elbow Method



- K Means Elbow is heuristic approach for determining number of clusters
- Perform K Means for range of number of clusters and plot final objective function value
- Identify “Elbow” in plot to determine number of clusters



- Choose number of clusters K so that if number is greater than K then, objective function decreases gradually
- See Resources file for link for additional information


# K Means Clustering: 3 versus 4 Clusters

- Dataset: sklearn varied\_blobs1 data set with 200 points
- Pick initial means at random
- Set stopping tolerance  $\epsilon=10^{-5}$




# K Means Clustering: Notes

- User must specify number of clusters (can use elbow approach)
- User specifies distance measure (L2 is used in this course)
- No guarantee that the objective function is minimized – typically will find local minimum
- Final cluster means and assignments depend on initial guesses
- K Means does not do well for non-convex clusters



Non-convex: line between points “not within cluster”



Convex: line between points “within cluster”

# K Means Clustering: Notes

K Means is an excellent starting point for clustering:

- Easy to implement and fast -  $O(M)$  operations as  $M \rightarrow \infty$
- Can use K Means ++ to choose initial means
- Can use Elbow Method to determine number of clusters K
- Can handle large numbers of dimensions



# Unsupervised Machine Learning with Python

# Section 6.2: K Means Code Design

# K Means Code Design


- This section contains information about design of the K Means code
- Design is based on algorithm described in Section 6.1 and makes use of numpy functionality
- Stop video here, if you would like to do code design yourself

# K Means Code Design

- (1) Derive kmeans class from clustering\_base class
- (2) Key to implementation is Distance Squared Matrix
- (3) Create K Means versions of plot\_cluster and plot\_cluster\_animation to be able to plot evolution of cluster means

# Distance Squared Matrix

- Consider example with 5 data points and 2 clusters



- $\text{dist2}[i,j]$  = distance squared between mean  $i$  and point  $j$
- Example:

$$\text{dist2} = \begin{bmatrix} 1.1 & 5.4 & 4.3 & 0.5 & 1.4 \\ 2.1 & 0.9 & 0.7 & 3.5 & 4.4 \end{bmatrix}$$

Distance squared between data points and M0

Distance squared between data points and M1

# Computing Cluster Assignment



Start with dist2 matrix:

$$dist2 = \begin{bmatrix} \boxed{1.1} & 5.4 & 4.3 & \boxed{0.5} & 4.4 \\ 2.1 & \boxed{0.9} & \boxed{0.7} & 3.5 & \boxed{1.4} \end{bmatrix}$$

← Distance squared between data points and M0  
← Distance squared between data points and M1

## Cluster assignment

- Point is assigned to cluster with closest mean
  - For each data point determine row index of dist2 with smallest entry (numpy argmin)
- Cluster Assignment =  $\boxed{0} \ \boxed{1} \ \boxed{1} \ \boxed{0} \ \boxed{1}$



# Objective Function

Start with dist2 matrix:

$$\text{dist2} = \begin{bmatrix} \boxed{1.1} & 5.4 & 4.3 & \boxed{0.5} & 4.4 \\ 2.1 & \boxed{0.9} & \boxed{0.7} & 3.5 & \boxed{1.4} \end{bmatrix}$$

← Distance squared between data points and M0  
← Distance squared between data points and M1

Objective Function

- Let  $S_k$  denote cluster  $k=0,\dots,K-1$  and let  $C_k$  denote mean

$$\text{Objective} = \sum_{k=0}^{K-1} \sum_{X \in S_k} \text{dist}(X, C_k)^2$$

- Equivalent to sum of distance squared to closest mean
- Distance squared to closest mean:  $\boxed{1.1} \quad \boxed{0.9} \quad \boxed{0.7} \quad \boxed{0.5} \quad \boxed{1.4}$ 
  - Use numpy min function
- Sum is 4.6

# Updating Cluster Means



- Data

$$X = \begin{bmatrix} 1 & 2 & -1 & -2 & 3 \\ 3 & 4 & -4 & -5 & 6 \\ 5 & 6 & -7 & -8 & 9 \end{bmatrix}$$

- Cluster assignment: *Assignment* =  $[0 \ 1 \ 1 \ 0 \ 1]$
- Update cluster means using assignments
  - use numpy mean in column direction

$$M0 = \text{mean}(X[\text{col} = 0,3]) = \text{mean} \begin{bmatrix} 1 & -2 \\ 3 & -5 \\ 5 & -8 \end{bmatrix} = \begin{bmatrix} -0.5 \\ -1 \\ -1.5 \end{bmatrix}$$

$$M1 = \text{mean}(X[\text{col} = 1,2,4]) = \text{mean} \begin{bmatrix} 2 & -1 & 3 \\ 4 & -4 & 6 \\ 6 & -7 & 9 \end{bmatrix} = \begin{bmatrix} 1.33 \\ 2 \\ 2.66 \end{bmatrix}$$





# kmeans class: Principal Variables

| Variable           | Type                    | Description  |
|--------------------|-------------------------|--|
| self.time_fit      | float                   | Time for clustering  |
| self.objectivesave | list                    | Value of the objective function for each iteration<br>Example with 3 iterations: [525, 425, 310]   |
| self.X             | 2d numpy array          | Dataset<br>Number of rows = number of dimensions for data<br>Number of cols = number of data points<br>Example: 2 dimensions and 5 data points: $\begin{bmatrix} 1 & 1.1 & 0.8 & 0.6 & 0.6 \\ 0.9 & 1.0 & 0.7 & 0.5 & 0.5 \end{bmatrix}$   |
| self.clustersave   | list of 1d numpy arrays | self.clustersave[i][j] is cluster assignment for iteration i, data point j<br>Example: for 3 iterations:<br>$\begin{bmatrix} -1 & -1 & -1 & -1 & -1 \\ 0 & 1 & 1 & 0 & 1 \\ 0 & 0 & 1 & 0 & 1 \end{bmatrix}$   |
| self.meansave      | list of list of means   | Cluster means: meansave[i][j] is the mean for iteration i and cluster j<br>Example with 3 iterations and 2 means<br>$\begin{bmatrix} \begin{bmatrix} 2 \\ 1 \end{bmatrix}, \begin{bmatrix} 3 \\ 2 \end{bmatrix}, \begin{bmatrix} 2 \\ 2 \end{bmatrix}, \begin{bmatrix} 3 \\ 3 \end{bmatrix}, \begin{bmatrix} 1 \\ 4 \end{bmatrix}, \begin{bmatrix} 4 \\ 3 \end{bmatrix} \end{bmatrix}$ |
| dist2              | 2d numpy array          | dist2[i,j] is distance squared between mean i and data point j<br>Example with 2 means and 5 data points: $\begin{bmatrix} 1.1 & 5.4 & 4.3 & 0.5 & 1.4 \\ 2.1 & 0.9 & 0.7 & 3.5 & 4.4 \end{bmatrix}$   |

# kmeans class – Key Methods

| Method                                 | Input  | Description  |
|--|--|--|
| <code>__init__</code>                  | <code>ncluster</code> (integer)<br><code>initialization</code> (string)  | Constructor for the class – input the number of clusters and initialization method (“random” or “kmeans++”)  |
| <code>initialize_algorithm</code>      |  | Initialize <code>self.clustersave</code> , <code>self.objectivesave</code> , and <code>self.meansave</code><br>Return: nothing   |
| <code>fit</code>                       | <code>X</code> (2d numpy array)<br><code>max_iter</code> (integer)<br><code>tolerance</code> (float)<br><code>verbose</code> (boolean) | Performs K means algorithm until distance between current and previous means is less than tolerance for maximum of <code>max_iter</code> iterations.<br>Return: nothing  |
| <code>compute_distance2</code>         | <code>list_mean</code> (list numpy column vectors)   | Compute distance squared between each data point and each mean in <code>list_mean</code><br>Return: <code>dist2</code> (2d numpy array)<br>See: <a href="#">UnsupervisedML/Examples/Section03/Distance.ipynb</a> |
| <code>update_cluster_assignment</code> | <code>dist2</code> (2d numpy array)  | Compute the cluster assignments based on info in <code>dist2</code><br>Return: nothing (update <code>self.clustersave</code> )   |

# kmeans class – Key Methods

| Method                 | Input   | Description  |
|------------------------|---|--|
| update_objective       | dist2 (2d numpy array)  | Compute latest value of objective function<br>Return: nothing (append to self.objectivsave)  |
| update_mean            |   | Compute means based on current cluster assignments<br>Return: nothing (append to self.meansave)  |
| compute_diff_mean      |   | Determine maximum distance between current and previous estimate for means<br>Return: maximum difference in means  |
| plot_cluster           | level (integer)<br>title,xlabel,ylabel (strings)                    | Plot the clusters and the means for specified level (iteration)<br>Return: nothing<br>See UnsupervisedML/Exercises/Section02/Exercise_2.4.2.ipynb  |
| plot_cluster_animation | level (integer)<br>interval (float)<br>title,xlabel,ylabel(strings) | Create animation showing data points and evolution of cluster assignments and means for iterations up to specified level (iteration)<br>Return: nothing<br>See UnsupervisedML/Exercises/Section02/Exercise_2.4.2.ipynb |

# Unsupervised Machine Learning with Python

# Section 6.3: K Means Clustering

## Code Walkthrough

# K Means Clustering: Code Walkthrough

Code located at:

- UnsupervisedML/Code/Programs

| Files to Review    | Description                   |
|--------------------|-------------------------------|
| clustering_base.py | Base class for clustering     |
| kmeans.py          | Class for K Means clustering  |
| driver_kmeans.py   | Driver for K Means clustering |

Course Resources at:

- <https://github.com/satishchandrareddy/UnsupervisedML/>
- Stop video if you would like to implement code yourself first