

Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

Showing results for contents of text-input area

Checker Input

Show ☒ source ☐ outline ☐ image report [Options...](#)

Check by ☐ css

```
<!DOCTYPE html>
<html lang="{{ app()->getLocale() }}">
  <head>
    <title>{{ config('app.name', 'Laravel') }}</title>

    <!-- Metadata -->
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <!-- CSRF Token -->
    <meta name="csrf-token" content="{{ csrf_token() }}">

    <!-- Styles -->
    <link rel="stylesheet" href="{{ asset('css/auth.css') }}">
```

[Check](#)

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

Message Filtering

- Error** Bad value `{{ app()->getLocale() }}` for attribute `lang` on element `html`: Subtags must not exceed 8 characters in length.
[From line 1, column 16; to line 2, column 38](#)

```
TYPE html>{{<html lang="{{ app()->getLocale() }}">{{<
```
- Error** Bad value `{{ asset('css/auth.css') }}` for attribute `href` on element `link`: Illegal character in path segment: `{` is not allowed.
[From line 15, column 9; to line 15, column 66](#)

```
>{{<link rel="stylesheet" href="{{ asset('css/auth.css') }}">{{
```
- Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.
[At line 17, column 51](#)

```
pt" src={{ url('js/app.js') }}
```

4. **Error** A slash was not immediately followed by `>`.
[At line 17, column 55](#)
`src={{ url('js/app.js') }} def`
5. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.
[At line 17, column 61](#)
`url('js/app.js') }} defer>`
6. **Warning** Attribute `url('js` is not serializable as XML 1.0.
[From line 17, column 9; to line 17, column 72](#)
`><script type="text/javascript" src={{ url('js/app.js') }}
defer>`
7. **Warning** Attribute `app.js')` is not serializable as XML 1.0.
[From line 17, column 9; to line 17, column 72](#)
`><script type="text/javascript" src={{ url('js/app.js') }}
defer>`
8. **Warning** Attribute `}}` is not serializable as XML 1.0.
[From line 17, column 9; to line 17, column 72](#)
`><script type="text/javascript" src={{ url('js/app.js') }}
defer>`
9. **Error** Bad value `{{` for attribute `src` on element `script`: Illegal character in path segment: `{` is not allowed.
[From line 17, column 9; to line 17, column 72](#)
`><script type="text/javascript" src={{ url('js/app.js') }}
defer>`
10. **Error** Attribute `url('js` not allowed on element `script` at this point.
[From line 17, column 9; to line 17, column 72](#)
`><script type="text/javascript" src={{ url('js/app.js') }}
defer>`
Attributes for element `script`:
[Global attributes](#)
[src](#) — Address of the resource
[type](#) — Type of script
[nomodule](#) — Prevents execution in user agents that support [module scripts](#)
[async](#) — Execute script when available, without blocking while fetching
[defer](#) — Defer script execution

[crossorigin](#) — How the element handles crossorigin requests

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[blocking](#) — Whether the element is [potentially render-blocking](#)

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

11. **Error** Attribute `app.js` not allowed on element `script` at this point.

From line 17, column 9; to line 17, column 72

```
><script type="text/javascript" src={{ url('js/app.js') }}
defer>
```

Attributes for element `script`:

[Global attributes](#)

[src](#) — Address of the resource

[type](#) — Type of script

[nomodule](#) — Prevents execution in user agents that support [module scripts](#)

[async](#) — Execute script when available, without blocking while fetching

[defer](#) — Defer script execution

[crossorigin](#) — How the element handles crossorigin requests

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[blocking](#) — Whether the element is [potentially render-blocking](#)

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

12. **Error** Attribute `}}` not allowed on element `script` at this point.

From line 17, column 9; to line 17, column 72

```
><script type="text/javascript" src={{ url('js/app.js') }}
defer>
```

Attributes for element `script`:

[Global attributes](#)

[src](#) — Address of the resource

[type](#) — Type of script

[nomodule](#) — Prevents execution in user agents that support [module scripts](#)

[async](#) — Execute script when available, without blocking while fetching

[defer](#) — Defer script execution

[crossorigin](#) — How the element handles crossorigin requests

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[blocking](#) — Whether the element is [potentially render-blocking](#)

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

13. **Warning** The `type` attribute is unnecessary for JavaScript resources.
[From line 17, column 9; to line 17, column 72](#)

```
>... <script type="text/javascript" src={{ url('js/app.js') }}
defer>...
```
14. **Error** Bad value `{{ url('/logout') }}` for attribute `href` on element `a`: Illegal character in path segment: `{` is not allowed.
[From line 24, column 21; to line 24, column 66](#)

```
<a class="button" href="{{ url('/logout') }}"> Logou
```
15. **Warning** Section lacks heading. Consider using `h2` - `h6` elements to [add identifying headings to all sections](#), or else use a `div` element instead for any cases where no heading is needed.
[From line 27, column 13; to line 27, column 34](#)

```
<section id="content">...
```

Document checking completed.

Source

```
1. <!DOCTYPE html>
2. <html lang="{{ app()->getLocale() }}">
3.   <head>
4.     <title>{{ config('app.name', 'Laravel') }}</title>
5.
6.     <!-- Metadata -->
7.     <meta charset="utf-8">
8.     <meta http-equiv="X-UA-Compatible" content="IE=edge">
9.     <meta name="viewport" content="width=device-width, initial-
10. scale=1">
11.
12.     <!-- CSRF Token -->
13.     <meta name="csrf-token" content="{{ csrf_token() }}">
14.
15.     <!-- Styles -->
16.     <link rel="stylesheet" href="{{ asset('css/auth.css') }}">
17.     <link rel="stylesheet"
18. href="https://cdnjs.cloudflare.com/ajax/libs/font-
19. awesome/5.15.4/css/all.min.css">
20.     <script type="text/javascript" src="{{ url('js/app.js') }}
21. defer>
22.   </script>
23. </head>
24. <body>
25.   <main>
26.     {{--<header>
27.       @if (Auth::check())
28.         <a class="button" href="{{ url('/logout') }}">
29. Logout </a> <span>{{ Auth::user()->name }}</span>
30.       @endif
31.     </header>--}}
32.     <section id="content">
33.       @yield('content')
34.     </section>
35.   </main>
36. </body>
37. </html>
```

Used the HTML parser.

Total execution time 4 milliseconds.

[About this checker](#) • [Report an issue](#) • Version: 24.11.29