


ZXHN H208N

Status
Network
WAN
WLAN
LAN
DHCP Server
DHCP Binding
DHCP Port Service
Routing(IPv4)
Security
Application
Administration
Help

 Help

Path:Network-LAN-DHCP Server

[Logout](#)

NOTE: 1. The DHCP Start IP Address and DHCP End IP address should be in the same subnet as the LAN IP.

2. When LAN IP's Network Number changes, please make sure those special pool IP Addresses are in the same subnet as the LAN IP.

LAN IP Address Subnet Mask Enable DHCP Server ☒DHCP Start IP Address DHCP End IP Address Assign IspDNS ☐DNS Server1 IP Address DNS Server2 IP Address DNS Server3 IP Address Default Gateway Lease Time sec

Allocated Address

MAC Address	IP Address	Remaining Lease Time	Host Name	Port
ba:e3:9a:a9:da:05	192.168.1.7	50715	A50-pol-zovatela-	SSID1
bc:5f:f4:63:15:73	192.168.1.2	infinity	Comp	LAN1
c0:25:2f:3a:3c:c0	192.168.1.8	77798	AC12	LAN2
92:2e:d5:e7:48:1a	192.168.1.4	69862	HUAWEI_nova_5	SSID1
70:bb:e9:eb:09:05	192.168.1.6	73001	MI8Lite-MI8Lite	SSID1
a8:9c:ed:3f:32:47	192.168.1.5	81743	Redmi7-?	SSID1
a0:a4:c5:e2:7d:13	192.168.1.3	infinity	eug1n1	SSID1

©2008-2015 ZTE Corporation. All rights reserved

