

# **Antelope Toolbox for Matlab:**

## **Version 1.1**

### **User's Manual and Tutorial**

*Kent Lindquist*  
*Lindquist Consulting*

## Introduction

This document describes an Antelope Software toolbox for Matlab. Matlab is a product of Mathworks, Inc. Antelope is a product of Boulder Real-Time technologies, Inc. Included in Antelope is the Datascope relational database system. The major strengths of this Matlab toolbox include those of the Antelope package itself, such as schema-independent relational database support, a generalized and powerful parameter-file management architecture, and a number of tools useful to seismologists.

This toolbox follows closely the interfaces to Datascope and Antelope built into other scripting environments such as Perl and TCL/Tk. This toolbox was developed under Solaris 2.6 on Sun Ultra computers, using Matlab version 5.3, and has since been upgraded for consistency with Solaris 2.8, Linux, and Matlab 6.5.

## Installation

The Antelope Toolbox for Matlab is intended to be installed in

`$ANTELOPE/data/matlab/antelope`

The source code for the package is available via the Antelope contributed-code web site, <http://www.indiana.edu/~aug..> The Antelope toolbox should compile into the correct place along with the rest of the contributed code. The `$MATLAB` environment variable should be set correctly before compilation.

In addition, the paths to the matlab commands need to be made available to the users. The usual system-wide strategy to do this is to modify the file

`$MATLAB/toolbox/local/pathdef.m`.

to have three more entries<sup>1</sup>:

```
p = [...
    getenv('ANTELOPE'),'/data/matlab/antelope/antelope:',...
    getenv('ANTELOPE'),'/data/matlab/antelope/scripts:',...
    getenv('ANTELOPE'),'/data/matlab/antelope/examples:',...
    matlabroot,'/toolbox/matlab/general:',...]
```

---

1. Note the assumption that the ANTELOPE environment variable is correctly set. Note also that the old utility *install\_matlab\_antelope\_links* is deprecated and out of date. With Matlab 6.1 and higher, no links should be necessary.

```
matlabroot,'/toolbox/matlab/ops:',...
```

There are three directories that get included in the path. The *\$ANTELOPE/data/matlab/antelope/antelope* directory is for the main routines of the Antelope Toolbox for Matlab. The *\$ANTELOPE/data/matlab/antelope/examples* directory is for the example scripts for each command, discussed below. The *\$ANTELOPE/data/matlab/antelope/scripts* directory is a common location for scripts that are written using the Antelope Toolbox for Matlab. Users that write scripts of general utility may want to put them in this directory.

Finally, there is an additional directory *\$ANTELOPE/data/matlab/antelope/html* with the html versions of all the documentation, plus a copy of this tutorial. This path should be added to the file

```
$MATLAB/toolbox/local/docopt.m
```

by changing the docpath option (under the “elseif isunix” clause in docopt.m) to

```
docpath = [getenv('ANTELOPE'),'data/matlab/antelope/html'];
```

## Help

All toolbox commands are documented with the standard Matlab help utilities. To see a list of available commands, type

```
>> help antelope
```

or (for the Matlab help window)

```
>> helpwin antelope
```

or (for an HTML index of the help entries in a web browser)

```
>> doc antelope
```

For a list of examples, type

```
>> help antelope/examples
```

‘For help on individual commands, give the name of the command. For example:

```
>> help dbopen
```

```
DBOPEN Open a Datascope Database
```

DBPTR = DBOPEN ( FILENAME, OPENTYPE )

dbopen opens the database specified by the path name FILENAME, using the permissions given by opentype. A database pointer with the database index filled in is returned in DBPTR. The opentype may be either r (for read only) or r+ (for reading and writing). In the latter case, the db package will attempt to open tables read/write, but if permissions are incorrect, will open the table read only.

Antelope Toolbox for Matlab

[Antelope is a product of Boulder Real Time Technologies, Inc.]

Kent Lindquist

Lindquist Consulting

1997-2003

>>

The other versions of the help system also work for individual commands:

>> **helpwin dbopen**

or

>> **doc dbopen**

For further insight, consult the man pages and manuals provided with the Antelope software and the Matlab software.

Finally, all commands in the Antelope Toolbox for Matlab come with an example demonstrating their use. To see the example in action, precede the command with the prefix “**dbexample\_**”. For example, to see the **dbopen** command being used, type **dbexample\_dbopen**. There is also a script **dbexample\_runall** which will run all available examples. This is useful primarily for system testing. There are also a couple example scripts covering special topics, such as **dbexample\_joins**, **dbexample\_get\_hypocenter\_vitals**, **dbexample\_sort\_and\_subset**, and **dbexample\_writing**.

## Opening a Database

Databases are opened with the **dbopen** command, which takes a filename and a permissions flag. For convenience the Matlab Antelope Toolbox contains a demonstration database from the Joint Seismic Program Center. The schema for this database is CSS3.0. The filename of this database is available through the command

```
>> dbexample_get_demodb_path
demodb_path is /opt/antelope/4.2u/data/matlab/antelope/examples/demodb/demo
>>
```

The **dbopen** command returns a four-element structure called a database pointer:

```
>> db = dbopen(demodb_path,'r')

db =

    database: 0
      table: -501
       field: -501
    record: -501

>>
```

Under normal conditions the user does not modify these fields directly, with the possible exception of the record field. Two tools are provided to aim the database pointer at specific parts of the database (i.e. set the integers correctly). **dblookup** is the most general of the two. A shorthand version of **dblookup**, **dblookup\_table**, is provided for the most common operation, aiming the database pointer at a given table of the database:

```
>> db=dblookup_table(db,'origin')

db =

    database: 0
      table: 10
       field: -501
    record: -501

>>
```

Databases may be closed with the **dbclose** command, which destroys the database pointer:

```
>> dbclose(db)
```

```
>>
```

## Handling Parametric Data

The following examples show some common database operations. These examples presume you have already opened the database and looked up the origin table, as shown in the steps above. We can subset our database:

```
>>db=dbsubset(db,'mb > 6');
```

Find out how many records we have:

```
>> dbquery(db,'dbRECORD_COUNT')
```

```
ans =
```

```
18
```

```
>>
```

Ask for a column of values:

```
>> mb=dbgetv(db,'mb')
```

```
mb =
```

```
6.4200
```

```
6.4000
```

```
6.2000
```

```
6.2000
```

```
6.2300
```

```
6.4000
```

```
6.3100
```

```
6.0200
```

```
6.2800
```

```
6.5000
```

```
6.5700
```

```
6.1100
```

```
6.0500
```

```
6.2100
```

```
6.3000
```

```
6.3000
```

6.2700

6.1400

Or ask for several columns of values:

```
>> [lat,lon,depth,time] = dbgetv(db,'lat','lon','depth','time');
```

Convert the epoch-times (seconds since 1970) for the hypocentral occurrence time to a standard readable format:

```
>> stryctime(time)
```

ans =

```
' 5/04/1992 (125) 8:45:10.089'
' 5/12/1992 (133) 18:05:42.600'
' 5/15/1992 (136) 7:05:05.300'
' 5/17/1992 (138) 9:49:19.100'
' 5/17/1992 (138) 9:49:21.689'
' 5/17/1992 (138) 10:15:31.300'
' 5/17/1992 (138) 21:36:00.492'
' 5/19/1992 (140) 14:42:48.813'
' 5/20/1992 (141) 12:20:34.700'
' 5/21/1992 (142) 4:59:57.500'
' 5/21/1992 (142) 5:00:00.399'
' 5/21/1992 (142) 18:05:48.543'
' 5/22/1992 (143) 21:40:36.691'
' 5/25/1992 (146) 2:51:32.311'
' 5/25/1992 (146) 16:55:04.100'
' 5/27/1992 (148) 5:13:38.800'
' 5/27/1992 (148) 5:13:41.635'
' 5/28/1992 (149) 21:24:51.822'
```

Or we can customize the time-conversion format:

```
>> epoch2str(time,'%A %b %d %I:%M %p %Z')
```

ans =

```
'Monday May 04 08:45 AM UTC'
'Tuesday May 12 06:05 PM UTC'
'Friday May 15 07:05 AM UTC'
'Sunday May 17 09:49 AM UTC'
'Sunday May 17 09:49 AM UTC'
'Sunday May 17 10:15 AM UTC'
'Sunday May 17 09:36 PM UTC'
```

```
'Tuesday May 19 02:42 PM UTC'
'Wednesday May 20 12:20 PM UTC'
'Thursday May 21 04:59 AM UTC'
'Thursday May 21 05:00 AM UTC'
'Thursday May 21 06:05 PM UTC'
'Friday May 22 09:40 PM UTC'
'Monday May 25 02:51 AM UTC'
'Monday May 25 04:55 PM UTC'
'Wednesday May 27 05:13 AM UTC'
'Wednesday May 27 05:13 AM UTC'
'Thursday May 28 09:24 PM UTC'
```

```
>>
```

As an aside, we can go the other way too:

```
>> str2epoch('2/13/98 15:17')
```

```
ans =
```

```
887383020
```

```
>>
```

or

```
>> str2epoch('now')
```

```
ans =
```

```
9.2039e+08
```

```
>>
```

We can pick out the first record in our database view (note the indexing convention!):

```
>> db.record=0
```

```
db =
```

```
database: 0
table: 36
field: -501
record: 0
```

```
>>
```



Find the iasp91 P-phase travel time in seconds from the hypocenter to Fairbanks:

```
>> dbeval(db,'pphasetime(distance(lat,lon,64.836,-147.7048),depth)')

ans =

    780.7877

>>
```


We can launch a spreadsheet tool (*dbe*) on our whole database:

```
>> unix(['dbe ' demodb_path '&'])
[1] 17990

ans =

     0

>>
```



and examine the individual tables by clicking on the buttons.

## Handling Waveform Data

The database contains data for one earthquake. We can get the data for the P wave in one of two ways. First we need to get the correct database pointer:

```
>> db=dblookup_table(db,'wfdisc');
>> dbt=dblookup_table(db,'arrival');
>> db=dbjoin(dbt,db);
>> db=dbsubset(db,'arrival.chan == wfdisc.chan');
>> dbt=dblookup_table(db,'assoc');
>> db=dbjoin(dbt,db);
>> dbt=dblookup_table(db,'origin');
>> db=dbjoin(dbt,db);
```

```
>> db=dbsubset(db,'sta == "CHM" && chan == "BHZ");
>> [time,endtime]=dbgetv(db,'time','endtime')
```

```
time =
```

```
7.061397100070000e+08
```

```
endtime =
```

```
7.061398415000000e+08
```

```
>>
```

Now we have a couple options for getting data. We can use `TRLOAD_CSS` to load the database waveform contents into a trace-object, another database pointer that includes information on waveforms loaded into memory; or we can use `TRGETWF`. The former, which is the preferred method, requires us to call `TREXTRACT_DATA` to get the actual waveform data:

```
>> tr=trload_css(db,time,endtime);
>> data1=trextract_data(tr);
```

Or we can go directly to the waveform data from the database pointer:

```
>> [data2,nsamp,t0,t1]=trgetwf(db,time,endtime);
```

## Response information

Response information stored in a database may be loaded into a *dbresponse* object for evaluation. We precede our demonstration of this with an extraction of the correct filename from the database:

```
>> db=dblookup_table(db,'sensor');
>> dbinst=dblookup_table(db,'instrument');
>> db=dbjoin(db,dbinst);
>> db.record=dbfind(db,'sta == "CHM" && chan == "BHZ");
>> respfile = dbfilename(db)
```

```
respfile =
```

```
/opt/antelope/4.2u/data/matlab/antelope/examples/demodb/response/sts2_vel_RT72A.1
```

```
>>
```

Now we use this filename to construct a *dbresponse* object:

```
>> resp=dbresponse(respfile)
resp =

    dbresponse object: 1-by-1
```

```
>>
```

Next we use the **eval\_response** command to evaluate the response curve at 5 Hz, noting the conversion to radians/sec:

```
>> eval_response(resp, 5 * 2 * pi)

ans =

    0.9969 - 0.0749i

>>
```

The returned value is in general complex. Next we evaluate the response for several frequencies at once:

```
>> myvals = eval_response(resp,[0.1; 1; 10]*6.28)

myvals =

    0.9968 - 0.0502i
    0.6239 - 0.7815i
   -0.0115 - 0.0053i

>>
```

These results are of course amenable to standard Matlab processing:

```
>> abs(myvals)

ans =

    0.9980
    1.0000
    0.0126

>> angle(myvals)*180/pi
```

```
ans =
    -2.8853
   -51.3982
  -155.2421

>>
```

When we are done with the *dbresponse* object, we remove it with the **free\_response** command:

```
>> free_response(resp)
>>
```

## Parameter files

Antelope parameter files allow the specification of ASCII-text parameter files. For complete documentation, see the Antelope manuals.

As an example, here's a small text file in my current working directory:

```
nordic% cat /home/kent/temp/test.pf
cat /home/kent/temp/test.pf

# Test parameter file

number_of_things 3
string_thing Dr. Seuss Lives
myboolean True

thing_names &Tbl{
ball
chew-toy
toy mouse
}

thing_owners &Arr{
    ball      Kirby
    chewtoy    Rover
    mouse     Jasmine
}
on_the_fly &ask What is a convenient value for this
```

```
nordic%
```

To open this as a parameter file, type the following:

```
>> pf=dbpf('test')

pf =

    dbpf object: 1-by-1

>>
```

The returned object is called a parameter-file (*dbpf*) object. This one was actually constructed from the single file shown above. However, the PFPATH environment variable specifies all the locations which may contain parameter files, and all files of the specified name are read. Repeated parameters are overwritten in the order in which they are read, allowing users to override default settings of software packages with subsets of parameter files in their own directories and with correct settings of PFPATH.

To see which existent, readable files will contribute to a *dbpf* object, use **pffiles**:

```
>> pffiles('test')

ans =

    './test.pf'

>>
```

To see all the possibilities that are investigated, regardless of whether they exist or are readable, use the 'all' option:

```
>> pffiles('test','all')

ans =

    '/opt/antelope/4.2u/data/maps/site/test.pf'
    '/opt/antelope/4.2u/data/pf/test.pf'
    '/opt/antelope/4.2u/data/pf/site/test.pf'
    '/home/kent/data/pf/test.pf'
    './test.pf'

>>
```

Now, to see the parameter names in the parameter-file object, use **pfkeys**:

```
>> pfkeys(pf)

ans =

    'number_of_things'
    'string_thing'
    'thing_names'
    'thing_owners'

>>
```

To convert the entire object to a string, use **pf2string**:

```
>> pf2string(pf)

ans =

myboolean True
number_of_things    3
on_the_fly &ask What is a convenient value for this
string_thing  Dr. Seuss Lives
thing_names    &Tbl{
ball
chew-toy
toy mouse
}
thing_owners    &Arr{
ball  Kirby
chewtoy Rover
mouse Jasmine
}

>>
```

To extract a single numeric parameter out of the *dbpf* object, use **pfget\_num**. This actually retrieves the parameter as a string, then applies the Matlab **str2num** function.

```
>> pfget_num(pf,'number_of_things')

ans =

    3

>>
```

To get string values, use **pfget\_string**:

```
>> pfget_string(pf,'string_thing')
```

```
ans =
```

```
Dr. Seuss Lives
```

```
>>
```

To get boolean values, use **pfget\_boolean**. This returns -1 (which evaluates to true in an **if** statement) for affirmative values ('true', 'yes', etc.) in the parameter file, and 0 for negative values.

```
>> pfget_boolean(pf,'myboolean')
```

```
ans =
```

```
-1
```

```
>>
```

Lists of things may be retrieved from the parameter file with **pfget\_tbl**:

```
>> pfget_tbl(pf,'thing_names')
```

```
ans =
```

```
'ball'
```

```
'chew-toy'
```

```
'toy mouse'
```

```
>>
```

Also, the parameter file may contain associative arrays of key--value pairs. Notice that such an entity is really just like a nested parameter file, so these are returned as subsidiary *dbpf* objects, as shown by this return from the **pfget\_arr** command:

```
>> pfget_arr(pf,'thing_owners')
```

```
ans =
```

```
dbpf object: 1-by-1
```

```
>>
```

Of course, Matlab has a built-in strategy for dealing with blocks of key-value pairs, namely the structure. Therefore there is a command **pf2struct** to convert a *dbpf* object to a Matlab *struct*. There is a caveat here, however. Matlab structure-field names are limited in length, and are not allowed to contain any strange characters. The underlying parameter-file implementation is much more tolerant. Therefore if you have long names or weird names with dots and hashes in them, **pf2struct** will fail and you will need to use **pfget\_string** or other appropriate functions on the subsidiary *dbpf* object.

With reasonable parameter files, however, **pf2struct** will work fine:

```
>> mystruct=pf2struct(ans)
```

```
mystruct =
```

```
    ball: 'Kirby'
  chewtoy: 'Rover'
    mouse: 'Jasmine'
```

```
>>
```

In order to simplify reading complex, nested parameter files, the **pfget\_arr**, **pfget\_tbl**, **pf2struct**, **pfget**, and **pfresolve** commands (the latter are described below) allow a ‘recursive’ option:

```
>> pfget_arr(pf,'thing_owners','recursive')
```

```
ans =
```

```
    ball: 'Kirby'
  chewtoy: 'Rover'
    mouse: 'Jasmine'
```

```
>>
```

The **pfget** routine is generic, exercising its discretion on what datatype to return. Numbers are always considered string values, which may be converted by the user with Matlab’s **str2num** function:

```
>> pfget(pf,'thing_names')
```

```
ans =
```

```
    'ball'
    'chew-toy'
    'toy mouse'
```

```
>>
```



If a parameter-file entry is specified with the *&ask* tag, as is the parameter named *on\_the\_fly* above, the user will be queried directly. This is based on the Matlab INPUT command, which means that answer may be given using the full-fledged Matlab interpreter:

```
>> pfget(pf,'on_the_fly')
What is a convenient value for this : 27 + 13*pi

ans =

    67.8407

>>
```

Repeated calls are dynamically re-queried:

```
>> pfget(pf,'on_the_fly')
What is a convenient value for this : 'a string value'

ans =

    a string value

>>
```

Next, we will look at a more complex example. Real-time operations at the Alaska Earthquake Information Center are managed in part by a parameter-file specifying real-time system setup. This is actually one of several files, helping administrators track the multiple *Antelope Seismic Information Systems* that are running.

```
>> setup=dbpf('aeic_rtsys')

setup =

    dbpf object: 1-by-1

>>
```

Again, we will use the **pfiles** command to see the filenames contributing to this *dbpf* object:

```
>> pfiles('aeic_rtsys')

ans =

    '/opt/antelope/4.2u/data/pf/site/aeic_rtsys.pf'

>>
```

As an interlude to help the reader understand the following demonstration of parameter file commands, here is the `aeic_rtsys.pf` parameter file itself:

```
nordic% cat /opt/antelope/4.2u/data/pf/site/aeic_rtsys.pf

primary_system op

processing_systems &Arr{

    op &Arr{
        system_name      Operation
        host              earlybird
        site_database     /iwrn/op/params/Stations/worm
        archive_database  /iwrn/op/db/archive/archive
    }

    dev &Arr{
        system_name      Development
        host             nordic
        site_database     /iwrn/dev/params/Stations/worm
        archive_database  /iwrn/dev/db/archive/archive
    }

    bak &Arr{
        system_name      Backup
        host             ice
        site_database     /iwrn/bak/params/Stations/worm
        archive_database  /iwrn/bak/db/archive/archive
    }
}

rtexec_run_dirs &Arr{
    nordic      /iwrn/dev/run
    earlybird   /iwrn/op/run
    ice         /iwrn/bak/run
    fk         /home/bbanddat/run
    beam       /iwrn/acq/run
    marvin     /home/uafarr/run
    megathrust /home/beeper/run
    strike     /export/mitch/run
    ugle       /Seis/ugle1/run
}
nordic%
```

Again, the **pfkeys** command names the component parameters:

```
>> pfkeys(setup)
```

```
ans =
```

```
    'primary_system'
    'processing_systems'
    'rtexec_run_dirs'
```

We will take three approaches to answering the question “where is the primary acquisition system currently putting continuous waveform data.” The first mechanism of asking this from the parameter file is deliberately long-winded, for instructional purposes:

```
>> sys=pfget(setup,'processing_systems')
```

```
sys =
```

```
    dbpf object: 1-by-1
```

```
>> pfkeys(sys)
```

```
ans =
```

```
    'bak'
    'dev'
    'op'
```

```
>>
```

```
>> op = pfget(sys,'op')
```

```
op =
```

```
    dbpf object: 1-by-1
```

```
>>
```

```
>> pfkeys(op)
```

```
ans =
```

```
    'archive_database'
    'host'
    'site_database'
    'system_name'
```

```
>> pfget_string(op,'archive_database')
```

```
ans =

/iwrun/op/db/archive/archive

>>
```

Now let's speed that up a bit:

```
>> nestedanswer = pf2struct(setup,'recursive');
>> nestedanswer.processing_systems.op.archive_database

ans =

/iwrun/op/db/archive/archive

>>
```

In addition to the parameter-file reading interface described above, there is an alternative interface through the **pfresolve** command. This allows square-brackets in the parameter name to index list (Tbl) entries, and curly braces to index associative-array entries. We will combine these with a nested **pfget** inquiry to find the name of the primary system:

```
>> name=[ 'processing_systems{' pfget(setup,'primary_system') ...
' }{archive_database}'];
>> pfresolve(setup,name)

ans =

/iwrun/op/db/archive/archive

>>
```

Note that this setup allows system maintainers to smoothly transition between operational and backup Antelope systems. By switching the primary system from Operation to Backup, operators can preserve continuous, transparent service to user processes while installing new disk drives etc.

About this time, when one gets multiple *dbpf* objects constructed and needs to keep track of them, it is useful to be able to identify the type of each dbpf object. This is done with the **pftype** command:

```
>> pftype(sys)

ans =

PFARR
```

```
>> pftype(setup)
```

```
ans =
```

```
PFFILE
```

```
>>
```

Top-level *dbpf* objects will be of type PFFILE. Subsidiary arrays are indicated with PFARR. The names under which PFFILE-type *dbpf* objects were launched may be obtained with the **pfname** command:

```
>> pfname(pf)
```

```
ans =
```

```
test
```

```
>> pfname(setup)
```

```
ans =
```

```
aeic_rtsys
```

```
>>
```

When one is done with a Matlab *dbpf* object, one can call **pf-free** or **clear()** on it in order to remove the object. Note, however, that subsidiary parameter-file objects will no longer be useful once the parent is cleared, so it is important to get all the information one wants out of a parameter file object before freeing or clearing it.

```
>> pf-free(setup)
```

```
>>
```

```
>> clear(op)
```

```
>> clear(sys)
```

```
>>
```

Values may also be written to parameter files with the **pfput** series of command, or with the **dbpf** command used to compile strings into parameter files. This is explained in the documentation for the individual commands below. If a parameter file is changing from the outside as your Matlab program runs, the **pfupdate** command may be used to keep up with any changes to the parameter file.

## Advanced Example

Get 100 seconds of data that occurred 10 minutes ago on the network of stations at Shishaldin volcano:

```

pf=dbpf('aeic_rtsys');

% Get the name of the current archive database from our local parameter file
primary = pfget(pf,'primary_system');
dbname = pfresolve(pf,['processing_systems{' primary '}{archive_database}']);

db = dbopen( dbname, 'r' );

db = dblookup_table( db, 'affiliation' );

net = 'Shshldn';
db = dbsubset(db, ['net == "' net '"]);

dbw = dblookup_table( db, 'wfdisc');
db=dbjoin(db, dbw);

% Get data from 10 minutes ago:
st = str2epoch('now') - 600;
et = st + 100;

tr = trload_css( db, st, et );


nrecs = dbquery( tr, 'dbRECORD_COUNT');

for i=1:nrecs,
    subplot( nrecs, 1, i )
    tr.record=i-1;
    data=trextract_data(tr);
    plot(data)
    ylabel(dbgetv(tr,'sta'));
end

trdestroy( tr );
dbclose( db );

```

Channel names are not labelled. One station has three components, and another has both a vertical component and a pressure sensor, explaining the repetition of names in this figure.



## Examples of each command

Many of these presume you have run the command **dbexample\_get\_demodb\_path**, which sets the variable *demodb\_path* to the name of a sample database. An attempt was made to make each of these examples self-sufficient. Hence there are usually a number of setup commands to make the example call possible. Some of the examples may be a bit contrived. Note that in practice, it is not necessary to keep reopening a database or a parameter-file object! The parameter-file routines use the *dbloc2.pf* and the *rtexec.pf* parameter files as examples. They should be available on any properly installed Antelope system. There are also Matlab .m files showing examples of each command in use. These example files should be in \$ANTELOPE/data/matlab/antelope/examples on a properly configured system. For a list of available examples, type **help antelope/examples**.

### *arrtimes*

The **arrtimes** command calculates the travel-times of all known seismic phases, given the distance *delta* in degrees to the earthquake and the depth of the earthquake in kilometers. The default travel-time model is IASPEI '91, however this may be modified with the *TAUP\_TABLE* environment variable. The returned travel-time values are in seconds. In this example, we feed the result to **strtdelta** to produce a more readable result.

```
>> delta = 20;
>> depth = 10;

>> [times, phasenames] = arrtimes( delta, depth );

>> [char(strtdelta(times)) char(phasenames)]
```

```
ans =
```

4:33 minutes	P
4:34 minutes	Pn
4:36 minutes	pP
4:37 minutes	sP
4:37 minutes	pPn
4:38 minutes	P
4:39 minutes	sPn
4:41 minutes	pP
4:42 minutes	sP
4:49 minutes	PnPn
8:18 minutes	S
8:20 minutes	Sn
8:20 minutes	S
8:21 minutes	S
8:23 minutes	sS



8:24 minutes	sSn
8:25 minutes	sS
8:25 minutes	sS
8:27 minutes	S
8:30 minutes	pS
8:32 minutes	sS
8:36 minutes	SnSn
8:48 minutes	PcP
12:25 minutes	ScP
12:26 minutes	PcS
16:07 minutes	ScS
16:37 minutes	PKiKP
16:41 minutes	pPKiKP
16:42 minutes	sPKiKP
20:08 minutes	SKiKP
31:47 minutes	PKKPdf
35:18 minutes	SKKPdf
35:19 minutes	PKKSdf
38:50 minutes	SKKSdf
40:17 minutes	P'P'df
42:47 minutes	P'P'ab
54:25 minutes	S'S'df

&gt;&gt;

## ***cggrid***

The **cggrid** command creates a Matlab object with references an Antelope computational-geome-try grid. This command may be given one argument or three. A single argument will be inter-preted as a filename, out of which a previously saved grid will be retrieved. If three arguments are given, they should be matrices of X,Y, and Z coordinate values for the grids, in the style of the Matlab **mesh** command.

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z )
```

cgg =

cggrid object: 1-by-1

&gt;&gt;

## ***cggrid\_dx***

This command returns the grid-spacing of a computational-geometry grid in the x direction:

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );

>> dx = cggrid_dx( cgg )

dx =

    0.2000

>>
```

### ***cggrid\_dy***

This command returns the grid-spacing of a computational-geometry grid in the y direction:

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );

>> dy = cggrid_dy( cgg )

dy =

    0.3000

>>
```

### ***cggrid\_free***

The **cggrid\_free** command removes a previously created cggrid object, freeing all underlying references to the Antelope cgeom(3) library. This is equivalent to the (overloaded) **clear** command for the cggrid object.

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );
>> cggrid_free( cgg )
>>
```

### ***cggrid\_get***

The **cggrid\_get** command returns a two-dimensional array of x,y, and z values for the specified grid. The second and third return values are the number of points in the x and y directions, respectively (useful if one wishes to call the **reshape** command on the result).

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );

>> [mytriplets, nx, ny] = cggrid_get( cgg );

>> whos mytriplets
Name          Size          Bytes Class

mytriplets    441x3           10584 double array

Grand total is 1323 elements using 10584 bytes

>> nx

nx =

    21

>> ny

ny =

    21


>>
```

## ***cggrid\_getmesh***

The **cggrid\_getmesh** command formats a cggrid object into three arrays of X,Y, and Z coordinate values, suitable for direct use with the Matlab **mesh**, **surf**, and related commands.

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );
>> [myx, myy, myz] = cggrid_getmesh( cgg );

>> surf( myx, myy, myz )
>>
```



### ***cggrid\_nx***

This command returns the number of points for a computational-geometry grid in the x direction:

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );
```

```
>> nx = cggrid_nx( cgg )
```

```
nx =
```

```
21
```

```
>>
```

## ***cggrid\_ny***

This command returns the number of points for a computational-geometry grid in the y direction:

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );

>> ny = cggrid_ny( cgg )

ny =

    21

>>
```

## ***cggrid\_write***

The **cggrid\_write** command sends a **cggrid** object to a filename in the specified format. The format is indicated by a two-letter string, such as 'as' or 't4', as documented in the Unix man-page **cggrid(5)**.

```
>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );
>> outfile = ['/tmp/mycggrid_' getenv('USER')];

>> cggrid_write( cgg, 't4', outfile )
>>
```

## ***cggrid2db***

The **cggrid2db** command assumes the specified grid is associated with an earthquake. The database-pointer provided must be aimed at a row containing the origin-time ('time') and origin-id ('orid') for the hypocenter. The database must also contain a 'qgrid' table as in the gme1.0 database schema, to hold a reference to the output qgrid file. The arguments to **cggrid2db** in the example below are, respectively, the input grid; the database pointer containing information on the corresponding earthquake; the name of the recipe used to create the grid; the name of the grid itself; a formatting string for the filename in which to save the grid; the format of the grid; and the units of the grid (acceleration in g):

```
>> % Construct a contrived grid:
```

```

>> [X,Y] = meshgrid(-2:0.2:2,-3:0.3:3);
>> Z = exp( -X.^2 - Y.^2 );
>> cgg = cggrid( X, Y, Z );

>> % Save this to a fake database as though it belonged
>> % to an earthquake:

>> output_dir = ['/tmp/templdir_' getenv('USER')];
>> unix( ['/bin/rm -rf ' output_dir] );
>> unix( ['mkdir ' output_dir] );

>> output_dbname = [output_dir 'newdb'];
>> fid = fopen( output_dbname, 'w' );
>> fprintf( fid, '#\nschema rt1.0:gme1.0\n' );
>> fclose( fid );

>> db=dbopen( output_dbname,'r+' );
>> db=dblookup( db,',','origin',',',');

>> orid = dbnextid( db, 'orid' );
>> db.record = dbaddv( db, 'lat', -116, ...
    'lon', 34, ...
    'depth', 0, ...
    'time', str2epoch( '12/31/2002' ), ...
    'orid', orid );

>> cggrid2db( cgg, db, 'dbexample_fake', 'testgrid', ...
    '%Y/%j/%j%{gridname}_%{recipe}.%{qgridfmt}', ...
    't4', 'g' );
>>

```

## *clear\_register*

Most of the toolbox routines are pretty good about complaining of problems when they occur. However, if you suspect the package is caching a useful error message, this is the way to bring them to the surface.

```

>> clear_register('print')
>>
>> % [...if there were error messages accumulated, this would have flushed them out...]

```

## *db2struct*

This is probably one of the more useful commands in the toolbox. It can operate on a database table or on a view that contains only one table (for example, it will work on a view showing a subset of the origin table, but not a view that was made by joining the origin and assoc tables).

```
>> db = dbopen(demodb_path,'r');
>> db = dblookup_table( db, 'origin' );
>> db.record=0;
>>
>> % Example 1:
>> db2struct(db)
```

```
ans =
```

```
    lat: 40.0740
    lon: 69.1640
  depth: 155.1660
   time: 7.0437e+08
    orid: 1
    evid: -1
   jdate: 1992118
    nass: 7
    ndef: 7
    ndp: -1
    grn: 715
    srn: 48
   etype: '-'
  review: ''
  depdp: -999
   dtype: 'f'
    mb: 2.6200
   mbid: 1
    ms: -999
   msid: -1
    ml: -999
   mlid: -1
algorithm: 'locsat:kyrgyz'
   auth: 'JSPC'
  commid: -1
   lddate: 790466871
```

```
>>
>>
>> % Example 2:
>> db=dblookup(db,'','','dbALL');
>> db2struct(db)
```

ans =

1x1351 struct array with fields:

lat  
lon  
depth  
time  
orid  
evid  
jdate  
nass  
ndef  
ndp  
grn  
srn  
etype  
review  
depdp  
dtype  
mb  
mbid  
ms  
msid  
ml  
mlid  
algorithm  
auth  
commid  
lddate

>>

>>

>> % Example 3:

>> **db.record=0;**

>> **db2struct(db,'lat','lon','depth','mb')**

ans =

lat: 40.0740  
lon: 69.1640  
depth: 155.1660  
mb: 2.6200

>>



## *dbadd*

The raw storage format of the Datascope files is fixed-format ASCII rows. Usually, interaction with the database tables is smoother if you avoid handling entire rows at once. However, there are occasions where it is useful to move an entire row around. **dbadd** adds an entire database row to the flat-file table at once. The database pointer for each table contains something called a ‘scratch’ record for that table. The scratch record is an entire row that is in memory for the sole purpose of scribbling. In this example we add several values to the scratch row of the origin table, then write the scratch row to the database (i.e. in this example that means we’ve written the fixed-format ASCII row to the end of the file /tmp/newdb.origin).

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup(db,'','origin','','dbSCRATCH');
>> dbputv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>> db.record=dbadd(db,'dbSCRATCH')

db =

    database: 0
      table: 10
      field: -501
    record: 0

>>
```

## *dbadd\_remark*

The css3.0 schema, plus several other related schemas, have a separate table for comments. This table is infrequently used. The **dbadd\_remark** and **dbget\_remark** functions encapsulate the operations involved in adding a row to the remark table and linking it to a database row on another table such as the origin table..

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> db.record = dbaddnull(db);
>> dbputv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>> dbadd_remark(db,'This earthquake occurred under Palmer, Alaska')
>>
```

## *dbaddnull*

Similar to **dbadd**, **dbaddnull** puts into a database table an entire fixed-format ASCII row, with format appropriate for that table. In this case all the fields of the new row are set to their null values.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> db.record = dbaddnull(db)
```

```
db =
```

```
database: 0
table: 10
field: -501
record: 0
```

```
>>
```

## ***dbaddv***

This is one of the most commonly used functions in the Datascope libraries. **dbaddv** adds a new fixed-format row to the specified table, setting all fields to their null values. It then modifies the specified fields to contain the more interesting values given in each key-value pair. **dbaddv** checks to make sure none of the primary keys match those for another row of the database, i.e. it takes some steps to keep you from corrupting your database.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
```

```
db =
```

```
database: 0
table: 10
field: -501
record: 0
```

```
>>
```

## ***dbclose***

This routine closes a database pointer, freeing all the associated resources (It does no harm to the underlying database files).

```
>> db = dbopen(demodb_path,'r');
>> dbclose(db)
>>
```

## *dbcrunch*

Removing rows from a database is usually done in two steps. The first is to set all the fields of a row to their null values, but to leave the row in its place. This first step is performed by **dbmark**. The second stage, accomplished by the **dbcrunch** command, is to actually remove the null rows from the database table. This two-step procedure prevents skewing of all the record numbers for a table, often useful if the program is still working on the table.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> % Add four copies of the same quake, all at slightly different times:
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>>
>> db.record=1;
>> dbmark(db)
>> dbcrunch(db)
>> dbquery(db,'dbRECORD_COUNT')

ans =

     3

>>
```

## *dbdelete*

This command immediately deletes a row from a database table.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> % Add four copies of the same quake, all at slightly different times:
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>>
>> dbquery(db,'dbRECORD_COUNT')

ans =

     4
```

```
>> db.record=1;
>> dbdelete(db)
>> dbquery(db,'dbRECORD_COUNT')
```

```
ans =
```

```
3
```

```
>>
```

## ***dbeval***

This command is a general-purpose calculator which has access to standard math commands, useful seismological functions such as travel-time calculators, and to all the fields of a database view which is fed to the command.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'origin');
>> dbs=dblookup_table(db,'site');
>> db.record=0;
>> db=dbjoin(db,dbs);
>> db.record=0;
>> dbeval(db,'arrival("PKiKP")-time')
```

```
ans =
```

```
982.2883
```

```
>>
```

```
>> dbeval(db,'distance(site.lat,site.lon,origin.lat,origin.lon)')
```

```
ans =
```

```
27.4124
```

```
>>
```

## ***dbextfile***

In the css3.0 schema and related schemas, many times external files are referenced in tables by the two fields *dir* and *dfile*. The **dbextfile** command combines these two fields into a full pathname, resolving all relative pathnames into absolute pathnames as well as adjusting for the actual loca-

tion of the database table. The `dbextfile` command requires the name of the base table from which the *dir* and *dfile* fields should come. (Note that in many cases, the simpler **dbfilename** command will suffice instead of **dbextfile**).

```
>> db = dbopen( demodb_path,'r' );
>> db = dblookup_table( db, 'wfdisc' );
>> dbt = dblookup_table( db, 'sensor' );
>> db = dbjoin( db, dbt );
>> dbt = dblookup_table( db,'instrument' );
>> db = dbjoin( db, dbt );

>> db.record=0;

>> dbextfile( db, 'instrument' )

ans =

/usr/local/matlab/toolbox/antelope/examples/demodb/response/sts2_vel_RT72A.1

>> dbextfile( db, 'wfdisc' )

ans =

/usr/local/matlab/toolbox/antelope/examples/demodb/wf/knetc/1992/138/210426/
19921382155.15.CHM.BHZ

>>
```

## ***dbfilename***

In the `css3.0` schema and related schemas, many times external files are referenced in tables by the two fields *dir* and *dfile*. The **dbfilename** command combines these two fields into a full pathname, resolving all relative pathnames into absolute pathnames as well as adjusting for the actual location of the database table.

```
>> db = dbopen(demodb_path,'r');
>> dblookup_table(db,'instrument');
>> db.record=0;
>> dbfilename(db)

ans =

/opt/antelope/4.2u/data/matlab/antelope/examples/demodb/response/sts2_vel_RT72A.1
```

```
>>
```

Note that if more than one table with external file references is present in the input view, only the first one will be chosen and returned. This may not always be the intended filename. For cases where the *dir* and *dfile* fields appear multiple times in the input view, use **dbextfile** instead of **dbfilename**.

## ***dbfind***

This command is a general-purpose utility to hunt through a database table or view for a record matching a specific criterion. Useful features include the ability to skip the first few matches, or to search backwards through the view.

```
>> db = dbopen(demodb_path,'r');
>> db = dblookup_table( db, 'origin' );
>> db.record = dbfind(db,'mb>6',0)
```

```
db =
```

```
database: 0
table: 10
field: -501
record: 80
```

```
>>
```

```
>> db.record = dbfind(db,'mb>6',0,3)
```

```
db =
```

```
database: 0
table: 10
field: -501
record: 266
```

```
>>
```

```
>> db.record = dbfind(db,'mb>6','backwards')
```

```
db =
```

```
database: 0
table: 10
field: -501
record: 1262
```

```
>>
>> dbgetv(db,'mb')
```

```
ans =
```

```
6.1400
```

```
>>
```

## ***dbfree***

This command frees up the resources allocated when a new view is created. The input database pointer must identify a single table, that is db.table and db.database should be valid. Generally, it is only necessary to explicitly free database views when they are very large or many of them are made within the same program.

```
>> db = dbopen( demodb_path,'r' );
>> dbarrival = dblookup_table( db,'arrival' );
>> % Make a temporary view
>> dbtemp = dbsubset( dbarrival, 'sta == "AAK"' );
```

```
>> % Get something out of the temporary view
>> dbgetv( dbtemp, 'deltim' )
```

```
ans =
```

```
0.0980
```

```
2.1640
```

```
2.2220
```

```
>> % Free resources associated with the temporary view
>> dbfree( dbtemp );
>>
```

## ***dbget***

As explained for the **dbadd** command, the underlying storage of database tables is as fixed-format ASCII rows. The **dbget** command can be used to retrieve an entire database row as a string (in fact, it is much more general, allowing the retrieval of entire tables or just specific fields depending on the value of the database pointer). Rather than trying to parse the output of **dbget**, use **dbgetv** to find specific pieces of information in a table or database row.

```
>> db = dbopen(demodb_path,'r');
>> db = dblookup_table( db, 'origin' );
>> db.record=0;
```

```
>> dbget(db)
```

```
ans =
```

```
40.0740 69.1640 155.1660 704371900.66886 1 -1 1992118 7 7 -1 715
48 - -999.0000 f 2.62 1 -999.00 -1 -999.00 -1 locsat:kyrgyz JSPC -
1 790466871.00000
```

```
>>
```

## ***dbget\_remark***

As explained under **dbadd\_remark**, **dbget\_remark** eases the retrieval of comments in databases with the css3.0 *remark* table.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> db.record = dbaddnull(db);
>> dbputv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>> dbadd_remark(db,'This earthquake occurred under Palmer, Alaska')
>> dbget_remark(db)
```

```
ans =
```

```
This earthquake occurred under Palmer, Alaska
```

```
>>
```

## ***dbgetv***

The **dbgetv** command is one of the most frequently used commands in the Antelope programming environment. With **dbgetv** one can get specific fields out of a database row. A unique characteristic of the Matlab-interface **dbgetv** command is the ability to extract entire columns at once out of a database table.

```
>> db = dbopen(demodb_path,'r');
>> db = dblookup_table( db, 'origin' );
>> db.record=0;
>> [lat,lon,auth] = dbgetv(db,'lat','lon','auth')
```

```
lat =
```

```
40.0740
```



```
lon =
```

```
69.1640
```

```
auth =
```

```
JSPC
```

```
>>
```

```
>> db = dbsubset(db,'mb>6');
```

```
>> dbgetv(db,'mb')
```

```
ans =
```

```
6.4200
```

```
6.4000
```

```
6.2000
```

```
6.2000
```

```
6.2300
```

```
6.4000
```

```
6.3100
```

```
6.0200
```

```
6.2800
```

```
6.5000
```

```
6.5700
```

```
6.1100
```

```
6.0500
```

```
6.2100
```

```
6.3000
```

```
6.3000
```

```
6.2700
```

```
6.1400
```

```
>>
```

## ***dbgroup***

The **dbgroup** command takes a sorted view and groups the records into ‘bundles’, clustering together all those records that have the same values for the group fields. For example, in the operation below we take the arrival table, sort it by station, and group arrivals together by station. This allows us to make an easy count of the number of arrivals at each station, via the ‘count()’ function in **dbeval**. The input list of group fields should be a cell-array of strings, hence the squiggly brackets in the **dbgroup** call below.

```

>> db = dbopen( demodb_path,'r' );
>> db = dblookup_table( db, 'arrival' );
>> db = dbsort( db, 'sta' );
>> db = dbgroup( db, { 'sta' } );
>> % Find the number of arrivals at each station:
>> for i=1:dbnrecs(db)
    db.record=i-1;
    sta = dbgetv(db,'sta');
    narr = dbeval( db, 'count()' );
    sprintf( '%s %d\n', sta, narr )
>> end

```

ans =

AAK 3

ans =

CHM 2

ans =

EKS2 1

ans =

KBK 2

ans =

KMI 1

ans =

TKM 1

ans =

USP 2

## ***dbinvalid***

The database-pointer is actually a structure of four integers. There is an 'invalid' value for all of these which is occasionally useful for tests or as the input to some commands.

```
>> db = dbinvalid
```

```
db =
```

```
database: -102
table: -102
field: -102
record: -102
```

```
>>
```

## ***dbjoin***

dbjoin allows the user to construct composite views in a relational database. Information in each table is cross-referenced according to its primary fields to construct a set of the corresponding, joined rows.

```
>> db = dbopen(demodb_path,'r');
>> dbarrival=dblookup_table(db,'arrival');
>> dbwfdisc=dblookup_table(db,'wfdisc');
>> db=dbjoin(dbarrival,dbwfdisc)
```

```
db =
```

```
database: 0
table: 34
field: -501
record: -501
```

```
>>
```

## ***dbjoin\_keys***

The standard Datascope join operations between database tables are accomplished by inferring the sensible join keys with which to combine the two tables. **dbjoin\_keys** explains which fields were used or will be used to perform a join.

```
>> db = dbopen(demodb_path,'r');
>> dbarrival=dblookup_table(db,'arrival');
>> dbwfdisc=dblookup_table(db,'wfdisc');
>>
>> % Example 1:
>> dbjoin_keys(dbarrival,dbwfdisc)
```

```

ans =

    'sta'
    'time == time::endtime'

>>
>> % Example 2:
>> dbjoin_keys(db,'origin','assoc')

ans =

    'orid'

>>

```

## ***dblookup***

The four-element dbpointer structure, used as a handle to reference different fields or sections of a relational database, is rarely modified by hand. **dblookup** allows the four elements of the dbpointer structure to be aimed based on human-readable names for the tables and fields. Additionally, several recognized constants such as 'dbALL' and 'dbSCRATCH' allow further control of the parts of the database to which dblookup aims the database pointer.

```

>> db = dbopen(demodb_path,'r');
>> dblookup(db,',','origin',',','dbALL')

ans =

    database: 0
    table: 10
    field: -501
    record: -501

>>

```

## ***dblookup\_table***

One of the most common operations with **dblookup** is to aim the database pointer at a particular table. **dblookup\_table** is an easier-to-type shorthand for this operation.

```

>> db = dbopen(demodb_path,'r');
>> db = dblookup_table(db,'origin')

db =

```

```

database: 0
table: 10
field: -501
record: -501

```

```
>>
```

## ***dbmark***

This command is the first stage of a two-part process to remove a row from a database table, as explained under **dbcunch**. For the impatient, see **dbdelete**.

```

>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> % Add four copies of the same quake, all at slightly different times:
>> db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>>db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>>db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>>db.record=dbaddv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'));
>>
>> db.record=1;
>> dbmark(db)
>>

```

## ***dbnextid***

In several of the css3.0-style database tables, entries such as hypocentral solutions (“origin” table) or seismic phase arrivals (“arrival” table) are identified with unique, integer id’s. The **dbnextid** command allows the retrieval of the next unused value for any of these integer indices.

```

>> db=dbopen('/tmp/newdb','r+');
>> dbnextid(db,'orid')

```

```
ans =
```

```
1
```

```
>>
```

## ***dbnojoin***

Similar to **dbjoin**, the **dbnojoin** command returns a view showing rows in the first table that have no counterpart in the second.

```
>> db = dbopen(demodb_path,'r');
>> dbarrival=dblookup_table(db,'arrival');
>> dbwfdisc=dblookup_table(db,'wfdisc');
>> db=dbnojoin(dbarrival,dbwfdisc)
```

```
db =
```

```
database: 0
table: 36
field: -501
record: -501
```

```
>>
```

## ***dbnrecs***

The **dbnrecs** command returns the number of records in a database table or view.

```
>> db = dbopen( demodb_path,'r' );
>> db = dblookup_table( db,'origin' );
>> nrecs = dbnrecs( db )
```

```
nrecs =
```

```
1351
```

```
>>
```

## ***dbopen***

The first step in using Datascope on a relational database is to create a ‘handle’, called a database pointer, to the ASCII flat files which store the database contents. This step is performed by **dbopen**. Here we have written a small routine to reliably provide the pathname of a sample database for these examples.

```
>> dbexample_get_demodb_path
```

```
demodb_path =
```

```
/opt/antelope/4.2u/data/matlab/antelope/examples/demodb/demo
```

```
>> db = dbopen(demodb_path,'r')
```

```
db =
```

```

database: 0
table: -501
field: -501
record: -501

```

```
>>
```

## ***dbpf***

Many programs require some form of parameter file to store information about run-time configuration. The Antelope parameter-file utility provides a very powerful mechanism to handle such input files, including boolean, string, and numeric values as well as tables or key-value arrays, all of which can be nested. In the Antelope Toolbox for Matlab, interaction with a parameter file is through a 'handle' called a dbpf object. See the Antelope documentation for more details on the parameter file mechanism.

```
>> pf = dbpf( 'dbloc2' )
```

```
pf =
```

```
dbpf object: 1-by-1
```

```

>> % Now as a contrived example of the other methods of use,
>> % convert it to a string, then compile it into a new parameter-file object:
>> string_version = pf2string( pf );
>> % Create an empty parameter-file object:
>> newpf = dbpf

```

```
newpf =
```

```
dbpf object: 1-by-1
```

```

>> % Compile the new string into the empty parameter-file object:
>> % (you can compile into parameter-file objects that aren't empty as well)
>> newpf = dbpf( newpf, string_version)

```

```
newpf =
```

```
dbpf object: 1-by-1
```

```
>>
```

## ***dbprocess***

**Dbprocess** provides a simplified interface for forming various views. When a sequence of standard database operations (such as subsets, joins, sorts, etc.) need to be performed all in a row, they can be combined into a single block, passed as a list of statements to **dbprocess**.

```
>> db = dbopen( demodb_path,'r' );

>> db = dbprocess( db, { 'dbopen arrival';
                          'dbsubset sta == "AAK"';
                          'dbjoin assoc' } );

>> [iphase, delta] = dbgetv( db,'iphase', 'timeres' )

iphase =

    'P'
    'S'

delta =

   -0.0500
    0.8600

>>
```

Detailed explanations of the valid statements available in dbprocess may be found in the unix man-pages for the dbprocess command. For reference, a summary list is provided here:

```
dbopen table
dbjoin [-o] table [ key key ..]
dbgroup key [ key ..]
dbleftjoin [-o] table [ key key ..]
dbnojoin table [ key key ..]
dbselect expr [expr ...]
dbseparate table
dbsever table
dbsort [-ru] key .. ]
dbsubset expression
dbtheta table [ expression ..]
dbungroup
```

## ***dbput***



This function is similar to **dbput**, however it does not automatically add its own null row. Also, it does not do any consistency checking to make sure the new row makes sense given the contents of the rest of the table. Again, avoid working with entire rows at once unless necessary. Consider using **dbputv** if possible.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> db.record = dbaddnull(db);
>> dbputv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>> record = dbget(db)
```

```
record =
```

```
61.5922 -149.1300 20.0000 923760231.63253 -1 -1 -1 -1 -1 -1 -1 -1
- - -999.0000 - -999.00 -1 -999.00 -1 -999.00 -1 - - - -1
923760231.66952
```

```
>>
>> db.record = dbaddnull(db);
>> dbput(db,record)
>>
```

## ***dbputv***

The **dbputv** command is used to put individual field values into a database row. This is an extremely important command in the Datascope library. Here, we make a new row with the **dbaddnull** command so we have somewhere to put our values.

```
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'origin');
>> db.record = dbaddnull(db);
>> dbputv(db,'lat',61.5922,'lon',-149.130,'depth',20,'time',str2epoch('now'))
>>
```

## ***dbquery***

The **dbquery** command is used to request a wide variety of information about a database or one of its component parts. One of the most common uses is to count the number of records in a table.

```
>> db = dbopen(demodb_path,'r');
>> db = dblookup_table(db,'origin');
>> dbquery(db,'dbRECORD_COUNT')
```

```
ans =
```

```
1351
```

```
>>
```

```
>> dbquery(db,'dbTABLE_FIELDS')
```

```
ans =
```

```
'lat'  
'lon'  
'depth'  
'time'  
'orid'  
'evid'  
'jdate'  
'nass'  
'ndef'  
'ndp'  
'grn'  
'srn'  
'etype'  
'review'  
'depdp'  
'dtype'  
'mb'  
'mbid'  
'ms'  
'msid'  
'ml'  
'mlid'  
'algorithm'  
'auth'  
'commid'  
'lddate'
```

```
>>
```

```
>> dbquery(db,'dbDATABASE_NAME')
```

```
ans =
```

```
/opt/antelope/4.2u/data/matlab/antelope/examples/demodb/demo
```

```
>>
```

## ***dbread\_view***

**dbread\_view** is a less common command, used to read a view out of a file (for example, out of the file saved by **dbsave\_view**). An example of that straightforward usage is shown in the script **dbexample\_dbread\_view.m**. For the tutorial we will show a far more unconventional use just to add interest. We will create a named-pipe with the unix *mkfifo*(1) command, then write to that pipe by calling the command-line version of *dbsubset* [Note for the advanced that it's necessary to do that in the background when using the Matlab **unix()** command, since the pipe will not close until the other end is read and flushed]. Then we get the database view out of the pipe and into Matlab with the **dbread\_view** command:

```
>> unix('mkfifo /tmp/mypipe');
>> unix(['dbsubset ' demodb_path '.origin "ms > 6.8" > /tmp/mypipe &']);
>> db = dbread_view( '/tmp/mypipe' )
```

```
db =
```

```
database: 3
table: 45
field: -501
record: -501
```

```
>> dbgetv( db, 'ms' )
```

```
ans =
```

```
7.1000
7.5000
6.9000
7.0000
```

```
>>
```

## ***dbresponse***

The css3.0 schemas and related schemas reference instrument response information in separate files. These response files allow poles-and-zeros format, frequency-amplitude-phase triplet format, FIR format, and more. The **dbresponse** object is a handle to one of these response files, from which response information can be extracted.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'instrument');
>> db.record=0;
>> file=dbfilename(db)
```

```

file =

/opt/antelope/4.2u/data/matlab/antelope/examples/demodb/response/sts2_vel_RT72A.1

>>
>> resp = dbresponse(file)

resp =

    dbresponse object: 1-by-1

>>

```

## *dbsave\_view*

**dbsave\_view** takes a current view into a database and saves it as though it were a base table of the main database. This is useful if a lot of processing was necessary to create the original view. Note that because the Antelope Toolbox for Matlab does not currently support named views, the name of the saved view will default to the name assigned by Datascope. However, once the database is closed the file may be moved to a new name. Also note that saved views are binary files of indexes. The **dbe** program should be used to view them. Views will become stale if any of the component tables change. To make an example of this command, we will copy the necessary parts of the demo database, make a joined view, and save it:

```

>> output_dbname = ['/tmp/newdb_' getenv('USER')];
>> unix( ['cp ' demodb_path '.arrival ' output_dbname '.arrival'] );
>> unix( ['cp ' demodb_path '.wfdisc ' output_dbname '.wfdisc'] );
>> db = dbopen( output_dbname,'r' );

>> dbarrival=dblookup_table( db,'arrival' );
>> dbwfdisc=dblookup_table( db,'wfdisc' );
>> db=dbjoin( dbarrival,dbwfdisc );

>> dbsave_view( db );
>>

```

## *dbseparate*

**dbseparate** extracts the rows from the specified base table that participate in a given view. For example, we can start with a whole set of wfdisc records, construct a view that joins them ultimately to hypocentral information, subset for a hypocenter of interest, and then extract the resulting wfdisc records which have matched:

```

>> db = dbopen( demodb_path,'r' );
>> db = dbprocess( db, { 'dbopen wfdisc'; ...

```

```

    'dbjoin arrival'; ...
    'dbjoin assoc'; ...
    'dbjoin origin'; ...
    'dbsubset orid == 645' } );
>> db = dbseparate( db, 'wfdisc' );

>> db.record=0;
>> dbextfile( db, 'wfdisc' )

ans =

/opt/antelope/data/db/demo/wf/knetc/1992/138/210426/19921382155.15.CHM.BHZ

>>

```

For brevity, we have only printed one of the resulting file names from the records this retrieved.

## ***dbsever***

The **dbsever** command takes an existing view and removes an unwanted or no-longer needed table from that view. The returned value is a view without any fields from the removed table. If necessary, the resulting view is condensed to eliminate any duplicate rows.

```

>> db = dbopen( demodb_path,'r' );
>> dborigin=dblookup_table( db,'origin' );
>> dbstamag=dblookup_table( db,'stamag' );
>> db=dbjoin( dborigin, dbstamag );

>> % Get rid of the stamage values now that we know which orids have stamags:
>> db= dbsever( db, 'stamag' )

db =

database: 1
table: 46
field: -501
record: -501

>> dbgetv( db, 'orid' )

ans =

645

>>

```

## ***dbsort***

This command takes any database view and returns a view sorted according to the specified expression.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'origin');
>> db=dbsubset(db,'mb>6.3');
>> db=dbsort(db,'mb');
>> dbgetv(db,'mb')
```

ans =

```
6.3100
6.4000
6.4000
6.4200
6.5000
6.5700
```

```
>>
```

If one of the arguments to `dbsort` is `'dbSORT_UNIQUE'`, the view returned will have only one representative for each unique value of the sort field(s). I.e. rows which have duplicate sort keys will be eliminated. If one of the arguments is `'dbSORT_REVERSE'`, the sort will be performed in reverse order.

## ***dbsubset***

This command, fairly self-explanatory, returns a database view containing only those rows from the input view which match the specified expression.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'origin');
>> db=dbsubset(db,'mb>6.3');
>> dbgetv(db,'mb')
```

ans =

```
6.4200
6.4000
6.4000
6.3100
6.5000
```

6.5700

>>

## ***dbtheta***

In the **dbjoin** command, specified above, the comparison fields (“join keys”) used to describe which rows correspond were inferred. The **dbtheta** command allows you to perform the join with full command over whether or not two rows should be associated together or not, based on the supplied test expression.

```
>> db = dbopen(demodb_path,'r');
>> dbassoc = dblookup_table(db,'assoc');
>> dbwfdisc = dblookup_table(db,'wfdisc');
>> db=dbtheta(dbassoc,dbwfdisc,'assoc.sta == wfdisc.sta')
```

db =

```
database: 0
table: 45
field: -501
record: -504
```

>>

## ***dbungroup***

The **dbungroup** command is the inverse of the **dbgroup** command. It unpacks a bundle of rows into a view containing the individual rows.

```
>> db = dbopen( demodb_path,'r' );
>> db = dblookup_table( db, 'arrival' );
>> db = dbsort( db, 'sta' );
>> db = dbgroup( db, { 'sta' } );

>> % Subset for one station:
>> db = dbsubset( db, 'sta == "AAK"' );

>> db = dbungroup( db );

>> % Get the arriving phases detected at this station:
>> db = dblookup( db, ',', ',', ',', 'dbALL' );
>> dbgetv( db, 'iphase' )
```

ans =

```

'S'
'P'
'del'

>>

```

## ***dbunjoin***

Once a view is created, many database operations can be performed on it which winnow out certain rows of each component table. The resulting view may be split into the component rows from each participating table and written to a new database. This is accomplished with the **dbunjoin** command.

```

>> db = dbopen(demodb_path,'r');
>> dbarrival=dblookup_table(db,'arrival');
>> dbwfdisc=dblookup_table(db,'wfdisc');
>> db=dbjoin(dbarrival,dbwfdisc);
>> dbunjoin(db,'/tmp/newdb');
>> !ls /tmp/newdb*
/tmp/newdb.arrival /tmp/newdb.wfdisc
>>

```

## ***dbwrite\_view***

**dbwrite\_view** writes a database view to a file. This can be used in a number of ways, for example to pipe a view to an external command (such as *dbe(1)*) via a named pipe. First we will set up the named pipe, and set up the Antelope *dbe* program (running in the background) waiting for input from the pipe. Then we will create our customized view in Matlab. Finally, we will write our view to the named pipe (which, like everything in unix, just looks like a file). At that point *dbe* will receive its input

```

>> pipe_name = ['/tmp/mypipe_' getenv('USER')];
>> unix( ['mkfifo ' pipe_name] );
>> unix( ['cat ' pipe_name ' | dbe - &'] );

>> db = dbopen( demodb_path,'r' );
>> dbarrival=dblookup_table( db,'arrival' );
>> dbwfdisc=dblookup_table( db,'wfdisc' );
>> db=dbjoin( dbarrival,dbwfdisc );

>> dbwrite_view( db, pipe_name );
>>

```



This causes a *dbe(1)* window to appear, showing the view that was calculated in Matlab.

## *epoch2str*

Most time handling in Antelope (not to mention Unix) is done in terms of Unix epoch seconds, or seconds since 1970. The **epoch2str** command provides a highly flexible method for creating more human-readable time strings from an epoch time.

```
>> now = str2epoch('now')

now =

    9.237062953704129e+08

>> epoch2str( now, '%D %H:%M:%S %Z')

ans =

    4/10/99 01:04:55 UTC

>> epoch2str( now, '%A, %B %d %Y')

ans =

    Saturday, April 10 1999

>>
>> epoch2str( now, '%G %l %p')

ans =

    1999-04-10  1 AM

>>
```

## *eval\_response*

This function allows a **dbresponse** object (ultimately, a file of instrument response information stored as poles and zeroes or frequency-amplitude-phase triplets etc.) to be queried for the complex response at certain frequency values.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'instrument');
>> db.record=0;
```

```
>> file=dbfilename(db);
>> resp = dbresponse(file);
>> eval_response(resp,6.28)
```

```
ans =
```

```
1.0008 - 0.0041i
```

```
>>
```

```
>> eval_response(resp,transpose([0.01 0.1 1 10])*6.28)
```

```
ans =
```

```
0.2550 + 0.8025i
```

```
0.9936 + 0.1116i
```

```
1.0008 - 0.0041i
```

```
0.0000 - 0.0000i
```

```
>>
```

## ***free\_response***

Once the user is done with a dbresponse object, it must be freed with the **free\_response** command.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'instrument');
>> db.record=0;
>> file=dbfilename(db);
>> resp = dbresponse(file);
>> free_response( resp )
>>
```

## ***getpid***

Get the system process-id of the Matlab interpreter from which this was called:

```
>> mypid = getpid
```

```
mypid =
```

```
4764
```

```
>>
```

## ***orbafter***

This command allows the user to set the beginning time for reading from an Antelope real-time ORB buffer. Note that all the orb examples below require a running orb, for which you have permission to connect.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> [result,time, srcname, pktid] = orbget( fd );
>> pktid

pktid =

    2357

>> % Get the next packet with timestamp after the packet we just got:
>> % (note that there's no a-priori requirement that packets arrive on the
>> % orb in time order)
>> orbafter( fd, time )

ans =

    497

>>
```

## ***orbclose***

This allows the user to close down an open connection to an Antelope ORB.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> orbclose( fd )
>>
```

## ***orbget***

The **orbget** command collects the specified packet from an Antelope ORB, unpacks it based on its type, and returns it to the user. Currently the understood types are waveform, parameter-file (you can put an entire parameter file on an ORB), and database-row. Other types of packets are returned as byte vectors. Each packet on an orb has a timestamp and a source-name, which are also returned.

```

>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>>
>> % First we'll get a waveform-data object from an orb:
>> fd = orbopen( 'nordic', 'r' );
>> orbreject( fd, '/db./*/pf./*' );
>> [result, time, srcname, pktid, type] = orbget( fd )

```

result =

```

    database: 16
      table: 5
      field: -501
    record: 0

```

time =

```

    9.4638e+08

```

srcname =

```

    AT_MID_SHZ

```

pktid =

```

    724328

```


type =

waveform

```

>> result.record = 0;
>> plot( trextract_data( result ) );

```



```
>> trdestroy( result );
>> orbclose( fd );

>> % Now get a database-row object from an orb:
>> fd = orbopen('megathrust','r');
>> orbselect(fd,'/db/.*');
>> orbseek(fd,'ORBOLDEST');
>> result=orbget(fd)
```

result =

```
database: 0
table: 19
field: -501
record: -504
```

```
>> [lat,lon,mb]=dbgetv(result,'lat','lon','ml')
```

lat =

```
59.8962
```

lon =

```
-152.0661
```

mb =

1.8600

```
>> % Finally, get a parameter-file object from an orb:
>> orbselect(fd,'/pf/.*');
>> orbseek(fd,'ORBOLDEST');
>> result=orbget(fd)
```

result =

dbpf object: 1-by-1

```
>> pf2string(result)
```

ans =

cmdstring "echo hi | mail kent"

```
>>
```

## ***orbopen***

The **orbopen** command allows you to establish a read or write connection to a running Antelope ORB server anywhere on the internet (provided the orbserver maintainers have given you permission to connect to that orb). You may have multiple connections at once to the same ORB.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' )
```

fd =

21

```
>>
```

## ***orbping***

This command is primarily useful to verify that an ORB connection is up and running. It has the side benefit of telling you the version number of the orbserver.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> orbping( fd )
```

```
ans =
```

```
6
```

```
>>
```

## ***orbread***

This is one of the most common orb commands. Evaluated in a tight loop, it allows you to successively receive packet after packet for the streams you've chosen. Each packet can then be processed as necessary.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> for i = 1:3,
[result,time,srcname] = orbread( fd );
srcname
end
```

```
srcname =
```

```
AK_MDM_SHZ
```

```
srcname =
```

```
AK_KTH_SHZ
```

```
srcname =
```

```
AK_MCK_SHZ
```

```
>>
```

## ***orbreject***

This command allows the user to reject certain packets from ever coming across a particular orb connection. The specification is by means of regular-expression matching on the source-names of the packets.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> % Reject all parameter-file packets, all database-row packets,
```

```
>> % and all waveform packets for the Alaska net whos station-names
>> % start with A,B, or C:
>> % (return the number of sources still available on the connection)
>> orbreject( fd, '/db/.*/pf/.*/AK_[A-C].*' )
```

```
ans =
```

```
276
```

```
>>
```

## ***orbseek***

For a given read connection to an orbserver, the **orbseek** command allows the user to position the reading point in the stream to a certain packet number or to a specified relative location in the stream (newest packet, oldest packet, next packet, etc.).

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> orbseek( fd, 'ORBOLDEST' )
```

```
ans =
```

```
790548
```

```
>> orbseek( fd, 'ORBNEXT' )
```

```
ans =
```

```
790549
```

```
>> orbseek( fd, 'ORBNEWEST' )
```

```
ans =
```

```
321046
```

```
>> orbseek( fd, 'ORBPREV' )
```

```
ans =
```

```
321045
```

```
>> orbseek( fd, 'ORBPREV' )
```



```

ans =

    321044

>> mypktid = orbtell( fd )

mypktid =

    321044

>> orbseek( fd, 'ORBPREV' )

ans =

    321043

>> orbseek( fd, mypktid )

ans =

    321044

>>

```

## ***orbselect***

**Orbselect** is a very useful command which allows the user to filter packets from an orb connection so that only those matching certain source-name criteria get through.

```

>> fd = orbopen( 'nordic', 'r' );
>> % Choose all components of station DIV (Divide, Alaska)
>> % Return the number of selected sources
>> orbselect( fd, 'AK_DIV_.*' )

ans =

     3

>>

```

## ***orbtell***

This command returns the packet-identification-number for the current packet on read connection to an orbserver.

```
>> % This presumes that you have connect permission to a running
>> % orb called 'nordic' (you probably don't...)
>> fd = orbopen( 'nordic', 'r' );
>> % Find the packet-id for the current packet:
>> ortell( fd )
```

```
ans =
```

```
377956
```

```
>>
```

## ***parsepath***

**parsepath** separates a pathname into its component parts. This is done entirely by text analysis of the input string, without any regard to whether the files, directories, or whatever they are actually exist. If the third output argument is specified, any suffix is separated from the basename of the file. Otherwise the file basename is left intact with any suffix.

```
>> [dir, base] = parsepath( '/home/kent/testfile.txt' )
```

```
dir =
```

```
/home/kent
```

```
base =
```

```
testfile.txt
```

```
>> [dir, base, suffix] = parsepath( '/home/kent/testfile.txt' )
```

```
dir =
```

```
/home/kent
```

```
base =
```

```
testfile
```

```
suffix =
```

```
txt
```

```
>>
```

## ***pf2string***

An entire parameter file (being essentially an ASCII file) or subsection thereof may be converted to a string.

```
>> pf=dbpf('dbfixids');
>> pf2string(pf)
```

```
ans =
```

```
css3.0 &Arr{
aliases &Arr{
magid  mbid msid mlid
orid  prefor
}
}
rt1.0 &Arr{
aliases &Arr{
magid  mbid msid mlid
orid  prefor
}
}
```

```
>>
```

## ***pf2struct***

The Matlab Antelope Toolbox allows an entire parameter file to be loaded into a Matlab struct, which is very close to the same idea: a flexible set of key-value pairs. The 'recursive' option to pf2struct can be used to read a complex parameter file in all at once into an easy-to-use Matlab-style object.

```
>> pf=dbpf('dbloc2');
>> pf2struct(pf)
```

```
ans =
```

```
Define: [1x1 dbpf]
Processes: [1x1 dbpf]
Run: [1x1 dbpf]
```

```

State: [1x1 dbpf]
User: [1x1 dbpf]

>>
>> pf2struct(pf,'recursive')

ans =

    Define: [1x1 struct]
    Processes: [1x1 struct]
        Run: [1x1 struct]
        State: [1x1 struct]
        User: [1x1 struct]

>>
>> ans.Define

ans =

    Results_dir: 'results'
    Temporary_db: 'trial'
    Work_dir: 'tmp'
    arrival_color: 'purple'
    arrival_info: 'arid sta time iphase deltim fm amp per auth'
    arrivals_height: '300'
    arrivals_width: '800'
    azimuth_font: '-Adobe-Helvetica-Bold-O-Normal--*-120-*'
    azimuth_info: 'azimuth delaz'
    bad_residual_color: 'orange'
    button_row: '49'
    dbpick_channel_options: [1x1 struct]
    dbpick_options_order: 'Vertical Horizontal All Selected'
    dbpick_revert_to_default: 'yes'
    fixedwidth_font: '-Adobe-Courier-Bold-R-Normal--*-120-*'
    ignored_color: 'gray60'
    max_event_delta: '5'
    max_event_time_difference: '25'
    maxcol: '25'
    maxrow: '50'
    ok_residual_color: 'DodgerBlue'
    origin_color: 'magenta'
    origin_info: [1x69 char ]
    origins_height: '150'
    origins_width: '800'
    partial_color: 'cyan'
    plain_font: '-Adobe-Helvetica-Bold-R-Normal--*-120-*'

```

```

        site_info: 'staname {lat . " , " . lon} gregion(lat,lon)'
    slowness_info: 'slow del slo'
    station_color: 'gray'
    time_font: '-Adobe-Courier-Bold-R-Normal--*-120-*'
    used_color: 'black'

```

```
>>
```

## ***pffiles***

The Antelope parameter-file mechanism allows the parameters to be extracted from any of the matching parameter files along an entire search path (specified in the PFPATH environment variable). The **pffiles** command shows which pathnames actually contributed to a given parameter-file-object's contents. The 'all' option shows all the files that were tested for existence and possible contribution.

```
>> pffiles('rtexec')
```

```
ans =
```

```
    '/opt/antelope/4.2u/data/pf/rtexec.pf'
```

```
>> pffiles('rtexec','all')
```

```
ans =
```

```
    '/opt/antelope/4.2u/data/maps/site/rtexec.pf'
```

```
    '/opt/antelope/4.2u/data/pf/rtexec.pf'
```

```
    '/opt/antelope/4.2u/data/pf/site/rtexec.pf'
```

```
    '/home/kent/data/pf/rtexec.pf'
```

```
    './rtexec.pf'
```

```
>>
```

## ***pffree***

This frees the resources used by a dbpf object when it is no longer needed.

```
>> pf = dbpf( 'dbloc2' );
```

```
>> pffree(pf)
```

```
>>
```

## ***pfget***

The **pfget** command retrieves the specified parameter from the dbpf object into an appropriate format.

```
>> pf = dbpf( 'rtexec' );
>> pfget( pf, 'Database' )
```

```
ans =
```

```
rtsys/rtsys
```

```
>>
```

## ***pfget\_arr***

This retrieves an associative array from a parameter-file object.

```
>> pf = dbpf( 'rtexec' );
>> pfget_arr(pf,'Limit')
```

```
ans =
```

```
dbpf object: 1-by-1
```

```
>>
```

```
>> pfget_arr(pf,'Limit','recursive')
```

```
ans =
```

```
coredumpsize: 'unlimited'
cputime: 'unlimited'
datasize: 'unlimited'
descriptors: 'unlimited'
filesize: 'unlimited'
stacksize: 'unlimited'
vmemoryuse: 'unlimited'
```

```
>>
```

## ***pfget\_boolean***

This retrieves a boolean value from a parameter-file object, translating strings such as 'yes' or 'false' into numeric values.

```
>> pf=dbpf('dbloc2')
```

```

pf =
    dbpf object: 1-by-1

>>
>> subpf=pfget(pf,'State')

subpf =
    dbpf object: 1-by-1

>>
>> pfget_boolean(subpf,'auto_save')

ans =

    -1

>>
>> pfget_boolean(subpf,'auto_associate')

ans =

     0

>>

```

## ***pfget\_num***

This command retrieves a numeric value from a parameter file.

```

>> pf = dbpf( 'rtexec');
>> pfget_num( pf, 'Time_to_die' )

ans =

    20

>>

```

## ***pfget\_string***

This command retrieves a string value from a parameter file.

```

>> pf = dbpf( 'rtexec');

```

```
>> pfget_string( pf, 'Database' )
```

```
ans =
```

```
rtsys/rtsys
```

```
>>
```

## ***pfget\_tbl***

This command retrieves a table of values from a parameter file.

```
>> pf = dbpf( 'rtexec' );
```

```
>> pfget_tbl( pf, 'Buttons' )
```

```
ans =
```

```
'top    xterm -geom 80x25 -e top'
'clients xterm -geom 132x25 -e orbstat -c localhost 5'
'sources xterm -geom 132x60 -e orbstat -s localhost 5'
'rtld    orbmonrtd localhost'
'dbevents dbevents archive/nw'
'qtmon    qtmon localhost localhost localhost'
```

```
>>
```

## ***pfkeys***

This command extracts the key names for the key-value pairs in a parameter file.

```
>> pf = dbpf( 'rtexec' );
```

```
>> pfkeys(pf)
```

```
ans =
```

```
'ANTELOPE'
'Buttons'
'Crontab'
'Database'
'Env'
'Limit'
'Minimum_period_between_starts'
'Network_database'
'Parameter_files'
'Processes'
```



```
'ROOT'
'Run'
'Shutdown_order'
'Shutdown_tasks'
'Start_period'
'Startup_tasks'
'Time_to_die'
'Use_UTC'
'disks'
'orbname'
'orbtasks'
```

```
>>
```

## ***pfname***

This command returns the parameter-file name from which a parameter-file object was created.

```
>> pf = dbpf( 'rtexec' );
>> pfname(pf)
```

```
ans =
```

```
rtexec
```

```
>>
```

## ***pfput\_boolean***

This function puts a value into a parameter file as a boolean.

```
>> pf = dbpf;
>> pfput_boolean( pf, 'myboolean', 'True' )
```

```
>> pf2string( pf )
```

```
ans =
```

```
myboolean    True
```

```
>>
```

## ***pfput***

The **pfput** command is a very general routine to put strings, numbers, cellarrays (as tables), or structures (as associative arrays) into a parameter-file object.

```
>> pf = dbpf;
>>
>> pfput( pf, 'mydouble', 3.14 )
>> pfput( pf, 'myint', 24 )
>> pfput( pf, 'mystring', 'test string' )
>>
>> z.a = 21;
>> z.b = 'hello';
>> z.c = '45.6';
>> pfput( pf, 'myarray', z )
>>
>> pfput( pf, 'mytable', {'hello' 'yes' 'no' 'goodbye'})
>>
>>
>> pf2string( pf )
```

ans =

```
myarray &Arr{
a    21
b    hello
c    45.6
}
mydouble    3.14
myint  24
mystring    test string
mytable &Tbl{
hello
yes
no
goodbye
}

>>
```

## ***pfresolve***

This is an alternative interface to the parameter-file objects with a naming convention that reflects any nesting in the parameter-file components (tables and hashes). For further detail see the Datascope man pages.

```
>> pf = dbpf( 'rtexec');
```

```
>> pfresolve(pf,'Limit{filesize}')
```

```
ans =
```

```
unlimited
```

```
>>
```

## ***pf*****type**

Only top-level parameter-file objects are of file type. Subsidiary key-value structures (arrays) inside a parameter file will have dbpf objects of type PFARR.

```
>> pf = dbpf( 'rtexec');
```

```
>> pftype(pf)
```

```
ans =
```

```
PFFILE
```

```
>>
```

## ***pf*****update**

This command allows your program to stay current with a parameter file if outside forces are changing it while your program is running.

```
>> % Create a parameter file and put one value in it
```

```
>> unix( 'echo myint 13 > /tmp/myfile.pf' );
```

```
>> % Open the parameter file and extract the parameter:
```

```
>> pf = dbpf( '/tmp/myfile.pf' );
```

```
>> pfget_num( pf, 'myint' )
```

```
ans =
```

```
13
```

```
>> % Now change the parameter file from outside the Matlab context:
```

```
>> unix( 'echo myint 25 > /tmp/myfile.pf' );
```

```
>> % a retrieval of the parameter returns the previously cached value:
```

```
>> pfget_num( pf, 'myint' )
```

```
ans =
```

13

```
>> % Updating the parameter-file object refreshes the cached values:
```

```
>> [pf, modified] = pfupdate( pf )
```

```
pf =
```

```
    dbpf object: 1-by-1
```

```
modified =
```

```
    1
```

```
>> % Now the retrieved parameter reflects the changed file:
```

```
>> pfget_num( pf, 'myint' )
```

```
ans =
```

```
    25
```

```
>>
```

## ***pfwrite***

A dbpf object, possibly modified, may be written out to the specified filename.

```
>> pf = dbpf( 'rtexec' );
```

```
>> pfwrite(pf,'tmp/rtexec_copy.pf')
```

```
>>
```

## ***str2epoch***

This utility is a very powerful and flexible parsing utility to turn a human-readable time string into an epoch time.

```
>> format long
```

```
>> str2epoch('now')
```

```
ans =
```

```
    9.237016155097741e+08
```

```
>> str2epoch('3/17/99 15:24:16.5')
```

```

ans =

    9.216842565000000e+08

>>
>> str2epoch('January 27, 1973 4:00 pm')

ans =

    96998400

>>

```

## ***strdate***

This utility takes a Unix epoch time and returns a stock day format.

```

>> strdate(96998400)

ans =

    1/27/1973

>>

```

## ***strtdelta***

This utility turns the input number of seconds into a reasonably-formatted value for a time interval.

```

>> strtdelta(7200)

ans =

    2:00 hours

>> strtdelta(3*86400+15*3600)

ans =

    3 days 15.0 hours

>> strtdelta(912343243)

ans =

```

28 years 339 days

>>

### ***strtime***

This function takes a Unix epoch time and returns a stock-format time and day string.

```
>> strtime(96998400)
```

ans =

1/27/1973 16:00:00.000

>>

### ***strydtime***

This function is the same as the strtime function but includes as well the day number of the year.

```
>> strydtime(96998400)
```

ans =

1/27/1973 (027) 16:00:00.000

>>

### ***tr\_endtime***

This is a safe macro to reliably construct an endtime from a starting time, sample rate, and number of samples. All other useful permutations of this routine exist as well (below).

```
>> time, endtime, nsamp, samprate
```

time =

7.061397152000000e+08

endtime =

7.061398415000000e+08

```
nsamp =
```

```
2527
```

```
samprate =
```

```
20
```

```
>>
```

```
>> tr_endtime(time,samprate,nsamp)
```

```
ans =
```

```
7.061398415000000e+08
```

```
>>
```

### ***tr\_nsamp***

```
>> tr_nsamp(time,samprate,endtime)
```

```
ans =
```

```
2527
```

```
>>
```

### ***tr\_samp2time***

```
>> tr_samp2time(time,samprate,1000)
```

```
ans =
```

```
7.061397651500001e+08
```

```
>>
```

### ***tr\_samprate***

```
>> tr_samprate(time,nsamp,endtime)
```

```
ans =

20.000000000755087

>>
```

### ***tr\_time2samp***

```
>> tr_time2samp(time,samprate,7.061397651500001e+08)

ans =

1000

>>
```

### ***tr2struct***

**tr2struct** is most useful for creating a standalone structure of waveform data and its vital statistics. This structure can be saved for export to a Matlab user who wants waveform data but does not have the Antelope toolbox. This utility is implemented as a *.m* function rather than a mex file, thus users may modify it easily to change its behavior. The input is a trace object containing the waveform data to package for export.

```
>> db = dbopen( demodb_path,'r' );
>> db=dblookup_table( db,'wfdisc' );
>> dbsite=dblookup_table( db,'site' );
>> db=dbjoin( db, dbsite );

>> % For now just use the time window of the first row to decide what to get:
>> db.record=0;
>> [time,endtime]=dbgetv( db,'time','endtime' );

>> tr = trload_css( db, time, endtime );

>> s = tr2struct( tr );

>> % Save the structure to a file to send elsewhere:
>> save '/tmp/dbexample_data.mat' s
```

### ***trapply\_calib***

This function applies the calibration constant to waveform data contained in the trace object.



```

>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db.record=0;
>> [time,endtime,nsamp,samprate]=dbgetv(db,'time','endtime','nsamp','samprate');
>> tr = trload_css(db,time,endtime);
>> trapply_calib(tr)
>>

```

## ***trdestroy***

This routine frees all resources associated with a trace-object.

```

>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db.record=0;
>> [time,endtime,nsamp,samprate]=dbgetv(db,'time','endtime','nsamp','samprate');
>> tr = trload_css(db,time,endtime);
>> trdestroy( tr )
>>

```

## ***trextract\_data***

A trace-object is just a database pointer, pointing to an open database in the Trace4.0 schema. The “trace” table of this database has a field called “data”, which contains the address of some waveform data in memory. The **trextract\_data** command gets this address and loads the data contained into a Matlab vector.

```

>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db.record=0;
>> [time,endtime,nsamp,samprate]=dbgetv(db,'time','endtime','nsamp','samprate');
>> tr = trload_css(db,time,endtime);
>> tr.record=0;
>> data=trextract_data(tr);
>> whos data
  Name      Size      Bytes Class

  data    2150x1      17200 double array


```

Grand total is 2150 elements using 17200 bytes

```

>> plot(data)

```



## *trfree*

**Trfree** is a way to free resources for part of a trace-object structure. Consider using **trdestroy** unless you know what you're doing.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db.record=0;
>> [time,endtime,nsamp,samprate]=dbgetv(db,'time','endtime','nsamp','samprate');
>> tr = trload_css(db,time,endtime);
>> trfree( tr )
>>
```

## *trgetwf*


This command is one of several methods to extract waveform data from a database.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db.record=0;
>> [data,nsamp,t0,t1]=trgetwf(db);
>> whos data
Name      Size      Bytes Class
```

data 2527x1 20216 double array

Grand total is 2527 elements using 20216 bytes

```
>> plot(data)
```



## *trinsert\_data*

This is the converse of the **trextract\_data** command, described above.

```
>> tr=trnew;
>> tr=dblookup_table(tr,'trace');
>>
>> % Construct a fake waveform:
>> data=sin([0:999]);
>> nsamp=1000;
>> sta='SINE';
>> chan='BHZ';
>> time=str2epoch('now');
>> samprate=20;
>> endtime=tr_endtime(time,samprate,nsamp);
>>
>> % Put the waveform into the trace-object:
>> tr.record=dbaddnull(tr);
>> dbputv(tr,'time',time,'samprate',samprate,'endtime',endtime,'sta',sta,'chan',chan);
>> trinsert_data(tr,data)
>>
```

## ***trload\_css***

This command loads the specified time range of data from a database pointer into a trace object (which, of course, is also a database pointer but in a special schema designed for the the handling of waveform data in memory).

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db.record=0;
>> format long
>> [time,endtime,nsamp,samprate]=dbgetv(db,'time','endtime','nsamp','samprate')
```

time =

```
7.061397152000000e+08
```

endtime =

```
7.061398415000000e+08
```

nsamp =

```
2527
```

samprate =

```
20
```

```
>> tr = trload_css(db,time,endtime)
```

tr =

```
database: 1
table: 5
field: -501
record: -501
```

```
>>
```

## ***trload\_cssgrp***

This command is similar to **trload\_css** described above.

```
>> db = dbopen( demodb_path,'r' );
>> db=dblookup_table( db,'wfdisc' );
>> db= dbsort( db, 'sta', 'chan', 'time' );
>> [time,endtime,nsamp,samprate]=dbgetv( db,'time','endtime','nsamp','samprate' );
>> tr = trload_cssgrp( db,time(1),endtime(1) )
```

tr =

```
database: 8
table: 5
field: -501
record: -501
```

```
>> tr.record=0;
>> data=trextract_data( tr );
>> plot(data)
```

## ***trnew***

The **trnew** command creates a new, empty trace-object database.

```
>> tr=trnew
```

tr =

```
database: 0
table: -501
field: -501
record: -501
```

```
>> dbquery(tr,'dbDATABASE_NAME')
```

ans =

```
/tmp/trdb0ewpxx
```

```
>> dbquery(tr,'dbSCHEMA_NAME')
```

ans =


Trace4.0

```
>>
```

## *trputwf*

This is a deprecated interface for putting waveform data into a database. Please switch to **trsave\_wf**.

```
>> db=dbopen('/tmp/newdb','r+');
>> db = dblookup_table( db, 'wfdisc' );
>>
>> % Construct a fake waveform:
>> data = (0:999);
>> data = data * 32 * pi / 1000;
>> data = sin( data );
>>
>> % Construct some variables describing the waveform:
>> nsamp = 1000;
>> samprate = 20;
>> foff = 0;
>> datatype='t4';
>> dir='/tmp';
>> dfile='demo_sinewave';
>> sta='SINE';
>> chan='BHZ';
>> time = str2epoch('5/12/97 13:57:18.143');
>> endtime = tr_endtime( time, samprate, nsamp );
>>
>> % Enter the description of the waveform data into the wfdisc table:
>> db.record = dbaddv(db,'sta',sta,'chan',chan, 'nsamp', nsamp, ...
'samprate', samprate, 'time', time, 'endtime',endtime, ...
'foff',foff, 'datatype',datatype, 'dir',dir,'dfile', dfile);
>>
>> % Now put the actual data samples into the file, in the specified format:
>> trputwf( db, data );
>> % As a test, get the data back out:
>> [newdata, nsamp, t0, t1] = trgetwf( db, time-1, endtime+1 );
>>
>> plot( newdata );
>>
```



## *trsave\_wf*

This command is the generic interface to put waveform database from a trace object into a database. For details see the Datascope man page on **trsave\_wf**.

```
>> tr=trnew;
>> tr=dblookup_table(tr,'trace');
>>
>> % Construct a fake waveform:
>> amp = 10000;
>> data = amp * sin([0:999]);
>> nsamp=1000;
>> sta='SINE';
>> chan='BHZ';
>> time=str2epoch('now');
>> samprate=20;
>> endtime=tr_endtime(time,samprate,nsamp);
>>
>> % Put the waveform into the trace-object:
>> tr.record=dbaddv( tr, 'net', 'AK', 'sta', 'SINE', 'chan', 'BHZ', 'nsamp', ...
>> 'samprate', samprate, 'time', time, 'endtime', endtime );
>> trinsert_data(tr,data)
>>
>> % Save the trace data in a new database, with the underlying file in miniseed format:
>> db=dbopen('/tmp/newdb','r+');
>> db=dblookup_table(db,'wfdisc');
```

```
>> trsave_wf(tr,db,'sd','')
>>
```

## *trsplice*

This routine attempts to splice together as many data segments as possible that are contained in the input trace object.

```
>> db = dbopen(demodb_path,'r');
>> db=dblookup_table(db,'wfdisc');
>> db=dbsubset(db,'sta == "CHM" && chan == "BHZ"');
>> db.record=0;
>> [time,endtime,samprate,nsamp]=dbgetv(db,'time','endtime','samprate','nsamp')
```

```
time =
```

```
7.0614e+08
```

```
endtime =
```

```
7.0614e+08
```

```
samprate =
```

```
20
```

```
nsamp =
```

```
2527
```

```
>>
```

```
>> tr=trload_css(db,time,time+10);
>> tr=trload_css(db,time+10,time+20,tr);
>> dbquery(tr,'dbRECORD_COUNT')
```

```
ans =
```

```
2
```

```
>>
```

```
>> strtime(dbgetv(tr,'time'))
```



```

ans =

    ' 5/17/1992 21:55:15.200'
    ' 5/17/1992 21:55:25.200'

>> strtime(dbgetv(tr,'endtime'))

ans =

    ' 5/17/1992 21:55:25.150'
    ' 5/17/1992 21:55:35.150'

>>
>> trsplice(tr,0.5)
>> dbquery(tr,'dbRECORD_COUNT')

ans =

    1

>> strtime(dbgetv(tr,'time'))

ans =

    5/17/1992 21:55:15.200

>> strtime(dbgetv(tr,'endtime'))

ans =

    5/17/1992 21:55:35.150

>>

```

## ***trwfname***

The **trwfname** command helps generate file and pathnames for external files. When given a database row filled with information on an external file, and with *dir* and *dfile* fields that need to be filled in, **trwfname** will construct appropriate *dir* and *dfile* values, add them to the database row, create the external directories for the path if necessary, and return the resulting path. If no pattern is specified, **trwfname** uses a default pattern of information taken from the *sta*, *chan*, and *time* fields of the input row. Optionally, one can specify a different pattern for the filename and path, using the ‘%’ escape codes from **epoch2str** and ‘%{field}’ tokens to refer to fields in the database row. For more detail, see the Unix man page on *trwfname*(3).

```

>> output_dbname = ['/tmp/newdb_' getenv('USER')];
>> unix( ['/bin/rm -f ' output_dbname '*'] );
>> db = dbopen( output_dbname,'r+' );
>> db = dblookup_table( db, 'wfdisc' );

>> nsamp = 1000;
>> amp = 10000;
>> samprate = 20;
>> time = str2epoch( '9/30/02 11:15 AM' );
>> endtime = tr_endtime( time, samprate, nsamp );

>> db.record = dbaddv( db, ...
    'sta', 'FAKE', 'chan', 'BHZ', 'nsamp', nsamp, ...
    'samprate', samprate, 'time', time, 'endtime', endtime );

>> path = trwfname( db )

path =

/tmp/2002/273/FAKE.BHZ.2002:273:11:15:00

>> % Alternatively:
>> path = trwfname( db, 'Mydir/station_%{sta}/%A_%B_%o_%Y.data' )

path =

/tmp/Mydir/station_FAKE/Monday_September_30th_2002.data

>>

```

## ***yearday***

This command takes a Unix epoch time and returns  $\text{year} \times 1000 + \text{day-of-year}$ .

```

>> yearday(96998400)

ans =

    1973027

>>

```

## ***zepoch2str***

The `zepoch2str` command is similar to `epoch2str`, however one may specify the time-zone in which one wants the result expressed. An empty string for the time-zone will default to the setting of the TZ environment variable on the host, which should be the local time-zone on a properly configured system.

```
>> myepoch = str2epoch( '10/13/02 12:00 am' )

myepoch =

    1.0345e+09

>> zepoch2str( myepoch, '%m/%d/%Y %H:%M:%S %Z', 'US/Alaska')

ans =

10/12/2002 16:00:00 AKDT

>> zepoch2str( myepoch, '%m/%d/%Y %H:%M:%S %Z', 'US/Pacific')

ans =

10/12/2002 17:00:00 PDT

>> zepoch2str( myepoch, '%m/%d/%Y %H:%M:%S %Z', 'GMT-2')

ans =

10/13/2002 02:00:00 GMT

>> zepoch2str( myepoch, '%m/%d/%Y %H:%M:%S %Z', '')

ans =

10/12/2002 16:00:00 AKDT

>>
```

## **Differences between the Matlab Antelope Toolbox and other Antelope language interfaces**

The Matlab Antelope toolbox differs in several aspects from the Antelope language interfaces in C, Tcl, Fortran, and Perl. First, the natural mode of operation in Matlab is to work on entire arrays at once. Therefore, where possible, Antelope database commands have been expanded to read in entire matrices of results when appropriate (e.g. **dbgetv**), or to act on entire matrices at once (e.g. **epoch2str**). Similarly, where naming conventions permit, parameter-files may be loaded whole-sale into Matlab structures with **pf2struct**, and database tables may be loaded into structures with **db2struct**.

Special options to Antelope commands are usually specified with string input arguments, such as 'backwards' for **dbfind**. In many cases the order of placement of these options is important--see the help pages on each command for details.

The most general interface to Antelope, the C language interface, allows temporary views to be given user-specified names. This feature is not supported in the current release of the Matlab toolbox.

## Caveats

This toolbox was developed on Sun-solaris 2.6, Matlab version 5.3. It has not been tested with other platforms and versions. The current version is tested against Sun Solaris 2.8, Linux with the 2.4 kernel, and Matlab 6.5.

Several aspects of this current beta release must be treated with caution. First, the database-pointer DBPTR and trace-pointer TRPTR objects refer to databases and memory open by the underlying Antelope libraries. Freeing these objects with the Matlab clear command does not appropriately close the underlying databases, nor free the corresponding memory. These objects must be removed from the Matlab workspace with the DBCLOSE and TRDESTROY commands provided. Note that the DBPTR and TRPTR structures are not objects in the Matlab sense--the word is being used loosely here, paralleling the Datascope documentation (for the trace objects). Conceptually they are very similar to objects, though the user can see and manipulate the private variables directly (useful, for example, to loop over the DBPTR.record field), and also there is no Matlab class tag. These items have been kept as Matlab structures rather than Objects to preserve similarity between the Matlab Antelope toolbox and other programming interfaces for Antelope.

The parameter-file objects actually are Matlab objects. Again, though, they must be cleared carefully. The clear function is overloaded for the DBPF class of Objects, however at least in Matlab 5.2 the command/function duality is broken by the CLEAR command, and apparently the generic CLEAR command is not smart enough to call the overloaded methods for DBPF objects. One must specifically call the CLEAR function (i.e. use parentheses around the argument), or the equivalent PFFREE function, on the DBPF object. Also, the pf routines may at times return derivative DBPF objects, representing complex entries in the parent parameter-file (DBPF object). These first of all are not allowed to be cleared by the PFFREE command. Second, they lose mean-

ing but unfortunately stay resident when the parent DBPF object (the one returned when the whole parameter file was read in) is cleared. Acting on them after destroying the originating DBPF may produce unpredictable results.

There are a lot more trace-library commands available, many of which have not yet been implemented.

The response-file objects are also actually Matlab objects. Just as with the DBPF objects, these need to be explicitly cleared with the overloaded clear functions, `CLEAR(DBRESPONSE)` or equivalently `FREE_RESPONSE`.

While the `doc` command works for Antelope Toolbox commands, the Matlab helpdesk search engine does not yet recognize them. In order to search for Antelope Toolbox commands, use the matlab **lookfor** command or the search window in the Matlab **helpwin** help window.

Unlike the other Antelope language interfaces, the Matlab **dbeval** is able to return entire columns of values if the input database pointer refers to more than one row. As a standard feature, `dbeval` can return values that are aggregate expressions over the whole table such as `max()`. If more than one row is passed to such an aggregate expression in Matlab, the aggregate expression will be recalculated for each row, which redundancy can cause huge performance drops for a large database. Therefore, unless otherwise necessary, the user should avoid passing multiple rows to **dbeval** when using aggregate expressions. See the Unix `dbex_eval(3)` man pages for the list of aggregate functions in the Antelope expressions calculator.

The Matlab interface to the orb routines is fairly new, and though tested, the Matlab toolbox routines have not been extensively used in implementation. There is the possibility of some change if initial experience shows any inconveniences.

## Author

The Antelope Software system, including the Datascope relational-database management system, is a product of Boulder Real-Time Technologies, Inc., <http://brtt.com/>

The Antelope Toolbox for Matlab was written by Kent Lindquist, without funding and in his spare time. Version 1.0 was written while at the University of Alaska's Geophysical Institute. Version 1.1 is a product of Lindquist Consulting, which is providing continued maintenance and expansion of the interface as time permits.

## Acknowledgment

This project would of course have gone nowhere without the underlying Antelope and Datascope software package provided by Boulder Real Time Technologies, Inc. The author would like to thank Danny Harvey for initial impetus, and Dan Quinlan for extensive and valuable technical consultation and support in this work. Frank Vernon has provided strong and continuous encouragement from the beginning of the project. His research group has also provided significant help in beta-testing and debugging a production release. Beta testing was kindly provided by the research group of Gary Pavlis (including Scott Neal and Christian Poppeliers) at the University of Indiana, and by Geoff Abers at the University of Kansas. Local tolerance of experimental versions has been patiently extended to the author by University of Alaska Matlab users, notably Guy Tytgat. The author is indebted to Jason Crosswhite of the University of Oregon and Ken Dueker of the University of Wyoming for identifying the compile issues necessary to port this Matlab toolbox to Linux, as well as for numerous helpful comments. Jason also contributed code for the interface to the **dbsever** command.

## References

Boulder Real Time Technologies, Inc. <http://brtt.com/>

Kinematics, Inc. <http://www.kinematics.com/>

Mathworks, Inc. <http://www.mathworks.com/>