A16	ABS control module
B161	AC refrigerant pressure sensor
B138	Accelerator pedal position (APP) sensor
G1	Alternator
31	Battery -
30	Battery +
S13-I	Brake pedal position (BPP) switch 1
S258	Clutch pedal position (CPP) switch
CAN-H	Controller area network (data bus) high
CAN-L	Controller area network (data bus) low
B54	Crankshaft position (CKP) sensor
X1	Data link connector (DLC)
A207	Electronic stability program (ESP) control module
A35	Engine control module (ECM)
M6	Engine coolant blower motor
A95	Engine coolant blower motor control module
K12	Engine coolant blower motor relay
B24	Engine coolant temperature (ECT) sensor
S186	Engine coolant temperature (ECT) switch
H63	Engine malfunction indicator lamp (MIL)
Y104	Evaporative emission (EVAP) canister purge valve
M12	Fuel pump (FP)
F	Fuse
X28-II	Fuse box/relay plate - engine bay 1
X28-I	Fuse box/relay plate - fascia
B72-I	Heated oxygen sensor (HO2S) 1
B72-II	Heated oxygen sensor (HO2S) 2
T1	Ignition coil
15	Ignition switch - ignition ON
Y3	Injector
A5	Instrument panel
A75	Instrumentation control module
B69	Knock sensor (KS)
B83	Manifold absolute pressure (MAP) sensor
A11-I	Multifunction control module 1
A11-II	Multifunction control module 2
P7	Tachometer
M89	Throttle motor
B169	Throttle motor position sensor
VAN	Vehicle area network (data bus)
P9	Vehicle speedometer

bl = blue	br = brown	el = cream	ge = yellow
gn = green	gr = grey	nf = neutral	og = orange
rs = pink	rt = red	sw = black	vi = violet
ws = white	hbl = light blue	hgn = light green	rbr = maroon
x = braided cable	y = high tension	z = non-cable connection	

NOTE: In certain diagrams (Citroen, Peugeot & Renault), colour codes are replaced by numbers which are used to identify a particular cable and not the colour. In this instance, the cables will be numbered at each end close to the harness connector.

30

15

X28-II

A=16 sw
B=16 gr
C=16 gn
D=10 sw
E=8 sw

F8 20A

A11-II

F4 10A

F15 30A

F2 15A

| 1351A/B | 1355 | 1320 | 1150 | 1235 | 1203 | 1229 | 1226 | CM15A | C01 |

1211 el | 1212 el | 1213 el | 1214 el | 1355 ws | 1150 rt | CM15E | CE01B

Y3-I Y3-II Y3-III Y3-IV Y104 T1 S13-I S258 X1 MG A95 K12 MG AC A/C A/C

| 1321 gn | 1322 rt | 1323 rt | 1324 gn | 1203 br | 1229 ge | 1232 vi | 1151 vi | 1152 br | 1135 ge | 1226 bl | CM15G rt | 6702C ws | 1384 rt | 9006D vi | 1540B | 1599B | 1540A vi | 1599A gn | 151 | 151A |

A=32 gr B=48 br C=32 sw

A35

| 131 rt | 130 gn | 122 bl | 1303 rt | 1302 gn | 124 br | 1377C ws | 1379C gn | 1378C bl | 1380C vi | 1361 rt | 1362 gn | 1393 br | 1363 vi | 1341 ws | 1364 bl | 1335 br | 1334 rt | 1367 bl | 1219 rs | 1220 gn | 1218 bl | 135 rt | 134 gn | 104 ws |

1235 vi

M12 B72-I B72-II 1377 1379 1378 1380 B138 B54 B83 M89 B169 B69 G1

1351B 1351A 1364

ME32 M211

31

EP2

305998

Wiring diagram labels:

- 30
- 15
- 9005/D
- 9004/D
- VAN VAN — 10 G, 8 G — X28-I
- A11-I
- C= 40 sw, G= 10 sw
- VAN VAN — 1, 3 — A5
- A75
- H63
- P7 P9
- C 2, C 4
- rt 9000 CAN-H, vi 9001 CAN-L
- 9000L, 9001L
- 11 15 — A16 — A207 — 12 14
- 9000A CAN-H, 9001A CAN-L
- rt, vi
- B h3, B h4
- A35
- A=32 gr B=48 br C=32 sw
- d4 e4, h4 h1, L4 M4, d4 e4 a3
- C C, C A, B B, B B B
- ws 1357, bl 1366, gn ge M132A, gn ge M132C, gn ge M132C, gn ge M132D, ws 8092A, ge 8093A, bl 8094A
- 1366A, 1366B
- 2 1 — B24
- 2 — S186
- 1 2 3 — B161 AC
- ME01, MC11A
- 31
- EP4, EP1, 305999