
X88	AC connector		
31	Battery -		
30	Battery +		
X1	Data link connector (DLC)		
A35	Engine control module (ECM)		
B24	Engine coolant temperature (ECT) sensor		
H63	Engine malfunction indicator lamp (MIL)		
B75	Engine speed (RPM) sensor		
Y104	Evaporative emission (EVAP) canister purge valve		
M12	Fuel pump		
F	Fuse		
B72	Heated oxygen sensor (HO2S)		
Y99	Idle air control (IAC) valve		
T1	Ignition coil		
15	Ignition switch - ignition ON		
Y3	Injector		
B25	Intake air temperature (IAT) sensor		
R9	Intake manifold heater		
B69	Knock sensor (KS) - RFX		
B83	Manifold absolute pressure (MAP) sensor		
K46	Relay module		
K4	Starter motor relay (AT)		
C3	Suppressor		
P7	Tachometer		
B147	Throttle position (TP) sensor		
B33	Vehicle speed sensor (VSS)		



bl = blue	br = brown	el = cream	ge = yellow
gn = green	gr = grey	nf = neutral	og = orange
rs = pink	rt = red	sw = black	vi = violet
ws = white	hbl = light blue	hgn = light green	rbr = maroon
x = braided cable	y = high tension	z = non-cable connection	

NOTE: In certain diagrams (Citroen, Peugeot & Renault), colour codes are replaced by numbers which are used to identify a particular cable and not the colour. In this instance, the cables will be numbered at each end close to the harness connector.

Manufacturer: Peugeot
Engine code: XU10J2C (RFX)
Tuned for: R-Cat

Model: 405 2,0

Output: 89 (122) 5750 Year: 1992-97 © Autodata Limited 2010

Valid forever. 10.10.2020

V8.500- /Autodata

