



| A16 | ABS control module |
|--------|--|
| S292 | |
| | AC/heater function control panel |
| B138 | Accelerator pedal position (APP) sensor |
| B121 | Barometric pressure (BARO) sensor |
| 31 | Battery - |
| 30 | Battery + |
| S13 | Brake pedal position (BPP) switch |
| B132 | Camshaft position (CMP) sensor |
| S258 | Clutch pedal position (CPP) switch |
| CAN-H | Controller area network (data bus) high |
| CAN-L | Controller area network (data bus) low |
| B54 | Crankshaft position (CKP) sensor |
| S79 | Cruise control master switch |
| X1 | Data link connector (DLC) |
| A161 | Digital multifunction display |
| K46 | Engine control (EC) relay |
| A35 | Engine control module (ECM) |
| A95 | Engine coolant blower motor control module |
| M50 | Engine coolant pump motor |
| K105 | Engine coolant pump relay |
| B24 | Engine coolant temperature (ECT) sensor |
| H63 | Engine malfunction indicator lamp (MIL) |
| Y104 | Evaporative emission (EVAP) canister purge valve |
| M12 | Fuel pump (FP) |
| K20 | Fuel pump (FP) relay |
| F | Fuse |
| X28-II | Fuse box/relay plate, engine bay 1 |
| X28-I | Fuse box/relay plate, fascia |
| B72-II | Heated oxygen sensor (HO2S) - after cat |
| B72-I | Heated oxygen sensor (HO2S) - before cat |
| T1 | Ignition coil |
| 15 | Ignition switch - ignition ON |
| A162 | Immobilizer control module |
| Y3 | Injector |
| A5 | Instrument panel |
| A75 | Instrumentation control module |
| B25 | Intake air temperature (IAT) sensor |
| B69 | Knock sensor (KS) |
| B83 | Manifold absolute pressure (MAP) sensor |
| B30 | Mass air flow (MAF) sensor |
| M142 | Power steering pump |
| H50 | Service indicator |
| H101 | Throttle control system warning lamp |
| A177 | Throttle control unit |
| M89 | Throttle motor |
| B169 | Throttle motor position sensor |
| Y153 | Turbocharger (TC) intake divert valve |
| Y68 | Turbocharger (TC) wastegate regulating valve |
| A123 | Vehicle speed sensor (VSS) signal amplifier |
| B19 | Wheel speed sensor, left front |
| = .* | |