Detector induced assymetry in CP violation measurements

Eugenia Spedicato, Lina Maria Ortiz Parra, Jonah Blank

February 12, 2020

Comments - efficiencies

- very small errors in $D = \frac{\epsilon_+ \epsilon_-}{\epsilon_+ + \epsilon_-}$ $\rightarrow D = 0$ out of 5σ -range
- smaller error for *UP*-polarity due to higher statistics
- no difference between UP and DOWN within scope of the error
- in the MC: $\epsilon_{D^*}=0$ (Dst_reconstructed always 0) in our computation: $\epsilon_{D^*}=\epsilon_{\pi,s}\cdot\epsilon_{D^0}$

Comments - plots


- lacksquare structure of $\epsilon(\phi)$ probably due to rectangular detector shape
- peak in $\epsilon_{D^*}(\theta)$ within scope of error

Total


Efficiencies

Polarity	ϵ_{π}	$\epsilon_{\mathcal{K}}$	$\epsilon_{\pi,s}$	ϵ_{D^0}	ϵ_{D^*}
UP	86.61 ± 0.04	84.65 ± 0.04	76.61 ± 0.05	$\textbf{73.33} \pm \textbf{0.05}$	56.26 ± 0.06
DOWN	86.61 ± 0.04	84.67 ± 0.05	$\textbf{76.54} \pm \textbf{0.06}$	$\textbf{73.33} \pm \textbf{0.06}$	56.23 ± 0.07


π -efficiency




K-efficiency




soft π -efficiency



D^0 -efficiency



D*-efficiency




Charge: +

Efficiencies


Polarity	ϵ_{π}	ϵ_{K}	$\epsilon_{\pi,s}$	ϵ_{D^0}	ϵ_{D^*}
UP DOWN	$86.62 \pm 0.06 \\ 86.65 \pm 0.06$	$85.05 \pm 0.06 \\ 85.10 \pm 0.07$	$76.25 \pm 0.07 \\ 76.78 \pm 0.08$	$72.99 \pm 0.07 \\ 72.98 \pm 0.08$	$55.71 \pm 0.08 \\ 56.14 \pm 0.09$
UP	π	К	soft π	D^0	<i>D</i> *
$N_{\rm reco} \ N_{ m tot}$	323 475 373 456	317 441 373 249	284 753 373 456	272 602 373 456	208 042 373 456
DOW	N π	K	soft π	D^0	<i>D</i> *
$N_{ m reco}$				210 563 288 516	161 974 288 516




π -efficiency




K-efficiency




soft π -efficiency



D^0 -efficiency



D*-efficiency




Charge: -


Efficiencies

Polarity	ϵ_{π}	ϵ_{K}	$\epsilon_{\pi,s}$	ϵ_{D^0}	ϵ_{D^*}
UP DOWN	$86.60 \pm 0.06 \\ 86.64 \pm 0.06$	$84.30 \pm 0.06 \\ 83.95 \pm 0.07$	$76.97 \pm 0.07 \\ 76.36 \pm 0.07$	$73.65 \pm 0.07 \\ 73.74 \pm 0.08$	$56.81 \pm 0.08 \\ 56.38 \pm 0.09$
UP	π	К	soft π	D^0	<i>D</i> *
$N_{ m reco} \ N_{ m tot}$	323 251 373 249	314 671 373 456	287 331 373 249	274 932 373 249	212 081 373 249
DOW	N π	K	soft π	D^0	<i>D</i> *
$N_{ m reco}$	250 83 288 74			213 485 288 742	163 206 288 742


π -efficiency




K-efficiency




soft π -efficiency



D^0 -efficiency



D*-efficiency




Deviation


Table: The deviation
$$\frac{\epsilon_+ - \epsilon_-}{\epsilon_+ + \epsilon_-}/10^{-3}$$

Polarity	π	K	$soft\pi$	D^0	D^*
UP	0.2 ± 0.8	4.0 ± 0.8	-5.0 ± 1.0	-4.0 ± 1.0	-9.8 ± 1.1
DOWN -	-0.4 ± 0.9	8.0 ± 0.9	2.3 ± 1.1	-6.0 ± 1.2	-2.5 ± 1.3


Comparison of different charges with UP polarity - D^*




Comparison of different charges with DOWN polarity - D^*





Comparison - $\overline{D^*p_T}$







Comparison - $D^*\phi$







Comparison - $D^*\theta$






Comparison - $D^*\eta$






D* deviation dependencies - UP polarity



$\overline{D^*}$ deviation dependencies- DOWN polarity



D^* deviation - ϕ

