

Linear Types with Dynamic Multiplicities in Dependent Type Theory

**WG6 meeting, Genoa
17 April 2025**

Maximilian Doré, maximilian.dore@cs.ox.ac.uk

Specifying variable use with linear types

Linear logic: Don't drop or duplicate variables. $A \otimes B \not\multimap A$ $A \not\multimap A \otimes A$

Specifying variable use with linear types

Linear logic: Don't drop or duplicate variables. $A \otimes B \not\multimap A$ $A \not\multimap A \otimes A$

Useful for programming: all programs of type $\text{List } A \multimap \text{List } A$ are permutations.


Specifying variable use with linear types

Linear logic: Don't drop or duplicate variables. $A \otimes B \not\multimap A$ $A \not\multimap A \otimes A$

Useful for programming: all programs of type $\text{List } A \multimap \text{List } A$ are permutations.

Natural extension: quantitative types.
(Quantitative TT, Graded TT, Linear Haskell, ...)

$\text{copy} : (x : A) \multimap^2 A \times A$

 called *multiplicity* of x

Specifying variable use with linear types

Linear logic: Don't drop or duplicate variables. $A \otimes B \not\multimap A$ $A \not\multimap A \otimes A$

Useful for programming: all programs of type $\text{List } A \multimap \text{List } A$ are permutations.

Natural extension: quantitative types.

(Quantitative TT, Graded TT, Linear Haskell, ...)

$\text{copy} : (x : A) \multimap^2 A \times A$

called *multiplicity* of x

What's the type of $\text{safeHead} : (xs : \text{List } A) \multimap^1 (y : A) \multimap A \times \text{List } A$

$\text{safeHead } [] \quad y = (y, [])$

$\text{safeHead } (x :: xs) \quad _ = (x, xs)$

Specifying variable use with linear types

Linear logic: Don't drop or duplicate variables. $A \otimes B \not\multimap A$ $A \not\multimap A \otimes A$

Useful for programming: all programs of type $\text{List } A \multimap \text{List } A$ are permutations.

Natural extension: quantitative types.

(Quantitative TT, Graded TT, Linear Haskell, ...)

$\text{copy} : (x : A) \multimap^2 A \times A$

called *multiplicity* of x

What's the type of $\text{safeHead} : (xs : \text{List } A) \multimap^1 (y : A) \multimap^? A \times \text{List } A$

$\text{safeHead } [] \quad y = (y, [])$

$\text{safeHead } (x :: xs) \quad _ = (x, xs)$

multiplicity depends on whether xs is empty

Specifying variable use with linear types

Linear logic: Don't drop or duplicate variables. $A \otimes B \not\multimap A$ $A \not\multimap A \otimes A$

Useful for programming: all programs of type $\text{List } A \multimap \text{List } A$ are permutations.

Natural extension: quantitative types.

(Quantitative TT, Graded TT, Linear Haskell, ...)

$\text{copy} : (x : A) \multimap^2 A \times A$

called *multiplicity* of x

What's the type of $\text{safeHead} : (xs : \text{List } A) \multimap^1 (y : A) \multimap^? A \times \text{List } A$

$\text{safeHead } [] \quad y = (y, [])$

$\text{safeHead } (x :: xs) \quad _ = (x, xs)$

multiplicity depends on whether xs is empty

Proposal: impose linear rules *inside* dependent type theory.

This allows us to have *dynamic/dependent* multiplicities.

$\Gamma \vdash \underbrace{\Delta \vdash A}$

defined as certain dependent type

(Linear) judgment day

Cubical Agda supports finite multisets, which behave just like lists except that the order of elements does not matter.

```
data FMSet (A : Type) : Type where
  ◇       : FMSet A
  _::_     : A → FMSet A → FMSet A
  comm    : ∀ x y xs → x :: y :: xs ≡ y :: x :: xs
  trunc   : isSet (FMSet A)
```


(Linear) judgment day

Cubical Agda supports finite multisets, which behave just like lists except that the order of elements does not matter.

We can append finite multisets:

```
data FMSet (A : Type) : Type where
  ◇      : FMSet A
  _∷_    : A → FMSet A → FMSet A
  comm   : ∀ x y xs → x ∷ y ∷ xs ≡ y ∷ x ∷ xs
  trunc  : isSet (FMSet A)
```

```
_⊗_ : FMSet A → FMSet A → FMSet A
```

(Linear) judgment day

Cubical Agda supports finite multisets, which behave just like lists except that the order of elements does not matter.

We can append finite multisets:

We call a bag of terms a *supply*:

```
data FMSet (A : Type) : Type where
  ◇      : FMSet A
  _::_    : A → FMSet A → FMSet A
  comm    : ∀ x y xs → x :: y :: xs ≡ y :: x :: xs
  trunc   : isSet (FMSet A)
```

```
_⊗_ : FMSet A → FMSet A → FMSet A
```

```
Supply : Type
Supply = FMSet (Σ[ A ∈ Type ] A)
```

(Linear) judgment day

Cubical Agda supports finite multisets, which behave just like lists except that the order of elements does not matter.

We can append finite multisets:

We call a bag of terms a *supply*:

We can define a unit supply:

```
data FMSet (A : Type) : Type where
  ◇      : FMSet A
  _∷_    : A → FMSet A → FMSet A
  comm   : ∀ x y xs → x ∷ y ∷ xs ≡ y ∷ x ∷ xs
  trunc  : isSet (FMSet A)
```

```
_⊗_ : FMSet A → FMSet A → FMSet A
```

```
Supply : Type
Supply = FMSet (Σ[ A ∈ Type ] A)
```

```
η : A → Supply
η a = (A , a) ∷ ◇
```

(Linear) judgment day

Cubical Agda supports finite multisets, which behave just like lists except that the order of elements does not matter.

We can append finite multisets:

We call a bag of terms a *supply*:

We can define a unit supply:

And introduce a *linear judgment*:

```
data FMSet (A : Type) : Type where
  ◇      : FMSet A
  _::_    : A → FMSet A → FMSet A
  comm    : ∀ x y xs → x :: y :: xs ≡ y :: x :: xs
  trunc   : isSet (FMSet A)
```

```
_⊗_ : FMSet A → FMSet A → FMSet A
```

```
Supply : Type
Supply = FMSet (Σ[ A ∈ Type ] A)
```

```
η : A → Supply
η a = (A , a) :: ◇
```

```
_⊨_ : Supply → Type → Type
Δ ⊨ A = Σ[ a ∈ A ] (Δ “≡” η a)
```

(Linear) judgment day

Cubical Agda supports finite multisets, which behave just like lists except that the order of elements does not matter.

```
data FMSet (A : Type) : Type where
  ◇      : FMSet A
  _::_    : A → FMSet A → FMSet A
  comm    : ∀ x y xs → x :: y :: xs ≡ y :: x :: xs
  trunc   : isSet (FMSet A)
```

We can append finite multisets:

```
_⊗_ : FMSet A → FMSet A → FMSet A
```

We call a bag of terms a *supply*:

```
Supply : Type
Supply = FMSet (Σ[ A ∈ Type ] A)
```

We can define a unit supply:

```
η : A → Supply
η a = (A , a) :: ◇
```

And introduce a *linear judgment*:

```
_⊢_ : Supply → Type → Type
Δ ⊢ A = Σ[ a ∈ A ] (Δ "≡" η a)
```

we already have many useful equalities, e.g., $\text{swap} : \Delta_0 \otimes \Delta_1 \equiv \Delta_1 \otimes \Delta_0$

Same, but different. But still same

```
switch : (z : A × B) → η z ⊢ B × A  
switch (x , y) = (y , x) , {Goal: η (x , y) “≡” η (y , x) }
```

Same, but different. But still same

```
switch : (z : A × B) → η z ⊢ B × A
switch (x , y) = (y , x) , {Goal: η (x , y) “≡” η (y , x) }
```

Adding and removing pair constructor doesn't change the free variables of a supply.
→ introduce notion of sameness for supplies, which we call *productions*.

```
data _⊗_ : Supply → Supply → Type where
  id : Δ ⊗ Δ
  _°_ : Δ1 ⊗ Δ2 → Δ0 ⊗ Δ1 → Δ0 ⊗ Δ2
  _⊗f_ : Δ0 ⊗ Δ1 → Δ2 ⊗ Δ3 → (Δ0 ⊗ Δ2) ⊗ (Δ1 ⊗ Δ3)

  cn, : η (a , b) ⊗ (η a ⊗ η b) : wk,           (for a : A, b : B a)
```

```
_⊢_ : Supply → Type → Type
Δ ⊢ A = Σ[ a ∈ A ] (Δ ⊗ η a)
```

Same, but different. But still same

```
switch : (z : A × B) → η z ⊢ B × A
switch (x , y) = (y , x) , wk , ◦ swap (η x) (η y) ◦ cn,
```

Adding and removing pair constructor doesn't change the free variables of a supply.
→ introduce notion of sameness for supplies, which we call *productions*.

```
data _⊗_ : Supply → Supply → Type where
  id : Δ ⊗ Δ
  _◦_ : Δ1 ⊗ Δ2 → Δ0 ⊗ Δ1 → Δ0 ⊗ Δ2
  _⊗f_ : Δ0 ⊗ Δ1 → Δ2 ⊗ Δ3 → (Δ0 ⊗ Δ2) ⊗ (Δ1 ⊗ Δ3)

  cn, : η (a , b) ⊗ (η a ⊗ η b) : wk,           (for a : A, b : B a)
```

```
_⊢_ : Supply → Type → Type
Δ ⊢ A = Σ[ a ∈ A ] (Δ ⊗ η a)
```


A natural resource algebra

We get multiplicities for free using the standard natural numbers type:

$$\begin{aligned} \frac{}{\Delta} \wedge & : \text{Supply} \rightarrow \mathbb{N} \rightarrow \text{Supply} \\ \Delta \wedge \text{zero} & = \diamond \\ \Delta \wedge (\text{suc } n) & = \Delta \otimes (\Delta \wedge n) \end{aligned}$$

A natural resource algebra

We get multiplicities for free using the standard natural numbers type:

$$\begin{aligned} \frac{}{\Delta \wedge \text{zero} = \diamond} & : \text{Supply} \rightarrow \mathbb{N} \rightarrow \text{Supply} \\ \Delta \wedge (\text{suc } n) &= \Delta \otimes (\Delta \wedge n) \end{aligned}$$

It's straightforward to work with these multiplicities:

$$\begin{aligned} \text{copy} & : (x : A) \rightarrow \eta \ x \wedge 2 \Vdash A \times A \\ \text{copy } x &= (x , x) , \text{wk}, \end{aligned}$$

A natural resource algebra

We get multiplicities for free using the standard natural numbers type:

$$\begin{aligned} \frac{}{\Delta \wedge \text{zero} = \diamond} & : \text{Supply} \rightarrow \mathbb{N} \rightarrow \text{Supply} \\ \Delta \wedge (\text{suc } n) &= \Delta \otimes (\Delta \wedge n) \end{aligned}$$

It's straightforward to work with these multiplicities:

$$\begin{aligned} \text{copy} & : (x : A) \rightarrow \eta \, x \wedge 2 \Vdash A \times A \\ \text{copy } x &= (x , x) , \text{wk}, \\ \text{compose} & : ((x : A) \rightarrow \eta \, x \wedge n \Vdash B) \rightarrow ((y : B) \rightarrow \eta \, y \wedge m \Vdash C) \\ & \rightarrow (x : A) \rightarrow \eta \, x \wedge (n \cdot m) \Vdash C \\ \text{compose } f \, g \, x &= g \, (f \, x . \text{fst}) . \text{fst} , \dots \end{aligned}$$

A natural resource algebra

We get multiplicities for free using the standard natural numbers type:

$$\begin{aligned} \frac{}{\Delta \wedge} & : \text{Supply} \rightarrow \mathbb{N} \rightarrow \text{Supply} \\ \Delta \wedge \text{zero} & = \diamond \\ \Delta \wedge (\text{suc } n) & = \Delta \otimes (\Delta \wedge n) \end{aligned}$$

It's straightforward to work with these multiplicities:

$$\begin{aligned} \text{copy} & : (x : A) \rightarrow \eta \ x \wedge 2 \Vdash A \times A \\ \text{copy } x & = (x \text{ , } x) \text{ , wk,} \end{aligned}$$
$$\begin{aligned} \text{compose} & : ((x : A) \rightarrow \eta \ x \wedge n \Vdash B) \rightarrow ((y : B) \rightarrow \eta \ y \wedge m \Vdash C) \\ & \rightarrow (x : A) \rightarrow \eta \ x \wedge (n \cdot m) \Vdash C \end{aligned}$$
$$\text{compose } f \ g \ x = g \ (f \ x \text{ . fst) . fst , } \dots$$

some work is necessary here...

A natural resource algebra

We get multiplicities for free using the standard natural numbers type:

$$\begin{aligned} \frac{}{\Delta \wedge \text{zero} = \diamond} & : \text{Supply} \rightarrow \mathbb{N} \rightarrow \text{Supply} \\ \Delta \wedge (\text{suc } n) &= \Delta \otimes (\Delta \wedge n) \end{aligned}$$

It's straightforward to work with these multiplicities:

$$\begin{aligned} \text{copy} & : (x : A) \rightarrow \eta \ x \wedge 2 \Vdash A \times A \\ \text{copy } x &= (x \ , \ x) \ , \ \text{wk}, \end{aligned}$$
$$\begin{aligned} \text{compose} & : ((x : A) \rightarrow \eta \ x \wedge n \Vdash B) \rightarrow ((y : B) \rightarrow \eta \ y \wedge m \Vdash C) \\ & \rightarrow (x : A) \rightarrow \eta \ x \wedge (n \cdot m) \Vdash C \\ \text{compose } f \ g \ x &= g \ (f \ x \cdot \text{fst}) \cdot \text{fst} \ , \ \dots \end{aligned}$$

some work is necessary here...

$$\begin{aligned} \text{copytwice} & : (x : A) \rightarrow \eta \ x \wedge 4 \Vdash (A \times A) \times (A \times A) \\ \text{copytwice} &= \text{compose } \text{copy} \ \text{copy} \end{aligned}$$

...but this directly computes!

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⊗_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⊗ ◇ : wk[]
  cn:: : η (x :: xs) ⊗ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⊗_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⊗ ◇ : wk[]
  cn:: : η (x :: xs) ⊗ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
  → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊨ A × List A
safeHead []      y = (y , []) , {Goal: (η y ^ 1 ⊗ η []) ⋈ η (y , []) }
safeHead (x :: xs) y = (x , xs) , {Goal: (η y ^ 0 ⊗ η (x :: xs)) ⋈ η (x , xs) }
```


Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
  → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊢ A × List A
safeHead []      y = (y , []) , wk,
safeHead (x :: xs) y = (x , xs) , {Goal: (η y ^ 0 ⊗ η (x :: xs)) ⋈ η (x , xs) }
```

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
           → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊢ A × List A
safeHead []      y = (y , []) , wk,
safeHead (x :: xs) y = (x , xs) , wk, ∘ cn::
```

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
  → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊢ A × List A
safeHead [] y = (y , []) , wk,
safeHead (x :: xs) y = (x , xs) , wk, ∘ cn::
```

```
foldr : ((x : A) → (b : B) → η b ⊗ η x ⊗ Δ1 ⊢ B) → Δ0 ⊢ B
  → (xs : List A) → Δ0 ⊗ Δ1 ^ (length xs) ⊗ η xs ⊢ B
foldr f (z , δ) [] =
foldr f z (x :: xs) =
```

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
  → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊢ A × List A
safeHead [] y = (y , []) , wk,
safeHead (x :: xs) y = (x , xs) , wk, ∘ cn::
```

```
foldr : ((x : A) → (b : B) → η b ⊗ η x ⊗ Δ1 ⊢ B) → Δ0 ⊢ B
  → (xs : List A) → Δ0 ⊗ Δ1 ^ (length xs) ⊗ η xs ⊢ B
foldr f (z , δ) [] = {Goal: Δ0 ⊗ Δ1 ^ length [] ⊗ η [] ⊢ B }
foldr f z (x :: xs) =
```

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
  → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊢ A × List A
safeHead [] y = (y , []) , wk,
safeHead (x :: xs) y = (x , xs) , wk, ° cn::
```

```
foldr : ((x : A) → (b : B) → η b ⊗ η x ⊗ Δ1 ⊢ B) → Δ0 ⊢ B
  → (xs : List A) → Δ0 ⊗ Δ1 ^ (length xs) ⊗ η xs ⊢ B
foldr f (z , δ) [] = z , δ ⊗f cn[]
foldr f z (x :: xs) =
```

Programming linearly with lists

We introduce productions for the lists constructors:

```
data _⋈_ : Supply → Supply → Type where
  ...
  cn[] : η [] ⋈ ◇ : wk[]
  cn:: : η (x :: xs) ⋈ (η x ⊗ η xs) : wk::           (for x : A , xs : List A)
```

That's all we need to incorporate lists in our system!

```
safeHead : (xs : List A) → (y : A)
  → η y ^ (if null xs then 1 else 0) ⊗ η xs ⊢ A × List A
safeHead []          y = (y , []) , wk,
safeHead (x :: xs) y = (x , xs) , wk, ° cn::
```

```
foldr : ((x : A) → (b : B) → η b ⊗ η x ⊗ Δ1 ⊢ B) → Δ0 ⊢ B
  → (xs : List A) → Δ0 ⊗ Δ1 ^ (length xs) ⊗ η xs ⊢ B
```

```
foldr f (z , δ) [] = z , δ ⊗f cn[]
```

```
foldr f z (x :: xs) = f x @ foldr f z xs ...
```

$((x : A) \rightarrow \eta x \otimes \Delta_0 \vdash B) \rightarrow \Delta_1 \vdash A \rightarrow \Delta_0 \otimes \Delta_1 \vdash B$

Recap

- Supplies as *finite multisets of pointed types* are a useful notion of resource, dependent pairs allow us to define a linear judgment *inside* type theory.

$$\Delta \Vdash A = \sum [a \in A] (\Delta \ltimes \eta a)$$

- Productions capture which supplies have the *same multiset of free variables*. Incorporate datatypes by stipulating productions for each constructor.
→ quantitative elimination principles are *derived* using dependent elimination!
- Dependent types are naturally part of the system.
- This is already practical for programming, for example it's easy to construct sorting algorithms. Simple tactic could automatically find most productions.

Leaving cubical behind

We can carry out our construction in any dependent type theory with Π and Σ :

$$\begin{array}{c} Tm : Cx^{op} \rightarrow \mathbf{Set} \\ \downarrow \pi \\ Ty : Cx^{op} \rightarrow \mathbf{Set} \end{array}$$

Leaving cubical behind

We can carry out our construction in any dependent type theory with Π and Σ :

$$\begin{array}{c} Tm \\ \downarrow \pi \\ Ty \end{array}$$

Leaving cubical behind

We can carry out our construction in any dependent type theory with Π and Σ :

$$\begin{array}{ccc} Tm & \xrightarrow{\eta} & Sp : Cx^{op} \rightarrow \mathbf{SMCat} \\ \downarrow \pi & & \\ Ty & & \end{array}$$

Leaving cubical behind

We can carry out our construction in any dependent type theory with Π and Σ :

$$\begin{array}{ccc} Tm & \xrightarrow{\eta} & Sp : Cx^{op} \rightarrow \mathbf{SMCat} \\ \downarrow \pi & & \\ Ty & & \end{array}$$

- $Sp(\Gamma)$ live in type theory ($Sp(\Gamma) \in Ty(\Gamma)$ etc.)
- $\eta(a) \otimes \eta(b) \simeq \eta(a, b)$ for any $a : A$ and $b : B(a)$

Leaving cubical behind

We can carry out our construction in any dependent type theory with Π and Σ :

$$\begin{array}{c} Tm \xrightarrow{\eta} Sp : Cx^{op} \rightarrow \mathbf{SMCat} \\ \downarrow \pi \\ Ty \end{array}$$

- $Sp(\Gamma)$ live in type theory ($Sp(\Gamma) \in Ty(\Gamma)$ etc.)
- $\eta(a) \otimes \eta(b) \simeq \eta(a, b)$ for any $a : A$ and $b : B(a)$

Using this, we can define a linear judgment, giving rise to a two-step derivation:

$$\Gamma \vdash \Delta \Vdash A$$

Leaving cubical behind

We can carry out our construction in any dependent type theory with Π and Σ :

$$\begin{array}{c} Tm \xrightarrow{\eta} Sp : Cx^{op} \rightarrow \mathbf{SMCat} \\ \downarrow \pi \\ Ty \end{array}$$

- $Sp(\Gamma)$ live in type theory ($Sp(\Gamma) \in Ty(\Gamma)$ etc.)
- $\eta(a) \otimes \eta(b) \simeq \eta(a, b)$ for any $a : A$ and $b : B(a)$

Using this, we can define a linear judgment, giving rise to a two-step derivation:

$$\Gamma \vdash \Delta \Vdash A$$

Can we internalise this structure? In other words, how to add function types?

Proposal for internalising $\Gamma \vdash \Delta \Vdash A$

Add two more things:

- exponentials $[\Delta_0, \Delta_1]$
- $\Lambda_{x:A} \Delta$ binding x in Δ

$$Sp : Cx^{op} \rightarrow \mathbf{SMCCat}$$

functor $\Lambda_A : Sp(\Gamma . A) \rightarrow Sp(\Gamma)$ that's right adjoint to context extension $Sp(\mathbf{p}_A) : Sp(\Gamma) \rightarrow Sp(\Gamma . A)$

Proposal for internalising $\Gamma \vdash \Delta \Vdash A$

Add two more things:

- exponentials $[\Delta_0, \Delta_1]$
- $\Lambda_{x:A} \Delta$ binding x in Δ

$$Sp : Cx^{op} \rightarrow \mathbf{SMCCat}$$

functor $\Lambda_A : Sp(\Gamma . A) \rightarrow Sp(\Gamma)$ that's right adjoint to context extension $Sp(\mathbf{p}_A) : Sp(\Gamma) \rightarrow Sp(\Gamma . A)$

This allows us to define a type of dependent linear functions from A to B :

$$(x : A) \multimap B(x) := (x : A) \rightarrow B(x) , \lambda f \rightarrow \Lambda_{x:A}[\eta(x), \eta(f x)]$$

We can derive intuitive introduction and elimination rules for $(x : A) \multimap B(x)$.

Proposal for internalising $\Gamma \vdash \Delta \Vdash A$

Add two more things:

- exponentials $[\Delta_0, \Delta_1]$
- $\Lambda_{x:A} \Delta$ binding x in Δ

$$Sp : Cx^{op} \rightarrow \mathbf{SMCCat}$$

functor $\Lambda_A : Sp(\Gamma . A) \rightarrow Sp(\Gamma)$ that's right adjoint to context extension $Sp(\mathbf{p}_A) : Sp(\Gamma) \rightarrow Sp(\Gamma . A)$

This allows us to define a type of dependent linear functions from A to B :

$$(x : A) \multimap B(x) := (x : A) \rightarrow B(x) , \lambda f \rightarrow \Lambda_{x:A}[\eta(x), \eta(f x)]$$

(generalise η to dependent supplies for higher-order functions)

We can derive intuitive introduction and elimination rules for $(x : A) \multimap B(x)$.

Summary

- Adding symmetric monoidal structure to dependent type theory is useful.
 - This also happens with non-idempotent intersection types (De Carvalho, Ronchi della Rocca, Gardner), but more powerful base theory makes our life easier.
- Quantitative features come for free, multiplicities are (open) terms of type \mathbb{N} .
 - We can type many more programs than systems with static resource algebra (QTT, Graded TT, Linear Haskell). Observation due to Pierre-Marie Pedrót (*Dialectica the Ultimate*, talk at TLLA 2024).
- WIP: expand idea to incorporate *dependent linear function types*. Gives rise to a *dependent linear type theory* with *dependent multiplicities*.

<https://github.com/maxdore/dlitt/>

Dependent linear functions

$$(x : A) \multimap B(x) := (x : A) \rightarrow B(x) \text{ , } \lambda f \rightarrow \Lambda_{x:A}[\eta(x), \eta(f \ x)]$$

$$\frac{\Gamma, x : A \vdash \Delta \otimes \eta(x)^m \Vdash b : B(x)}{\Gamma \vdash \Delta \Vdash \lambda x . b : (x : A) \multimap^m B(x)} \multimap I \ (x \notin \Delta)$$

$$\frac{\Gamma \vdash \Delta_0 \Vdash f : (x : A) \multimap^m B(x) \quad \Gamma \vdash \Delta_1 \Vdash a : A}{\Gamma \vdash \Delta_0 \otimes \Delta_1^m \Vdash f \ a : B(a)} \multimap E$$

Dependent linear type theory

We can define a type theory with linear dependent types using the following:

$$\begin{array}{ccc}
 Tm & \xrightarrow{\eta} & Sp : Cx^{op} \rightarrow \mathbf{SMCCat} \\
 \downarrow \pi & & \\
 Ty & &
 \end{array}
 \qquad
 \begin{array}{ccc}
 & \xrightarrow{Sp(\mathbf{p}_A)} & \\
 Sp(\Gamma) & \perp & Sp(\Gamma . A) \\
 & \xleftarrow{\Lambda_A} &
 \end{array}$$

+ for Σ types: iso between $\eta(a) \otimes \eta(b)$ and $\eta(a, b)$ for any $a : A$ and $b : B(a)$

Linear types without finite multisets

```
data Supply : Type where
```

```
  ◇ : Supply
```

```
  η : {A : Type} (a : A) → Supply
```

```
  _⊗_ : Supply → Supply → Supply
```

```
data _⌋_ : Supply → Supply → Type where
```

```
  id : ∀ Δ → Δ ⌋ Δ
```

```
  _∘_ : ∀ {Δ0 Δ1 Δ2} → Δ1 ⌋ Δ2 → Δ0 ⌋ Δ1 → Δ0 ⌋ Δ2
```

```
  _⊗f_ : ∀ {Δ0 Δ1 Δ2 Δ3} → Δ0 ⌋ Δ1 → Δ2 ⌋ Δ3 → Δ0 ⊗ Δ2 ⌋ Δ1 ⊗ Δ3
```

```
  unitr : ∀ Δ → Δ ⊗ ◇ ⌋ Δ
```

```
  unitr' : ∀ Δ → Δ ⌋ Δ ⊗ ◇
```

```
  swap : ∀ Δ0 Δ1 → Δ0 ⊗ Δ1 ⌋ Δ1 ⊗ Δ0
```

```
  assoc : ∀ Δ0 Δ1 Δ2 → (Δ0 ⊗ Δ1) ⊗ Δ2 ⌋ Δ0 ⊗ (Δ1 ⊗ Δ2)
```

Currying example

$$\begin{array}{c}
 \frac{x : A, y : B(x) \vdash \Delta \Vdash f : \mathbb{H}_{\text{pair}(x,y):\Sigma_A(B)}^1(C(y)) \quad \frac{}{x : A, y : B(x) \vdash \eta(\text{pair}(x, y)) \Vdash \text{pair}(x, y) : \Sigma_A(B)} \text{ID}}{\quad} \mathbb{H} \text{APP} \\
 \frac{}{x : A, y : B(x) \vdash \Delta \otimes \eta(\text{pair}(x, y)) \Vdash f(\text{pair}(x, y)) : C(y)} \omega_{\text{pair}} \\
 \frac{}{x : A, y : B(x) \vdash \Delta \otimes \eta(x) \otimes \eta(y) \Vdash f(\text{pair}(x, y)) : C(y)} \mathbb{H} \text{I} \\
 \frac{}{x : A \vdash \Delta \otimes \eta(x) \Vdash \lambda y. f(\text{pair}(x, y)) : \mathbb{H}_{B(x)}^1(C)} \mathbb{H} \text{I} \\
 \frac{}{\vdash \Delta \Vdash \lambda x. \lambda y. f(\text{pair}(x, y)) : \mathbb{H}_{x:A}^1(\mathbb{H}_{B(x)}^1(C))} \mathbb{H} \text{I}
 \end{array}$$