

Karabo Overview

Dr. Gero Flucke
for the
Control and Analysis Software group

Satellite Workshop on
Karabo Control and Data Analysis at European XFEL
January 24th, 2019



Outline


- Karabo Framework Overview
- Graphical User Interface
- Data Acquisition and Scanning
- Data Analysis Capabilities

Introduction

- Karabo is custom made European XFEL's
 - **Control** System: controls a wide-range of light source instruments
 - **Data acquisition** system: GB/s scientific data collection
 - **Data processing** framework: Native support of distributed process chaining using pipelines.
- Under active development
- Drives European XFEL commissioning and user experiments








Unified approach required for:


- Instrument Control
- Data Acquisition (DAQ)
- Data Management (DM)
- Scientific Computing (SC)



Karabo: Device Based Communication via a Message Broker and TCP/IP Data Pipelines

Individual Karabo Devices


-  Equipment control, e.g. motors, valves,...
-  Detectors like
 -  big 2D detectors,
 -  cameras
-  Data storage
-  System services
-  Online/offline data analysis, e.g. calibration



Four Application Programming Interfaces

...and whom they address:

- **Macros:**
instrument scientists,
possibly later users
- **Middlelayer:**
Control experts with feedback
from instruments,
maybe instrument scientists
- **Hardware interface:**
Control experts with hardware
knowledge



Data Types Supported by Karabo Communication

- 8-, 16-, 32-, 64-bit signed and unsigned integer values
 - 8-bit raw data, booleans
- 32- and 64-bit floating point numbers
 - complex numbers thereof
- strings
- vectors (lists) of all the above
- NDArray (for pipelines): container of multi-dimensional “big data”, optimised serialisation
- ImageData: container for
 - NDArray
 - meta-data like info about bits-per-pixel, roi offsets, binning, encoding type,...
- Karabo Hash as nested key / value container
 - string keys – nested access through concatenation separated by dot: `aHash.get("key1.k2.k3")`
 - values can be any of the above

Unified Device States


■ Predefined list of device states

■ Inheritance system

■ E.g. ERROR is more concrete than KNOWN

■ Unified colour representation in the GUI

■ Colour inherited if not explicit




About 60 more states inheriting from those of the last row.

Data Logging and History Reading for Control

- Provides history retrieval for
 - GUI trendlines and configurations from past
 - CLI interface
- Not a data acquisition, no data policy, no pipeline nor big 2D detector data:
 - No data for users...
- Karabo logger service devices subscribe to parameter changes
- Store data in human readable text files per device (and index files):
20190115T013900.706424Z|1547516340.706424|0|perfStats.maxProcessingLatency|UINT32|35||VALID
 - Data older than about a month compressed and put on archive
- Karabo reader service reads back using index files
- Plans for refurbishment:
 - Proper data base to replace storage in text files
 - Karabo-less interface

Graphical User Interface: Integrated cockpit



Unified tool:

For experts:

- Full system view.
- Detailed access to configurations.
- Integrated command line.

For everybody:


- Customizable “scenes” (no coding required).
- Rich set of widgets.
- Coherent handling, e.g. limits of settings.
- Visualisation of
 - ▶ error state,
 - ▶ properties in alarm condition.

■ ...

Graphical User Interface

Navigation panel:


- Complete Karabo system topology
- Searchable
- Colour coded device state indicator (error vs. healthy)
- Alarm levels icons if reached:



Graphical User Interface

Configuration panel


- Edit online and offline device configuration
- Send commands to devices
- State field colouring
- Coloured background for properties in alarm



Graphical User Interface

Project panel


- Project data:
 - device configurations,
 - scenes (→),
 - macros,
 - sub-projects.
- Projects stored in central data base as XML files.
 - local storage option



Graphical User Interface

Panels for


- Message logging
- Alarm handling
- Integrated command line



Scenes

- Easily editable
 - using drag and drop,
 - include svg files,
 - link to other scenes.
- Rich widget set
 - various image views,
 - trend and spark lines,
 - commands,
 - device states,
 - standardized icons,
 - editable tables, FIXME
 - (some details in backup)
- Can un-dock from main window (as all panels)
- Now can run standalone (“cinema” mode)

Graphical User Interface




Scene Example

Beamline Control: SASE1

Icons, e.g.
ion pumps,
valves

State coloured:
open,
passive/
closed,
interlock


Scene links



Scene Example

Diagnostic:
XGM monitoring

- More icons, e.g.
 - gauges,
 - turbo pumps,
 - scroll pumps
- More state colours:
 - unknown (i.e. no h/w info),
 - disabled / interlocked



Scene Example

Detector control:
LPD Tile Control

View result of
online
calibration


The screenshot displays the Karabo 2 Tile Control interface, which is divided into several functional panels:

- 2 Tile Control:** Contains buttons for 'Connect FEM', 'Disconnect FEM', 'Upload FEM config', 'Prepare next config', 'Start DAQ', and 'Stop DAQ'. It also shows status indicators for 'AsicPowerEnable0/1' and 'SensorBiasEnable0/1', and a 'FemAsicGain' slider.
- DAQ and Run Configuration:** Features a 'Data source list' table with columns for Source, Type, Behavior, and Monitor. It includes buttons for 'Save configuration', 'Push to DAQ', 'Ignore data', 'Apply configuration', 'Monitor data', 'Start run', and 'Stop run'. A note indicates that data sources must be configured above the push button.
- Online Correction and Preview:** Includes a 'State' dropdown set to 'ACTIVE' and buttons for 'Init', 'Reset', 'End', and 'Commit'. It also has 'enablePreview' and 'pulseToPreview' checkboxes and input fields.
- Starting up system:** A text panel providing hardware initialization steps (1-4) and DAQ configuration steps (5-9). It also includes an 'Online Correction and Preview' section with steps (1) and (2).
- Restarting DAQ:** A text panel explaining when the DAQ might report out of buffers and providing steps (1-5) for restarting the process.
- Data Visualizations:** Two plots are shown at the bottom right: 'Raw' data (a heatmap with a color scale from 1.000 to 7.000) and 'Offset corrected' data (a heatmap with a color scale from -250 to 50). Both plots have axes for 'Indexed axis' and 'Pulse/cell'.


Scene Example

AGIPD Data Preview

- View of online calibrated data
- All 16 readout streams combined



European XFEL: Photons come in trains with short pulses



Pattern:

- **Trains with 10 Hz**
 - Relevant time unit for data storage
- **Up to 2700 pulses per train**
 - pulse duration < 100 fs
 - 220 ns spacing (4.5 MHz)
 - => train length 600 μs
 - Goal: 600 pulses at end of 2019
- **On average:**
 - up to 27 kHz of pulses
 - (up to 6 kHz in 2019)

Karabo Data Acquisition (DAQ) Integration

Support for different types of data sources:

- Control data with train resolution: e.g. sensors, motors (Karabo)
→ slow data
- 2D or pulse resolved data: e.g. cameras, digitizers (Karabo pipeline)
→ fast and/or medium sized data
- Big 2D detectors as LPD, AGIPD (XFEL train data format)
→ big & fast data

Data acquisition organised via several Karabo devices

Data stored in HDF5 files

- available after run has finished,
- Karabo and data access tools provide data of all pulses of a train in one go.

Provide data stream for online display and online analysis,

- e.g. feeds calibration of big 2D detectors,
- can be replicated offline to tune online tools.

FIXME: new scenes requested from DJELLOUL
Karabo Data Acquisition (DAQ) Configuration

- Configure run-by-run which data to store:
- select sources (~devices) via run configuration scene

SA1_DAQ_DATA/DM/SA1_XTD2_IMGP145_GROUP

Group name

SA1_XTD2_IMGP145

Description

TOPIC : SA1
LOCATION : XTD2 TUNNEL

ALL THE DEVICES OF IMAGER

Update Group

User Sources

	Source	Type
0	SA1_XTD2_IMGP145/SWITCH/SCREEN_OUT	control
1	SA1_XTD2_IMGP145/DCTRL/CAM_POWER	control
2	SA1_XTD2_IMGP145/DCTRL/LED_POWER	control

Expert Sources

	Source	Type	Behavior	Monitor
0	SA1_XTD2_IMGP145/DCTRL/CAM_POWER	control	record-all	<input checked="" type="checkbox"/>
1	SA1_XTD2_IMGP145/DCTRL/LED_POWER	control	record-all	<input checked="" type="checkbox"/>

SA1_DAQ_DATA/DM/CONFIGURATOR

Run config. groups

source	type	behavior	monitor	access
<input checked="" type="checkbox"/> SPB_XTD9_XGM				
<input checked="" type="checkbox"/> SA1_XTD2_IMGP145				
SA1_XTD2_IMGP145/DCTRL/CAM_POWER	control	record-all	True	expert
SA1_XTD2_IMGP145/DCTRL/LED_POWER	control	record-all	True	expert
SA1_XTD2_IMGP145/SWITCH/SCREEN_OUT	control	record-all	True	expert
SA1_XTD2_IMGP145/CAM/BEAMVIEW	control	record-all	True	expert
SA1_XTD2_IMGP145/CAM/BEAMVIEW:daqOutput	control	record-all	True	expert
SA1_XTD2_IMGP145/MOTOR/SCREEN	control	record-all	True	expert
<input checked="" type="checkbox"/> SA1_XTD2_IMGSR				
<input checked="" type="checkbox"/> SA1_XTD2_XGM				
<input type="checkbox"/> SA1_XTD2_KMONO				
<input type="checkbox"/> SA1_XTD2_IMGFEL				
<input type="checkbox"/> HIREX DATA				
<input type="checkbox"/> MCP_X2_DOWNSTREAM				
<input type="checkbox"/> SA1_WP74_KMONO_DOCS				
<input type="checkbox"/> MCP_X1_UPSTREAM				
<input type="checkbox"/> SCANTOOL SA1				
<input type="checkbox"/> BEAM_COND				
<input type="checkbox"/> SA1_XTD2_IMGFEL_RED				
<input type="checkbox"/> SA1_MOTOR				
<input type="checkbox"/> SA1_XTD2_CRL				
<input type="checkbox"/> SA1_XTD9_IMGP145				
<input type="checkbox"/> SPB_XTD9_IMGP1				

Send to DAQ

Run Control

SA1 Run Controller

Proposal number

900007

900007

Retrieve proposal

Update

State

MONITORING

White list

SA1_DAQ_DATA/DA/1

SA1_DAQ_DATA/DA/1

Black list

Pipeline data handlers

SA1_DAQ_DATA/DA/1

Slow data handlers

SA1_DAQ_DATA/DA/1

Available

SA1_DAQ_DATA/DA/1

Disabled

XTDF data handlers

Ignore data

Assign data sources to aggregators

Data sources to data aggregators mapping

	Data source	Data aggregator
0	@SA1_XTD2_IMGP145	SA1_DAQ_DATA/DA/1
1	@SPB_XTD9_XGM	SA1_DAQ_DATA/DA/1

Ignore data

Apply configuration

Experiment

Sample

Train Id

18516999

Run number

0


Monitor data

Start run

Stop run

Scan Tool

- DAQ-integrated step scans:
 - one scan - one DAQ run.
- GUI and (spec like) command line.
- Configure devices:
 - abstract motor(s): steps to take,
 - passive and active (“triggers”) data sources.
- Scan types
 - absolute – 1-4 motors: ascan, a2scan,...
 - relative – 1-4 motors: dscan, d2scan,...
 - 2D grid – absolute and relative: mesh, dmesh
- Plotting being extended to non-scalar data



State
Progress 0 %

isConfigured ●

Start Scan

Start Scan

Stop Scan

Stop Scan

Toggle scan

Toggle scan

Configure

Configure

Scan Parameter

Scan Type

ascan

ascan

Start Positions

0.0

0.0

Stop Positions

10.0

10.0

Steps

10

10

Bidirectional

☒

[19:18:33]: No sources selected!

[19:18:38]: Scan environment is configured!

----- Configuration -----

Motors: ['MOTOR1:default']


Data Sources: ['SENS1:default']

Triggers: []

Ongoing Karabo Development in 2018

■ Five main, 19 hotfix releases

■ Release schedule and deployment driven by EuXFEL schedule to minimise risks



Karabo Release High Lights in 2018

- 2.2.2 February 2018: refurbished GUI client for speed
- 2.2.3 April 2018: Substantial stabilisation of servers with hundreds of devices
- 2.2.4 June 2018: Significant speed-up of serialisation in data pipelines
- 2.3.0 December 2018:
 - Configuration retrieval from past in GUI
 - Double-click access to parameter trendlines
 - Double-click access to device specific GUI scenes
 - Defined interfaces with CLI listing: motor, camera, trigger, processor, multi axis motor
 - Python 3.4.3 ➔ 3.6.6
 - GUI “cinema” mode to run scenes only
- All along:
 - Bug fixes, stability, performance, minor features, harmonizing APIs, improve interface to accelerator control system DOOCS,...

Karabo: Supervisory Control and Data Acquisition (SCADA) at work!

■ More than 10 large Karabo “ecosystems” for instruments and photon beamlines

■ Nov. 2018 count:

- ▶ more than 400 installations (plus those for GUI clients),
- ▶ 8266 devices (excl. Karabo services),
- ▶ 1.087 million of control points

■ Communication in between ecosystems being improved

■ **FIXME Krzystof ???** TB of data stored in 2018

■ Performance experiences:


■ Single device can stably consume 2 kHz of messages

- ▶ production systems have usually an overall rate 50-500 Hz

■ Latencies at GUI server << 100 ms

■ Online calibration pipelines run smoothly with 2 s latency and 1.79 GB/s throughput

Online Data Analysis



- Karabo goes beyond
 - data on tape
 - online preview

- Online pipeline can contain be extended by analysis devices


- Karabo bridge device opens space of Karabo agnostic user tools via ZeroMQ

- Details in later talks

Summary


- Karabo, an integrated framework for
 - Instrument Control
 - Data Acquisition
 - Data Management
 - Scientific Computing
- Broker based communication
- Workflow support through data pipelines, e.g. for online monitoring
- Four APIs (C++, Python) for extensions
- GUI easily customizable via scenes (by operator or device programmer)
- Experiment automation using macros and scan tools
- Online analysis with external tools

Architecture



Alarms

- Reports any trespassing of property-specific thresholds
- Can be investigated from the GUI (and CLI) and acknowledged as soon as the alarm condition has passed



ID	of First Occur	ne of Occuren	Device ID	Property	Type	Description	Acknowledge	Show Device
9	12/16/16 8:...	12/16/16 9:...	cppServer/...	floatProperty	alarmLow	A descripti...	Acknowledg	Show Device
13	12/16/16 9:...	12/16/16 9:...	cppServer/...	floatProperty	alarmHigh	A descripti...	Acknowledg	Show Device
15	12/16/16 9:...	12/16/16 9:...	cppServer/...	floatProperty	warnHigh		Acknowledg	Show Device
17	12/16/16 9:...	12/16/16 9:...	cppServer/...	global	none		Acknowledg	Show Device
18	12/16/16 9:...	12/16/16 9:...	cppServer/...	global	none		Acknowledg	Show Device

Scene Example

Experiment Control: FXE's Beam Imaging Unit

The screenshot displays the Karabo software interface for the FXE's Beam Imaging Unit. The interface is divided into several panels:

- Navigation Panel (Left):** Shows a hierarchical view of the system components. The 'Operator' role is selected. The 'RunConfigurator' component is highlighted, showing its sub-components: FXE_DAQ_DATA/DM/CONFIGURATOR, RunController, Simulated2DPixelDetector, SimulatedDataSource, SimulatedTimeServer, StatisticsBuilder, and TrainBuilder.
- Projects Panel (Bottom Left):** Lists the active projects, including 'Device Servers' and 'FXE_OGT1_BIU/CAM/CAMERA'.
- Main View (Center):** Displays a live image of the beam spot. The image shows a bright, elongated spot in the center of a dark field. The frame rate is 10.00 Hz. Below the image, there are controls for Gain, Exposure Time (70.0 ms), Image Binning X and Y (both 1 px), Number of Frames (0), and TriggerMode (ExtTrigMult).
- Configuration Editor (Right):** Shows the current values for various parameters. The 'Property' column lists parameters, and the 'Current value on device' column shows their values. Parameters include:
 - Allow Gaussian Rotation: False
 - Min/Max/Mean Evaluation Time: 0.00844264 s
 - Pixel Value Frequency Time: 0.0101583 s
 - Background Image Subtraction Time: 0.0 s
 - Pedestal Subtraction Time: 0.00298786 s
 - Image X-Y Sums Time: 0.0047884 s
 - Centre-Of-Mass Time: 0.0147908 s
 - 1D Gaussian Fit Time (X distribution): 0.00158143 s
 - 1D Gaussian Fit Time (Y distribution): 0.00177193 s
 - 2D Gaussian Fit Time: 0.0 s
 - Min Px Value: 0.0
 - Max Pixel Value: 4095.0
 - Mean Pixel Value: 26.3339255507
 - Pixel counts distribution: [4120. 8679. 15753.]
 - X Distribution: [12579. 12867. 12847.]
 - Y Distribution: [12487. 12051. 14886.]
 - x0 (Centre-Of-Mass): 536.626986579 px
 - sigma_x (Centre-Of-Mass): 37.6725713539 px
 - y0 (Centre-Of-Mass): 615.299663788 px
 - sigma_y (Centre-Of-Mass): 18.7717813195 px
 - x Success (1D Fit): 1 px
 - Ax (1D Fit): -5748.79868649
 - x0 (1D Fit): 539.289344274 px
 - sigma(x0) (1D Fit): 0.328600858551 px
 - sigma_x (1D Fit): -38.7143185785 px
 - sigma(sigma_x) (1D Fit): 0.329556258877 px
 - Beam Width (1D Fit): -0.0 um
 - y Success (1D Fit): 1
 - Ay (1D Fit): -6414.03550049
 - y0 (1D Fit): 615.99193819 px
 - sigma(y0) (1D Fit): 0.215909656204 px
- Console (Bottom Center):** Shows a log of messages. The log includes several 'WARN' messages from the 'FXE_XTD9...' instance, indicating 'alarmHigh: Value 1 of parameter "performanceStatistics.me...'.

Introduction to Value Displays

- Karabo comes with a set of standard visualization options for:
 - ▶ Scalars
 - ▶ Vectors
 - ▶ Images
 - ▶ Image stacks


- For scalars: value field, expression evaluation, trendline, sparklines, x-y plots, bit fields, checkboxes

- For vectors: value fields, x-y plots, categorial plot

- For images: scientific, webcam, minimal, stacked

Introduction to Value Displays - Scalars

Trendline




Sparkline



BitField




European XFEL



Introduction to Value Displays - Vectors


X-y plot



Categorical plot

Introduction to Value Displays - Images

Webcam




image

European
XFEL

Minimal

Scientific,
stacked



European XFEL