EWS Architecture
Basic Minimum System

QZSS

QZSS Control Office
Japan

Send by e-mail

Send confirmation of
receive of message

1 EWS Test Message
Teams generate sample EWS message
See documents: EWS_Format.pdf
EWS_Message_Example.pdf

SPRESENSE Device

2 Coding
Display EWS
Message

EWS Message
Decoding

GNSS
(Pos. Vel.,Time)

Coding Interface

NB-IoT

WiFi / BLE

3 NB-IoT
WiFi/BT

4 Alarm, Evacuation
Guidance

5 Flashing light

6 Wailing siren

7 Showing message
on signage display

Minimum Requirement as MVP (Minimum Viable Product) for PoC level Prototype:
Item (1) : Generate sample test EWS message
Item (2) : Read EWS message from Spresense device and display in a PC

EWS Architecture
System with GNSS-based Flood Sensors

GNSS Rx
as a sensor
(network)

8 NB-IoT

QZSS



QZSS Control Office
Japan

Send by e-mail

Send confirmation of
receive of message

1 EWS Test Message
Teams generate sample EWS message
See documents: EWS_Format.pdf
EWS_Message_Example.pdf



SPRESENSE Device

2 Coding
Display EWS
Message

EWS Message
Decoding

GNSS
(Pos. Vel.,Time)

Coding Interface

NB-IoT

WiFi / BLE

3 NB-IoT
WiFi/BT

4

Alarm, Evacuation
Guidance

5

Flashing light

6

Wailing siren

7

Showing message
on signage display

Minimum Requirement as MVP (Minimum Viable Product) for PoC level Prototype:
Item (1) : Generate sample test EWS message
Item (2) : Read EWS message from Spresense device and display in a PC

EWS Architecture
System with GNSS-based Flood Sensors and Local Broadcasting

GNSS Rx
as a sensor
(network)

8 NB-IoT

QZSS



QZSS Control Office
Japan

Send by e-mail

1 EWS Test Message
Teams generate sample EWS message
See documents: EWS_Format.pdf
EWS_Message_Example.pdf

Send confirmation of
receive of message

9 NB-IoT



SPRESENSE Device

2 Coding
Display EWS
Message

EWS Message
Decoding

GNSS
(Pos. Vel.,Time)

Coding Interface

NB-IoT

WiFi / BLE

3 NB-IoT
WiFi/BT

4

Alarm, Evacuation
Guidance

5

Flashing light

6

Wailing siren

7

Showing message
on signage display

Minimum Requirement as MVP (Minimum Viable Product) for PoC level Prototype:
Item (1) : Generate sample test EWS message
Item (2) : Read EWS message from Spresense device and display in a PC

EWS Architecture
System with GNSS-based Flood Sensors and Local Broadcasting Only



Water level increased above the threshold
Send warning message

1 **EWS Test Message**
Teams generate sample EWS message
See documents: EWS_Format.pdf
EWS_Message_Example.pdf

9 NB-IoT

2 Coding Display EWS Message

EWS Message Decoding
GNSS (Pos. Vel.,Time)
Coding Interface
NB-IoT
WiFi / BLE

Which area will be affected? When they will be affected?

3 NB-IoT WiFi/BT

4 Alarm, Evacuation Guidance

5 Flashing light

6 Wailing siren

7 Showing message on signage display

Minimum Requirement as MVP (Minimum Viable Product) for PoC level Prototype:
Item (1) : Generate sample test EWS message
Item (2) : Read EWS message from Spresense device and display in a PC