

1Voucher — Technical Docs

Operator reference for the platform's value model, contracts, functions and the on-chain events that drive reporting. For a high-level product overview, see the **About** page.

Concepts Payments Gas fees Merchant Contracts Functions Events & Reporting

API

TreasuryToken

Permissioned ERC-20 (e.g. TTZA), 2 decimals. Compliance runs in the `_update` hook.

Function	Purpose	Caller
<code>initialize(name, symbol, admin, supply)</code>	One-time proxy init; mints initial supply to admin	deploy
<code>mint(to, amt)</code>	Credit on fiat deposit / voucher redeem	MINTER_ROLE
<code>burn(from, amt)</code>	Burn on settlement (fiat out)	MINTER_ROLE
<code>burnOwn(amt)</code>	Holder burns own balance	any holder
<code>transfer</code> / <code>transferFrom</code> / <code>approve</code>	Standard ERC-20, subject to the compliance/freeze hook	token holder
<code>pause</code> / <code>unpause</code>	Halt / resume all transfers	PAUSER_ROLE
<code>addToBlacklist</code> / <code>removeFromBlacklist</code>	Block / unblock a wallet	DEFAULT_ADMIN_ROLE
<code>addToWhitelist</code> / <code>removeFromWhitelist</code>	Manage trusted allow-list (platform, merchants)	COMPLIANCE_ROLE
<code>setWhitelistEnabled(bool)</code>	Toggle hard allow-list mode	DEFAULT_ADMIN_ROLE
<code>setConsumerContract</code> / <code>setComplianceEnabled</code>	Wire Consumer registry / toggle the KYC-jurisdiction gate	DEFAULT_ADMIN_ROLE
<code>freezePartialTokens</code> / <code>unfreezePartialTokens</code>	Lock / release part of a balance	COMPLIANCE_ROLE