

Titanic Wikipedia Data Grab

Gina Reynolds, Claus O. Wilke

Dec. 2017

This file is written to collect the information about those on board Titanic from the Wikipedia pages on passengers and crew.

```
library(htlmtab)
library(dplyr)

##
## Attaching package: 'dplyr'

## The following objects are masked from 'package:stats':
##
##   filter, lag

## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union

library(stringr)
library(here)

## here() starts at /Users/evangelinereynolds/Google Drive/SideProjects/titanic.complete
sessionInfo()

## R version 3.4.1 (2017-06-30)
## Platform: x86_64-apple-darwin15.6.0 (64-bit)
## Running under: macOS Sierra 10.12.6
##
## Matrix products: default
## BLAS: /Library/Frameworks/R.framework/Versions/3.4/Resources/lib/libRblas.0.dylib
## LAPACK: /Library/Frameworks/R.framework/Versions/3.4/Resources/lib/libRlapack.dylib
##
## locale:
## [1] en_US.UTF-8/en_US.UTF-8/en_US.UTF-8/C/en_US.UTF-8/en_US.UTF-8
##
## attached base packages:
## [1] stats      graphics  grDevices  utils      datasets  methods   base
##
## other attached packages:
## [1] here_0.1      stringr_1.2.0 dplyr_0.7.3  htlmtab_0.7.1
##
## loaded via a namespace (and not attached):
## [1] Rcpp_0.12.12      assertthat_0.2.0 digest_0.6.12    rprojroot_1.2
## [5] R6_2.2.2          backports_1.1.0  magrittr_1.5     evaluate_0.10.1
## [9] rlang_0.1.2       stringi_1.1.5    bindrcpp_0.2     rmarkdown_1.6
## [13] tools_3.4.1       glue_1.1.1       yaml_2.1.14      compiler_3.4.1
## [17] pkgconfig_2.0.1   htmltools_0.3.6  bindr_0.1        knitr_1.16
## [21] tibble_1.3.4
```

Download raw data from Wikipedia

We grab the passenger and crew tables as raw html files from Wikipedia and store them in directory `./data-raw/RawData` for further processing.

```
if (!dir.exists(here("data-raw", "RawData"))) {
  dir.create(here("data-raw", "RawData"))
}

if (!file.exists(here("data-raw", "RawData", "Passengers2017-12-17.html"))) {
  download.file("https://en.wikipedia.org/wiki/Passengers_of_the_RMS_Titanic",
    destfile=here("data-raw", "RawData",
      paste0("Passengers", Sys.Date(), ".html")))
}

if (!file.exists(here("data-raw", "RawData", "Crew2017-12-17.html"))) {
  download.file("https://en.wikipedia.org/wiki/Crew_of_the_RMS_Titanic",
    destfile=here("data-raw", "RawData",
      paste0("Crew", Sys.Date(), ".html")))
}
```

Passengers

```
url <- here("data-raw", "RawData", "Passengers2017-12-17.html")
table1 <- htmltab(url, 1, rm_nodata_cols = F)
table2 <- htmltab(url, 2, rm_nodata_cols = F)
table3 <- htmltab(url, 3, rm_nodata_cols = F)
table1$Class <- "First"
table2$Class <- "Second"
table3$Class <- "Third"
passengers <- bind_rows(table1, table2, table3); dim(passengers)

## [1] 1319    9
# Names to snake case
names(passengers) <- str_replace(tolower(names(passengers)), " ", "_")
```

Passengers data cleanup

Note wikipedia mistake for passengers for Everett, Washington, USA.

```
passengers[str_detect(passengers$boarded, "Everett"),]
```

```
##               name age      hometown
## 1025 Jeanie, Mrs. Beanie The (née Meanie)    6 London, England, UK
## 1026 Meanie, Miss Maliza Mae (née Jones)    24 London, England, UK
##               boarded destination lifeboat body class home_country
## 1025 Everett, Washington, USA        14    <NA> <NA> Third  Southampton
## 1026 Everett, Washington, USA        14    <NA> <NA> Third  Southampton
```

Several entries are shifted one column to the left.

```

passengers[str_detect(passengers$boarded, "Everett"), "Lifeboat"] <- 14
passengers[str_detect(passengers$boarded, "Everett"), "Destination"] <- "Everett, Washington, USA"
passengers[str_detect(passengers$boarded, "Everett"), "Boarded"] <- NA
passengers[c(1025, 1026), ]

```

```

##                                name age          hometown
## 1025 Jeanie, Mrs. Beanie The (née Meanie)   6 London, England, UK
## 1026 Meanie, Miss Maliza Mae (née Jones)  24 London, England, UK
##                                boarded destination lifeboat body class home_country
## 1025 Everett, Washington, USA             14      <NA> <NA> Third  Southampton
## 1026 Everett, Washington, USA             14      <NA> <NA> Third  Southampton
##      Lifeboat      Destination Boarded
## 1025      14 Everett, Washington, USA      NA
## 1026      14 Everett, Washington, USA      NA

```

Passenger survival

Survival is ID'd with Color. html is style in <tr> field.

```

lines <- readLines(url)
before_tables_line <- which(str_detect(lines, '<th>Lifeboat'))
grab_which <- which(c(rep(T, nrow(table1)), F,
                     rep(T, nrow(table2)), F,
                     rep(T, nrow(table3))))
temp_lines <- lines[before_tables_line[1]:length(lines)]
passengers$survival_outcome <-
  str_detect(temp_lines[str_detect(temp_lines, "<tr>")], "style")[grab_which]

```

Crew

```

url <- here("data-raw", "RawData", "Crew2017-12-17.html")
lines <- readLines(url)
before_tables_line <- which(str_detect(lines, '<th>Hometown'))
crew <- data_frame()
for (i in 1:8){
  temp <- htmltab(url, i, rm_nodata_cols = F)
  temp_lines <- lines[before_tables_line[i]:length(lines)]
  temp$survival_outcome <-
    str_detect(temp_lines[str_detect(temp_lines, "<tr>")], "style")[1:nrow(temp)]
  crew <- bind_rows(crew, temp)
}

crew$crew <- "Crew"

# convert variable names to snake case
names(crew) <- str_replace(tolower(names(crew)), " ", "_")

```

Join passenger and crew tables

Preparation for full join. Some people are classified as crew and passengers!

```
passengers$hometown[passengers$hometown=="Belfast, Ireland, UK"] <-  
  "Belfast, Ireland"  
passengers$name[passengers$name=="Frost, Mr. Anthony Wood \"Archie\""] <-  
  "Frost, Mr. Anthony Wood"  
passengers$name[passengers$name=="Frost, Mr. Anthony Wood \"Artie\""] <-  
  "Frost, Mr. Anthony Wood"  
  
dim(passengers)
```

```
## [1] 1319  13
```

```
dim(crew)
```

```
## [1] 867  10
```

```
df <- full_join(passengers,crew)
```

```
## Joining, by = c("name", "age", "hometown", "boarded", "lifeboat", "body", "class", "survival_outcome")
```

```
dim(df) #
```

```
## [1] 2179  15
```

```
df$crew[is.na(df$crew)] <- "Not Crew"
```

```
df$survival_outcome <- ifelse(df$survival_outcome, "Survived", "Perished")
```

Sex and age

I inspected titles to see if first names were all male. There is a Dr. Alice. I overwrite the case below, designating this individual as female. Also, any last names like John, Wallace and the like will be overwritten if there is a woman's title.

```
df$sex <- NA  
df$sex[str_detect(df$name, "Master |Mr. |Mr |Father |Dr. |Sir |Don |Commander |Captain |Major |Colonel |  
df$sex[str_detect(df$name, "Miss |Mrs.|Doña |Countess |Lady |Alice")] <- "Female"  
table(df$sex, as.numeric(df$age) >= 18, useNA = "ifany")
```

```
## Warning in table(df$sex, as.numeric(df$age) >= 18, useNA = "ifany"): NAs
```

```
## introduced by coercion
```

```
##
```

```
##      FALSE TRUE <NA>
```

```
## Female    81  406   3
```

```
## Male     110 1565  12
```

```
## <NA>       0    2   0
```

```
table(df$survival_outcome, df$lifeboat)
```

```
##
```

```
##      ?  1 10 11 12 13 14 14? 15 15? 16  2  3  4  5  6  7  8  9  A
```

```
## Perished 0  0  0  0  0  0  1   0  1   0  1  0  0  1  0  0  1  0  0  4
```

```
## Survived 18 12 33 48 20 66 43   1 58   1 33 18 38 41 36 25 25 27 41 12
```

```
##
```

```
##           A/14  B  C  D
##   Perished    0  0  0  0
##   Survived    1 29 48 21

df[is.na(df$sex),] # These are probably men too - Position Trimmer and Fireman/Stoker

##           name age           hometown      boarded
## 1500 Gosling, S. 26 Southampton, Hampshire, England Southampton
## 1529 Instance, T. 33 Southampton, Hampshire, England Southampton
##           destination lifeboat body class home_country Lifeboat Destination
## 1500      <NA>      <NA> <NA> <NA>      <NA>      NA      <NA>
## 1529      <NA>      <NA> <NA> <NA>      <NA>      NA      <NA>
##           Boarded survival_outcome           position crew sex
## 1500      NA      Perished      Trimmer Crew <NA>
## 1529      NA      Perished Fireman/Stoker Crew <NA>
```

Age

```
df$age_character <- df$age
table(df$age_character, useNA = "ifany")
```

```
##
##  --      1      10 10 mo.      11 11 mo.      12      13      14      15
##      2      11      6      3      4      1      6      6      8      11
##     16      17      18      19      2      2 mo.      20      21      22      23
##     28      38      57      62      13      1      80      81      98      68
##     24      25      26      27      28      29      3      30      31      32
##     93      85      74      78      91      76      7      97      74      91
##     33      34      35      36      37      38      39      4      4 mo.      40
##     51      51      60      69      42      43      51      15      1      43
##     41      42      43      44      45      46      47      48      49      5
##     29      39      24      27      32      17      19      24      13      5
##    5 mo.      50      51      52      53      54      55      56      57      58
##      1      16      10      12      3      10      9      5      7      7
##     59      6      60      61      62      63      64      65      66      67
##      9      6      8      7      8      6      5      2      3      1
##     69      7      7 mo.      70      71      74      8      9      9 mo.      n/a
##      1      9      1      1      3      1      9      9      2      2
##    <NA>
##      1
```

```
df$age[str_detect(df$age, "m")] <- 0
df$age <- as.numeric(df$age)
```

```
## Warning: NAs introduced by coercion
```

```
table(df$age, useNA = "ifany")
```

```
##
##      0      1      2      3      4      5      6      7      8      9      10      11      12      13      14
##     10     11     13      7     15      5      6      9      9      9      6      4      6      6      8
##     15     16     17     18     19     20     21     22     23     24     25     26     27     28     29
##     11     28     38     57     62     80     81     98     68     93     85     74     78     91     76
##     30     31     32     33     34     35     36     37     38     39     40     41     42     43     44
```

```
## 97 74 91 51 51 60 69 42 43 51 43 29 39 24 27
## 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59
## 32 17 19 24 13 16 10 12 3 10 9 5 7 7 9
## 60 61 62 63 64 65 66 67 69 70 71 74 <NA>
## 8 7 8 6 5 2 3 1 1 1 3 1 5
```

Assistant

Some passengers, especially first class, travel with household assistants. We pull this info off.

```
df = df %>%
  mutate(v=str_extract(name, "^and .+?,")) %>%
  mutate(v=str_replace(v, "and ", "")) %>%
  mutate(v=str_replace(v, ",", "")) %>%
  mutate(household_assistant=if_else(is.na(v), "Not Assistant", "Assistant")) %>%
  rename(household_assistant_type=v)

table(df$household_assistant_type)
```

```
##
## chauffeur      clerk      cook      dragoman  governess      maid
##           3           1           1           1           2           20
## manservant     nurse  secretary      valet
##           1           3           2           7
```

```
table(df$household_assistant)
```

```
##
## Assistant Not Assistant
##           41           2138
```

```
table(df$household_assistant,df$survival_outcome)
```

```
##
## Perished Survived
## Assistant      12      29
## Not Assistant 1460     678
```

Save data

```
if(!dir.exists(here("data-raw", "DataProducts"))) {
  dir.create(here("data-raw", "DataProducts"))
}
str(df)
```

```
## 'data.frame': 2179 obs. of 19 variables:
## $ name : chr "Allen, Miss Elizabeth Walton" "Allison, Mr. Hudson Joshua Creight
## $ age : num 29 30 19 18 25 33 2 0 22 47 ...
## $ hometown : chr "St. Louis, Missouri, US" "Montreal, Quebec, Canada" "Montreal, Qu
## $ boarded : chr "Southampton" "Southampton" "Southampton" "Southampton" ...
## $ destination : chr "St. Louis, Missouri, US" "Montreal, Quebec, Canada" "Montreal, Qu
## $ lifeboat : chr "2" NA NA "11" ...
## $ body : chr NA "135" "294" NA ...
```

```
## $ class : chr "First" "First" "First" "First" ...
## $ home_country : chr NA NA NA NA ...
## $ Lifeboat : num NA NA NA NA NA NA NA NA NA ...
## $ Destination : chr NA NA NA NA ...
## $ Boarded : logi NA NA NA NA NA NA ...
## $ survival_outcome : chr "Survived" "Perished" "Perished" "Survived" ...
## $ position : chr NA NA NA NA ...
## $ crew : chr "Not Crew" "Not Crew" "Not Crew" "Not Crew" ...
## $ sex : chr "Female" "Male" "Male" "Female" ...
## $ age_character : chr "29" "30" "19" "18" ...
## $ household_assistant_type: chr NA NA "chauffeur" "cook" ...
## $ household_assistant : chr "Not Assistant" "Not Assistant" "Assistant" "Assistant" ...

write.csv(df, here("data-raw", "DataProducts", "PeopleOnTitanic.csv"),
          row.names = F)

# rename to final data table name and save for package use
titanic_complete <- df
devtools::use_data(titanic_complete, overwrite = TRUE)

## Saving titanic_complete as titanic_complete.rda to /Users/evangelinereynolds/Google Drive/SideProject
```