



Petro-Canada Lubricants

Lubrifiants Petro-Canada

Lubricants Centre  
385 Southdown Road  
Mississauga, Ontario, L5J 2Y3

Centre des lubrifiants  
385, Southdown Road  
Mississauga, Ontario, L5J 2Y3

PETRO CANADA PRODUCTS - LUBEPLEX, MISSISSAUGA, ON  
CERTIFICATE OF ANALYSIS

Sold to : **3800373 VALVOLINE LLC**  
Sales Order : **713507863**  
Delivery : **820408006**  
Attn. : **WILLIAM LYONS**  
Shipped to : **5068065**  
Address : **VALVOLINE**  
**RIVER RD (T/T)**  
**CINCINNATI, OH**  
**45204-1033**

Purchase Order : **4522589951**  
SOrg/DstCh/Div : **LUB2 L2 00**  
Telephone :  
Fax No :  
E-mail: **WJLyons@valvoline.com**

Material : **PL65BLK**  
Batch No : **240657**  
Date of Manufacture : **2024/12/23**  
Prod Order No : **1594298**  
Carrier : **CONTRANS TANK GROUP LP**

Shipping Date : **2025/01/10**  
Shipping Point : **NATT**  
B/L No :  
Tank No : **T48**  
Trailer No : **CO 224202**  
Vehicle : **CON 23103**  
Seal# From/To : **-**

Material Name : **PURITY L65 BASE OIL BULK**

CHARACTERISTIC	METHOD	LOWER	UPPER	RESULT
Appearance, Visual	LORM 004			CLR
Moisture Test, Crackle	LORM 001			DRY
Colour, ASTM ,none	ASTM D1500		0.5	<0.5
Density, kg/L at 15 °C ,kg/l	ASTM D4052	0.815	0.850	0.828
Flash point, C O C, ° C ,°C	ASTM D92	170		180
Kinematic Viscosity, cSt at 100 °C ,cSt	ASTM D445	2.3	2.7	2.6
Kinematic Viscosity, cSt at 40 °C ,cSt	ASTM D445			9.49
Pour point, °C ,°C	ASTM D5950		-30	-42
Saybolt Universal Viscosity at 100°F ,sus	ASTM D2161			59.4
Saybolt Universal Viscosity at 210°F ,sus	ASTM D2161			35.0
Viscosity Index ,none	ASTM D2270	90		108

FILL LOT ID: 0002896830

1. 14.25

V-ASAMPS

QUALITY CONTROL DEPARTMENT - Email: [HFLS-QCTeam@HFSinclair.com](mailto:HFLS-QCTeam@HFSinclair.com)

V-ASAMPS



An ISO Approved Company