Chain Support Guides

Solana Support

Copy page

How to Deposit or Withdraw on Solana from an EVM Chain

Relay now fully supports depositing & withdrawing to Solana from any EVM chain we support. This is a great way to get users funds on Solana to complete transactions. You can onboard users funds from Blast ETH to Solana USDC to make transactions on a game. You could also swap funds from Solana SOL to Zora ETH for users to mint. The possibilities are limitless when you use Relay embedded in your app.

Required Information

There are few things that make transacting on Solana different than another EVM chain. The provided information below should review all the exceptions where your input is Solana specific.

⚠ Solana wallet addresses are case sensitive.

SDK Properties

Action	Parameter	Input	Description
Deposit to Solana	`toChainId`	`792703809`	Chain ID assigned to access Solana for Relay's tools.
	`recipient`	User's Solana Address	Must be a valid Solana address. Do **not** use an Ethereum wallet address. *Case Sensitive*

Action	Parameter	Input	Description
	`toCurrency`	Contract Address of Solana Token	Must be a valid Solana token address. Do **not** use an EVM address. We support all tokens tradeable on **Jupiter**.
Withdraw from Solana	`chainId`	`792703809`	Chain ID assigned to access Solana for Relay's tools.
	`currency`	Contract Address of Solana Token	Must be a valid Solana token address. Do **not** use an EVM address. We support all tokens tradeable on **Jupiter**.

When withdrawing from Solana using the SDK, you will not need to specify the depositing wallet address.

Solana Tokens

In the table, we have provided the most frequently used Solana tokens & their contract addresses. We do support all tradeable tokens on **Jupiter**.

Solana token addresses are case sensitive.

Token	Token Address	Token Symbol	Decimals
SOL	`11111111111111111111111111111111`	SOL	9
USDC	`EPjFWdd5AufqSSqeM2qN1xzybapC8G4wEGGkZwyTDt1v`	USDC	6
wSol	`So11111111111111111111111111111111111111112`	wSOL	9
USDT	`Es9vMFrzaCERmJfrF4H2FYD4KCoNkY11McCe8BenwNYB`	USDT	6

Relay supports **any** Solana token available on Jupiter. You can visit **Jupiter** to explore all the tokens available.

API

Params

Action	Parameter	Input	Description
Deposit to Solana	`recipient`	User's Solana Address	Must be a valid Solana address. Do **not** use an Ethereum wallet address. *Case Sensitive*
	`destinationChainId`	`792703809`	Chain ID assigned to access Solana for Relay's tools.
	`destinationCurrency`	Contract Address of Solana Token	Must be a valid Solana token address. Do **not** use an EVM address. We support all tokens tradeable on **Jupiter**.
Withdraw from Solana	`user`	User's Solana Address	Must be a valid Solana address. Do **not** use an Ethereum wallet address. *Case Sensitive*
	`originChainId`	`792703809`	Chain ID assigned to access Solana for Relay's tools.
	`originCurrency`	Contract Address of Solana Token	Must be a valid Solana token address. Do **not** use an EVM address. We support all tokens tradeable on **Jupiter**.

Execution

Once you have the necessary information, you can start utilizing our API for full Solana withdrawal and deposit support. To get started, check out the **execution steps** of our API. Then when you're ready to swap, head over to the **Get Quote** API endpoint.

Please note that instead of the usual calldata returned with EVM transactions, there's different calldata that needs to be handled accordingly.

Example: Deposit to Solana from Base

Request Response

```
curl -X POST "https://api.relay.link/quote/v2" \
  -H "Content-Type: application/json" \
  -d '{
    "user": "0x03508bb71268bba25ecacc8f620e01866650532c",
    "originChainId": 8453,
    "originCurrency": "0x833589fcd6edb6e08f4c7c32d4f71b54bda02913",
    "destinationChainId": 792703809,
    "destinationCurrency": "EPjFWdd5AufqSSqeM2qN1xzybapC8G4wEGGkZwyTDt1v",
    "recipient": "GTtzwxqy67xx9DVESJjx28TgXqpc8xTqtiytgNMaQBTE",
    "tradeType": "EXACT_INPUT",
    "amount": "10000000"
  }'
```

SDK

To use the SDK with Solana, install and configure the . The adapter handles transaction signing and broadcasting.

```
npm install @relayprotocol/relay-svm-wallet-adapter
```

For implementation details and code samples, see the .

Was this page helpful? Yes No