Token API Quickstart

A new developer's guide to using the Token API and getting token information. Query Token data using alchemy-web3 (recommended) or fetch.

How to query the Token API

Fetch

You can interact with Alchemy's Token API using fetch requests. No additional dependencies required with Node.js 18+.

Usage

alchemyplatform/**token-api-javascript-scripts**

A collection of Javascript scripts running with Alchemy Web3.js, Fetch, or Axios Topics Resources

1 Contributor
0 Issues
4 Stars
10 Forks

token-api-javascript-scripts/alchemy-web3-script.js at main · alchemyplatform/token-api-javascript-scripts ↗

shell

```shell
$ touch token-api-script.js
```

And then paste the following code snippet into the file:

token-api-script.js

```javascript
// Replace with your Alchemy API Key
const apiKey = "demo";
const baseURL = `https://eth-mainnet.g.alchemy.com/v2/${apiKey}`;

async function getTokenData() {
  try {
    // The wallet address / token we want to query for:
    const ownerAddr = "0x3f5ce5fbfe3e9af3971dd833d26ba9b5c936f0be";
    const tokenAddr = "0x607f4c5bb672230e8672085532f7e901544a7375";

    // Get token balances
    const balanceResponse = await fetch(baseURL, {
      method: 'POST',
      headers: {
        'Content-Type': 'application/json',
      },
      body: JSON.stringify({
        jsonrpc: "2.0",
        method: "alchemy_getTokenBalances",
        params: [ownerAddr, [tokenAddr]],
        id: 1
      })
    });

```

```
      headers: {
        'Content-Type': 'application/json',
      },
      body: JSON.stringify({
        jsonrpc: "2.0",
        method: "alchemy_getTokenMetadata",
        params: [tokenAddr],
        id: 2
      })
    });

    const metadataData = await metadataResponse.json();

    console.log("Token Balances:");
    console.log(balanceData.result);
    console.log("Token Metadata:");
    console.log(metadataData.result);

  } catch (error) {
    console.error('Request failed:', error.message);
  }
}

getTokenData();
```

From your command line, you can execute the script with:

shell

```
$ node token-api-script.js
```

You should see output like this:

shell

```
>       {
>         contractAddress: '0x607f4c5bb672230e8672085532f7e901544a7375',
>         tokenBalance: '0x0000000000000000000000000000000000000000000000000
>         error: null
>       }
>     ]
>   }
$   Token Metadata:
>   {
>     decimals: 9,
>     logo: 'https://static.alchemyapi.com/images/assets/1637.png',
>     name: 'iExec RLC',
>     symbol: 'RLC'
>   }
```

Usage

alchemyplatform/**token-api-javascript-scripts**

A collection of Javascript scripts running with Alchemy Web3.js, Fetch, or Axios Topics Resources

1 Contributor | 0 Issues | 4 Stars | 10 Forks

token-api-javascript-scripts/fetch-script.js at main · alchemyplatform/token-api-javascript-scripts ↗

shell

```shell
$ touch fetch-script.js
```

and then paste the following code snippet into the file to explore the `getNFTs` method:=

fetch-script.js

```fetch-script.js
// alchemy-token-api/fetch-script.js


// Replace with your Alchemy API key:
const apiKey = "demo";
const fetchURL = `https://eth-mainnet.g.alchemy.com/v2/${apiKey}`;

// Replace with the wallet address you want to query:
const ownerAddr = "0x3f5ce5fbfe3e9af3971dd833d26ba9b5c936f0be";
// Replace with the token contract address you want to query:
const tokenAddr = "0x607f4c5bb672230e8672085532f7e901544a7375";

var raw = JSON.stringify({
  "jsonrpc": "2.0",
  "method": "alchemy_getTokenBalances",
  "headers": {
    "Content-Type": "application/json"
  },
  "params": [
    `${ownerAddr}`,
    [
      `${tokenAddr}`,
    ]
  ],
```

```
  body: raw,
  redirect: 'follow'
};

// Make the request and print the formatted response:
fetch(fetchURL, requestOptions)
  .then(response => response.json())
  .then(response => JSON.stringify(response, null, 2))
  .then(result => console.log(result))
  .catch(error => console.log('error', error));
```

From your command line, you can execute the script with:

shell

```
$ node fetch-script.js
```

Your output should look like the following:

json

```
{
  "jsonrpc": "2.0",
  "id": 42,
  "result": {
    "address": "0x3f5ce5fbfe3e9af3971dd833d26ba9b5c936f0be",
    "tokenBalances": [
      {
        "contractAddress": "0x607f4c5bb672230e8672085532f7e901544a7375",
        "tokenBalance": "0x0000000000000000000000000000000000000000000000
        "error": null
      }
    ]
  }
```

Was this page helpful? Yes No

Previous

alchemy_getTokenAllowance
Returns the token allowance by spender for a given owner.

Next