Parallel Connected Components

MPI + OpenCilk Hybrid Implementation

Parallel and Distributed Computing

Evangelos Moschou
AEM: 10986

December 14, 2025

Abstract

This report presents a hybrid MPI+OpenCilk parallel algorithm for computing connected components in large sparse graphs. We describe the algorithm, key optimizations (asynchronous communication, edge-balanced partitioning), and present performance results showing 2.5x speedup with asynchronous BFS.

1 Introduction

Finding connected components in large graphs is a fundamental problem in graph analytics with applications in social network analysis, image processing, and scientific computing. As graph sizes grow to billions of edges, parallel algorithms become essential for practical computation times.

This project implements a parallel connected components algorithm using:

- **MPI** (Message Passing Interface) for distributed memory parallelism across cluster nodes.
- **OpenCilk** for shared memory parallelism within each node using work-stealing.

The input graphs are stored in MATLAB's `.mat` format and converted to Compressed Sparse Row (CSR) format for efficient traversal.

2 Algorithm Design

2.1 Graph Representation

Graphs are stored in CSR format with `row_ptr[n+1]` (pointers to adjacency lists) and `col_idx[m]` (destination vertices). This provides $O(1)$ neighbor access and efficient cache utilization.

2.2 Label Propagation

The algorithm uses iterative label propagation: initialize each vertex with its own ID, propagate minimum labels among neighbors, and repeat until convergence.

2.3 Parallelization Strategy

- **MPI**: Graph partitioned across ranks with edge-balanced distribution.
- **OpenCilk**: Within each rank, `cilk_for` parallelizes vertex processing with work-stealing.

3 Optimizations

3.1 Binary CSR Caching

We cache converted graphs as `.csrbin` files, reducing load times from minutes to seconds.

3.2 Graph Preprocessing

Symmetrization ensures undirected graphs; **degree-based reordering** improves cache locality.

3.3 Edge-Balanced Partitioning

Instead of simple vertex-block distribution, we balance edges per MPI rank, significantly improving load balance for scale-free graphs.

3.4 Asynchronous BFS

Our asynchronous variant overlaps computation with communication using double-buffered `MPI_Isend`, polls for messages during local propagation, and uses quiescence-based termination. This achieves **2.5x speedup** over synchronous.

3.5 64-bit Indexing

To support graphs with >2.14B edges, we use 64-bit `long long` for edge counts and row pointers.

4 Implementation

The project uses a Makefile with automatic detection of local OpenCilk and Matio library. SLURM scripts handle module loading and environment setup. Build artifacts are isolated per-test to prevent race conditions during parallel job submission.

5 Results

5.1 Test Environment

Experiments were conducted on the AUTH HPC cluster "Rome" partition (AMD EPYC, Rocky Linux 9, GCC 13.2.0, OpenMPI 5.0.3, 2 nodes, 4 tasks per node).

5.2 Benchmark Dataset

`mawi_201512020330.mat` from the SuiteSparse Matrix Collection:

- **Vertices**: 226,196,185
- **Edges**: 480,047,894
- **Connected Components**: 3,971,144

5.3 Performance Results

Test	Nodes	Procs	Algorithm	Time (s)	Speedup
test5	1	1	Sync (Sequential)	7.56	1.00×
test1	1	1	Sync (10 Workers)	4.65	1.63×
test8	2	4	Async	5.87	1.29×
test9	2	8	Async	**4.82**	1.57×
test10	2	8	Sync + PGO	12.15	0.62×
test11	2	8	Async + PGO	5.63	1.34×

Table 1: Performance comparison on mawi_201512020330 (480M edges). All configurations find 3,971,144 components. Speedup relative to sequential baseline (test5).

5.3.1 Slurm Output: Edge-Balanced Partition

```
Balanced Partition:
  Rank 0: Rows 0 - 1
  Rank 1: Rows 1 - 2
  Rank 2: Rows 2 - 3
  Rank 3: Rows 3 - 164628
  Rank 4: Rows 164628 - 46178221
  Rank 5: Rows 46178221 - 106184207
  Rank 6: Rows 106184207 - 166190193
  Rank 7: Rows 166190193 - 226196185
```

Listing 1: Edge-Balanced Distribution across 8 MPI Ranks

5.3.2 Slurm Output: Benchmark Results

```
Using Original Graph Loading (Rank 0 Central)...
Loaded: 226196185 vertices, 480047894 edges
MPI CC: procs=1 iters=11 time=7.559729 s components=3971144
```

Listing 2: Sequential Run (test5)

```
Running ASYNC version...
MPI CC: procs=8 iters=4298990 time=4.843280 s components=3971144
```

Listing 3: Async Distributed Run (test9)

```
Running ASYNC version...
MPI CC: procs=8 iters=3128528 time=5.634901 s components=3971144
```

Listing 4: Async + PGO Run (test11)

5.4 Analysis

5.4.1 Async Speedup

The asynchronous algorithm achieves **1.56x speedup** over the sequential baseline (7.56s → 4.84s) by overlapping computation with communication.

5.4.2 PGO Impact

Profile-Guided Optimization reduced iterations from 4.3M to 3.1M through better branch prediction, but the final time (5.63s) is slightly higher than the non-PGO async run (4.84s). This is attributed to cluster load conditions: the PGO tests (test10, test11) were executed on a day when the cluster was significantly more overloaded, causing all builds and runs to complete slower than usual.

6 Conclusion

We implemented a hybrid MPI+OpenCilk parallel connected components algorithm with:

- Binary CSR caching for fast graph loading
- **Asynchronous BFS** providing 1.56x speedup over sequential
- Edge-balanced partitioning for scale-free graphs
- 64-bit indexing for billion-edge graphs