

# THE RULE OF THREE LINKED LISTS (CONT.)

---

Problem Solving with Computers-II

C++

```
#include <iostream>
using namespace std;

int main(){
    cout<<"Hola Facebook\n";
    return 0;
}
```



# RULE OF THREE

If a class defines one (or more) of the following it should probably explicitly define all three:

1. Destructor
2. Copy constructor
3. Copy assignment

The questions we ask are:

1. What is the behavior of these defaults?
2. What is the desired behavior ?
3. How should we over-ride these methods?

```
void test_append_0(){  
    LinkedList ll;  
    ll.append(10);  
    ll.print();  
}
```

**Assume:**

- \* **Default destructor**
- \* **Default copy constructor**
- \* **Default copy assignment**

What is the result of running the above code?

- A. Compiler error
- B. Memory leak
- C. Segmentation fault
- D. None of the above

# Behavior of default copy constructor

```
void test_copy_constructor() {  
    LinkedList l1;  
    l1.append(1);  
    l1.append(2);  
    LinkedList l2{l1};  
    // calls the copy c'tor  
    l1.print();  
    l2.print();  
}
```

**Assume:**

**destructor: overloaded**

**copy constructor: default**

What is the output?

- A. Compiler error
- B. Memory leak
- C. Segmentation fault
- D. All of the above
- E. None of the above

# Behavior of default copy assignment

l1 : 1 -> 2 -> 5 -> null

```
void default_assignment_1(LinkedList& l1){  
    LinkedList l2;  
    l2 = l1;  
}
```

\* What is the behavior of the default assignment operator?

**Assume:**

- \* **Overloaded** destructor
- \* **Default copy constructor**
- \* **Default copy assignment**

# Behavior of default copy assignment

```
void test_default_assignment_2() {  
    LinkedList l1, l2;  
    l1.append(1);  
    l1.append(2)  
    l2 = l1;  
    l2.print()  
}
```

What is the result of running the above code?

- A. Prints 1 , 2
- B. Segmentation fault
- C. Memory leak
- D. A & B
- E. A, B and C

**Assume:**

- \* **Overloaded** destructor
- \* **Default copy constructor**
- \* **Default copy assignment**

# Behavior of default copy assignment

```
void test_default_assignment_3(){  
    LinkedList l1;  
    l1.append(1);  
    l1.append(2)  
    LinkedList l2{l1};  
    l2.append(10);  
    l2.append(20);  
    l2 = l1;  
    l2.print()  
}
```

What is the result of running the above code?

- A. Prints 1 , 2
- B. Segmentation fault
- C. Memory leak
- D. A &B
- E. A, B and C

**Assume:**

- \* **Overloaded** destructor
- \* **Overloaded** copy constructor
- \* **Default** copy assignment

# Overloading Operators

Overload relational operators for LinkedLists

`==`

`!=`

and possibly others

```
void test_equal(const LinkedList & l1, const LinkedList &l2){  
    if (l1 == l2)  
        cout<<"Lists are equal"<<endl;  
    else  
        cout<<"Lists are not equal"<<endl;  
}
```



# Overloading Arithmetic Operators

Define your own addition operator for linked lists:

```
LinkedList l1, l2;
```

```
//append nodes to l1 and l2;
```

```
LinkedList l3 = l1 + l2 ;
```

# Overloading input/output stream

Wouldn't it be convenient if we could do this:

```
LinkedList list;  
cout<<list; //prints all the elements of list
```

# Next time

- Binary Search Trees