

RESTful standard used:

- Collections use plural nouns such as /api/students and /api/teachers.
- Single resources append an ID parameter in braces, such as /api/students/{studentId}.
- Real requests replace the parameter with a numeric ID, such as /api/students/1.
- GET is used for read-only lookup.
- Protected endpoints keep role middleware and branch access validation.

Added URIs:

GET /api/branches/{branchId} -> example /api/branches/1 -> get one branch by ID -> public

GET /api/students/{studentId} -> example /api/students/1 -> get one student by ID -> director

GET /api/teachers/{teacherId} -> example /api/teachers/1 -> get one teacher by ID -> director

GET /api/class-plans/{classPlanId} -> example /api/class-plans/1 -> get one class plan by ID -> teacher/dir

GET /api/attendance-records/{attendanceRecordId} -> example /api/attendance-records/1 -> get one atten

GET /api/branch-finance-reports/{financeReportId} -> example /api/branch-finance-reports/1 -> get one fin

GET /api/professional-events/{eventId} -> example /api/professional-events/1 -> get one professional even

Implementation summary:

1. The route file 06Code/Controller/routes/api.php maps each URI to a show method.
2. Each controller reads the ID from Slim args, for example args[studentId].
3. The controller searches the related model by ID.
4. If no record exists, the API returns HTTP 404.
5. If the user cannot access the branch or role, the API returns HTTP 403.
6. Successful responses return the selected record inside a JSON data object.

Example request:

GET /api/students/1

Authorization: Bearer <director-token>

Example JSON response:

```
{
  "data": {
    "id": 1,
    "full_name": "Example Student",
    "branch_id": 1
  }
}
```