

1. Description

1.1. Project

Project Name	EVO_Main_STM32
Board Name	custom
Generated with:	STM32CubeMX 6.9.1
Date	10/24/2023


1.2. MCU

MCU Series	STM32F1
MCU Line	STM32F103
MCU name	STM32F103C8Tx
MCU Package	LQFP48
MCU Pin number	48

1.3. Core(s) information

Core(s)	Arm Cortex-M3

2. Pinout Configuration




3. Pins Configuration

Pin Number	Pin Name	Pin Type	Alternate	Label
LQFP48	(function after		Function(s)	
	reset)		· · ·	
1	VBAT	Power		
2	PC13-TAMPER-RTC *	I/O	GPIO_Output	TOP_HEATER_EN
3	PC14-OSC32_IN *	I/O	GPIO_Output	nCHARGE_SHUNT
4	PC15-OSC32_OUT *	I/O	GPIO_Output	REMOTE_LAMP_EN
5	PD0-OSC_IN	I/O	RCC_OSC_IN	
6	PD1-OSC_OUT	I/O	RCC_OSC_OUT	
7	NRST	Reset		
8	VSSA	Power		
9	VDDA	Power		
10	PA0-WKUP	I/O	ADC1_IN0	REMOTE_LAMP_CURREN T_FB
11	PA1	I/O	ADC1_IN1	LAMP_CURRENT_FB
12	PA2	I/O	ADC1_IN2	TOP_BATTERY_TEMP_FB
13	PA3	I/O	ADC1_IN3	BOTTOM_BATTERY_TEMP _FB
14	PA4	I/O	SPI1_NSS	RF_CS
15	PA5	I/O	SPI1_SCK	RF_SCK
16	PA6	I/O	SPI1_MISO	RF_MISO
17	PA7	I/O	SPI1_MOSI	RF_MOSI
18	PB0	I/O	ADC1_IN8	BATTERY_VOLTAGE_FB
19	PB1 *	I/O	GPIO_Output	nRF_RST
21	PB10 *	I/O	GPIO_Output	BOTTOM_HEATER_EN
23	VSS	Power		
24	VDD	Power		
27	PB14 *	I/O	GPIO_Output	BATTERY_PSU_EN
28	PB15 *	I/O	GPIO_Output	nUSB_EN
29	PA8	I/O	TIM1_CH1	LED_B
30	PA9	I/O	TIM1_CH2	LED_G
31	PA10	I/O	TIM1_CH3	LED_R
32	PA11	I/O	USB_DM	
33	PA12	I/O	USB_DP	
34	PA13	I/O	SYS_JTMS-SWDIO	
35	VSS	Power		
36	VDD	Power		
37	PA14	I/O	SYS_JTCK-SWCLK	
38	PA15	I/O	TIM2_CH1	ZERO_CROSS

Pin Number LQFP48	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
39	PB3	I/O	GPIO_EXTI3	RF_INT
40	PB4	I/O	TIM3_CH1	IR_INPUT
41	PB5	I/O	GPIO_EXTI5	TEST_BUTTON
42	PB6	I/O	TIM4_CH1	CHARGE_PWM
43	PB7	I/O	TIM4_CH2	LAMP_PWM
44	воото	Boot		
47	VSS	Power		
48	VDD	Power		

^{*} The pin is affected with an I/O function

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value
Project Name	EVO_Main_STM32
Project Folder	C:\Nan work place\Projects\EVO\Firmware\EVO_Main_VerB_STM32
Toolchain / IDE	MDK-ARM V5
Firmware Package Name and Version	STM32Cube FW_F1 V1.8.5
Application Structure	Advanced
Generate Under Root	No
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	Yes
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power	No
consumption)	
Enable Full Assert	No

5.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_ADC1_Init	ADC1
4	MX_SPI1_Init	SPI1
5	MX_TIM1_Init	TIM1
6	MX_TIM2_Init	TIM2
7	MX_TIM3_Init	TIM3
8	MX_TIM4_Init	TIM4
9	MX_USB_DEVICE_Init	USB_DEVICE

EVO_Main_STM32 Project
Configuration Report

1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32F1
Line	STM32F103
мси	STM32F103C8Tx
Datasheet	DS5319_Rev17

1.2. Parameter Selection

Temperature	25
Vdd	3.3

1.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


1.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.3	3.3
Voltage Source	Battery	Battery
Range	No Scale	No Scale
Fetch Type	FLASH	n/a
CPU Frequency	72 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator LP
Clock Source Frequency	8 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	27 mA	14 μΑ
Duration	0.1 ms	0.9 ms
DMIPS	90.0	0.0
Ta Max	100.1	105
Category	In DS Table	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	2.71 mA
Battery Life	1 month, 21 days,	Average DMIPS	61.0 DMIPS
	17 hours		

1.6. Chart



2. Peripherals and Middlewares Configuration

2.1. ADC1 mode: IN0 mode: IN1 mode: IN2 mode: IN3 mode: IN8

2.1.1. Parameter Settings:

ADCs_Common_Settings:

Mode Independent mode

ADC Settings:

Data Alignment Right alignment Enabled Scan Conversion Mode Disabled Continuous Conversion Mode Discontinuous Conversion Mode Enabled *

Number Of Discontinuous Conversions

ADC_Regular_ConversionMode:

Enable Regular Conversions Fnable **Number Of Conversion** 5 *

External Trigger Conversion Source Regular Conversion launched by software

Rank

Channel 0 Channel

Sampling Time 239.5 Cycles *

Rank 2 *

Channel Channel 1 * Sampling Time

Rank 3 *

Channel Channel 2 * Sampling Time 239.5 Cycles *

Rank 4 *

Channel Channel 3 * Sampling Time 239.5 Cycles *

Rank 5 *

Channel Channel 8 * Sampling Time 239.5 Cycles *

ADC_Injected_ConversionMode:

239.5 Cycles *

Enable Injected Conversions Disable

WatchDog:

Enable Analog WatchDog Mode false

2.2. RCC

High Speed Clock (HSE): Crystal/Ceramic Resonator

2.2.1. Parameter Settings:

System Parameters:

VDD voltage (V) 3.3
Prefetch Buffer Enabled

Flash Latency(WS) 2 WS (3 CPU cycle)

RCC Parameters:

HSI Calibration Value 16
HSE Startup Timout Value (ms) 100
LSE Startup Timout Value (ms) 5000

2.3. SPI1

Mode: Full-Duplex Master

Hardware NSS Signal: Hardware NSS Output Signal

2.3.1. Parameter Settings:

Basic Parameters:

Frame Format Motorola

Data Size 8 Bits

First Bit MSB First

Clock Parameters:

Prescaler (for Baud Rate) 8 *

Baud Rate 9.0 MBits/s *

Clock Polarity (CPOL) Low
Clock Phase (CPHA) 1 Edge

Advanced Parameters:

CRC Calculation Disabled

NSS Signal Type Output Hardware

2.4. SYS

Debug: Serial Wire

Timebase Source: SysTick

2.5. TIM1

Channel1: PWM Generation CH1 Channel2: PWM Generation CH2 Channel3: PWM Generation CH3

2.5.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 17999 *

Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 15 *

Internal Clock Division (CKD) No Division

Repetition Counter (RCR - 8 bits value) 0

auto-reload preload Enable *

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)

Disable (Trigger input effect not delayed)

Trigger Event Selection

Reset (UG bit from TIMx_EGR)

Break And Dead Time management - BRK Configuration:

BRK State Disable
BRK Polarity High

Break And Dead Time management - Output Configuration:

Automatic Output State Disable
Off State Selection for Run Mode (OSSR) Disable
Off State Selection for Idle Mode (OSSI) Disable
Lock Configuration Off

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable

Fast Mode Disable

CH Polarity Low *

CH Idle State Set *

PWM Generation Channel 2:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload

Fast Mode

CH Polarity

CH Idle State

Disable *

Low *

Set *

PWM Generation Channel 3:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload

Fast Mode

CH Polarity

CH Idle State

Disable *

Low *

Set *

2.6. TIM2

Slave Mode: Reset Mode Trigger Source: TI1FP1

Clock Source : Internal Clock

Channel1: Input Capture direct mode Channel2: Input Capture indirect mode

2.6.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 71 *
Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 59999 *

Internal Clock Division (CKD) No Division
auto-reload preload Disable
Slave Mode Controller Reset Mode

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection Reset (UG bit from TIMx_EGR)

Input Capture Channel 1:

Polarity Selection Falling Edge *

IC Selection Direct
Prescaler Division Ratio No division

Input Filter (4 bits value) 0

Input Capture Channel 2:

Polarity Selection Rising Edge

IC Selection Indirect
Prescaler Division Ratio No division

2.7. TIM3

Slave Mode: Reset Mode Trigger Source: TI1FP1 mode: Clock Source

Channel1: Input Capture direct mode Channel2: Input Capture indirect mode

2.7.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value)

Counter Mode

Up

Counter Period (AutoReload Register - 16 bits value)

65535

Internal Clock Division (CKD)

No Division

auto-reload preload

Slave Mode Controller

Reset Mode

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection Reset (UG bit from TIMx_EGR)

Input Capture Channel 1:

Polarity Selection Falling Edge *

IC Selection Direct
Prescaler Division Ratio No division

Input Filter (4 bits value) 0

Input Capture Channel 2:

Polarity Selection Rising Edge
IC Selection Indirect
Prescaler Division Ratio No division

2.8. TIM4

mode: Clock Source

Channel1: PWM Generation CH1 Channel2: PWM Generation CH2

2.8.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 359 *

Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 99 *

Internal Clock Division (CKD) No Division

auto-reload preload Enable *

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection Reset (UG bit from TIMx_EGR)

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable

Fast Mode Disable

CH Polarity High

PWM Generation Channel 2:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable
Fast Mode Disable
CH Polarity High

2.9. USB

mode: Device (FS)

2.9.1. Parameter Settings:

Basic Parameters:

Speed Full Speed 12MBit/s

Power Parameters:

Low PowerDisabledLink Power ManagementDisabledBattery ChargingDisabled

2.10. USB DEVICE

Class For FS IP: Communication Device Class (Virtual Port Com)

2.10.1. Parameter Settings:

Basic Parameters:

USBD_MAX_NUM_INTERFACES (Maximum number of supported interfaces)

USBD_MAX_NUM_CONFIGURATION (Maximum number of supported configuration)

USBD_MAX_STR_DESC_SIZ (Maximum size for the string descriptors)

512

USBD_SELF_POWERED (Enabled self power)

Enabled

USBD_DEBUG_LEVEL (USBD Debug Level) 0: No debug message

Class Parameters:

USB CDC Rx Buffer Size 1024
USB CDC Tx Buffer Size 1024

2.10.2. Device Descriptor:

Device Descriptor:

VID (Vendor IDentifier) 0x483

LANGID_STRING (Language Identifier) English(United States)

MANUFACTURER_STRING (Manufacturer Identifier) STMicroelectronics

Device Descriptor FS:

PID (Product IDentifier) 0x5740

PRODUCT_STRING (Product Identifier) STM32 Virtual ComPort

CONFIGURATION_STRING (Configuration Identifier)

INTERFACE_STRING (Interface Identifier)

CDC Interface

CDC Interface

^{*} User modified value

3. System Configuration

3.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
ADC1	PA0-WKUP	ADC1_IN0	Analog mode	n/a	n/a	REMOTE_LAMP_CURRE NT_FB
	PA1	ADC1_IN1	Analog mode	n/a	n/a	LAMP_CURRENT_FB
	PA2	ADC1_IN2	Analog mode	n/a	n/a	TOP_BATTERY_TEMP_F B
	PA3	ADC1_IN3	Analog mode	n/a	n/a	BOTTOM_BATTERY_TEM P_FB
	PB0	ADC1_IN8	Analog mode	n/a	n/a	BATTERY_VOLTAGE_FB
RCC	PD0- OSC_IN	RCC_OSC_IN	n/a	n/a	n/a	
	PD1- OSC_OUT	RCC_OSC_OUT	n/a	n/a	n/a	
SPI1	PA4	SPI1_NSS	Alternate Function Push Pull	n/a	High *	RF_CS
	PA5	SPI1_SCK	Alternate Function Push Pull	n/a	High *	RF_SCK
	PA6	SPI1_MISO	Input mode	No pull-up and no pull-down	n/a	RF_MISO
	PA7	SPI1_MOSI	Alternate Function Push Pull	n/a	High *	RF_MOSI
SYS	PA13	SYS_JTMS- SWDIO	n/a	n/a	n/a	
	PA14	SYS_JTCK- SWCLK	n/a	n/a	n/a	
TIM1	PA8	TIM1_CH1	Alternate Function Push Pull	n/a	High *	LED_B
	PA9	TIM1_CH2	Alternate Function Push Pull	n/a	High *	LED_G
	PA10	TIM1_CH3	Alternate Function Push Pull	n/a	High *	LED_R
TIM2	PA15	TIM2_CH1	Input mode	No pull-up and no pull-down	n/a	ZERO_CROSS
TIM3	PB4	TIM3_CH1	Input mode	No pull-up and no pull-down	n/a	IR_INPUT
TIM4	PB6	TIM4_CH1	Alternate Function Push Pull	n/a	Medium *	CHARGE_PWM
	PB7	TIM4_CH2	Alternate Function Push Pull	n/a	Medium *	LAMP_PWM
USB	PA11	USB_DM	n/a	n/a	n/a	
	PA12	USB_DP	n/a	n/a	n/a	
GPIO	PC13- TAMPER- RTC	GPIO_Output	Output Push Pull	Pull-down *	Low	TOP_HEATER_EN
	PC14- OSC32_IN	GPIO_Output	Output Push Pull	Pull-down *	Low	nCHARGE_SHUNT
	PC15- OSC32_OU T	GPIO_Output	Output Push Pull	Pull-down *	Low	REMOTE_LAMP_EN

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
	PB1	GPIO_Output	Output Push Pull	Pull-up *	Medium *	nRF_RST
	PB10	GPIO_Output	Output Push Pull	Pull-down *	Low	BOTTOM_HEATER_EN
	PB14	GPIO_Output	Output Push Pull	Pull-down *	Low	BATTERY_PSU_EN
	PB15	GPIO_Output	Output Push Pull	Pull-up *	Low	nUSB_EN
	PB3	GPIO_EXTI3	External Interrupt Mode with Rising edge trigger detection	No pull-up and no pull-down	n/a	RF_INT
	PB5	GPIO_EXTI5	External Interrupt	No pull-up and no pull-down	n/a	TEST_BUTTON
			Mode with Falling			
			edge trigger detection			

3.2. DMA configuration

nothing configured in DMA service

3.3. NVIC configuration

3.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority	
Non maskable interrupt	true	0	0	
Hard fault interrupt	true	0	0	
Memory management fault	true	0	0	
Prefetch fault, memory access fault	true	0	0	
Undefined instruction or illegal state	true	0	0	
System service call via SWI instruction	true	0	0	
Debug monitor	true	0	0	
Pendable request for system service	true	0	0	
System tick timer	true	0	0	
EXTI line3 interrupt	true	1	0	
USB high priority or CAN TX interrupts	true	0	0	
USB low priority or CAN RX0 interrupts	true	0	0	
EXTI line[9:5] interrupts	true	2	0	
TIM2 global interrupt	true	0	0	
TIM3 global interrupt	true	0	0	
SPI1 global interrupt	true	0	0	
PVD interrupt through EXTI line 16		unused		
Flash global interrupt		unused		
RCC global interrupt	unused			
ADC1 and ADC2 global interrupts	unused			
TIM1 break interrupt	unused			
TIM1 update interrupt	unused			
TIM1 trigger and commutation interrupts	unused			
TIM1 capture compare interrupt	unused			
TIM4 global interrupt	unused			

3.3.2. NVIC Code generation

Enabled interrupt Table	Select for init sequence ordering	Generate IRQ handler	Call HAL handler
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Prefetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false


Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
System tick timer	false	true	true
EXTI line3 interrupt	false	true	true
USB high priority or CAN TX interrupts	false	true	true
USB low priority or CAN RX0 interrupts	false	true	true
EXTI line[9:5] interrupts	false	true	true
TIM2 global interrupt	false	true	true
TIM3 global interrupt	false	true	true
SPI1 global interrupt	false	true	true

^{*} User modified value

4. System Views

- 4.1. Category view
- 4.1.1. Current





5. Docs & Resources

Type Link

BSDL files https://www.st.com/resource/en/bsdl_model/stm32f1_bsdl.zip

IBIS models https://www.st.com/resource/en/ibis_model/stm32ibis.zip

System View https://www.st.com/resource/en/svd/stm32f1_svd.zip

Description

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_embedded_software_solutions.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_eval-

tools_portfolio.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_stm8_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_software_development_tools.pdf

Brochures https://www.st.com/resource/en/brochure/breveco0518.pdf

Brochures https://www.st.com/resource/en/brochure/products-and-solutions-for-plcs-

and-smart-i-os.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstmcsuite.pdf

Flyers https://www.st.com/resource/en/flyer/fldpstpfc11120.pdf

Product https://www.st.com/resource/en/certification_document/1239988349.pdf

Certifications

Product https://www.st.com/resource/en/certification_document/stm32_authenticat

Certifications ion_can.pdf

Application Notes https://www.st.com/resource/en/application_note/an1181-electrostatic-

discharge-sensitivity-measurement-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2586-getting-started-

with-stm32f10xxx-hardware-development-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2604-stm32f101xx-

- and-stm32f103xx-rtc-calibration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-microcontroller-system-memory-boot-mode-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2639-soldering-recommendations-and-package-information-for-leadfree-ecopack-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2834-how-to-get-the-best-adc-accuracy-in-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2945-stm8s-and-stm32-mcus-a-consistent-832bit-product-line-for-painless-migration-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3070-managing-the-driver-enable-signal-for-rs485-and-iolink-communications-with-the-stm32s-usart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3095-stevalisv002v1-stevalisv002v2-3-kw-gridconnected-pv-system-based-on-the-stm32f103xx-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3108-stlm75-firmware-library-for-the-stm32f10x-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-waveform-generation-using-the-dac-in-stm32-products-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3128-stm32-embedded-graphic-objectstouchscreen-library-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3154-can-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3364-migration-and-compatibility-guidelines-for-stm32-microcontroller-applications-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an3422-migration-of-microcontroller-applications-from-stm32f1-to-stm32l1-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3427-migrating-a-microcontroller-application-from-stm32f1-to-stm32f2-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3429-stm32-proprietary-code-protection-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3961-stevalime003v1-demonstration-board-based-on-the-sthv748-ultrasound-pulser-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-stm32-crossseries-timer-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4070-250-w-grid-connected-microinverter-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4076-two-or-three-shunt-resistor-based-current-sensing-circuit-design-in-3phase-inverters-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4088-migrating-between-stm32f1-and-stm32f0-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4228-migrating-from-stm32f1-series-to-stm32f3-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4229-how-to-implement-a-vocoder-solution-using-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-using-stm32-device-pwm-shutdown-features-for-motor-control-and-digital-power-conversion-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4649-migrating-from-stm32f1-series-to-stm32l4-series--stm32l4-series-microntrollers-stmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4724-stm32cube-firmware-examples-for-stm32f1-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4904-migration-of-microcontroller-applications-from-stm32f1-series-to-stm32f4-access-lines-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4908-stm32-usart-automatic-baud-rate-detection-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-thermal-management-guidelines-for-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5225-usb-typec-power-delivery-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5543-enhanced-methods-to-handle-spi-communication-on-stm32-devices-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4899-stm32-microcontroller-gpio-hardware-settings-and-lowpower-consumption-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5612-esd-protection-of-stm32-mcus-and-mpus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-stm32-microcontrollers-security-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2548-using-the-stm32f0f1f3cxgxlx-series-dma-controller-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4838-introduction-to-

memory-protection-unit-management-on-stm32-mcus-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4879-introduction-to-

usb-hardware-and-pcb-guidelines-using-stm32-mcus-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an1202_freertos_guide-

for related Tools freertos-guide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1602_semihosting_in for related Tools _truestudio-how-to-do-semihosting-in-truestudio-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an1801_stm32cubeprog for related Tools rammer_in_truestudio-installing-stm32cubeprogrammer-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/atollic_editing_keyboard

for related Tools _shortcuts-atollic-editing-keyboard-shortcuts-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/iar_to_atollic_truestudio

for related Tools __migration_guide-truestudio-for-arm-migration-guide-iar-embedded-

& Software workbench-to-truestudio-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/stm32cubemx_installatio

for related Tools n_in_truestudio-stm32cubemx-installation-in-truestudio-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2557-stm32f10x-

for related Tools inapplication-programming-using-the-usart-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2592-achieving-32bit-

for related Tools timer-resolution-with-software-expansion-for-stm32cube-and-standard-

& Software peripheral-library-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2594-eeprom-for related Tools emulation-in-stm32f10x-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2598-smartcard-

for related Tools interface-with-stm32f10x-and-stm32l1xx-microcontrollers-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2629-stm32f101xx-for related Tools stm32f102xx-and-stm32f103xx-lowpower-modes-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2656-stm32f10xxx-

& Software

Application Notes https://www.st.com/resource/en/application_note/an2668-improving-for related Tools stm32f1-series-stm32f3-series-and-stm32lx-series-adc-resolution-by-

& Software oversampling-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2739-how-to-use-the-

for related Tools highdensity-stm32f103xx-microcontroller-to-play-audio-files-with-an-

& Software external-is-audio-codec-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2784-using-the-for related Tools highdensity-stm32f10xxx-fsmc-peripheral-to-drive-external-memories-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an2790-tft-lcd-

for related Tools interfacing-with-the-highdensity-stm32f10xxx-fsmc-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2820-driving-bipolar-for related Tools stepper-motors-using-a-mediumdensity-stm32f103xx-microcontroller-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2821-clockcalendar-

for related Tools implementation-on-the-stm32f10xxx-microcontroller-rtc-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2824-stm32f10xxx-ic-

for related Tools optimized-examples-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2841-led-dimming-

for related Tools implemented-on-stm32-microcontroller-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2868-stm32f10xxx-

for related Tools internal-rc-oscillator-hsi-calibration-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an2931-implementing-

for related Tools the-adpcm-algorithm-in-highdensity-stm32f103xx-microcontrollers-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2953-how-to-migrate-for related Tools from-the-stm32f10xxx-firmware-library-v203-to-the-stm32f10xxx-standard-

& Software peripheral-library-v300-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3012-getting-started-for related Tools with-uclinux-for-stm32f10x-highdensity-devices-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3078-stm32-for related Tools inapplication-programming-over-the-ic-bus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3109-communication-

for related Tools peripheral-fifo-emulation-with-dma-and-dma-timeout-in-stm32f10x-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3116-stm32s-adc-

for related Tools modes-and-their-applications-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3174-implementing-

for related Tools receivers-for-infrared-remote-control-protocols-using-stm32f10xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3240-ultrasound-hv-

for related Tools pulser-demonstration-board-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application note/an3241-gvga-tftlcd-

for related Tools direct-drive-using-the-stm32f10xx-fsmc-peripheral-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3307-guidelines-for-

for related Tools obtaining-iec-60335-class-b-certification-for-any-stm32-application-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3970-plm-smartplug-

for related Tools v2-getting-started-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an3991-how-to-drive-

for related Tools multiple-stepper-motors-with-the-l6470-motor-driver-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4075-stevalifp016v2-

for related Tools iolink-communication-master-transceiver-demonstration-board-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-

for related Tools with-stemwin-library-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32-

& Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4453-implementing-for related Tools the-adpcm-algorithm-in-stm32l1xx-microcontrollers-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4499-stm32--

for related Tools nrf51822-bluetooth-low-energy-system-solution-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application note/an4578-16channels-led-

for related Tools driver-with-independent-pwm-dimming-control-based-on-led7708-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-

for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4724-stm32cube-

for related Tools firmware-examples-for-stm32f1-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-

for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4903-generating-jerk-

for related Tools limited-move-profiles-with-the-stevalihm042v1-evaluation-board-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5054-secure-for related Tools programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5418-how-to-build-afor related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5426-migrating-

for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4502-stm32-

for related Tools smbuspmbus-expansion-package-for-stm32cube-stmicroelectronics.pdf

& Software

Device Option https://www.st.com/resource/en/device_option_list/opl_stm32f103_64k.zip

Lists

Errata Sheets https://www.st.com/resource/en/errata_sheet/es096-stm32f101x8b-

stm32f102x8b-and-stm32f103x8b-mediumdensity-device-limitations-

stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/cd00161566.pdf

Programming https://www.st.com/resource/en/programming_manual/pm0056-Manuals

stm32f10xxx20xxx21xxxl1xxxx-cortexm3-programming-manual-

stmicroelectronics.pdf

Programming https://www.st.com/resource/en/programming_manual/pm0075-Manuals stm32f10xxx-flash-memory-microcontrollers-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference manual/rm0008-stm32f101xx-

stm32f102xx-stm32f103xx-stm32f105xx-and-stm32f107xx-advanced-Manuals

armbased-32bit-mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn0516-overview-of-the-

& Articles stm32f0xf100xxf103xx-and-stm32f2xxf30xf4xx-mcus-pmsm-singledual-

foc-sdk-v40-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1433-reference-device-& Articles marking-schematics-for-stm32-microcontrollers-and-microprocessors-

stmicroelectronics.pdf

User Manuals https://www.st.com/resource/en/user_manual/um1561-stevalisv003v1-

firmware-user-manual-stmicroelectronics.pdf

User Manuals https://www.st.com/resource/en/user_manual/um1573-st7540-power-line-

modem-firmware-stack-stmicroelectronics.pdf