

EventGenie

Entity Relationship Documentation

Database: PostgreSQL via Neon · ORM: Prisma · Version 1.0

Overview

EventGenie uses a relational PostgreSQL database managed through Prisma ORM. All entities use CUID primary keys. Soft deletion is implemented via an `isArchived` flag on all deletable entities — records are never physically removed from the database.

The database is hosted on Neon (neon.tech) with two databases:

`eventgenie_dev` — Development environment

`eventgenie_prod` — Production environment

CONVENTIONS

Convention	Description
Primary Key	All entities use CUID (<code>@default(cuid())</code>) — collision-resistant, URL-safe, sortable
Soft Delete	<code>isArchived</code> : Boolean — set to true instead of deleting. All queries filter <code>isArchived = false</code>
Audit Fields	<code>createdBy</code> , <code>updatedBy</code> store the User ID of who made the change (on applicable entities)
Timestamps	<code>createdAt</code> : DateTime <code>@default(now())</code> <code>updatedAt</code> : DateTime <code>@updatedAt</code>
Optional Fields	Nullable fields use <code>String?</code> or <code>Decimal?</code> — frontend should handle null values
Enums	All enums are defined at the database level via Prisma enums
Tenant Scoping	All tenant-owned data includes a <code>tenantId</code> foreign key for data isolation

ENUMS

The following enums are defined at the database level:

Enum	Values
SubscriptionTier	SPARK CELEBRATE ELEVATE
SubscriptionStatus	ACTIVE SUSPENDED CANCELLED
PlatformRole	SUPER_ADMIN TENANT_ADMIN EVENT_ADMIN
EventStatus	DRAFT PUBLISHED COMPLETED CANCELLED
InviteStatus	PENDING ACCEPTED DECLINED
DeliveryMethod	EMAIL SMS
MediaType	IMAGE VIDEO
VendorCategory	CATERING DECOR FURNITURE PHOTOGRAPHY ENTERTAINMENT FLORISTRY OTHER
VendorRole	VENDOR_OWNER VENDOR_STAFF

Relationship Map

From	Relationship	To	Notes
Tenant	ONE → MANY	User	A tenant has many platform users
Tenant	ONE → MANY	Event	A tenant owns many events
Tenant	ONE → MANY	VendorSpace	A tenant can own vendor profiles (optional)
User	ONE → MANY	Event	A user creates many events (createdByUserId)
User	ONE → MANY	MemoryItem	A user can upload memory items
User	ONE → MANY	OtpRecord	A user can have multiple OTP records
Event	ONE → MANY	EventDay	An event has one or more days
Event	ONE → MANY	Invite	An event has many invites
Event	ONE → ONE	MemoryHub	Each event has exactly one Memory Hub
Guest	ONE → MANY	Invite	A guest can have invites across events
Guest	ONE → MANY	MemoryItem	A guest can upload memory items
Invite	ONE → MANY	InviteEventDay	An invite references specific event days (junction)
Invite	ONE → MANY	Attendance	An invite records confirmed attendance days
EventDay	ONE → MANY	InviteEventDay	A day can appear on many invites
EventDay	ONE → MANY	Attendance	A day can have many attendance confirmations
MemoryHub	ONE → MANY	MemoryItem	A hub contains many media items
VendorSpace	ONE → MANY	VendorUser	A vendor space has managing users
VendorSpace	ONE → MANY	VendorService	A vendor space offers many services
VendorService	ONE → MANY	Product	A service contains many products

Entity Definitions

Field colours: Red = Primary Key · Orange = Foreign Key · Green = Regular field

CORE PLATFORM ENTITIES

Tenant			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
name	String	No	Organisation name
slug	String (unique)	No	URL-safe unique identifier e.g. "levy-events"
email	String (unique)	No	Primary contact email
subscriptionTier	SubscriptionTier	No	SPARK CELEBRATE ELEVATE — default: SPARK
subscriptionStatus	SubscriptionStatus	No	ACTIVE SUSPENDED CANCELLED — default: ACTIVE
isArchived	Boolean	No	Soft delete flag — default: false
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change

User			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
tenantId	String (FK → Tenant)	Yes	Null for SUPER_ADMIN only
firebaseUid	String (unique)	No	Firebase Authentication UID
email	String (unique)	No	User email address
username	String	No	Display name
role	PlatformRole	No	SUPER_ADMIN TENANT_ADMIN EVENT_ADMIN
isActive	Boolean	No	Account active status — default: true
isArchived	Boolean	No	Soft delete flag — default: false
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change

OtpRecord			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key

userId	String (FK → User)	No	The user this OTP belongs to
otp	String	No	6-digit verification code
expiresAt	DateTime	No	OTP expiry — set to 10 minutes from creation
usedAt	DateTime	Yes	Null until the OTP is consumed. Retained for audit.
createdAt	DateTime	No	Auto-set on creation

EVENT ENTITIES

Event			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
tenantId	String (FK → Tenant)	No	Owning tenant
createdByUserId	String (FK → User)	No	User who created the event
name	String	No	Event name
description	String	Yes	Optional event description
location	String	No	Venue name
address	String	Yes	Full street address
latitude	Decimal(10,7)	Yes	Used for vendor proximity search
longitude	Decimal(10,7)	Yes	Used for vendor proximity search
coverImageUrl	String	Yes	Cloudinary URL for event cover image
status	EventStatus	No	DRAFT PUBLISHED COMPLETED CANCELLED — default: DRAFT
isArchived	Boolean	No	Soft delete flag — default: false
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	User ID of creator — audit field
updatedAt	String	No	User ID of last modifier — audit field

EventDay			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
eventId	String (FK → Event)	No	Parent event
label	String	No	Human-readable label e.g. "Day 1 – Ceremony"
date	DateTime (Date)	No	Calendar date of this day
startTime	DateTime	Yes	Start time for the day
endTime	DateTime	Yes	End time for the day
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedAt	String	No	Audit field

GUEST AND INVITE ENTITIES

Guest			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
firstName	String	No	Guest first name
surname	String	No	Guest surname
email	String	Yes	Required if delivery method is EMAIL
phoneNumber	String	Yes	Required if delivery method is SMS
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change

Invite			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
eventId	String (FK → Event)	No	The event this invite belongs to
guestId	String (FK → Guest)	No	The guest being invited
token	String (unique)	No	Auto-generated unique RSVP token — 32 random bytes hex
status	InviteStatus	No	PENDING ACCEPTED DECLINED — default: PENDING
used	Boolean	No	Whether the RSVP link has been used — default: false
usedAt	DateTime	Yes	Timestamp when the link was first used
expiresAt	DateTime	Yes	Optional expiry for the invite link
editToken	String (unique)	Yes	Allows guest to amend their RSVP without re-auth
editTokenExpiresAt	DateTime	Yes	Expiry for the edit token
deliveryMethod	DeliveryMethod	No	EMAIL SMS
deliveredAt	DateTime	Yes	When the invitation was sent
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedBy	String	No	Audit field

InviteEventDay (Junction)			
Field	Type	Nullable	Notes

id	String (CUID)	No	Primary key
inviteId	String (FK → Invite)	No	The invite
eventDayId	String (FK → EventDay)	No	The day the guest is invited for
createdAt	DateTime	No	Auto-set on creation
	Unique constraint		@@unique([inviteId, eventDayId]) — no duplicate day per invite

Attendance (Junction / Fact)			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
inviteId	String (FK → Invite)	No	The invite that confirmed attendance
eventDayId	String (FK → EventDay)	No	The day being confirmed
confirmedAt	DateTime	No	When the guest confirmed — auto-set
	Unique constraint		@@unique([inviteId, eventDayId]) — one confirmation per day per guest

MEMORY HUB ENTITIES

MemoryHub			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
eventId	String (FK → Event, unique)	No	One hub per event — unique constraint
title	String	Yes	Hub display title
description	String	Yes	Hub description
isPublic	Boolean	No	Whether the hub has a public shareable link — default: false
shareToken	String (unique)	Yes	Auto-generated when isPublic is set to true
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedBy	String	No	Audit field

MemoryItem			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
memoryHubId	String (FK → MemoryHub)	No	Parent memory hub
uploadedByGuestId	String (FK → Guest)	Yes	Set when uploaded by a guest. Null if uploaded by organiser.
uploadedByUserId	String (FK → User)	Yes	Set when uploaded by a user. Null if uploaded by guest.
mediaUrl	String	No	Cloudinary URL of the uploaded media
mediaType	MediaType	No	IMAGE VIDEO
caption	String	Yes	Optional caption
isApproved	Boolean	No	Organiser approval flag — default: false
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedBy	String	No	Audit field

VENDOR ENTITIES

VendorSpace			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
tenantId	String (FK → Tenant)	Yes	Optional link to an owning tenant
name	String	No	Vendor business name
description	String	Yes	About the vendor
email	String	No	Contact email
phoneNumber	String	Yes	Contact phone
website	String	Yes	Website URL
address	String	Yes	Street address
latitude	Decimal(10,7)	No	Required — used for proximity search
longitude	Decimal(10,7)	No	Required — used for proximity search
isVerified	Boolean	No	Platform-verified vendor badge — default: false
isActive	Boolean	No	Whether the vendor is currently active — default: true
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedBy	String	No	Audit field

VendorUser			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
vendorSpaceId	String (FK → VendorSpace)	No	Parent vendor space
firebaseUid	String (unique)	No	Firebase UID of the vendor user
email	String (unique)	No	Vendor user email
name	String	No	Display name
role	VendorRole	No	VENDOR_OWNER VENDOR_STAFF — default: VENDOR_OWNER
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change

VendorService			
Field	Type	Nullable	Notes

id	String (CUID)	No	Primary key
vendorSpaceId	String (FK → VendorSpace)	No	Parent vendor space
name	String	No	Service name e.g. "Buffet Catering"
category	VendorCategory	No	CATERING DECOR FURNITURE PHOTOGRAPHY ENTERTAINMENT FLORISTRY OTHER
description	String	Yes	Service description
operatingDays	String	Yes	e.g. "Monday to Sunday"
operatingHours	String	Yes	e.g. "08:00 – 22:00"
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedBy	String	No	Audit field

Product			
Field	Type	Nullable	Notes
id	String (CUID)	No	Primary key
vendorServiceId	String (FK → VendorService)	No	Parent vendor service
name	String	No	Product name
description	String	Yes	Product description
price	Decimal(10,2)	Yes	Price in specified currency
currency	String	No	Currency code — default: ZAR
imageUrls	String[]	No	Array of Cloudinary image URLs
isAvailable	Boolean	No	Product availability — default: true
isArchived	Boolean	No	Soft delete flag
createdAt	DateTime	No	Auto-set on creation
updatedAt	DateTime	No	Auto-updated on every change
createdBy	String	No	Audit field
updatedBy	String	No	Audit field

PLATFORM CONFIGURATION

SubscriptionTierConfig			
Field	Type	Nullable	Notes
tier	SubscriptionTier (PK)	No	Primary key — SPARK CELEBRATE ELEVATE
maxEvents	Int	Yes	Max active events allowed. Null = unlimited.
maxGuestsPerEvent	Int	Yes	Max guests per event. Null = unlimited.
maxSmsPerMonth	Int	Yes	Max SMS per billing period. Null = unlimited.
emailEnabled	Boolean	No	Whether email invitations are available on this tier
smsEnabled	Boolean	No	Whether SMS invitations are available on this tier
vendorMarketplace	Boolean	No	Whether vendor marketplace is accessible
memoryHubEnabled	Boolean	No	Whether Memory Hub is accessible
dragDropBuilder	Boolean	No	Whether drag-and-drop RSVP builder is accessible

Seeded values:

Tier	Max Events	Max Guests/Event	Max SMS/Month	Email	SMS	Vendors	Memory Hub
SPARK	1	50	None	✓	✗	✗	✗
CELEBRATE	5	300	100	✓	✓	✓	✓
ELEVATE	Unlimited	Unlimited	Unlimited	✓	✓	✓	✓