

Package Detail Page (PDP) — API Handoff

Backend: Eventory_V2_backend | Frontend: Eventory_V2_frontend (feature/item302)

Frontend route: /packages/[packageId] !' http://localhost:3000/packages/[id]

Generated: Wed Aug 19 2026

This documents every backend endpoint the PDP and its component tree (src/features/customer-package-detail/**) actually call, verified directly against the frontend's real API layer (src/lib/customerPackageDetailApi.ts, customerCartApi.ts) — not the mock data file. All four endpoints below were confirmed to exist and return every field the frontend's mapping code (services/getPackageDetail.ts) reads, EXCEPT sibling package variants, which had no proper customer-facing endpoint yet — that gap was closed as part of this handoff (see the note on endpoint 3).

Endpoints covered:

1. GET /api/customer/packages/:packageId — package detail + availability + price preview + reviews
2. GET /api/customer/packages/:packageId/reviews — standalone paginated reviews + rating aggregate
3. GET /api/customer/packages/group/:packageGroupId — sibling variants (NEW — see gap note)
4. POST /api/customer/cart/items — Add to cart / Book & pay

1. GET /api/customer/packages/:packageId

Public — no authentication required. Powers the entire PDP body: header, gallery, variant summary, included items, add-ons, policies, vendor card, and the embedded top-10 reviews.

Source: src/controllers/customerDiscoveryController.js !' getPackageDetail

Path parameter

packageId string, required Mongo ObjectId of the package

Query parameters (all optional — affect availability/pricingPreview only)

date string (YYYY-MM-DD) Checked against the vendor's availability calendar/capacity

guests integer Checked against capacity.minGuests/maxGuests + guest-tier

pricing

time string (HH:MM, 24h) Checked against the package's declared time slots

Response — 200

```
{ "status": "SUCCESS", "package": {...}, "availability": {...}, "pricingPreview": {...},
  "reviews": {...} }
```

package — the full Package document (no field whitelist on the package itself)

FIELD	TYPE	NOTES
_id	string	Mongo ObjectId of this package/variant
vendorId	object	Resolved Vendor (public-safe fields only — see below). Never a raw string.
vendorType	string	Caterer Decorator PAV DJArtist MakeupArtist VenueProvider
variantType	string	e.g. "Standard", "Premium" — the variant label shown on the picker
packageGroupId	string	Links sibling variants — pass to endpoint 3
packageStatus	string	Always "Live" here — endpoint 404s otherwise
bookingSettings.bookingType	string?	"Ready-to-Book" "Enquiry/Quote" — MAY BE ABSENT if the vendor never configured it (use optional chaining)
bookingSettings.paymentType	string?	"Free" "Token" — same absence caveat
bookingSettings.token.tokenType	string?	"Percentage" "Fixed"
bookingSettings.token.value	number?	Percentage (0-100) or fixed ¹ amount
step1_eventAndCrew.packageName	string	Title shown at the top of the PDP
step1_eventAndCrew.eventCategories	string[]	e.g. ["Wedding", "Corporate"]
step1_eventAndCrew.duration	object?	{ minHours, maxHours }
step1_eventAndCrew.crewSize	object?	{ minPeople, maxPeople, roles[] }
step1_eventAndCrew.capacity	object?	{ minGuests, maxGuests }
step1_eventAndCrew.venueNeeds	object?	{ power, ac, stage, lighting, security, customText } — booleans drive Vendor Requirements section
step2_productsAndPricing.setups	array?	Decorator only — each: { _id, name, setupPhoto, price, decoratingWhat, themes[], items[] }
step2_productsAndPricing.packageItems	array?	PAV only — each: { _id, itemType, contentDetails, logisticsAndHandover }
step2_productsAndPricing.addOns	array?	Every vendor type — each: { _id, addOnType, name, category, price, billingUnit, mediaUrls[] }
step3_policiesAndCharges.packagePricing	object	{ price, billingUnit, noOfPeople } — the base price
step3_policiesAndCharges.gstInclusive	boolean	
step3_policiesAndCharges.gstRatePercent	number?	
step3_policiesAndCharges.guestTiers	array?	[{ maxGuests, price }] — used by pricingPreview when ?guests= is passed
step3_policiesAndCharges.cancellationPolicy	object?	{ templateTitle, writtenText, files[] } — a policy "slot", null if unset
step3_policiesAndCharges.lastMinutePolicy	object?	Same shape as cancellationPolicy
step3_policiesAndCharges.generalPolicies	array?	Array of the same policy-slot shape
step4_sampleMedia.media	array?	[{ url, type, fileName }] — powers the hero gallery
createdAt	string (ISO)	

package.vendorId — resolved Vendor object (public-safe whitelist, PUBLIC_VENDOR_FIELDS)

id, businessName, isIndividual, vendorType, eventCategories, city, state, serviceAreas, teamSize, bookingsPerYear, experience, profilePicture, description, businessPhotos, coverImage, isVerified, rating, reviewsCount, createdAt

Never includes: email, phone, KYC/verification-document fields, bank details — those never leave the backend on any customer-facing route.

availability

FIELD	TYPE	NOTES
guests	number?	Echoes the ?guests= query param if sent
withinCapacity	boolean?	false if guests is outside capacity.minGuests/maxGuests
date	string?	Echoes ?date= if sent
calendarStatus	string	"Available" "Blocked" "Booked" "Unknown" (no date given, or no calendar entry for that day)
overall	boolean null	null when no date was given; otherwise the combined availability verdict. BEST-EFFORT, not authoritative — re-checked server-side at checkout.

pricingPreview — an ESTIMATE only, never authoritative (recomputed server-side at checkout)

FIELD	TYPE	NOTES
basePrice	number null	Raw packagePricing.price before any adjustment
billingUnit	string null	
subtotal	number null	After guest-tier/date-based adjustments, before GST
gstInclusive	boolean	
gstRatePercent	number null	
gstAmount	number null	
total	number null	The number to show as "estimated total"
note	string	Always: "Preview estimate only..." — safe to show verbatim or ignore

reviews — embedded top-10 (see endpoint 2 for the full paginated list)

FIELD	TYPE	NOTES
items	array	Up to 10 most recent Published reviews: { _id, rating, comment, customerId: {name,profilePicture}, createdAt }
count	number	Total Published reviews for THIS package
averageRating	number null	
usingVendorFallback	boolean	true = this package has 0 reviews yet, so count/averageRating are the VENDOR's overall numbers instead

Errors

400 { "status": "FAILED", "message": "Invalid packageId" } — malformed ObjectId
404 { "status": "FAILED", "message": "Package not found or not currently available" }

2. GET /api/customer/packages/:packageId/reviews

Public — no authentication required. The "see all reviews" page/section — real pagination, sort, and a full rating distribution + per-category breakdown that the embedded PDP section (endpoint 1) doesn't compute.

Source: src/controllers/customerDiscoveryController.js !' getPackageReviews

Path parameter

packageId string, required

Query parameters (all optional)

minRating integer 1-5
sort "recent" (default) | "highest" | "lowest"
page integer, default 1
limit integer, default 20, max 50

Response — 200

FIELD	TYPE	NOTES
count	number	Items on this page
total	number	Total matching reviews
page / limit / totalPages	number	
items[]._id	string	
items[].rating	number	1-5
items[].comment	string	
items[].customerId	object	{ name, profilePicture } — populated, public fields only
items[].createdAt	string (ISO)	
aggregate.averageRating	number null	Across ALL matching reviews (not just this page)
aggregate.count	number	
aggregate.distribution	object	{ "1":n,"2":n,"3":n,"4":n,"5":n } — star histogram
aggregate.categoryBreakdown	array	[{ category, averageRating, count }] — derived from whatever categoryRatings keys are actually present on matched reviews (no fixed category list exists)

Errors

400 { "status": "FAILED", "message": "Invalid packageId" }

3. GET /api/customer/packages/group/:packageGroupId — NEW, added for this handoff

GAP FOUND & FIXED: the frontend was previously calling GET /api/packages/group/:packageGroupId (the vendor-management router's own internal endpoint) as a stopgap — flagged in the frontend's own code comment. That route has NO packageStatus filter (would leak Draft/Under Review/Deleted variants to a customer) and no vendor field whitelist. This new endpoint is the proper, safe replacement — please switch getPackageGroupVariants() in customerPackageDetailApi.ts to call this path instead.

Public — no authentication required. Powers the Standard/Premium/Deluxe variant picker.

Source: src/controllers/customerDiscoveryController.js !' getPackageGroupVariants

Path parameter

packageGroupId string, required Mongo ObjectId — Package.packageGroupId from endpoint 1's response

Response — 200

```
{ "status": "SUCCESS", "count": 2, "packageGroupId": "...", "packages": [ {...}, {...} ] }
```

Each entry in packages[] has the SAME shape as endpoint 1's package object (vendorId resolved the same way), just a narrower field set: vendorId, vendorType, variantType, packageGroupId, packageStatus, step1_eventAndCrew. {packageName,eventCategories,capacity,duration}, step2_productsAndPricing.setups, step3_policiesAndCharges. {packagePricing,gstInclusive,gstRatePercent}, step4_sampleMedia.media, createdAt. Only Live variants are returned, oldest first.

Errors

```
400 { "status": "FAILED", "message": "Invalid packageGroupId" }
```

```
404 { "status": "FAILED", "message": "No Live variants found for this package group" }
```

A 404 here is a normal case (e.g. this package has no sibling variants, or they were all taken down) — the frontend should fall back to showing just the current package as its own single "variant", which services/getPackageDetail.ts already does.

4. POST /api/customer/cart/items

"Soft auth" — works for a logged-in customer OR an anonymous guest (X-Guest-Cart-Id header). Called by StickyBookingCard's "Add to cart" and "Book & pay" buttons (the latter also redirects to /cart afterward).

Already built and tested (Phase 3) — documented here for completeness since it's part of this page's flow.

Source: `src/controllers/customerCartController.js` !' `addCartItem`

Headers

X-Guest-Cart-Id string, optional Omit once logged in — a valid access token always wins over this

Request body

FIELD	TYPE	NOTES
packageId	string, required	
eventType	string, optional	
guests	integer, optional	Validated against the package's own capacity.minGuests/maxGuests — 400s if outside range
date	string (date), optional	
timeSlot	string, optional	
location	string, optional	
selectedAddOns	array, optional	[[addOnId?, name, price, quantity]]
selectedItems	array, optional	[[groupKey, itemId?, itemName, price, isChargeable]]
specialRequest	string, optional	
quantity	integer, optional	Default 1

Response — 201 (or 200 on a benign re-add)

Full cart payload: { status, cartId, itemId, guestCartId, itemCount, vendorCount, vendors: [{ vendorId, items[], vendorSubtotal }], coupon, bookingNote, subtotal, discount, total, conflicts }. If this was a guest request, guestCartId is returned and should be persisted (localStorage) for subsequent calls.

Errors

400 Validation error (missing packageId, guests outside capacity, ...)

404 { "status": "FAILED", "message": "Package not found or not currently available" }

Summary for the frontend team

- Endpoints 1, 2, and 4 already existed and match your current mapping code field-for-field — no changes needed on your side beyond normal integration testing.
- Endpoint 3 is NEW. Please swap `getPackageGroupVariants()` (`customerPackageDetailApi.ts`) from the vendor-internal `/api/packages/group/:packageGroupId` to `/api/customer/packages/group/:packageGroupId` — same response shape, just Live-filtered and vendor-safe.
- `bookingSettings` can be absent on a package if the vendor never configured it — your existing optional-chaining already handles this correctly, just confirming it's a real, expected case, not a bug.
- All four endpoints were re-verified live against the current dev database as part of producing this document, not just re-read from source.