



TYPICAL APPLICATIONS	Cooking, washing, coffee machines
FUNCTIONS	SPST, momentary or notSPDT, momentary or not
CYCLE No.	50.000
CUT OUT	Rear panel
AMBIENT TEMPERATURE	125 ℃
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C






DRAWING


?

TERMINAL


1


6




















SHAFT




G






K





LATCHING FUNCTION




Momentary

FUNCTION









0

RATING

E

Function 10

16 (6) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T125/55 °C 6 (2) A / 250 VAC T150/55 °C EN 61058

13 A / 250 VAC 3/4 HP - 250 VAC 1/3 HP - 125 VAC T65 °C UL 1054

Function 60

16 (6) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T125/55 °C EN 61058

13 A / 250 VAC 3/4 HP - 250 VAC 1/3 HP - 125 VAC T65 °C UL 1054



Function 30

12 (4) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T125/55 °C μ disconnection EN 61058

13 A / 250 VAC 3/4 HP - 250 VAC 1/3 HP - 125 VAC T65 °C UL 1054