

SFO

10 A / 250 VAC
EN 60320

10 A / 250 VAC
15 A / 125 VAC
UL 498

TYPICAL APPLICATIONS	Computer and peripherals, connector for cold/warm conditions with earthing contact, rewirable
WIRING DIAGRAMAS	Power inlet connector 2-pole + earth
CUT OUT	With electric wire
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C on demand



SFO 430

C13
Class I
T 70 °C



Screw terminals

SFO 440

C13
Class I
T 70 °C



Screw terminals

SFO 550

C15
Class I
T 120 °C



Screw terminals

SCM81




10 A / 250 VAC
CEI 23-50 - II Ed. 2007
+V1:2008 +V2:2011

TYPICAL APPLICATIONS	Bathroom furniture
WIRING DIAGRAMAS	<ul style="list-style-type: none"> Italian 2-pole Italian 2-pole + earth
CUT OUT	27x12 mm
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C on demand



CUT OUT

DRAWING



Z	X	Y
0,75 ... 1,25	12,4	$27,3^{+0,2}_{-0,1}$
1,25 ... 2,0	12,4	$27,5^{+0,2}_{-0,1}$
2,0 ... 3,0	12,4	$27,9^{+0,2}_{-0,2}$
3,0 ... 4,0	12,4	$28,1^{+0,2}_{-0,2}$

