



TYPICAL APPLICATIONS	Cooking, washing, coffee machines
FUNCTIONS	<ul><li>SPST, momentary or not</li><li>SPDT, momentary or not</li></ul>
CYCLE No.	50.000
CUT OUT	Rear panel
AMBIENT TEMPERATURE	125 ℃
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C






**DRAWING** 


?

TERMINAL


1


6

















0




?

#### **SHAFT**




G






K



?

# **LATCHING FUNCTION**




M Momentary


RATING


# ? ?

#### **FUNCTION**

30







?



#### **RATING**

### E

## Function 10

16 (6) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T125/55 °C C (2) A / 250 VAC T150/55 °C EN 61058

13 A / 250 VAC 3/4 HP - 250 VAC 1/3 HP - 125 VAC T65 °C UL 1054

#### Function 60

16 (6) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T125/55 °C EN 61058

13 A / 250 VAC 3/4 HP - 250 VAC 1/3 HP - 125 VAC T65 °C UL 1054



#### Function 30

12 (4) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T125/55 °C μ disconnection EN 61058

13 A / 250 VAC 3/4 HP - 250 VAC 1/3 HP - 125 VAC T65 °C UL 1054