


SERIES


WIRES

TERMINAL







C Series 27 - 28 Signal Click



K Series 28 Wires crimped



R Series 27 - 28 Wires sealed



FUNCTION



Neon or Fluorescent lamp



Neon or Fluorescent lamp with anti-luminescence

3 Series 27 - 28



Incandescent lamp

5 Series 27 - 28



LED DC or AC current 2 ÷ 24 V

6 Series 28 Terminal 1



LED AC current 110 ÷ 250 V

7 Series 28 Terminal C - K - R



LED AC current 110 ÷ 250 V

?

VOLTAGE





2 Function 3 - 5

12 V

3 Function 3 - 5

24 V

4 Function 1 - 2 - 6 - 7

110 V

5 Function 1 - 2 - 6 - 7

125 V

6 Function 1 - 2 - 6 - 7

230 V

7 Function 1 - 2 - 6 - 7

250 V

8 Function 1-2

400 V

VDE or UL certified

?

Available on demand

X

Custom

TEMPERATURE COLOUR

Α T 75 °C

1 Function 1-2-3

T 90 °C

2 Function 1 - 2

T 120 °C

3 Function 1 - 2

T 150 °C

NO LENS 🕸



red light



ILLUMINATED 🖟



н orange





χ ? custom

WIRES

000 Terminal 1 - C

Indicator light without wires

??? Terminal K - R Indicator light with wires

Wires Material:

- PVC (up to T90 °C)
- SILICONE (up to T200 °C)

Wires Lenght: from 60 mm to 600 mm

(special version available up to 1.450 mm)

Wires Ends:

- pre-stripped (from 5.5 to 18 mm)
- stripped (from 5.5 to 18 mm)
- not stripped
- crimp terminals