

# **B4MASK**

TYPICAL APPLICATIONS	Outdoor electrical equipments, pumps, high pressure cleaners
FUNCTIONS	<ul><li>SPST</li><li>DPST, illuminated or not</li><li>DPCO</li></ul>
PROTECTION DEGREE	IP 65
CYCLE No.	50.000
CUT OUT	30x22 mm
AMBIENT TEMPERATURE	120 ℃
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C on demand



**DRAWING** 

B 4 M A S K

?

### **TERMINAL**


O






































0

## 0









smooth and plane surface







--33 Min -<del>-</del>

## **RATING**

40 Min

### C Function 9 16 (6) A / 250 VAC 10 (4) A / 250 VAC - 5E4 T120/55 °C EN 61058

z ---

Z

1,25 ... 2,0

2,0 ... 3,0

FUNCTION

TERMINAL

0,75 ... 1,25 22,0

22,0

22,0

RATING

20 A / 125 VAC 16 A / 250 VAC 1/3 HP - 125 VAC 3/4 HP - 250 VAC T105 °C UL 1054 CSA C22.2

### E

### Function 1

16 (8) A / 250 VAC 12 (10) A / 250 VAC - 5E4 T120 / 55 °C EN 61058

20 A / 125 VAC 20 A / 125 VAC 16 A / 250 VAC 1/3 HP - 125 VAC 3/4 HP - 250 VAC T105 °C UL 1054 CSA C22.2

### Function 2 - 8

16 (8) A / 250 VAC 12 (10) A / 250 VAC - 5E4 T120/55 °C EN 61058

20 A / 125 VAC 20 A / 123 VAC 16 A / 250 VAC 3/4 HP - 125 / 250 VAC T105 °C UL 1054 CSA C22.2

### S

### Function 2 - 8

20 (10) A / 250 VAC 14 (14) A / 250 VAC - 5E4 T120/55 °C EN 61058

25 A / 125 VAC 16 A /250 VAC 3/4 HP - 125 / 250 VAC T105 °C UL 1054 CSA C22.2

## ?

1

black

Х

30,8 ±0,1

ROCKER COLOUR

30,2 ±0,1

30,6 ±0,1

+0,2 0

+0,2 0

+0,2 0

RUBBER COLOUR

1

2

3

white

MARKING COLOUR

MARKING

## RUBBER COLOUR ROCKER COLOUR MARKING COLOUR MARKING

## 0



none











### **BRIGHT** 🗱









0









