


SXD₁


TYPICAL APPLICATIONS	Coffee makers, electric fryers, crèpes machines, ironing steam generators
FUNCTIONS	 SPST, momentary or not SPST, illuminated or not version with led light available
CYCLE No.	50.000
CUT OUT	See drawing
AMBIENT TEMPERATURE	125 ℃
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C on demand





DRAWING







1

2







3

4






Custom rocker shape




0

CUSTOM SHAPE ROCKER COLOUR LENS COLOUR DRAWING TERMINAL FUNCTION RATING

TERMINAL







CUSTOM SHAPE

0 none

X ? custom

0

FUNCTION











OVAL SHAPE







RATING Α

Function 1-5 16 (4) A / 250 VAC 10 (8) A / 250 VAC - 5E4 T125/55 °C EN 61058

Function P

12 (6) A / 250 VAC 8 (4) A / 250 VAC - 5E4 T125/55 °C EN 61058

В

Function 1-5

16 A / 125 VAC 1 HP / 125 VAC T105 °C UL 1054

C

Function 1-5

16 (4) A / 250 VAC T125/55 °C EN 61058

16 A 125 / 250 VAC 1 HP 125 / 250 VAC T105 °C UL 1054

Function P

12 (6) A / 250 VAC T125/55 °C EN 61058

12 A 125 / 250 VAC 1/2 HP 125 / 250 VAC T105 °C UL 1054

Е

Function 1-5

16 A / 250 VAC 1 HP / 250 VAC T105 °C UL 1054

