SCICODE2 | RESEARCH ISSUE CANDIDATE

Fast embedding decisions for general sparse-H decoding

Theory and useful comparisons under a finite quantum anneal

16 October 2026 | Independent problem formulation

Status: research-issue candidate, not a frozen evaluation prompt. The complete mathematical question is stated below; no private proposal, previous conversation or unpublished result is required to understand it.

Research question

Can a computationally inexpensive, theoretically justified criterion guide the construction or selection of compact annealer embeddings for general sparse parity-decoding instances, and identify when its choices improve original-error decoding under a common finite forward anneal?

The desired contribution is an algorithm and an honest account of its useful and inconclusive regimes. A globally optimal embedding, a universal winner, a quantum speedup over classical decoders and a simulation of a large commercial QPU are not required. A well-supported negative result is useful if it identifies a consequential limitation and a checkable regime in which a practical decision is possible.

Mathematical input and decoding target

A decoding instance consists of a sparse binary matrix H with m rows and n columns, a syndrome s in the image of H over GF(2), and finite real additive weights w supplied with an explicit numerical representation. Its target set is

$$S^* = \operatorname*{arg\,min}_{e\in\{0,1\}^n:\, He=s \pmod 2} w \cdot e.$$

All tied minimizers count as success. Zero and signed weights are allowed. The score concerns a minimum-cost feasible correction; it is not recovery of a hidden planted error or maximum-likelihood inference of a logical class. No CSS, planar, graphlike, independent-row, bounded-column-degree or named-code assumption may be silently imposed. Sparsity is the main structural information. Code families may illustrate transfer but must not define the entire claim.

Hardware input is an explicit target graph G, individual field/coupling ranges and any coupling-group constraints. An ideal Zephyr graph generated by the public D-Wave graph library is a credential-free reference; deleted sites/couplers may be supplied explicitly. Illustrative numerical ranges must be identified as modelling assumptions rather than a live device profile. Every reduction auxiliary, chain spin, nonzero interaction and physical coefficient must be included.

Finite-anneal model

For a chosen physical program $E(z) = \sum_q h_q z_q + \sum_{(q,r)} J_{qr} z_q z_r$ on its active physical spins, use

$$K(u) = -(1-u)\sum_q X_q + uE(Z), \qquad u = t/T, \quad 0 \le t \le T, \quad \hbar = 1.$$

Each run starts in $|+\rangle$ on every active physical spin and ends in a computational-basis measurement. All chain and reduction penalties, contact allocations and hardware rescaling are included in E. The driver acts on physical branch spins and auxiliaries. This is an ideal closed-system research model; it is not asserted to describe all commercial-device noise.

The original error is read from the output using a declared deterministic rule fixed before comparing candidates. A root in every original-variable branch is one sufficient convention; another consistently applied rule is allowed if specified and verified. Auxiliary excitations or broken chains do not automatically make the original correction wrong. The primary probability is $\Pr(e_{\text{out}} \in S^*)$, summing every measured state that produces such a correction.

A terminal Gibbs distribution, minimum-energy identity, chain-length statistic, or isolated encoded-state pause comparison does not by itself answer the finite-forward-anneal question. Such results can support a criterion only with their assumptions and transfer limitations made explicit.

Requested research

Develop a reusable H-to-program procedure and a criterion cheap enough to guide its embedding or programming decisions without repeatedly solving decoding or simulating the entire physical Hilbert space during selection. Explain what the criterion predicts, what it certifies and when it returns inconclusive. Representation, auxiliary construction, routing, contact allocation and the analytic method remain open. Establish the reduction/projection fidelity and physical ground-state conditions, including ties, offsets and scales. Classically computing an optimum and encoding that known answer does not by itself meet this construction goal; charge all preprocessing and postprocessing. A fixed target may not fit an input: distinguish a proved obstruction from unsuccessful heuristic search.

The general-H input interface must not depend on a named code. Stronger guarantees may hold in explicitly identified regimes, with inconclusive output outside them; a theorem informative on every sparse matrix is not required.

Assess the resulting decisions against a credible automatic embedding/programming baseline on structurally diverse ordinary sparse matrices, with reserved inputs after method development. Use identical candidate-search budgets when isolating a selection rule. If the representation or programming method changes, separate that effect from a mapping improvement. Record compactness, construction/evaluation cost, coefficient scale, failed searches and the original-error score.

Use tractable full physical quantum models as independent anchors. Choose larger instances only when the claimed theory or approximation can be checked with justified uncertainty; exponential state-vector timeout is not scientific difficulty. A useful answer must establish an explicit theoretical comparison or limitation in the declared forward model and test whether its proposed decision remains informative on ordinary instances. Large exact simulation and universally informative certificates are not required. Quantify the duration and effect-size regime in which a comparison is informative. A formally positive effect only at an arbitrarily small duration, or a truncated-series score without transfer/error control, is partial progress rather than sufficient evidence of a useful finite-anneal decision.

Before numerical comparisons, declare the finite duration menu, per-run physical-qubit cap, total run/anneal allowance, classical construction/evaluation allowance, anchor sizes and reserved-input rule. Hold these fixed across compared strategies, count every repeat or sector run if used, and report any classical preprocessing that computes an answer. These choices are part of the trial input/protocol and must be supplied explicitly before a scored run; they are not inferred from a private history.

How an answer can be checked

An independent reader should be able to reconstruct H,s,w and G; validate reduction fidelity, all branch sets and physical ranges; recompute the scored readout event; inspect the proof assumptions; and reproduce tractable forward probabilities with convergence checks or independent integration. Distinguish a rigorous bound, numerical evidence and an unverified heuristic. An improved bound alone is not an ordering of actual probabilities.

The issue is complete as a mathematical research question. A runnable benchmark trial additionally needs its declared input cohort and numerical resource/protocol manifest. Neither that preparation nor a text-only assessment establishes calibrated model difficulty.

Public starting references

- D-Wave, Minor-Embedding: Best Practices: hardware mapping, chain strength and coefficient-range tradeoffs.
- D-Wave, Annealing Implementation and Controls: physical annealing context; the dimensionless model above is defined independently.
- Choi, Minor-embedding in adiabatic quantum computation: I: parameter setting and ground-state fidelity.
- Cai, Macready and Roy, A practical heuristic for finding graph minors: automatic minor search.
- Fang and Warburton, Minimizing minor embedding energy: embedding parameter tradeoffs; no universal finite-time decoding ordering is assumed from this reference.