

# 基于贝叶斯方法的火焰识别

傅长青 金正中

Fudan University

*13307130300@fudan.edu.cn*

*13300180003@fudan.edu.cn*

December 15, 2017

# Overview

- 1 Fire Generation Model
  - Assumptions
  - A Template for Fire Generation
  - Cellular Automaton Algorithm
- 2 Fire Detection based on Bayes' Formula
  - Detection Scheme
- 3 Markov Model Optimization
  - Assumption
  - Detection Scheme
- 4 Outcome
- 5 Outcome

- 1 Fire Generation Model
- 2 Fire Detection based on Bayes' Formula
- 3 Markov Model Optimization
- 4 Outcome
- 5 Outcome

# Assumptions

## Assumption 1

Fire is evidently brighter than ordinary objects. (not enough)

# Assumptions

## Assumption 1

Fire is evidently brighter than ordinary objects. (not enough)

## Assumption 2

Fire is **chaotic**, randomly spread to its surrounding, i.e. each fire pixel is spread from its position to its neighborhood ball following uniform distribution.

# A Template for Fire Generation




Figure: 火焰生成算法效果

---

## 算法 1 Flame generation Algorithm

---

**procedure** FLAME-GENERATOR( $M_i$ ) ▷ Input  $M_i$ , Output next frame  $M_{i+1}$   
     $M_{i+1} \leftarrow 0$   
    **for**  $i = 1$  **to**  $n$  **do**  
        **for**  $j = 1$  **to**  $m$  **do**  
            Choose  $(\xi_i(i, j), \xi_j(i, j))$  randomly in  $N_b(0, 0)$   
             $M_{i+1}(i, j) \leftarrow M_i(i + \xi_i(i, j), j + \xi_j(i, j))$   
        **end for**  
    **end for**  
    **return**  $M_{i+1}$   
**end procedure**

---

- 1 Fire Generation Model
- 2 Fire Detection based on Bayes' Formula
- 3 Markov Model Optimization
- 4 Outcome
- 5 Outcome



## Detection Scheme

- 1 Fire Case
- 2 Non-fire Case
- 3 Overall Guess

Speculation error:

$$\begin{aligned} & \mathbb{P}(I'_t | I_t = M(x + \Delta x, y + \Delta y)) \\ &= \frac{1}{\sqrt{2\pi}\sigma} \exp\left(-\frac{(I'_t - M(x + \Delta x, y + \Delta y))^2}{2\sigma^2}\right) \end{aligned}$$

## Detection Scheme

- 1 Fire Case
- 2 Non-fire Case
- 3 Overall Guess

$$\begin{aligned} & \mathbb{P}(I'_t | \text{Flame}) \\ = & \sum_{(\Delta x, \Delta y) \in N_b(0,0)} \mathbb{P}(I'_t | I_t = M(x + \Delta x, y + \Delta y)) \\ & \mathbb{P}(I_t = M(x + \Delta x, y + \Delta y) | \text{Flame}) \\ = & \frac{1}{|N_b(0,0)|} \sum_{(\Delta x, \Delta y) \in N_b(0,0)} \frac{1}{\sqrt{2\pi}\sigma} \exp\left(-\frac{(I'_t - M(x + \Delta x, y + \Delta y))^2}{2\sigma^2}\right) \end{aligned}$$

where  $|N_b(0,0)|$  is the number of blocks in a single neighborhood.

## Detection Scheme

- 1 Fire Case
- 2 Non-fire Case
- 3 Overall Guess

$$\begin{aligned} & \mathbb{P}(I'_t | \overline{\text{Flame}}) \\ = & \mathbb{P}(I'_t | I_t = M(x + V_x, y + V_y)) \mathbb{P}(I_t = M(x + V_x, y + V_y) | \overline{\text{Flame}}) \\ = & \frac{1}{\sqrt{2\pi}\sigma} \exp\left(-\frac{(I'_t - M(x + V_x, y + V_y))^2}{2\sigma^2}\right) \end{aligned}$$

## Detection Scheme

- 1 Fire Case
- 2 Non-fire Case
- 3 Overall Guess

By Bayes' Formula,

$$\frac{\mathbb{P}(\text{Flame} | I_t)}{\mathbb{P}(\overline{\text{Flame}} | I_t)} = \frac{\mathbb{P}(I_t | \text{Flame}) \mathbb{P}(\text{Flame})}{\mathbb{P}(I_t | \overline{\text{Flame}}) \mathbb{P}(\overline{\text{Flame}})}$$

$\mathbb{P}(\text{Flame}) := 0.01$  is set manually, according to empirical test.

- 1 Fire Generation Model
- 2 Fire Detection based on Bayes' Formula
- 3 Markov Model Optimization**
- 4 Outcome
- 5 Outcome

# Markov Model Optimization

In our previous discussion, only two adjacent frames are considered. In order to improve robustness of the algorithm, we may consider Markov Model as an optimization.

# Assumptions

Recall:

## Assumption 2

Fire is **chaotic**, randomly spread to its surrounding, i.e. each fire pixel is spread from its position to its neighborhood ball following uniform distribution.

# Assumptions

Recall:

## Assumption 2

Fire is **chaotic**, randomly spread to its surrounding, i.e. each fire pixel is spread from its position to its neighborhood ball following uniform distribution.

## Assumption 2' (Markov Chain Property)

Each frame in a video containing fire **only** depends on its prior frame.



# Detection Scheme

$$\begin{aligned} & \frac{\mathbb{P}(\text{Flame} | I_n, I_{n-1}, \dots, I_1, I_0)}{\mathbb{P}(\overline{\text{Flame}} | I_n, I_{n-1}, \dots, I_1, I_0)} \\ = & \frac{\mathbb{P}(I_n, I_{n-1}, \dots, I_1 | I_0, \text{Flame}) \mathbb{P}(I_0, \text{Flame})}{\mathbb{P}(I_n, I_{n-1}, \dots, I_1 | I_0, \overline{\text{Flame}}) \mathbb{P}(I_0, \overline{\text{Flame}})} \\ = & \frac{\mathbb{P}(I_n | I_{n-1}, \text{Flame}) \mathbb{P}(I_{n-1} | I_{n-2}, \text{Flame}) \dots \mathbb{P}(I_1 | I_0, \text{Flame}) \mathbb{P}(\text{Flame} | I_0)}{\mathbb{P}(I_n | I_{n-1}, \overline{\text{Flame}}) \mathbb{P}(I_{n-1} | I_{n-2}, \overline{\text{Flame}}) \dots \mathbb{P}(I_1 | I_0, \overline{\text{Flame}}) \mathbb{P}(\overline{\text{Flame}} | I_0)} \end{aligned}$$

where  $\mathbb{P}(\text{Flame} | I_0)$  is estimated by brightness of  $I_0$  (recall assumption 1).  
 $n = 10$  is used in actual algorithm.

- 1 Fire Generation Model
- 2 Fire Detection based on Bayes' Formula
- 3 Markov Model Optimization
- 4 Outcome
- 5 Outcome

OpenCV, C++ open library.



# Outcome






Figure:  $\mathbb{P}(\text{Flame})(n = 10)$  vs video output

# Application

Early alarm of fire-fighting equipment in basement, factory, theater, etc.



(Image from <http://www.safor-tec.com>)

# Acknowledgement

Thanks for Mr Yang's advisory,  
Thank Mr.Ye and Shanghai Saifu Fire-fighting equipment Co. Ltd.(上海赛  
复安防科技有限公司) for their support and video source,  
Thanks for diligent work of relevant professors and students in the Science  
Innovation Center.

- 1 Fire Generation Model
- 2 Fire Detection based on Bayes' Formula
- 3 Markov Model Optimization
- 4 Outcome
- 5 Outcome

OpenCV, C++ open library.





# The End