

Lifelong Learning Techniques

for an Origami Robot

by

E. De Vroey

Student number: 4685156

Contents

1	Introduction	1
1.1	Application to soft (origami) robots	1
1.2	Challenges	1
2	Background and definition	3
3	Blackbox Methods	5
3.1	Learning Control Policies	5
3.2	Learning the Dynamic Model	6
3.3	Incremental Learning	7
3.4	Summary	8
4	Learning Architectures	9
4.1	Traditional Adaptive Control Architectures	9
4.2	Dual Architectures	9
4.3	Architectural Expansions	11
4.4	Summary	12
5	Storage and Retrieval	13
5.1	Knowledge bases	13
5.2	Retrieval and Detecting Distributional Shifts.	15
5.3	Maintaining the Knowledge Base	15
6	Discussion and conclusion	17

1

Introduction

1.1. Application to soft (origami) robots

1.2. Challenges

(Kim et al., 2021; Lesort et al., 2020).

How can lifelong learning methods be employed to manage the evolving dynamics due to wear and tear in the control of a soft origami robot over its operational lifespan?

2

Background and definition

(Annaswamy & Fradkov, 2021; Landau et al., 2011; Lesort et al., 2020).

3

Blackbox Methods

The term ‘blackbox’ in the context of lifelong learning techniques describes models that are inherently ‘data-driven’, requiring vast datasets to predict outcomes while often lacking in interpretability. These methods differ from traditional approaches, where clever architectural approaches or intuitive mathematical tricks might be exploited. Instead, so-called blackbox methods trade transparency for performance, as they process and learn from information in hard-to-interpret yet effective ways.

In this chapter, an overview is provided of how blackbox methods can be used as either building blocks for lifelong learning or to solve the lifelong learning challenge as complete solutions.

3.1. Learning Control Policies

A perfect example of a blackbox method is given by Alessi et al. (2023). In their study, they used Proximal Policy Optimization (PPO) (Schulman et al., 2017) to obtain a feedforward neural network (FNN) that can generalize over new dynamics and tasks. The controller is a blackbox: a desired trajectory, several measurements of the robot’s state, and other values of interest, such as the error of robot’s end-effector tip, are used as inputs, resulting in a control action. It essentially acts in a manner akin to a feedback controller using an inverse dynamics model, only in this case it is unknown what is happening *under the hood*.

The previous example is “*perfect*” in the sense that it perfectly embodies the simplistic nature of blackbox methods, however, it is worth noting that other techniques, such as more complicated architectures or combinations of multiple models, can be used in combination with these blackbox methods. Such architectural modifications will be discussed in chapter 4.

Apart from Alessi et al. (2023), several other examples of blackbox policies can be found in the literature.

In Zhou et al. (2022), two policies are learned for the control of a small humanoid robot. Exact details on the inputs and outputs of the controllers are not provided, but both policies are probabilistic in nature.

Thuruthel et al. (2019) use guided policy search (Levine & Koltun, 2013) over trajectory samples containing control actions for given regions in the state-space of a soft robotic manipulator. The resulting control policy is represented as a FNN which takes in current and previous states, as well as a desired target state, and returns the appropriate control action.

For the control of a soft robotic arm, in Nazeer et al. (2023), the policy is represented by a multi-layer perceptron (MLP) which takes in the arm’s current state¹ and outputs a control

¹Rather, the sum of the state and a correction term, resulting from a separate network (section 4.3), but that is not

action. The policy is trained using the Soft Actor-Critic (SAC) (Haarnoja et al., 2018) reinforcement learning algorithm.

In Lu et al. (2020), a more complicated technique is used. A probabilistic ‘skill’ distribution $p_\psi(z \mid s)$ and a neural network-based policy $\pi_\theta(a \mid s, z)$ are independently and simultaneously learned using SAC (refer to section 4.3). Both models are trained on rollouts of state transitions generated by a dynamics model. Once learned, a model-based planning algorithm called Model Path Predictive Integral (MPPI) (Williams et al., 2015) is used to find the optimal skill sequence in the skill distribution p_ψ , resulting in executable actions through the policy π_θ .

3.2. Learning the Dynamic Model

One way of having continually adapting control for soft robots is by implementing a (traditional) control scheme that uses a dynamic model (either forward or inverse) of the robot and then to incrementally update that model. The idea of learning a dynamic model for soft robots has advantages even outside the context of lifelong adaptation: many soft robots have such a large number of degrees of freedom and complex and nonlinear dynamics, that analytically deriving a dynamic model is both cumbersome and often insufficiently accurate (Gillespie et al., 2018; Giorelli et al., 2015; Kim et al., 2021; Thuruthel et al., 2019).

Blackbox methods also allow for learning both forward and inverse dynamic models and can thus be used in several control schemes. When learning a forward model, the robot’s actions and resulting states can be used as the inputs and outputs, respectively, this is so-called *direct modeling* (Nguyen-Tuong & Peters, 2011b). In the case of learning inverse dynamic models, such direct approaches might not always be applicable, due to the multiple solutions that exist for the inverse dynamics of robots with redundant degrees of freedom. Instead, an *indirect-modeling* approach can be taken, where the model is trained to minimize the error of the feedback controller (Nguyen-Tuong & Peters, 2011b).

The form that the dynamic model takes can vary. For example, in Gillespie et al. (2018), a neural network is trained to predict the next state of the robot, given the current state and a control action, the analytical gradients of these outputs w.r.t. the inputs are made available during the process of backpropagation and can be used in matrices A and B to form a more interpretable state-space system. In Thuruthel et al. (2019) on the other hand, a forward model is learned for open-loop control, using the control action, the current state, and the previous state as input, and the next state as output to train a recurrent neural network. This forward model is kept in its more abstract blackbox form as a recurrent neural network (RNN), and is used in combination with trajectory optimization to generate trajectories in open-loop control.

Since the lifelong adapting nature of the techniques is embedded in the dynamic model, the choice of control scheme in which the learned dynamic model is used can vary from implementation to implementation. To illustrate, the aforementioned matrices A and B from Gillespie et al. (2018) are used in a model predictive control setting, while the generated trajectories from Thuruthel et al. (2019) are used as samples to train a blackbox control policy (the dynamic model is in essence an intermediary step to create the blackbox policy mentioned in section 3.1). More examples of several blackbox dynamic models and their control scheme can be found in the literature.

Nazeer et al. (2023) represent a forward dynamic model of the soft robotic arm as an RNN model that uses the two preceding states and three preceding control actions to predict the next state. The model is then used with the previously discussed MLP policy (section 3.1).

Lu et al. (2020) was discussed in section 3.1 where it was briefly mentioned that training rollouts for the policies were generated using a dynamic model. This model is in fact also a data-driven model, being an ensemble of neural networks and predicting the next state s'

relevant for the basic idea of the policy.

based on the current state s and a control action yielded by the policy π_θ .

In and Nguyen-Tuong and Peters (2011a), the inverse dynamic model is represented by a Gaussian process (a type of probabilistic model) and is learned through Local Gaussian Process Regression (Nguyen-Tuong et al., 2008, 2009). The models are employed in a feed-forward control scheme, supplemented by a feedback term that adjusts the control action outputted by the dynamic model.

redundant references?

Romeres et al. (2016) represent an inverse dynamic model of a robotic arm as a Gaussian process, but also experiment with using the arm's rigid body dynamics in several ways to enhance the model's performance. By incorporating the information from the robot's physical parameters into both the mean function and the covariance kernel of the Gaussian process, they develop (a) semi-parametric model(s) that are used in a feedforward manner where a feedback controller adds small corrections to the control actions outputted by the dynamic model.

Add paragraph on Gijssberts and Metta (2011)

Contrary to blackbox policy learning methods, the adaptation to new tasks is not included in the learning process of the dynamic model, but is entirely dependent on the control policy. In case control policies have been defined in advance for several tasks, these task settings might serve as a test to verify that the dynamic model generalizes well over these different settings. In situations where tasks are not known in advance, a control scheme such as an incrementally updated (inverse) dynamics model in some form of a feedback control loop might serve for simple applications (Nguyen-Tuong & Peters, 2011a). For more complex tasks, a more intricate control system might be warranted.

rethink order of paragraphs?

3.3. Incremental Learning

In section 3.1 and 3.2 an overview was provided of how blackbox machine learning techniques can be used to model either control policies or dynamic models (to be used in control policies). The choice of machine learning method can be important when it comes to the desired incremental nature of the learning techniques. To illustrate, consider these two main strategies in continually adaptive control:

1. All training is performed offline (after gathering sufficient data), and the robot is now completely capable of immediately adapting to changing dynamics it will encounter during its operational lifespan.
2. Training is performed incrementally as data comes in, which can potentially be done in real-time.

In both scenarios, the control of the robot would be continually adaptive. However, only strategy 2 aligns with the incremental objectives of the adaptive control challenge. In addition, the complex dynamics and many degrees of freedom of soft robots might make it difficult to accurately represent all possible degradations in dynamics (such as damages) or state-space configurations of the robot, potentially causing an imbalance in the training dataset of strategy 1. Learning incrementally to adapt the control policy or dynamic model is thus far more desirable, since it can cope with unforeseen circumstances.

Not all the previously discussed methods are - or have the possibility to be - implemented in an incremental manner. As an example, the two policies from Zhou et al. (2022) mentioned in section 3.1 are trained sequentially: one online and the other offline. Each of these policies required different training/optimization algorithms for their specific setting, in this case Maximum a Posteriori Policy Optimization (MPO) (Abdolmaleki et al., 2018) for the online interaction setting, and Critic Regularized Regression (CRR) (Wang, Novikov, et al., 2020) for the offline distillation setting (see section 4.2).

To learn the dynamic model from Gijsberts and Metta (2011), the authors implement Ridge Regression (a linear regression method that aims at keeping the parameters as small as possible) incrementally, whereas normally it is used in a batch-learning setting. They achieve this by employing a modified numerical approach based on the QR algorithm (Sayed, 2008), a technique in linear algebra that can process new information incrementally using Givens rotations (a process that is particularly efficient for online learning scenarios) (Björck, 1996). This enables real-time learning as new data comes in without recalculating the full model.

Lu et al. (2020) implement both offline and online training, with the potential for the entire method to be implemented online. In fact, it is well known that SAC - the algorithm used for updating the skill-space distribution and the policy - is very suitable for online updates. When it comes to the dynamic model, they mention that it is incrementally updated through interactions with the environment, but do not provide any details on the algorithm used for training the dynamic model.

In Nguyen-Tuong and Peters (2011a), the authors not only update their model incrementally, but they also manage to do it in real-time. This is achieved by using incremental Gaussian process regression algorithm, which uses only a select number of data points to fit a model. In addition, they introduce an efficient way to incrementally update the dictionary of datapoints in a way that it maintains the most informative points for a given budget. These two techniques are key to reducing the computational demand and allowing for real-time updates.

The semi-parametric models from Romeres et al. (2016) are learned using the Recursive Least-Squares algorithm (Landau et al., 2011), which inherently updates the model incrementally. Much alike Gijsberts and Metta (2011), this method uses a numerical trick from the field of adaptive filtering (Cholesky-based updates) to improve efficiency and enable updates in real-time.

3.4. Summary

In Table 3.1, a clear comparison of blackbox methods in lifelong learning is provided. This summary aims to give a straightforward reference, highlighting the strengths of blackbox methods and their role in lifelong learning.

Reference	Dynamic model	Control policy	Incremental
Gillespie et al. (2018)	SS-matrices	MPC	–
Gijsberts and Metta (2011)	Linear model in random feature space	–	✓
Thuruthel et al. (2019) ²	RNN	Open-loop + trajectory optimization	–
Lu et al. (2020)	NN ensemble	MPPI + NN	✓
Nguyen-Tuong and Peters (2011a)	Gaussian process	Feedforward	✓
Romeres et al. (2016)	Gaussian process	feedforward + feedback	✓
Nazeer et al. (2023)	RNN	MLP	³
Thuruthel et al. (2019) ⁴	–	FNN	–
Alessi et al. (2023)	–	FNN	–
Zhou et al. (2022)	–	Probabilistic model	✓

Table 3.1: An overview blackbox methods and their ability to be implemented incrementally. For dynamic model learning methods, the control policy specifies the control scheme in which the model is used.

²Used for generating training samples

³The incremental nature of the method is achieved by a third network, not by the dynamics model or control policy

⁴After training on generated samples

add Lu2019 to chapter, add the training algorithm to the table (eg. PPO)?

Learning Architectures

[1] Added: entire chapter

Blackbox methods for lifelong learning are promising approaches to achieve continually adaptive control, but are hard-to-interpret. What other techniques can be implemented that are more intuitive in nature?

Well-designed control and learning architectures can either enable or facilitate lifelong learning, whether the control schemes use blackbox models or more traditional methods. For example, some techniques use two or more blackbox models, where the idea is to have each model deal with a separate challenge of the lifelong learning goal. Other architectural methods aim to expand existing control schemes or policies to enable them to continually adapt.

In this chapter, these two main strategies will be further explored in the literature.

4.1. Traditional Adaptive Control Architectures

1-2 paragraphs on traditional adaptive control, Anaswamy and Fradkov (2021) and Landau et al. (2011)

4.2. Dual Architectures

Under ‘dual architectures’ the methods are gathered that have separate modules for solving different aspects of the lifelong learning challenge. The term ‘dual’ is used here in a very broad sense because each module might be a grouping of various techniques with intricate architectures. However, studying the literature, it can be found that most of the methods discussed here can be broken down into two main modules. Generally, these dual architectures often exist either of a policy/control module in combination with some type of knowledge base used for storing previous experiences and informing the policy (refer to chapter 5 for details on how knowledge bases can differ in implementation), or two (or more) control policies that are each in turn capable of handling low uncertainty and high uncertainty situations.

To illustrate how these modules can be a very broad concept, consider a knowledge base: A knowledge base must first and foremost store knowledge, but additionally also maintain and update this library. Furthermore, the knowledge base should be capable of categorizing new observations in relation to its library. All these capabilities are seldom performed by a single module, but the techniques used vary wildly between different implementations. It is therefore not very interesting to differentiate between each different implementation in this chapter, but rather use the overarching term ‘knowledge base’ and discuss the more intricate details in chapter 5.

Having established the broad framework and significance of dual architectures, examples from literature that illustrate how these modular approaches have been effectively implemented can be discussed.

In Wang, Chen, and Dong (2020), a knowledge base stores potentially infinite sets of parametrized environments along with their respective control strategies. This repository is

used to guide the current control policy: When a new environment is encountered, the environment models in the knowledge base are evaluated on how well they fit the observations. The control policy is then initialized using the policy parameters belonging to the most similar environment found in this knowledge base, and the policy continues to learn online. In addition, environment models can be added to the library when no suitable match to the observations can be found.

Schwarz et al. (2018) utilize an architecture consisting of two modules, which they name the knowledge base and the active column. During two alternating phases, progression and compression, the active column learns a new task and the learned policy is distilled into the knowledge base, respectively. The knowledge base in this case is a policy π_t^{KB} that serves as a stable reference for the active policy π_{t+1} during progression and remains unchanged at this time. During compression, the newly learned active policy is distilled into π_t^{KB} resulting in an updated policy π_{t+1}^{KB} , and the cycle can repeat.

To combat the issue of forgetting previous policies while training on new tasks, a common approach is to store old experiences and intermittently reuse them during the training process of a new policy. One downside is that this approach can be very memory-inefficient. Shin et al. (2017) therefore propose a method where a deep generative model, a so-called *Generator*, is trained to mimic the training data provided for a task-solving model called the *Solver*. The Solver is then trained on a mix of actual training data and generated samples provided by the Generator. Likewise, when a new Generator is trained to mimic the data of the next task, some samples created by the previous Generator are mixed in. This ensures that knowledge is not forgotten, since each Generator also learns to recreate data generated by its predecessor.

In Sprechmann et al. (2018), an embedding network f_γ and an output network g_θ learn to maximize the likelihood of $p(y | x, \gamma, \theta) = g_\theta(f_\gamma(x))$. The reason for the embedding-output architecture is the expansion of the embedding network with a memory M . This memory contains embeddings from f_γ and corresponding training labels, stored during training. At test time, the embedding network queries the memory for similar embeddings it might contain, and uses these to construct a context (refer to chapter 5 for technical details). Based on this context, the parameters θ of the output network are adapted to obtain the more optimal $\theta^x = \theta + \Delta_M(x, \theta)$, where $\Delta_M(x, \theta)$ is a learned adaptation based on the context provided by x .

An example of another approach taken when using dual architectures is found in Lu et al. (2019). Two modules, a model-free and a model-based module, work in synthesis to simulate the way human beings behave: functioning on *autopilot* most of the time and extensively planning only when we are uncertain. In the model-free module, a policy optimization algorithm (in this case, TD3 (Fujimoto et al., 2018)) uses the policy to propose an initial plan, while the standard deviation across an ensemble of value functions is used to provide a measure of uncertainty. Based on this uncertainty, a planning horizon H is set (short horizons for high uncertainty, and vice versa) and the model-based planner (MPPI) begins updating the initial plan for the given horizon, using the ensemble of value functions to evaluate its plans. During this model-based planning, any rollouts of potential plans are added to a replay buffer $\mathcal{D}_\pi$ which is subsequently used to train the TD3 policy.

In Zhou et al. (2022) the development of a policy exists of two phases: an online interaction phase and an offline distillation phase. Each phase employs a different learning algorithm. During interaction, a policy π_0 is trained online using MPO, which is good at exploring and quickly adapting to new environments, but does not necessarily counter forgetting. This interaction and simultaneous training happens over multiple environments or tasks, and data such as the state transitions, actions, and rewards, is gathered and saved in a replay buffer $\mathcal{D}$. Once finished, the policy π_0 is discarded, and a new policy π_1 is trained offline on buffer $\mathcal{D}$ using CRR, which is much better for generalization. This second policy is then deployed, and the agent is

able to function in all environments encountered during interaction. Intuitively, the data in the buffer reflects the strong adaptability from the online algorithm and is therefore a good guide for the second policy. Additionally, whilst the initial policy π_0 might have forgotten important experiences by the end of its training, the second policy can generalize over the data and thus counter forgetting, while also resulting in a more refined or distilled version of the initial policy.

4.3. Architectural Expansions

This section groups methods where an already functional control scheme or policy is enhanced by adding one or more modules to the scheme, enabling it to learn and/or adapt continually without actually altering the preexisting policy. The idea behind such techniques was already discussed in section 4.1, but here the focus will be on approaches that incorporate more of a learning aspect rather than simply adapting.

An example of such a scheme is given by Nazeer et al. (2023). Their use of a blackbox control policy and a data-driven dynamic model was discussed in section 3.1 and 3.2. In this approach, the current state of the system is used to determine the next control action through the policy. This action then feeds into the dynamic model, predicting the system's next state. However, these models are static and do not adapt during operation. To ensure that the robot can continually adapt, an online regressing network is added in a feedback loop: With the physical robot as reference, the error between the actual state and the predicted state is measured. A buffer stores this error along with the policy's control action that produced these states. The online regressing network periodically trains on this buffer to predict the error that will result from a control input. This predicted error is added to the robot's actual resulting state to provide the policy with a mismatched state that will effectively result in a control action that compensates the error.

add Sun et al. (2011), or not?

A planner of choice is used to control a robot in Chatzilygeroudis et al. (2016). However, once a significant drop in performance is detected (e.g., due to unexpected damage), the method employs various extra modules to counter this performance-drop. Based on the *Intelligent Trial and Error* algorithm (IT&E) (Cully et al., 2015), the authors use MAP-elites (Mouret & Clune, 2015, refer to chapter 5) offline to create a behavior-performance map of atomic behaviors the robot could execute. Contrary to standard IT&E, the *performance* of a behavior is not a qualitative measure, but rather a Gaussian Process that describes the relative outcome of the behavior (termed the *Generic Reward* by the authors) and is aimed to be generic enough so that it is task-independent. A separate *Reward Selection Layer* (RSL) chooses the actual qualitative measure¹ to use as an evaluation of the *Generic Reward*.

As an illustrative example, a *Generic Reward* could be the relative position after executing an atomic behavior. The planner provides a target position to reach, and the RSL chooses the Euclidian distance to this point as a performance measure. Now, the behavior-performance map can be searched for the atomic behavior that will maximize the reward for the outcome of executing this behavior (i.e., the maximum reward of the *Generic Reward* of the behavior). The chosen behavior is executed (in the real world, or using simulation), the behavior and its outcome are used to update the Gaussian Processes, after which this process is repeated until a good compensatory behavior is reached.

In Lu et al. (2020), an agent initially learns a policy and a data-driven dynamic model. As discussed in chapter 3, the authors then expand on this basic setting by the inclusion of a skill-practice distribution $p_\psi(z | s)$. Related to this distribution is the skill-space itself, represented by an abstract higher-dimensional space $z \in [-1, 1]^{\dim(z)}$, and a skill-discriminator $q_v(s' | s, z)$. All trained independently, the skill-practice distribution $p_\psi(z | s)$ learns which skill to use given a certain state, a skill-discriminator q_v learns to model the result of using a skill in a certain

¹The authors do not provide any details on *how* this is achieved

state, and policy $\pi_\theta(a | s, z)$ learns a control action. These models update online by sampling a state uniformly from a replay buffer and sampling a skill from p_ψ . The resulting control action by p_{i_θ} is used in the data-driven dynamic model to obtain the next state, and the transition (s, a, z, s') is added to the buffer. Discriminator q_v updates based on the transition, and an intrinsic reward is calculated, aimed to encourage distinguishable and learnable skills. p_ψ , π_θ , and q_v are finally updated using soft actor-critic.

As discussed section 3.1, the purpose of this method is to allow an MPPI planner to plan in the skill-space, where it will result in a selection of skills the agent is “confident” in, and that will subsequently, through π_θ , result in more predictable and robust actions.

4.4. Summary

add footnote

Summarizing paragraph (+ table?)

Storage and Retrieval

[2] Added: chapter

In section 4.2, many of the methods discussed employ a dual architecture where one of the modules is somehow responsible for retaining previous experiences, often termed the ‘knowledge base’. It was also mentioned that the general idea of using a knowledge base might be shared amongst many lifelong learning techniques, but the implementation varies wildly between them. A knowledge base does not always consist of a single module, but can have a complex architecture in and of itself; something akin to a library where the knowledge is stored, and a librarian who can organize and retrieve the knowledge correctly.

This chapter will aim to provide an overview of the many different shapes and forms such libraries can take, as well as the manner in which librarians might keep them organized.

(Aljundi et al., 2017; Mouret & Clune, 2015; Nguyen-Tuong & Peters, 2011a; Shin et al., 2017; Sprechmann et al., 2018; Wang, Chen, & Dong, 2020; Xie & Finn, 2021).

5.1. Knowledge bases

In this section, a brief overview on the type of knowledge that is stored (e.g., a policy itself, state transitions), and the form in which they are stored (e.g., tuples, abstract representations).

In Nguyen-Tuong and Peters (2011a), the authors use Gaussian process regression to learn an inverse dynamic model (section 3.2). Since they want the model to incrementally learn in realtime, they limit themselves to a fixed budget of data points, represented as vectors $\mathbf{d}_i$, to use for updating the model. These datapoints are stored in a dictionary $\mathcal{D} = \{\mathbf{d}_i\}_{i=1}^m$ which is incrementally updated with the aim to be as informative as possible (section 5.2, 5.3). The contents of a point $\mathbf{d}_i$ are largely dependent on the application. Since Nguyen-Tuong and Peters (2011a) are trying to fit a model for a regression task, they opt for vectors of the form $\mathbf{d} = [\mathbf{x} \ \mathbf{y}]^T$, where $\mathbf{x}$ is simply the input vector and $\mathbf{y}$ are the target values.

In section 4.3 it was mentioned that Chatzilygeroudis et al. (2016) created a map of atomic behaviors an agent might execute. This map is created using Map-elites (Mouret & Clune, 2015), an algorithm that can set up a knowledge base containing many descriptions of solutions and recording their performance according to a specified performance measure. The knowledge base is represented by a discretized space of N user-defined dimensions. These dimensions define a feature-space of interest within a potentially huge or even infinite search space. The paper provides a conceptual example: “MAP-Elites could search in the space of all possible robot designs (a very high dimensional space) to find the fastest robot (a performance criterion) for each combination of height and weight” (Mouret & Clune, 2015). It can be noted that “search” can be interpreted as “store” in the context of the algorithm. The *description* of a solution can be stored in any way that suits the application, the performance metric is stored as a function. Chatzilygeroudis et al. (2016) provide a toy example for an agent that can move

in 2D space using a preset step size; the *description* of the behavior here is thus a single value θ that gives the direction of the step. The evaluation metric in this case is the *Generic Reward* of the behavior (section 4.3), namely two Gaussian processes describing the relative position of the agent after executing the behavior.

To accomplish a good performance over several different classification tasks, Aljundi et al. (2017) train multiple models: one per task. These models, termed ‘Experts’, are stored in the knowledge base, in a manner most fitting for the model type (e.g., a FNN as layer architectures with corresponding weights and biases). The purpose of this knowledge base is to identify a fitting model for a given task and only selectively load this model into memory. Furthermore, when a new task is encountered, the most relevant ‘Expert’ can be loaded in to function as a prior for training a new ‘Expert’.

As described in section 4.2, Sprechmann et al. (2018) introduce memory-based parameter adaptation, where a memory module M provides context to a network g_θ , allowing it to appropriately adapt its parameters for better performance. This memory contains key-value pairs (h_j, v_j) , obtained during training and given by the embedding networks output and the training labels, respectively, i.e., $h_j = f_V(x_j)$ and $v_j = y_j$. This means that the keys are represented by abstract feature vectors, the values are dependent on the task (e.g., one-hot encoded class labels for classification, target values for regression), and memory M is thus a higher-dimensional space spanned by these keys and values.

Schwarz et al. (2018) use a knowledge base in the form of a separate policy π_{KB} . This policy would thus be a neural network and is obtained through knowledge distillation, a process where the outputs of one model are used as labels to train a second model. Active policies can reference the knowledge base to accelerate learning (section 5.2). When it is time to store a newly learned policy π_t , the outputs of the knowledge base’s policy π_{t+1}^{KB} are trained to approximate the outputs of the active policy π , whilst also referencing π_t^{KB} to prevent drastic forgetting of old policies (section 5.3).

The knowledge base in Wang, Chen, and Dong (2020) stores a potentially infinite number of pairwise parameters (θ, ϑ) , where θ are the policy parameters, and ϑ represents the parametrized environment. The purpose of this library is to recognize the most similar environment model compared to the one currently encountered, and to use the corresponding policy parameters as a strong initial policy to finetune (section 5.2). The form of the policy parameters θ again depends on the form of the policy itself. The environments, however, can be parametrized as models by training the reward function $r = g_\vartheta^1(s, a)$ and the state transition function $s' = g_\vartheta^2(s, a)$ and concatenating them to obtain $[r, s'] = g_\vartheta(s, a)$. An environment model g_ϑ can be trained on sequences of state-action pairs to produce corresponding reward-state sequences, and the corresponding parameters ϑ are stored alongside θ in the library.

In Xie and Finn (2021), previous experiences are stored in the form of tuples (s, a, s', r) . These tuples are stored in a replay buffer $\mathcal{D}^i$ for each task $\mathcal{T}^i$. For *all* tasks, each replay buffer is stored; they will serve to provide offline data for pretraining an agent when learning a new task (section 5.2).

Similar to Schwarz et al. (2018), the authors in Shin et al. (2017) do not store knowledge explicitly in a buffer or library, but rather use a separate model to fulfill this function. However, contrary to Schwarz et al. (2018), the model is not a policy but a generative model trained to imitate training data from previous tasks. The generative model used in this case uses a Generative Adversarial Network (GAN) architecture. These models have a dual architecture of their own, where a generating model is trained to optimize producing outputs that can *fool* a discriminator, which is in turn trained to optimize distinguishing real data from generated data. These two networks are trained in parallel and compete against each other (hence, adversarial) to obtain the best result.

citation needed?

5.2. Retrieval and Detecting Distributional Shifts

Storing knowledge is not very useful in and of itself. To properly exploit the advantages of using a knowledge base, knowledge needs to be retrieved. This encompasses recognizing what might be relevant knowledge given new observations, using the knowledge base to detect when an agent is ‘breaking new ground’ in the data landscape, or the manner in which all information in the knowledge base generally can be used to inform an agent.

Dictionary $\mathcal{D}$ in Nguyen-Tuong and Peters (2011a) is simply used to fit the model using Gaussian process regression, and, being dynamically updated (section 5.3), thus informs the model by providing it with the most informative datapoints. However, a technique used to measure the informativeness of a point touches on detecting a distributional shift. The authors use a linear independence test to check whether a potentially new datapoint $\mathbf{d}_i$ can be approximated in the space spanned by all the vectors $\{\mathbf{d}_j\}_{j=1}^{i-1}$. The measure δ is thus the distance from point $\mathbf{d}_i$ to the (hyper-)plane $\{\mathbf{d}_1, \dots, \mathbf{d}_{i-1}\}$. A predetermined threshold can then be used to decide whether point $\mathbf{d}_i$

5.3. Maintaining the Knowledge Base

6

Discussion and conclusion

Todo list

redundant references?	7
Add paragraph on Gijsberts and Metta (2011)	7
rethink order of paragraphs?	7
add Lu2019 to chapter, add the training algorithm to the table (eg. PPO)?	8
1-2 paragraphs on traditional adaptive control, Annaswamy and Fradkov (2021) and Landau et al. (2011)	9
add Sun et al. (2011), or not?	11
add footnote	12
Summarizing paragraph (+ table?)	12
citation needed?	14

List of changes

Added: (Levine & Koltun, 2013)	5
Added: (Haarnoja et al., 2018)	6
Added: (Williams et al., 2015)	6
Added: (Sayed, 2008)	8
Added: (Björck, 1996)	8
Added: (Landau et al., 2011)	8
Added: MPC	8
Commented: Added: entire chapter	9
Commented: Added: chapter	13

Bibliography

- Abdolmaleki, A., Springenberg, J. T., Tassa, Y., Munos, R., Heess, N., & Riedmiller, M. (2018). Maximum a Posteriori Policy Optimisation. <http://arxiv.org/abs/1806.06920>
- Alessi, C., Hauser, H., Lucantonio, A., & Falotico, E. (2023). Learning a Controller for Soft Robotic Arms and Testing its Generalization to New Observations, Dynamics, and Tasks. *2023 IEEE International Conference on Soft Robotics (RoboSoft)*, 1–7. <https://doi.org/10.1109/RoboSoft55895.2023.10121988>
- Aljundi, R., Chakravarty, P., & Tuytelaars, T. (2017). Expert gate: Lifelong learning with a network of experts. *Proceedings - 30th IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, 2017-Janua*, 7120–7129. <https://doi.org/10.1109/CVPR.2017.753>
- Annaswamy, A. M., & Fradkov, A. L. (2021). A Historical Perspective of Adaptive Control and Learning. *Annual Reviews in Control*, 52, 18–41. <https://doi.org/10.1016/j.arcontrol.2021.10.014>
- Björck, Å. (1996, January). *Numerical Methods for Least Squares Problems*. Society for Industrial; Applied Mathematics. <https://doi.org/10.1137/1.9781611971484>
- Chatzilygeroudis, K., Cully, A., & Mouret, J.-B. (2016). Towards semi-episodic learning for robot damage recovery. <http://arxiv.org/abs/1610.01407>
- Cully, A., Clune, J., Tarapore, D., & Mouret, J. B. (2015). Robots that can adapt like animals. *Nature*, 521(7553), 503–507. <https://doi.org/10.1038/nature14422>
- Fujimoto, S., Van Hoof, H., & Meger, D. (2018). Addressing Function Approximation Error in Actor-Critic Methods. *35th International Conference on Machine Learning, ICML 2018*, 4, 2587–2601. <https://arxiv.org/abs/1802.09477v3>
- Gijssberts, A., & Metta, G. (2011). Incremental learning of robot dynamics using random features. *Proceedings - IEEE International Conference on Robotics and Automation*, 951–956. <https://doi.org/10.1109/ICRA.2011.5980191>
- Gillespie, M. T., Best, C. M., Townsend, E. C., Wingate, D., & Killpack, M. D. (2018). Learning nonlinear dynamic models of soft robots for model predictive control with neural networks. *2018 IEEE International Conference on Soft Robotics (RoboSoft)*, 39–45. <https://doi.org/10.1109/ROBOSOFT.2018.8404894>
- Giorelli, M., Renda, F., Calisti, M., Arienti, A., Ferri, G., & Laschi, C. (2015). Learning the inverse kinetics of an octopus-like manipulator in three-dimensional space. *Bioinspiration & Biomimetics*, 10(3), 035006. <https://doi.org/10.1088/1748-3190/10/3/035006>
- Haarnoja, T., Zhou, A., Abbeel, P., & Levine, S. (2018). Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. *35th International Conference on Machine Learning, ICML 2018*, 5, 2976–2989. <https://arxiv.org/abs/1801.01290v2>
- Kim, D., Kim, S.-H., Kim, T., Kang, B. B., Lee, M., Park, W., Ku, S., Kim, D., Kwon, J., Lee, H., Bae, J., Park, Y.-L., Cho, K.-J., & Jo, S. (2021). Review of machine learning methods in soft robotics (G. Gu, Ed.). *PLOS ONE*, 16(2), e0246102. <https://doi.org/10.1371/journal.pone.0246102>
- Landau, I. D., Lozano, R., M'Saad, M., & Karimi, A. (2011). *Adaptive Control*. Springer London. <https://doi.org/10.1007/978-0-85729-664-1>

- Lesort, T., Lomonaco, V., Stoian, A., Maltoni, D., Filliat, D., & Díaz-Rodríguez, N. (2020). Continual learning for robotics: Definition, framework, learning strategies, opportunities and challenges. *Information Fusion*, 58, 52–68. <https://doi.org/10.1016/j.inffus.2019.12.004>
- Levine, S., & Koltun, V. (2013). Guided policy search. *30th International Conference on Machine Learning, ICML 2013*, 28(PART 2), 1038–1046. <https://proceedings.mlr.press/v28/levine13.html>
- Lu, K., Grover, A., Abbeel, P., & Mordatch, I. (2020). Reset-Free Lifelong Learning with Skill-Space Planning. *ICLR 2021 - 9th International Conference on Learning Representations*. <http://arxiv.org/abs/2012.03548>
- Lu, K., Mordatch, I., & Abbeel, P. (2019). Adaptive Online Planning for Continual Lifelong Learning. <https://doi.org/10.48550/arXiv.1912.01188>
- Mouret, J.-B., & Clune, J. (2015). Illuminating search spaces by mapping elites. <http://arxiv.org/abs/1504.04909>
- Nazeer, M. S., Bianchi, D., Campinoti, G., Laschi, C., & Falotico, E. (2023). Policy Adaptation using an Online Regressing Network in a Soft Robotic Arm. *2023 IEEE International Conference on Soft Robotics, RoboSoft 2023*, 1–7. <https://doi.org/10.1109/RoboSoft55895.2023.10121927>
- Nguyen-Tuong, D., & Peters, J. (2011a). Incremental online sparsification for model learning in real-time robot control. *Neurocomputing*, 74(11), 1859–1867. <https://doi.org/10.1016/j.neucom.2010.06.033>
- Nguyen-Tuong, D., & Peters, J. (2011b). Model learning for robot control: a survey. *Cognitive Processing*, 12(4), 319–340. <https://doi.org/10.1007/s10339-011-0404-1>
- Nguyen-Tuong, D., Seeger, M., & Peters, J. (2008). Local Gaussian Process Regression for Real Time Online Model Learning and Control. *NIPS'08: Proceedings of the 21st International Conference on Neural Information Processing Systems*, 1193–1200. <https://doi.org/10.5555/2981780.2981929>
- Nguyen-Tuong, D., Seeger, M., & Peters, J. (2009). Model Learning with Local Gaussian Process Regression. *Advanced Robotics*, 23(15), 2015–2034. <https://doi.org/10.1163/016918609X12529286896877>
- Romeres, D., Zorzi, M., Camoriano, R., & Chiuso, A. (2016). Online semi-parametric learning for inverse dynamics modeling. <http://arxiv.org/abs/1603.05412>
- Sayed, A. H. (2008, March). *Adaptive Filters*. Wiley. <https://doi.org/10.1002/9780470374122>
- Schulman, J., Wolski, F., Dhariwal, P., Radford, A., & Klimov, O. (2017). Proximal Policy Optimization Algorithms. <http://arxiv.org/abs/1707.06347>
- Schwarz, J., Luketina, J., Czarnecki, W. M., Grabska-Barwinska, A., Teh, Y. W., Pascanu, R., & Hadsell, R. (2018). Progress & compress: A scalable framework for continual learning. *35th International Conference on Machine Learning, ICML 2018*, 10, 7199–7208. <http://arxiv.org/abs/1805.06370>
- Shin, H., Lee, J. K., Kim, J., & Kim, J. (2017). Continual Learning with Deep Generative Replay. <http://arxiv.org/abs/1705.08690>
- Sprechmann, P., Jayakumar, S. M., Rae, J. W., Pritzel, A., Badia, A. P., Uribe, B., Vinyals, O., Hassabis, D., Pascanu, R., & Blundell, C. (2018). Memory-based parameter adaptation. *6th International Conference on Learning Representations, ICLR 2018 - Conference Track Proceedings*. <http://arxiv.org/abs/1802.10542>
- Sun, T., Pei, H., Pan, Y., Zhou, H., & Zhang, C. (2011). Neural network-based sliding mode adaptive control for robot manipulators. *Neurocomputing*, 74(14–15), 2377–2384. <https://doi.org/10.1016/j.neucom.2011.03.015>

- Thuruthel, T. G., Falotico, E., Renda, F., & Laschi, C. (2019). Model-Based Reinforcement Learning for Closed-Loop Dynamic Control of Soft Robotic Manipulators. *IEEE Transactions on Robotics*, 35(1), 124–134. <https://doi.org/10.1109/TRO.2018.2878318>
- Wang, Z., Chen, C., & Dong, D. (2020). Lifelong Incremental Reinforcement Learning with Online Bayesian Inference. *IEEE Transactions on Neural Networks and Learning Systems*, 33(8), 4003–4016. <https://doi.org/10.1109/TNNLS.2021.3055499>
- Wang, Z., Novikov, A., Zolna, K., Springenberg, J. T., Reed, S., Shahriari, B., Siegel, N., Merel, J., Gulcehre, C., Heess, N., & de Freitas, N. (2020). Critic Regularized Regression. <http://arxiv.org/abs/2006.15134>
- Williams, G., Aldrich, A., & Theodorou, E. (2015). Model Predictive Path Integral Control using Covariance Variable Importance Sampling. <https://arxiv.org/abs/1509.01149v3> 20<http://arxiv.org/abs/1509.01149>
- Xie, A., & Finn, C. (2021). Lifelong Robotic Reinforcement Learning by Retaining Experiences. *Proceedings of Machine Learning Research*, 199, 838–855. <http://arxiv.org/abs/2109.09180>
- Zhou, W., Bohez, S., Humplik, J., Abdolmaleki, A., Rao, D., Wulfmeier, M., Haarnoja, T., & Heess, N. (2022). Forgetting and Imbalance in Robot Lifelong Learning with Off-policy Data. *Proceedings of Machine Learning Research*, 199, 294–309. <http://arxiv.org/abs/2204.05893>